

FCC RF Test Report

APPLICANT : PAX Technology Limited
EQUIPMENT : Smart Tablet
BRAND NAME : PAX
MODEL NAME : Aries6
FCC ID : V5PAR6
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure

The product was received on Apr. 11, 2019 and testing was completed on Jun. 10, 2019. We, Sporton International (ShenZhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (ShenZhen) Inc., the test report shall not be reproduced except in full.

Derreck Chen

Reviewed by: Derreck Chen / Supervisor

Eric Shih

Approved by: Eric Shih / Manager



Sporton International (ShenZhen) Inc.

**1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	6
1.6 Testing Location	7
1.7 Applicable Standards.....	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Carrier Frequency and Channel	9
2.2 Test Mode	10
2.3 Connection Diagram of Test System.....	11
2.4 Support Unit used in test configuration and system	12
2.5 EUT Operation Test Setup	12
2.6 Measurement Results Explanation Example.....	12
3 TEST RESULT	13
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement	13
3.2 Maximum Conducted Output Power Measurement	16
3.3 Power Spectral Density Measurement	17
3.4 Unwanted Emissions Measurement	19
3.5 AC Conducted Emission Measurement.....	24
3.6 Automatically Discontinue Transmission	26
3.7 Antenna Requirements	27
4 LIST OF MEASURING EQUIPMENT	28
5 UNCERTAINTY OF EVALUATION	29
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR941109F	Rev. 01	Initial issue of report	Aug. 02, 2019



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.403(i)	6dB, 26dB and 99% Occupied Bandwidth	> 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b)(4)(i) & 15.209(a)	Pass	Under limit 8.06 dB at 30.970 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 3.48 dB at 11.620 MHz
3.6	15.407(c)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.7	15.203 & 15.407(a)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

PAX Technology Limited

Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Road, Wanchai, Hong Kong

1.2 Manufacturer

PAX Computer Technology (Shenzhen) Co., Ltd.

4/F, No.3 Building, Software Park, Second Central Science-Tech Road, High-Tech industrial Park, Shenzhen, Guangdong, P.R.C.

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smart Tablet
Brand Name	PAX
Model Name	Aries6
FCC ID	V5PAR6
EUT supports Radios application	WCDMA/HSPA/DC-HSDPA/HSPA+(16QAM uplink is not supported)/LTE/GPS/NFC WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
IMEI Code	Conducted : 866732039393476 Conduction : 866732039389946 Radiation : 866732039393468
HW Version	N/A
SW Version	N/A
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	5745 MHz ~ 5825 MHz
Maximum Output Power	<5745 MHz ~ 5825 MHz> 802.11a : 13.80 dBm / 0.0240 W 802.11n HT20 : 13.36 dBm / 0.0217 W 802.11n HT40 : 12.87 dBm / 0.0194 W 802.11ac VHT20: 13.28 dBm / 0.0213 W 802.11ac VHT40: 12.78 dBm / 0.0190 W 802.11ac VHT80: 12.62 dBm / 0.0183 W
99% Occupied Bandwidth	802.11a : 18.93 MHz 802.11n HT20 : 19.53 MHz 802.11n HT40 : 36.86 MHz 802.11ac VHT80 : 75.64 MHz
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
Antenna Type / Gain	internal Antenna with gain 1.73 dBi

Note: For 802.11an HT20 / ac VHT20 and 802.11an HT40 / ac VHT40 mode, the whole testing have assessed only 802.11an HT20/ HT40 by referring to their maximum conducted power.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Location

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International (Shenzhen) Inc.		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-SZ TH01-SZ	CN1256	421272

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH06-KS	CN1257	314309

Note: Test data subcontracted: Unwanted emissions measurement in section 3.4 of this report.



1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5745-5825 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 [#]	5775	165	5825

Note:

1. The above Frequency and Channel in "*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "[#]" were 802.11ac VHT80.

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.


Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT80	MCS0

AC Conducted Emission	Mode 1 : WCDMA Band II Idle + Bluetooth Link + WLAN Link(5G) + Earphone + Battery + USB Cable(Charging from Adapter)
Remark: For Radiated Test Cases, The tests were performed with Adapter and USB Cable	


Ch. #		Band IV : 5725-5850 MHz			
		802.11a	802.11n HT20	802.11n HT40	802.11ac VHT80
L	Low	149	149	151	-
M	Middle	157	157	-	155
H	High	165	165	159	-

2.3 Connection Diagram of Test System

For Radiation



For Conducted Emission



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	WLAN AP	D-Link	DIR-820L	KA2IR820LA1	N/A	Unshielded,1.8m
3.	Notebook	Lenovo	E540	FCC DoC	N/A	AC I/P: Unshielded,1.2m DC O/P: Shielded, 1.8 m
4.	Earphone	Apple	MC690ZP/A	N/A	Shielded, 1.0m	N/A
5.	Earphone	Lenovo	SH100	N/A	Unshielded, 1.2m	N/A
6.	Bluetooth Earphone	Samsung	EO-MG900	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 6.6 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 6.6 + 10 = 16.6 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.



3.1.4 Test Setup






3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.





Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures


The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section F) Maximum power spectral density.

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).


- Measure the duty cycle.
 - Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 300 kHz.
 - Set VBW $\geq$ 1 MHz.
 - Number of points in sweep $\geq$ 2 Span / RBW.
 - Sweep time = auto.
 - Detector = RMS
 - Trace average at least 100 traces in power averaging mode.
 - Add $10 \log(500\text{kHz}/\text{RBW})$ to the test result.
 - Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.
-
1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
 2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

- (2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3



EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

Note: The following formula is used to convert the EIRP to field strength.

$$\text{EIRP} = E_{\text{Meas}} + 20\log(d_{\text{Meas}}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dBμV/m

d_{Meas} is the measurement distance, in m

(3) ANSI C63.10-2013 clause 12.7.3 note 97

As specified by regulatory requirements, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit. However, an out-of-band emission that complies with both the average and peak general regulatory limits is not required to satisfy the peak emission limit.

3.4.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures


1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section G) Unwanted emissions measurement.
 - (1) Procedure for Unwanted Emissions Measurements Below 1000MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
 - (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW $\geq$ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
 - (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.6 Automatically Discontinue Transmission

3.6.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 18, 2019	Jun. 08, 2019	Apr. 17, 2020	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1207253	30MHz~40GHz	Dec. 22, 2018	Jun. 08, 2019	Dec. 21, 2019	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Dec. 22, 2018	Jun. 08, 2019	Dec. 21, 2019	Conducted (TH01-SZ)
EMI Test Receiver	Keysight	N9038A	MY56400023	3Hz~8.5GHz; Max 30dBm	Oct. 12, 2018	Jun. 10, 2019	Oct. 11, 2019	Radiation (03CH06-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz~44GHz	Apr. 16, 2019	Jun. 10, 2019	Apr. 18, 2020	Radiation (03CH06-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 19, 2018	Jun. 10, 2019	Oct. 18, 2019	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz~1GHz	Dec. 28, 2018	Jun. 10, 2019	Dec. 27, 2019	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 20, 2018	Jun. 10, 2019	Oct. 19, 2019	Radiation (03CH06-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2019	Jun. 10, 2019	Jan. 04, 2020	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	187289	9KHz ~1GHZ	Aug. 06, 2018	Jun. 10, 2019	Aug. 05, 2019	Radiation (03CH06-KS)
Amplifier	MITEQ	TTA1840-35-HG	2014749	18~40GHz	Jan. 14, 2019	Jun. 10, 2019	Jan. 13, 2020	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2025788	1Ghz-18Ghz	Apr. 17, 2019	Jun. 10, 2019	Apr. 16, 2020	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY53270203	500MHz~26.5GHz	Apr. 15, 2019	Jun. 10, 2019	Apr. 14, 2020	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jun. 10, 2019	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jun. 10, 2019	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jun. 10, 2019	NCR	Radiation (03CH06-KS)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Dec. 23, 2018	Jun. 04, 2019	Dec. 22, 2019	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103912	9kHz~30MHz	Oct. 18, 2018	Jun. 04, 2019	Oct. 17, 2019	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Dec. 23, 2018	Jun. 04, 2019	Dec. 22, 2019	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 18, 2018	Jun. 04, 2019	Jul. 17, 2019	Conduction (CO01-SZ)

NCR: No Calibration Required

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.6dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------



Appendix A. Conducted Test Results

Report Number : FR941109F

Test Engineer:	Zhang Jiang	Temperature:	21~25	°C
Test Date:	2019/6/8	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

Band IV									
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	6 dB Bandwidth (MHz)	6dB Bandwidth min. Limit (MHz)	Pass/Fail
11a	6M bps	1	149	5745	18.83	22.88	16.30	0.5	Pass
11a	6Mbps	1	157	5785	18.93	23.33	16.30	0.5	Pass
11a	6Mbps	1	165	5825	18.88	22.83	16.30	0.5	Pass
HT20	MCS 0	1	149	5745	19.38	22.53	17.54	0.5	Pass
HT20	MCS 0	1	157	5785	19.43	22.88	17.52	0.5	Pass
HT20	MCS 0	1	165	5825	19.53	22.73	17.54	0.5	Pass
HT40	MCS 0	1	151	5755	36.76	41.09	36.04	0.5	Pass
HT40	MCS 0	1	159	5795	36.86	41.00	36.04	0.5	Pass
VHT80	MCS 0	1	155	5775	75.64	81.68	75.44	0.5	Pass

TEST RESULTS DATA
Average Power Table


Band IV										
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail
11a	6M bps	1	149	5745	0.13	13.11	30.00	1.73		Pass
11a	6Mbps	1	157	5785	0.13	13.44	30.00	1.73		Pass
11a	6Mbps	1	165	5825	0.13	13.80	30.00	1.73		Pass
HT20	MCS 0	1	149	5745	0.14	12.87	30.00	1.73		Pass
HT20	MCS 0	1	157	5785	0.14	13.15	30.00	1.73		Pass
HT20	MCS 0	1	165	5825	0.14	13.36	30.00	1.73		Pass
HT40	MCS 0	1	151	5755	0.28	12.63	30.00	1.73		Pass
HT40	MCS 0	1	159	5795	0.28	12.87	30.00	1.73		Pass
VHT20	MCS 0	1	149	5745	0.12	12.81	30.00	1.73		Pass
VHT20	MCS 0	1	157	5785	0.12	13.10	30.00	1.73		Pass
VHT20	MCS 0	1	165	5825	0.12	13.28	30.00	1.73		Pass
VHT40	MCS 0	1	151	5755	0.26	12.52	30.00	1.73		Pass
VHT40	MCS 0	1	159	5795	0.26	12.78	30.00	1.73		Pass
VHT80	MCS 0	1	155	5775	0.53	12.62	30.00	1.73		Pass

TEST RESULTS DATA
Power Spectral Density

Band IV										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	10log (500kHz /RBW) Factor (dB)	Average Power Density (dBm/500kHz)	Average PSD Limit (dBm/500kHz)	DG (dBi)	Pass/Fail
11a	6M bps	1	149	5745	0.13	2.22	0.24	30.00	1.73	Pass
11a	6Mbps	1	157	5785	0.13	2.22	0.54	30.00	1.73	Pass
11a	6Mbps	1	165	5825	0.13	2.22	0.42	30.00	1.73	Pass
HT20	MCS 0	1	149	5745	0.14	2.22	-0.95	30.00	1.73	Pass
HT20	MCS 0	1	157	5785	0.14	2.22	-0.04	30.00	1.73	Pass
HT20	MCS 0	1	165	5825	0.14	2.22	0.13	30.00	1.73	Pass
HT40	MCS 0	1	151	5755	0.28	2.22	-3.86	30.00	1.73	Pass
HT40	MCS 0	1	159	5795	0.28	2.22	-3.96	30.00	1.73	Pass
VHT80	MCS 0	1	155	5775	0.53	2.22	-6.40	30.00	1.73	Pass




Appendix B. AC Conducted Emission Test Results





Test Engineer :	Dalin Liu	Temperature :	22~25℃
		Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Site : CO01-SZ
Condition: FCC 15E_QP LISN_20180719_N NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.17	19.79	-35.02	54.81	9.60	0.03	10.16	Average
2	0.17	36.51	-28.30	64.81	26.32	0.03	10.16	QP
3	0.53	23.66	-22.34	46.00	13.47	0.02	10.17	Average
4	0.53	34.29	-21.71	56.00	24.10	0.02	10.17	QP
5	0.66	33.60	-12.40	46.00	23.40	0.02	10.18	Average
6	0.66	41.70	-14.30	56.00	31.50	0.02	10.18	QP
7	1.35	22.13	-23.87	46.00	11.90	0.05	10.18	Average
8	1.35	32.83	-23.17	56.00	22.60	0.05	10.18	QP
9	11.62	37.86	-12.14	50.00	27.38	0.22	10.26	Average
10 *	11.62	56.52	-3.48	60.00	46.04	0.22	10.26	QP
11	15.97	38.95	-11.05	50.00	28.30	0.38	10.27	Average
12	15.97	52.05	-7.95	60.00	41.40	0.38	10.27	QP



Appendix C. Radiated Spurious Emission

Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		5606.8	53.15	-15.15	68.3	40.41	34.6	8.34	30.2	100	188	P	H
		5653.6	53.83	-17.14	70.97	40.95	34.7	8.37	30.19	100	188	P	H
		5717.6	53.61	-56.62	110.23	40.66	34.77	8.42	30.24	100	188	P	H
		5722.4	53.56	-62.81	116.37	40.61	34.77	8.42	30.24	100	188	P	H
		5746	94.09	-	-	81.1	34.8	8.45	30.26	100	188	P	H
		5746	86.71	-	-	73.72	34.8	8.45	30.26	100	188	A	H
		5618.4	54.2	-14.1	68.3	41.43	34.63	8.34	30.2	110	165	P	V
		5653.6	53.03	-17.94	70.97	40.15	34.7	8.37	30.19	110	165	P	V
		5716.8	54.57	-55.44	110.01	41.66	34.73	8.42	30.24	110	165	P	V
		5722.8	60.52	-56.76	117.28	47.57	34.77	8.42	30.24	110	165	P	V
		5744	98.64	-	-	85.65	34.8	8.45	30.26	110	165	P	V
		5744	91.09	-	-	78.1	34.8	8.45	30.26	110	165	A	V
802.11a CH 165 5825MHz		5850.8	53.1	-67.38	120.48	39.86	35	8.57	30.33	102	189	P	H
		5868.8	53.77	-53.26	107.03	40.42	35.03	8.66	30.34	102	189	P	H
		5877.6	54.12	-49.25	103.37	40.73	35.07	8.66	30.34	102	189	P	H
		5936.8	53.67	-14.63	68.3	40.04	35.17	8.85	30.39	102	189	P	H
		5826	93.98	-	-	80.75	34.97	8.57	30.31	102	189	P	H
		5826	86.42	-	-	73.19	34.97	8.57	30.31	102	189	A	H
		5850	60.15	-62.15	122.3	46.91	35	8.57	30.33	116	163	P	V
		5856	57.09	-53.53	110.62	43.73	35.03	8.66	30.33	116	163	P	V
		5902.8	54.72	-29.97	84.69	41.22	35.1	8.76	30.36	116	163	P	V
		5978	53.62	-14.68	68.3	39.81	35.27	8.94	30.4	116	163	P	V
		5826	99.71	-	-	86.48	34.97	8.57	30.31	116	163	P	V
		5826	92.55	-	-	79.32	34.97	8.57	30.31	116	163	A	V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11490	39.69	-34.31	74	51.88	38.08	12.58	62.85	100	360	P	H
		11490	40.36	-33.64	74	52.55	38.08	12.58	62.85	100	360	P	V
802.11a CH 157 5785MHz		11570	40.18	-33.82	74	52.11	38.17	12.64	62.74	100	360	P	H
		11570	41.53	-32.47	74	53.46	38.17	12.64	62.74	100	360	P	V
802.11a CH 165 5825MHz		11650	41.35	-32.65	74	53.04	38.24	12.69	62.62	100	360	P	H
		11650	41.39	-32.61	74	53.08	38.24	12.69	62.62	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 149 5745MHz		5617.6	53.8	-14.5	68.3	41.03	34.63	8.34	30.2	204	271	P	H
		5674.4	53.3	-33.1	86.4	40.41	34.7	8.4	30.21	204	271	P	H
		5712.4	53.16	-55.61	108.77	40.25	34.73	8.42	30.24	204	271	P	H
		5721.6	54.83	-59.72	114.55	41.88	34.77	8.42	30.24	204	271	P	H
		5746	95.11	-	-	82.12	34.8	8.45	30.26	204	271	P	H
		5746	88	-	-	75.01	34.8	8.45	30.26	204	271	A	H
		5639.2	53.07	-15.23	68.3	40.22	34.67	8.37	30.19	100	345	P	V
		5652.8	53.89	-16.49	70.38	41.01	34.7	8.37	30.19	100	345	P	V
		5704.8	53.94	-52.71	106.65	41.03	34.73	8.42	30.24	100	345	P	V
		5724	56.71	-63.31	120.02	43.76	34.77	8.42	30.24	100	345	P	V
		5746	95.94	-	-	82.95	34.8	8.45	30.26	100	345	P	V
		5746	89.1	-	-	76.11	34.8	8.45	30.26	100	345	A	V
802.11n HT20 CH 165 5825MHz		5852	55.17	-62.57	117.74	41.93	35	8.57	30.33	167	317	P	H
		5854.8	53.77	-57.59	111.36	40.5	35.03	8.57	30.33	167	317	P	H
		5892	53.6	-39.08	92.68	40.2	35.1	8.66	30.36	167	317	P	H
		5996	54.28	-14.02	68.3	40.46	35.3	8.94	30.42	167	317	P	H
		5828	96.91	-	-	83.68	34.97	8.57	30.31	167	317	P	H
		5828	89.27	-	-	76.04	34.97	8.57	30.31	167	317	A	H
		5851.6	57.43	-61.22	118.65	44.19	35	8.57	30.33	104	345	P	V
		5861.6	55.22	-53.83	109.05	41.87	35.03	8.66	30.34	104	345	P	V
		5878	54.48	-48.59	103.07	41.09	35.07	8.66	30.34	104	345	P	V
		5949.2	54.99	-13.31	68.3	41.33	35.2	8.85	30.39	104	345	P	V
		5828	98.99	-	-	85.76	34.97	8.57	30.31	104	345	P	V
		5828	91.74	-	-	78.51	34.97	8.57	30.31	104	345	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20		11490	39.72	-34.28	74	51.91	38.08	12.58	62.85	100	360	P	H
CH 149 5745MHz		11490	39.77	-34.23	74	51.96	38.08	12.58	62.85	100	360	P	V
802.11n HT20		11570	40.76	-33.24	74	52.69	38.17	12.64	62.74	100	360	P	H
CH 157 5785MHz		11570	41.53	-32.47	74	53.46	38.17	12.64	62.74	100	360	P	V
802.11n HT20		11650	40.69	-33.31	74	52.38	38.24	12.69	62.62	100	360	P	H
CH 165 5825MHz		11650	41.08	-32.92	74	52.77	38.24	12.69	62.62	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 151 5755MHz		5635.6	53.38	-14.92	68.3	40.53	34.67	8.37	30.19	303	312	P	H
		5698.4	54.46	-49.66	104.12	41.59	34.7	8.4	30.23	303	312	P	H
		5720	57.47	-53.43	110.9	44.52	34.77	8.42	30.24	303	312	P	H
		5724.4	58.31	-62.62	120.93	45.36	34.77	8.42	30.24	303	312	P	H
		5850.4	53.34	-68.05	121.39	40.1	35	8.57	30.33	303	312	P	H
		5868.4	54.81	-52.34	107.15	41.46	35.03	8.66	30.34	303	312	P	H
		5880	53.79	-47.8	101.59	40.4	35.07	8.66	30.34	303	312	P	H
		5936.4	53.85	-14.45	68.3	40.22	35.17	8.85	30.39	303	312	P	H
		5756	93.79	-	-	80.79	34.83	8.45	30.28	303	312	P	H
		5756	86.51	-	-	73.51	34.83	8.45	30.28	303	312	A	H
		5641.2	53.14	-15.16	68.3	40.29	34.67	8.37	30.19	100	342	P	V
		5697.2	54.32	-48.92	103.24	41.45	34.7	8.4	30.23	100	342	P	V
		5718.4	58.32	-52.13	110.45	45.37	34.77	8.42	30.24	100	342	P	V
		5723.2	60.67	-57.53	118.2	47.72	34.77	8.42	30.24	100	342	P	V
		5851.6	52.22	-66.43	118.65	38.98	35	8.57	30.33	100	342	P	V
		5856.4	52.86	-57.65	110.51	39.5	35.03	8.66	30.33	100	342	P	V
		5884.4	53.29	-45.03	98.32	39.92	35.07	8.66	30.36	100	342	P	V
		5940	53.77	-14.53	68.3	40.11	35.2	8.85	30.39	100	342	P	V
		5754	94.18	-	-	81.16	34.83	8.45	30.26	100	342	P	V
		5754	87.15	-	-	74.13	34.83	8.45	30.26	100	342	A	V



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.		(MHz)	(dBμV/m)	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1				(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 159 5795MHz		5618	53.33	-14.97	68.3	40.56	34.63	8.34	30.2	303	311	P	H
		5667.2	53.52	-27.54	81.06	40.63	34.7	8.4	30.21	303	311	P	H
		5704	53.07	-53.35	106.42	40.15	34.73	8.42	30.23	303	311	P	H
		5721.6	54.2	-60.35	114.55	41.25	34.77	8.42	30.24	303	311	P	H
		5854.4	54.17	-58.1	112.27	40.9	35.03	8.57	30.33	303	311	P	H
		5862	53.8	-55.14	108.94	40.45	35.03	8.66	30.34	303	311	P	H
		5882.8	54.53	-44.98	99.51	41.14	35.07	8.66	30.34	303	311	P	H
		5933.2	54.44	-13.86	68.3	40.88	35.17	8.76	30.37	303	311	P	H
		5794	94.08	-	-	81	34.9	8.48	30.3	303	311	P	H
		5794	86.49	-	-	73.41	34.9	8.48	30.3	303	311	A	H
		5637.2	53.39	-14.91	68.3	40.54	34.67	8.37	30.19	106	344	P	V
		5670.4	53.31	-30.13	83.44	40.42	34.7	8.4	30.21	106	344	P	V
		5702	54.26	-51.6	105.86	41.34	34.73	8.42	30.23	106	344	P	V
		5723.6	53.46	-65.65	119.11	40.51	34.77	8.42	30.24	106	344	P	V
		5852	53.37	-64.37	117.74	40.13	35	8.57	30.33	106	344	P	V
		5858.8	53.63	-56.2	109.83	40.28	35.03	8.66	30.34	106	344	P	V
		5898.4	53.58	-34.37	87.95	40.08	35.1	8.76	30.36	106	344	P	V
		5999.2	53.62	-14.68	68.3	39.8	35.3	8.94	30.42	106	344	P	V
		5792	95.42	-	-	82.34	34.9	8.48	30.3	106	344	P	V
		5792	88	-	-	74.92	34.9	8.48	30.3	106	344	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40		11510	40.55	-33.45	74	52.72	38.1	12.58	62.85	100	360	P	H
CH 151 5755MHz		11510	39.81	-34.19	74	51.98	38.1	12.58	62.85	100	360	P	V
802.11n HT40		11590	40.16	-33.84	74	52.02	38.18	12.67	62.71	100	360	P	H
CH 159 5795MHz		11590	40.39	-33.61	74	52.25	38.18	12.67	62.71	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 155 5775MHz		5617.2	54.58	-13.72	68.3	41.81	34.63	8.34	30.2	100	327	P	H
		5686	60.68	-34.29	94.97	47.81	34.7	8.4	30.23	100	327	P	H
		5704.8	60.85	-45.8	106.65	47.94	34.73	8.42	30.24	100	327	P	H
		5720.4	61.89	-49.92	111.81	48.94	34.77	8.42	30.24	100	327	P	H
		5852.4	54.95	-61.88	116.83	41.71	35	8.57	30.33	100	327	P	H
		5856.4	53.27	-57.24	110.51	39.91	35.03	8.66	30.33	100	327	P	H
		5879.6	54.82	-47.06	101.88	41.43	35.07	8.66	30.34	100	327	P	H
		5927.6	53.59	-14.71	68.3	40.03	35.17	8.76	30.37	100	327	P	H
		5780	90.89	-	-	77.82	34.87	8.48	30.28	100	327	P	H
		5780	83.77	-	-	70.7	34.87	8.48	30.28	100	327	A	H
		5646.4	55.39	-12.91	68.3	42.54	34.67	8.37	30.19	300	251	P	V
		5699.6	59.15	-45.86	105.01	46.26	34.7	8.42	30.23	300	251	P	V
		5705.6	59.25	-47.62	106.87	46.34	34.73	8.42	30.24	300	251	P	V
		5720.8	61.19	-51.53	112.72	48.24	34.77	8.42	30.24	300	251	P	V
		5850.4	53.18	-68.21	121.39	39.94	35	8.57	30.33	300	251	P	V
		5864	54.29	-54.09	108.38	40.94	35.03	8.66	30.34	300	251	P	V
		5911.2	54.2	-24.28	78.48	40.68	35.13	8.76	30.37	300	251	P	V
		5968	53.64	-14.66	68.3	39.96	35.23	8.85	30.4	300	251	P	V
		5772	87.94	-	-	74.9	34.87	8.45	30.28	300	251	P	V
		5772	80.79	-	-	67.75	34.87	8.45	30.28	300	251	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**Band 4 5725~5850MHz****WIFI 802.11ac VHT80 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80		11550	40.59	-33.41	74	52.57	38.15	12.64	62.77	100	360	P	H
CH 155 5775MHz		11550	40.14	-33.86	74	52.12	38.15	12.64	62.77	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

5GHz WIFI 802.11ac VHT80 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11ac VHT80 LF		30.97	22.22	-17.78	40	30.72	23.52	0.58	32.6	-	-	P	H
		94.02	18.48	-25.02	43.5	34.05	15.64	0.99	32.2	-	-	P	H
		173.56	24.26	-19.24	43.5	39.47	15.47	1.37	32.05	-	-	P	H
		299.66	24.65	-21.35	46	35.51	19.2	1.84	31.9	-	-	P	H
		450.01	25.79	-20.21	46	32.66	22.6	2.23	31.7	-	-	P	H
		749.74	33.52	-12.48	46	36.88	25.49	2.95	31.8	100	0	P	H
		30.97	31.94	-8.06	40	40.44	23.52	0.58	32.6	100	360	P	V
		42.61	28.05	-11.95	40	42.77	17.1	0.62	32.44	-	-	P	V
		150.28	20.81	-22.69	43.5	35.12	16.51	1.28	32.1	-	-	P	V
		623.64	26.85	-19.15	46	31.27	24.67	2.66	31.75	-	-	P	V
		749.74	35.29	-10.71	46	38.65	25.49	2.95	31.8	-	-	P	V
		960.23	30.51	-23.49	54	31.57	27.1	3.36	31.52	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)


= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.


Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11a	96.98	1.399	0.715	0.75kHz
802.11n HT20	96.79	1.312	0.762	0.82kHz
802.11n HT40	93.68	0.645	1.551	1.6kHz
802.11ac VHT80	88.54	0.325	3.080	3.3kHz


802.11a



802.11n HT20



802.11n HT40





802.11ac VHT80

