

FCC TEST REPORT

(Part 15, Subpart C)

Applicant:	PAX Technology Limited
Address:	Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Hong Kong China


Manufacturer or Supplier:	PAX Computer Technology (Shenzhen) Co., Ltd.
Address:	4/F, No.3 Building, Software Park, Second Central Science-Tech Road, High-Tech industrial Park, Shenzhen, Guangdong, P.R.C.
Product:	Integrated Smart Terminal
Brand Name:	PAX
Model Name:	E700
FCC ID:	V5PE700GM2
Date of tests:	Jun. 24, 2022 ~ Jul. 18, 2022

The tests have been carried out according to the requirements of the following standard:

☒ **FCC Part 15, Subpart C, Section 15.247**

☒ **ANSI C63.10-2013**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Simon Wang Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
 Date: Jul. 18, 2022	 Date: Jul. 18, 2022

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 SUMMARY OF TEST RESULTS.....	5
1.1 MEASUREMENT UNCERTAINTY	5
2 GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	8
2.2.1 CONFIGURATION OF SYSTEM UNDER TEST	9
2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	9
2.3 DUTY CYCLE OF TEST SIGNAL	12
2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS	13
2.5 DESCRIPTION OF SUPPORT UNITS	13
3 TEST TYPES AND RESULTS.....	14
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	14
3.1.2 TEST INSTRUMENTS.....	14
3.1.3 TEST PROCEDURES	15
3.1.4 DEVIATION FROM TEST STANDARD	15
3.1.5 TEST SETUP	16
3.1.6 EUT OPERATING CONDITIONS	16
3.1.7 TEST RESULTS	17
3.2 RADIATED EMISSION MEASUREMENT	19
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	19
3.2.2 TEST INSTRUMENTS.....	20
3.2.3 TEST PROCEDURES	21
3.2.4 DEVIATION FROM TEST STANDARD	21
3.2.5 TEST SETUP	22
3.2.6 EUT OPERATING CONDITIONS	23
3.2.7 TEST RESULTS	24
3.3 6 DB BANDWIDTH MEASUREMENT	44
3.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT	44
3.3.2 TEST INSTRUMENTS.....	44
3.3.3 TEST PROCEDURE.....	44
3.3.4 DEVIATION FROM TEST STANDARD	45



3.3.5	TEST SETUP	45
3.3.6	EUT OPERATING CONDITIONS	45
3.3.7	TEST RESULTS	46
3.4	CONDUCTED OUTPUT POWER.....	47
3.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	47
3.4.2	TEST SETUP	47
3.4.3	TEST INSTRUMENTS	47
3.4.4	TEST PROCEDURES	47
3.4.5	DEVIATION FROM TEST STANDARD	47
3.4.6	EUT OPERATING CONDITIONS	47
3.4.7	TEST RESULTS	48
3.4.7.1	MAXIMUM PEAK OUTPUT POWER	48
3.4.7.2	AVERAGE OUTPUT POWER (FOR REFERENCE).....	49
3.5	POWER SPECTRAL DENSITY MEASUREMENT	50
3.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	50
3.5.2	TEST SETUP	50
3.5.3	TEST INSTRUMENTS	50
3.5.4	TEST PROCEDURE	50
3.5.5	DEVIATION FROM TEST STANDARD	50
3.5.6	EUT OPERATING CONDITION	50
3.5.7	TEST RESULTS	51
3.6	OUT OF BAND EMISSION MEASUREMENT	52
3.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	52
3.6.2	TEST SETUP	52
3.6.3	TEST INSTRUMENTS	52
3.6.4	TEST PROCEDURE	52
3.6.5	DEVIATION FROM TEST STANDARD	53
3.6.6	EUT OPERATING CONDITION	53
3.6.7	TEST RESULTS	53
4	PHOTOGRAPHS OF THE TEST CONFIGURATION	54
5	MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	55
6	APPENDIX 1 WLAN 2.4G	56
7	APPENDIX 2 BLE	101



Test Report No.: W7L-P22060025RF02

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
W7L-P22060025RF02	Original release	Jul. 18, 2022



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)		
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT
15.207	AC Power Conducted Emission	Compliance
15.205 15.209	Radiated Emissions	Compliance
15.247(d)	Out of band Emission Measurement	Compliance
15.247(a)(2)	6dB bandwidth	Compliance
15.247(b)	Conducted Output power	Compliance
15.247(e)	Power Spectral Density	Compliance
15.203	Antenna Requirement	Compliance

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	±2.70dB
Radiated emissions (30MHz~1GMHz)	±4.98dB
Radiated emissions (1GMHz ~6GMHz)	±4.70dB
Radiated emissions (6GMHz ~18GMHz)	±4.60dB
Radiated emissions (18GMHz ~40GMHz)	±4.12dB
Conducted emissions	±4.01dB
Occupied Channel Bandwidth	±43.58KHz
Conducted Output power	±2.06dB
Power Spectral Density	±0.85 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Integrated Smart Terminal
BRAND NAME	PAX
MODEL NAME	E700
NOMINAL VOLTAGE	24Vdc (adapter) 3.63Vdc (Li-ion, battery) 3.6 Vdc (Li-ion, battery)
MODULATION	CCK, OFDM, GFSK
TRANSMISSION RATE	802.11b: 11/ 5.5/ 2.0 / 1.0 Mbps 802.11g: 54/ 48/ 36 / 24 / 18 / 9/ 6 Mbps 802.11n20: up to 65 Mbps BT_LE: 1 Mbps
OPERATING FREQUENCY	2412-2462MHz for 11b/g/n(HT20) 2402-2480MHz for BT-LE(GFSK)
MAX. OUTPUT POWER	WLAN: 231.21mW (Maximum) BT-LE: 4.72mW (Maximum)
ANTENNA TYPE	PIFA Antenna with 1dBi gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	N/A

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. The EUT incorporates a SISO function. Physically, the EUT provides one transmitter and one receiver.

MODULATION MODE	TX/RX FUNCTION
802.11b	1TX /1RX
802.11g	1TX /1RX
802.11n (20MHz)	1TX /1RX
BT_LE(1MHz)	1TX /1RX

3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



Test Report No.: W7L-P22060025RF02

List of Accessory:

ACCESSORIES	BRAND	MODEL	SPECIFICATION
Battery1	EVE	A0671-LE	Capacity : 3.63vdc 2550mAh
Battery2	EVE	A0671B	Capacity : 3.6vdc 2550mAh
AC Adapter	HONOTO	ADS-65HI-19A-3 24065E	I/P:100-240Vac, 1.5A O/P: 24Vdc, 2.7A



2.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

40 channels are provided for BT-LE (GFSK):

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G**: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

RADIATED EMISSION TEST (BELOW 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11n HT20	1 to 11	1	OFDM	MCS0
BT-LE	0 to 39	39	GFSK	1.0



**BUREAU
VERITAS**

Test Report No.: W7L-P22060025RF02

RADIATED EMISSION TEST (ABOVE 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
BT-LE	0 to 39	0, 19, 39	GFSK	1

POWER LINE CONDUCTED EMISSION TEST

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11n HT20	1 to 11	11	OFDM	MCS0

BANDEDGE MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 11	DSSS	1.0
802.11g	1 to 11	1, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 11	OFDM	MCS0
BT-LE	0 to 39	0, 39	GFSK	1

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	CCK	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	1

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	23deg. C, 70%RH	DC 24V by adapter	Carl Xie
RE≥1G	23deg. C, 70%RH	DC 24V by adapter	Carl Xie
PLC	25deg. C, 52%RH	DC 24V by adapter	Lily Zhao
APCM	25deg. C, 60%RH	DC 24V by adapter	Lily Zhao



2.3 Duty Cycle of Test Signal

Please Refer to Appendix1/2 Of this test report.

WORST-CASE DATA:

Measured Duty Cycle		
Mode		Duty Cycle [%]
		ANT1
WIFI 2.4GHz	11B	98.83
	11G	93.33
	11N20	93.33
BT LE	BT4.0	61.90

Note:

Duty cycle of test signal is < 98%, duty factor shall be considered.

2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

KDB 558074 D01 DTS Meas Guidance v05r02

ANSI C63.10-2013

Note :

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Desktop	Lenovo	M73 SFF	PC04GRQV	N/A
2	Desktop	Lenovo	M73 SFF	PC06CS27	N/A
3	Laptop	Lenovo	Thnikpad T450	PC-049PT1	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line: Unshielded, Detachable 1.5m
2	AC Line: Unshielded, Detachable 1.5m
3	AC Line: Unshielded, Detachable 1.5m



3 TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	101900	Feb. 15,22	Feb. 14,23
EMC32 test software	Rohde&Schwarz	EMC32	NA	NA	NA
LISN network	Rohde&Schwarz	ENV216	101922	Mar. 04,22	Mar. 03,23

NOTE:

1. The test was performed in CE shielded room.

2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



3.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 DEVIATION FROM TEST STANDARD

No deviation.



3.1.5 TEST SETUP



- Note:**
- 1.Support units were connected to second LISN.
 - 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



3.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA:

Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	26deg. C, 51%RH
Tested By	Carl Xie		

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150000	---	27.84	56.00	28.16	L1	ON	9.7
0.150000	40.53	---	66.00	25.47	L1	ON	9.7
0.416000	---	29.97	47.53	17.56	L1	ON	9.7
0.416000	38.94	---	57.53	18.59	L1	ON	9.7
0.672000	---	15.09	46.00	30.91	L1	ON	9.7
0.672000	22.00	---	56.00	34.00	L1	ON	9.7
3.712000	---	17.38	46.00	28.62	L1	ON	9.7
3.712000	27.02	---	56.00	28.98	L1	ON	9.7
16.896000	---	21.17	50.00	28.83	L1	ON	9.8
16.896000	32.68	---	60.00	27.32	L1	ON	9.8
19.024000	---	24.40	50.00	25.60	L1	ON	9.8
19.024000	35.93	---	60.00	24.07	L1	ON	9.8

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.


3. The emission levels of other frequencies were very low against the limit.

4. Margin value = Limit value - Emission level

5. Correction factor = Insertion loss + Cable loss

6. Emission Level = Correction Factor + Reading Value.

Full Spectrum





**BUREAU
VERITAS**


Test Report No.: W7L-P22060025RF02

Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	26deg. C, 51%RH
Tested By	Carl Xie		

Frequency (MHz)	QuasiPeak (dBUV)	CAverage (dBUV)	Limit (dBUV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150000	---	26.34	56.00	29.66	N	ON	9.7
0.150000	37.85	---	66.00	28.15	N	ON	9.7
0.412000	---	27.80	47.61	19.80	N	ON	9.7
0.412000	37.79	---	57.61	19.82	N	ON	9.7
0.700000	---	13.14	46.00	32.86	N	ON	9.7
0.700000	18.20	---	56.00	37.80	N	ON	9.7
3.640000	---	15.12	46.00	30.88	N	ON	9.8
3.640000	25.75	---	56.00	30.25	N	ON	9.8
16.896000	---	23.26	50.00	26.74	N	ON	9.9
16.896000	33.41	---	60.00	26.59	N	ON	9.9
19.556000	---	24.79	50.00	25.21	N	ON	9.9
19.556000	36.75	---	60.00	23.25	N	ON	9.9

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Limit value - Emission level
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.

Full Spectrum





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



**BUREAU
VERITAS**

Test Report No.: W7L-P22060025RF02

3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	May. 19,20	May. 18,23
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Mar. 06,22	Mar. 05,23
Horn Antenna	ETS-LINDGREN	3117	00168692	Mar. 06,22	Mar. 05,23
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Aug. 25, 21	Aug. 24, 22
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	JS1120-3	3.2.06	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	1505	Jun. 02,22	Jun. 01,23
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Feb. 18,22	Feb. 17,23
Signal Pre-Amplifier	EMSI	EMC 9135	980249	May.12,22	May.11,23
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	May.12,22	May.11,23
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Feb. 21,22	Feb.20,23
DC Source	Kikusui/JP	PMX18-5A	0000001	Aug. 25,21	Aug. 24,22
Power Meter	Anritsu	ML2495A	1506002	Feb. 22,22	Feb. 21,23
Power Sensor	Anritsu	MA2411B	1339352	May. 06,22	May. 05,23
Loop Antenna	Schwarzbeck	FMZB 1519B	00173	Sep.05,21	Sep. 04,22

- NOTE:**
1. The calibration interval of the above test instruments is 12 months or 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 2. The test was performed in 3m Chamber.
 3. The FCC Site Registration No. is 525120; The Designation No. is CN1171.



3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($10 \log(1/\text{duty cycle})$).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

3.2.4 DEVIATION FROM TEST STANDARD

No deviation




BUREAU
VERITAS


Test Report No.: W7L-P22060025RF02

3.2.5 TEST SETUP


< Frequency Range below 30MHz >



< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



3.2.7 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

BELOW 1GHz WORST-CASE DATA:

30 MHz – 1GHz data:


802.11n (20MHz)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
39.7	31.61	55.05	40	-8.39	13.43	0.36	37.23	100	0	QP
155.13	38.09	63.63	43.5	-5.41	10.32	0.67	36.53	100	0	QP
250.19	42.36	64.3	46	-3.64	13.5	0.83	36.27	100	0	QP
375.32	41.95	61.64	46	-4.05	15.66	1.03	36.38	100	0	QP
482.02	28.38	46	46	-17.62	17.76	1.2	36.58	100	0	QP
605.21	32.09	47.79	46	-13.91	19.8	1.37	36.87	100	0	QP

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.





**BUREAU
VERITAS**


Test Report No.: W7L-P22060025RF02

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
40.67	31.64	56.37	40	-8.36	12.11	0.37	37.21	200	0	QP
156.1	32.49	57.61	43.5	-11.01	10.74	0.67	36.53	200	0	QP
250.19	33.61	56.44	46	-12.39	12.61	0.83	36.27	200	0	QP
375.32	37.36	56.98	46	-8.64	15.73	1.03	36.38	200	0	QP
480.08	28.34	46.39	46	-17.66	17.34	1.19	36.58	200	0	QP
597.45	28.83	44.76	46	-17.17	19.55	1.36	36.84	200	0	QP

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.



**ABOVE 1GHz WORST-CASE DATA:**

Note: 1. For radiated emissions testing , the full testing range of different modes have been scanned , only the worst case harmonic data is reported in the sheet.

2. All other emissions were greater than 20dB below the limit was not recorded.

3. For higher frequency, the emission is too low to be detected.

802.11b:

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	52.16	60.2	74	-21.84	31.75	6.18	45.97	100	325	Peak
2390	45.72	53.76	54	-8.28	31.75	6.18	45.97	100	325	Average
2412	103.55	111.48	/	/	31.82	6.21	45.96	100	325	Peak
2412	101.83	109.76	/	/	31.82	6.21	45.96	100	325	Average
2483.5	51.53	59.1	74	-22.47	32.05	6.31	45.93	100	325	Peak
2483.5	43.84	51.41	54	-10.16	32.05	6.31	45.93	100	325	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	51.33	58.98	74	-22.67	32.14	6.18	45.97	100	190	Peak
2390	44.33	51.98	54	-9.67	32.14	6.18	45.97	100	190	Average
2412	98.62	106.18	/	/	32.19	6.21	45.96	100	190	Peak
2412	97.12	104.68	/	/	32.19	6.21	45.96	100	190	Average
2483.5	51.45	58.71	74	-22.55	32.36	6.31	45.93	100	190	Peak
2483.5	44.32	51.58	54	-9.68	32.36	6.31	45.93	100	190	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2412MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P22060025RF02

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.94	58.98	74	-23.06	31.75	6.18	45.97	100	325	Peak
2390	43.82	51.86	54	-10.18	31.75	6.18	45.97	100	325	Average
2437	104.08	111.89	/	/	31.9	6.24	45.95	100	325	Peak
2437	102.96	110.77	/	/	31.9	6.24	45.95	100	325	Average
2483.5	52.13	59.7	74	-21.87	32.05	6.31	45.93	100	325	Peak
2483.5	44.06	51.63	54	-9.94	32.05	6.31	45.93	100	325	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.95	58.6	74	-23.05	32.14	6.18	45.97	100	190	Peak
2390	44.01	51.66	54	-9.99	32.14	6.18	45.97	100	190	Average
2437	97.57	105.03	/	/	32.25	6.24	45.95	100	190	Peak
2437	96.78	104.24	/	/	32.25	6.24	45.95	100	190	Average
2483.5	51.3	58.56	74	-22.7	32.36	6.31	45.93	100	190	Peak
2483.5	44.17	51.43	54	-9.83	32.36	6.31	45.93	100	190	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P22060025RF02

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.41	58.45	74	-23.59	31.75	6.18	45.97	100	325	Peak
2390	42.63	50.67	54	-11.37	31.75	6.18	45.97	100	325	Average
2462	104.84	112.52	/	/	31.98	6.28	45.94	100	325	Peak
2462	102.9	110.58	/	/	31.98	6.28	45.94	100	325	Average
2483.5	58.02	65.59	74	-15.98	32.05	6.31	45.93	100	325	Peak
2483.5	49.89	57.46	54	-4.11	32.05	6.31	45.93	100	325	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.16	57.81	74	-23.84	32.14	6.18	45.97	100	145	Peak
2390	44.08	51.73	54	-9.92	32.14	6.18	45.97	100	145	Average
2462	97.96	105.31	/	/	32.31	6.28	45.94	100	145	Peak
2462	96.7	104.05	/	/	32.31	6.28	45.94	100	145	Average
2483.5	52.51	59.77	74	-21.49	32.36	6.31	45.93	100	145	Peak
2483.5	45.73	52.99	54	-8.27	32.36	6.31	45.93	100	145	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P22060025RF02

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	62.86	70.9	74	-11.14	31.75	6.18	45.97	100	335	Peak
2390	50.37	58.41	54	-3.63	31.75	6.18	45.97	100	335	Average
2412	104.98	112.91	/	/	31.82	6.21	45.96	100	335	Peak
2412	97.81	105.74	/	/	31.82	6.21	45.96	100	335	Average
2483.5	51.79	59.36	74	-22.21	32.05	6.31	45.93	100	335	Peak
2483.5	43.04	50.61	54	-10.96	32.05	6.31	45.93	100	335	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	59.26	66.91	74	-14.74	32.14	6.18	45.97	100	195	Peak
2390	47.76	55.41	54	-6.24	32.14	6.18	45.97	100	195	Average
2412	99.53	107.09	/	/	32.19	6.21	45.96	100	195	Peak
2412	92.56	100.12	/	/	32.19	6.21	45.96	100	195	Average
2483.5	52.02	59.28	74	-21.98	32.36	6.31	45.93	100	195	Peak
2483.5	43.96	51.22	54	-10.04	32.36	6.31	45.93	100	195	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2412MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P22060025RF02

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	51.34	59.38	74	-22.66	31.75	6.18	45.97	100	335	Peak
2390	43.6	51.64	54	-10.4	31.75	6.18	45.97	100	335	Average
2437	106.49	114.3	/	/	31.9	6.24	45.95	100	335	Peak
2437	99.39	107.2	/	/	31.9	6.24	45.95	100	335	Average
2483.5	51.28	58.85	74	-22.72	32.05	6.31	45.93	100	335	Peak
2483.5	43.06	50.63	54	-10.94	32.05	6.31	45.93	100	335	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	51.36	59.01	74	-22.64	32.14	6.18	45.97	100	195	Peak
2390	44.84	52.49	54	-9.16	32.14	6.18	45.97	100	195	Average
2437	100.18	107.64	/	/	32.25	6.24	45.95	100	195	Peak
2437	93.49	100.95	/	/	32.25	6.24	45.95	100	195	Average
2483.5	51.85	59.11	74	-22.15	32.36	6.31	45.93	100	195	Peak
2483.5	44.81	52.07	54	-9.19	32.36	6.31	45.93	100	195	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P22060025RF02

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	51.12	59.16	74	-22.88	31.75	6.18	45.97	100	335	Peak
2390	42.21	50.25	54	-11.79	31.75	6.18	45.97	100	335	Average
2462	105.51	113.19	/	/	31.98	6.28	45.94	100	335	Peak
2462	98.5	106.18	/	/	31.98	6.28	45.94	100	335	Average
2483.5	64.11	71.68	74	-9.89	32.05	6.31	45.93	100	335	Peak
2483.5	50.06	57.63	54	-3.94	32.05	6.31	45.93	100	335	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	51.7	59.35	74	-22.3	32.14	6.18	45.97	100	195	Peak
2390	43.6	51.25	54	-10.4	32.14	6.18	45.97	100	195	Average
2462	99.45	106.8	/	/	32.31	6.28	45.94	100	195	Peak
2462	92.04	99.39	/	/	32.31	6.28	45.94	100	195	Average
2483.5	60.59	67.85	74	-13.41	32.36	6.31	45.93	100	195	Peak
2483.5	47.39	54.65	54	-6.61	32.36	6.31	45.93	100	195	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P22060025RF02

802.11n (20MHz)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	61.8	69.84	74	-12.2	31.75	6.18	45.97	100	335	Peak
2390	50.65	58.69	54	-3.35	31.75	6.18	45.97	100	335	Average
2412	104.97	112.9	/	/	31.82	6.21	45.96	100	335	Peak
2412	98.15	106.08	/	/	31.82	6.21	45.96	100	335	Average
2483.5	51.4	58.97	74	-22.6	32.05	6.31	45.93	100	335	Peak
2483.5	43.07	50.64	54	-10.93	32.05	6.31	45.93	100	335	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	60.05	67.7	74	-13.95	32.14	6.18	45.97	100	195	Peak
2390	45.95	53.6	54	-8.05	32.14	6.18	45.97	100	195	Average
2412	98.97	106.53	/	/	32.19	6.21	45.96	100	195	Peak
2412	92.28	99.84	/	/	32.19	6.21	45.96	100	195	Average
2483.5	51.77	59.03	74	-22.23	32.36	6.31	45.93	100	195	Peak
2483.5	42.92	50.18	54	-11.08	32.36	6.31	45.93	100	195	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2412MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P22060025RF02

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.99	59.03	74	-23.01	31.75	6.18	45.97	100	335	Peak
2390	42.62	50.66	54	-11.38	31.75	6.18	45.97	100	335	Average
2437	105.61	113.42	/	/	31.9	6.24	45.95	100	335	Peak
2437	99.14	106.95	/	/	31.9	6.24	45.95	100	335	Average
2483.5	51.73	59.3	74	-22.27	32.05	6.31	45.93	100	335	Peak
2483.5	42.77	50.34	54	-11.23	32.05	6.31	45.93	100	335	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	51.15	58.8	74	-22.85	32.14	6.18	45.97	100	195	Peak
2390	42.03	49.68	54	-11.97	32.14	6.18	45.97	100	195	Average
2437	99.45	106.91	/	/	32.25	6.24	45.95	100	195	Peak
2437	92.33	99.79	/	/	32.25	6.24	45.95	100	195	Average
2483.5	51.38	58.64	74	-22.62	32.36	6.31	45.93	100	195	Peak
2483.5	42.59	49.85	54	-11.41	32.36	6.31	45.93	100	195	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P22060025RF02

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.22	58.26	74	-23.78	31.75	6.18	45.97	100	335	Peak
2390	42.01	50.05	54	-11.99	31.75	6.18	45.97	100	335	Average
2462	105.3	112.98	/	/	31.98	6.28	45.94	100	335	Peak
2462	98.33	106.01	/	/	31.98	6.28	45.94	100	335	Average
2483.5	64.61	72.18	74	-9.39	32.05	6.31	45.93	100	335	Peak
2483.5	50.27	57.84	54	-3.73	32.05	6.31	45.93	100	335	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	51.43	59.08	74	-22.57	32.14	6.18	45.97	100	195	Peak
2390	42.2	49.85	54	-11.8	32.14	6.18	45.97	100	195	Average
2462	99.58	106.93	/	/	32.31	6.28	45.94	100	195	Peak
2462	91.5	98.85	/	/	32.31	6.28	45.94	100	195	Average
2483.5	60.99	68.25	74	-13.01	32.36	6.31	45.93	100	195	Peak
2483.5	46.63	53.89	54	-7.37	32.36	6.31	45.93	100	195	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.



**BUREAU
VERITAS**


Test Report No.: W7L-P22060025RF02

Worst case harmonic:

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m		
1	4824.000	44.84	46.25	74.00	-29.16	-1.41	Peak	Horizontal
2	4824.000	36.15	37.56	54.00	-17.85	-1.41	Average	Horizontal
3 PK	7236.000	45.14	43.37	74.00	-28.86	1.77	Peak	Horizontal
4 PP	7236.000	36.90	35.13	54.00	-17.10	1.77	Average	Horizontal






**BUREAU
VERITAS**

Test Report No.: W7L-P22060025RF02

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m		
1	4824.000	44.66	45.87	74.00	-29.34	-1.21	Peak	Vertical
2	4824.000	35.71	36.92	54.00	-18.29	-1.21	Average	Vertical
3 PK	7236.000	46.06	44.18	74.00	-27.94	1.88	Peak	Vertical
4 PP	7236.000	37.19	35.31	54.00	-16.81	1.88	Average	Vertical



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2412MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P22060025RF02

BELOW 1GHz WORST-CASE DATA:

30 MHz – 1GHz data:


BT-LE _1M

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
40.67	25.65	49.74	40	-14.35	12.75	0.37	37.21	100	360	QP
125.06	32.75	59.84	43.5	-10.75	9	0.6	36.69	100	360	QP
210.42	38.49	62.27	43.5	-5.01	11.76	0.75	36.29	100	360	QP
375.32	41.19	60.88	46	-4.81	15.66	1.03	36.38	100	360	QP
455.83	28.71	46.82	46	-17.29	17.26	1.16	36.53	100	360	QP
599.39	31.94	47.74	46	-14.06	19.69	1.36	36.85	100	360	QP

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value





BUREAU
VERITAS


Test Report No.: W7L-P22060025RF02

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
41.64	36.33	61.17	40	-3.67	11.97	0.37	37.18	100	0	QP
201.69	31.46	55.47	43.5	-12.04	11.54	0.74	36.29	100	0	QP
250.19	31.99	54.82	46	-14.01	12.61	0.83	36.27	100	0	QP
375.32	34.44	54.06	46	-11.56	15.73	1.03	36.38	100	0	QP
500.45	28.16	45.95	46	-17.84	17.61	1.22	36.62	100	0	QP
554.77	25.09	41.84	46	-20.91	18.7	1.3	36.75	100	0	QP

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



**ABOVE 1GHz TEST DATA**

Note: 1. For radiated emissions testing , the full testing range of different modes have been scanned , only the worst case harmonic data is reported in the sheet.

2. All other emissions were greater than 20dB below the limit was not recorded.

3. For higher frequency, the emission is too low to be detected.

BT-LE _1M

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	51.3	59.34	74	-22.7	31.75	6.18	45.97	100	340	Peak
2390	43.78	51.82	54	-10.22	31.75	6.18	45.97	100	340	Average
2402	99.99	107.98	/	/	31.79	6.19	45.97	100	340	Peak
2402	98	105.99	/	/	31.79	6.19	45.97	100	340	Average
2483.5	52.55	60.12	74	-21.45	32.05	6.31	45.93	100	340	Peak
2483.5	44.16	51.73	54	-9.84	32.05	6.31	45.93	100	340	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	51.55	59.2	74	-22.45	32.14	6.18	45.97	100	185	Peak
2390	44.19	51.84	54	-9.81	32.14	6.18	45.97	100	185	Average
2402	96.6	104.22	/	/	32.16	6.19	45.97	100	185	Peak
2402	94.61	102.23	/	/	32.16	6.19	45.97	100	185	Average
2483.5	52.35	59.61	74	-21.65	32.36	6.31	45.93	100	185	Peak
2483.5	44.64	51.9	54	-9.36	32.36	6.31	45.93	100	185	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2402MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P22060025RF02

CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	51.13	59.17	74	-22.87	31.75	6.18	45.97	100	340	Peak
2390	43.98	52.02	54	-10.02	31.75	6.18	45.97	100	340	Average
2440	99.46	107.25	/	/	31.91	6.25	45.95	100	340	Peak
2440	99.15	106.94	/	/	31.91	6.25	45.95	100	340	Average
2483.5	52.67	60.24	74	-21.33	32.05	6.31	45.93	100	340	Peak
2483.5	44.1	51.67	54	-9.9	32.05	6.31	45.93	100	340	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	52.3	59.95	74	-21.7	32.14	6.18	45.97	100	185	Peak
2390	44.3	51.95	54	-9.7	32.14	6.18	45.97	100	185	Average
2440	94.16	101.6	/	/	32.26	6.25	45.95	100	185	Peak
2440	93.8	101.24	/	/	32.26	6.25	45.95	100	185	Average
2483.5	52.08	59.34	74	-21.92	32.36	6.31	45.93	100	185	Peak
2483.5	44.57	51.83	54	-9.43	32.36	6.31	45.93	100	185	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2440MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P22060025RF02

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.88	58.92	74	-23.12	31.75	6.18	45.97	100	340	Peak
2390	43.7	51.74	54	-10.3	31.75	6.18	45.97	100	340	Average
2480	101.32	108.91	/	/	32.04	6.3	45.93	100	340	Peak
2480	99.18	106.77	/	/	32.04	6.3	45.93	100	340	Average
2483.5	51.75	59.32	74	-22.25	32.05	6.31	45.93	100	340	Peak
2483.5	44.53	52.1	54	-9.47	32.05	6.31	45.93	100	340	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	51.3	58.95	74	-22.7	32.14	6.18	45.97	100	185	Peak
2390	44.57	52.22	54	-9.43	32.14	6.18	45.97	100	185	Average
2480	95.97	103.25	/	/	32.35	6.3	45.93	100	185	Peak
2480	95.37	102.65	/	/	32.35	6.3	45.93	100	185	Average
2483.5	52.6	59.86	74	-21.4	32.36	6.31	45.93	100	185	Peak
2483.5	44.77	52.03	54	-9.23	32.36	6.31	45.93	100	185	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2480MHz: Fundamental frequency.



**BUREAU
VERITAS**


Test Report No.: W7L-P22060025RF02

Worst case harmonic:

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m		
1	PK 4960.000	45.04	46.23	74.00	-28.96	-1.19	Peak	Horizontal
2	PP 4960.000	36.04	37.23	54.00	-17.96	-1.19	Average	Horizontal
3	7440.000	44.26	42.28	74.00	-29.74	1.98	Peak	Horizontal
4	7440.000	35.63	33.65	54.00	-18.37	1.98	Average	Horizontal






**BUREAU
VERITAS**

Test Report No.: W7L-P22060025RF02

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m		
1	4960.000	45.17	46.16	74.00	-28.83	-0.99	Peak	Vertical
2	PP 4960.000	36.83	37.82	54.00	-17.17	-0.99	Average	Vertical
3	PK 7440.000	45.36	43.35	74.00	-28.64	2.01	Peak	Vertical
4	7440.000	36.63	34.62	54.00	-17.37	2.01	Average	Vertical



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2480MHz: Fundamental frequency.



3.3 6 dB BANDWIDTH MEASUREMENT

3.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

3.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Meter	ANRITSU	ML2495A	1506002	Feb. 22,22	Feb. 21,23
EXA Signal Analyzer	KEYSIGHT	N9010A-526	MY54510322	Feb. 18,22	Feb. 17,23
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510355	May.15,22	May.14,23
Power Sensor	ANRITSU	MA2411B	1339352	May. 06,22	May. 05,23

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in RF Oven room.

3.3.3 TEST PROCEDURE


1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



3.3.4 DEVIATION FROM TEST STANDARD

No deviation.

3.3.5 TEST SETUP



3.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



Test Report No.: W7L-P22060025RF02

3.3.7 TEST RESULTS

Please Refer to Appendix1/2 Of this test report.




3.4 CONDUCTED OUTPUT POWER

3.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

3.4.2 TEST SETUP



3.4.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

3.4.5 DEVIATION FROM TEST STANDARD

No deviation.

3.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



Test Report No.: W7L-P22060025RF02

3.4.7 TEST RESULTS

3.4.7.1 MAXIMUM PEAK OUTPUT POWER

Please Refer to Appendix1/2 Of this test report.



Test Report No.: W7L-P22060025RF02

3.4.7.2 AVERAGE OUTPUT POWER (FOR REFERENCE)

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

Please Refer to Appendix1/2 Of this test report.




3.5 POWER SPECTRAL DENSITY MEASUREMENT

3.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

3.5.2 TEST SETUP



3.5.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.5.4 TEST PROCEDURE

1. Set the span to 1.5 times the DTS bandwidth
2. Set the RBW = 3 kHz, VBW $\geq 3 \times$ RBW, Detector = peak.
3. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

3.5.5 DEVIATION FROM TEST STANDARD

No deviation.

3.5.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



Test Report No.: W7L-P22060025RF02

3.5.7 TEST RESULTS

Please Refer to Appendix1/2 Of this test report.




3.6 OUT OF BAND EMISSION MEASUREMENT

3.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

3.6.2 TEST SETUP



3.6.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

3.6.5 DEVIATION FROM TEST STANDARD

No deviation.

3.6.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.6.7 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.

Please Refer to Appendix1/2 Of this test report.



Test Report No.: W7L-P22060025RF02

4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.: W7L-P22060025RF02

5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.



6 Appendix 1 WLAN 2.4G

DTS BANDWIDTH

TEST RESULT

TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	6.560	2408.920	2415.480	0.5	PASS
		2437	7.480	2433.480	2440.960	0.5	PASS
		2462	7.000	2458.480	2465.480	0.5	PASS
11G	Ant1	2412	14.960	2404.480	2419.440	0.5	PASS
		2437	15.120	2429.440	2444.560	0.5	PASS
		2462	15.000	2454.440	2469.440	0.5	PASS
11N20SISO	Ant1	2412	12.600	2406.920	2419.520	0.5	PASS
		2437	15.480	2429.400	2444.880	0.5	PASS
		2462	13.880	2455.680	2469.560	0.5	PASS



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02

TEST GRAPHS

11B_Ant1_2412



11B_Ant1_2437



11B_Ant1_2462



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11G_Ant1_2412



11G_Ant1_2437



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11G_Ant1_2462



11N20SISO_Ant1_2412



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11N20SISO_Ant1_2437



11N20SISO_Ant1_2462



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



**OCCUPIED CHANNEL BANDWIDTH****TEST RESULT**

TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	11.358	2406.532	2417.890	---	---
		2437	11.008	2431.689	2442.697	---	---
		2462	10.879	2456.633	2467.512	---	---
11G	Ant1	2412	16.493	2403.827	2420.320	---	---
		2437	16.445	2428.921	2445.366	---	---
		2462	16.324	2453.855	2470.179	---	---
11N20SISO	Ant1	2412	16.482	2403.854	2420.336	---	---
		2437	16.469	2428.838	2445.307	---	---
		2462	16.380	2453.806	2470.186	---	---




BUREAU
VERITAS


Test Report No.: W7L-P22060025RF02

TEST GRAPHS

11B_Ant1_2412



11B_Ant1_2437




11B_Ant1_2462




BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11G_Ant1_2412




11G_Ant1_2437




BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11G_Ant1_2462




11N20SISO_Ant1_2412




BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11N20SISO_Ant1_2437



11N20SISO_Ant1_2462



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



**MAXIMUM CONDUCTED OUTPUT POWER****TEST RESULT**

TestMode	TX Mod.	Frequency [MHz]	Avg. power [dBm]	Peak power [dBm]	MAX Peak power [mw]	Limit [dBm]	IC EIRP [dBm]	IC EIRP [mw]	IC EIRP Limit [dBm]	Verdict	Power Setting
11B	SISO	2412	14.94	18.03	63.53	≤30.00	19.03	79.98	≤36.00	PASS	15
		2437	15.06	18.27	67.14	≤30.00	19.27	84.53	≤36.00	PASS	15
		2462	15.27	18.51	70.96	≤30.00	19.51	89.33	≤36.00	PASS	15
11g	SISO	2412	13.01	23.64	231.21	≤30.00	24.64	291.07	≤36.00	PASS	13
		2437	13.77	22.48	177.01	≤30.00	23.48	222.84	≤36.00	PASS	14
		2462	13.14	23.58	228.03	≤30.00	24.58	287.08	≤36.00	PASS	12.5
11N20	SISO	2412	12.41	22.06	160.69	≤30.00	23.06	202.30	≤36.00	PASS	13
		2437	12.65	22.26	168.27	≤30.00	23.26	211.84	≤36.00	PASS	13
		2462	12.27	23.05	201.84	≤30.00	24.05	254.10	≤36.00	PASS	12.5

**MAXIMUM POWER SPECTRAL DENSITY****TEST RESULT**

TestMode	Antenna	Freq(MHz)	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
11B	Ant1	2412	-15.75	≤8.00	PASS
		2437	-15.26	≤8.00	PASS
		2462	-14.69	≤8.00	PASS
11G	Ant1	2412	-17.94	≤8.00	PASS
		2437	-17.25	≤8.00	PASS
		2462	-16.89	≤8.00	PASS
11N20SISO	Ant1	2412	-18.27	≤8.00	PASS
		2437	-17.95	≤8.00	PASS
		2462	-17.43	≤8.00	PASS



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02

TEST GRAPHS

11B_Ant1_2412



11B_Ant1_2437



11B_Ant1_2462



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11G_Ant1_2412




11G_Ant1_2437



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11G_Ant1_2462



11N20SISO_Ant1_2412



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11N20SISO_Ant1_2437



11N20SISO_Ant1_2462



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



**REFERENCE LEVEL MEASUREMENT****TEST RESULT**

TestMode	Antenna	Freq(MHz)	Max.Point[MHz]	Result[dBm]
11B	Ant1	2412	2410.47	-2.91
		2437	2436.00	-2.40
		2462	2462.97	-1.77
11G	Ant1	2412	2413.28	-6.66
		2437	2436.36	-6.40
		2462	2461.35	-6.01
11N20SISO	Ant1	2412	2412.25	-7.75
		2437	2437.60	-7.01
		2462	2463.25	-6.20



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02

TEST GRAPHS

11B_Ant1_2412



11B_Ant1_2437



11B_Ant1_2462



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11G_Ant1_2412



11G_Ant1_2437



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11G_Ant1_2462



11N20SISO_Ant1_2412



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11N20SISO_Ant1_2437



11N20SISO_Ant1_2462



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



**BAND EDGE MEASUREMENTS****TEST RESULT**

TestMode	Antenna	ChName	Freq(MHz)	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	Low	2412	-2.91	-43.07	≤-22.91	PASS
		High	2462	-1.77	-44.01	≤-21.77	PASS
11G	Ant1	Low	2412	-6.66	-44.05	≤-26.66	PASS
		High	2462	-6.01	-44.3	≤-26.01	PASS
11N20SISO	Ant1	Low	2412	-7.75	-43.63	≤-27.75	PASS
		High	2462	-6.20	-44.27	≤-26.2	PASS




BUREAU
VERITAS


Test Report No.: W7L-P22060025RF02

TEST GRAPHS

11B_Ant1_Low_2412



11B_Ant1_High_2462




11G_Ant1_Low_2412




BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11G_Ant1_High_2462



11N20SISO_Ant1_Low_2412




BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11N20SISO_Ant1_High_2462



**CONDUCTED SPURIOUS EMISSION****TEST RESULT**

TestMode	Antenna	Freq(MHz)	FreqRange [Mhz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
11B	Ant1	2412	30~1000	-2.91	-41.32	≤-22.91	PASS
			1000~26500	-2.91	-38.1	≤-22.91	PASS
		2437	30~1000	-2.40	-43.01	≤-22.4	PASS
			1000~26500	-2.40	-37.47	≤-22.4	PASS
		2462	30~1000	-1.77	-42.67	≤-21.77	PASS
			1000~26500	-1.77	-37.38	≤-21.77	PASS
11G	Ant1	2412	30~1000	-6.66	-41.7	≤-26.66	PASS
			1000~26500	-6.66	-37.06	≤-26.66	PASS
		2437	30~1000	-6.40	-43.25	≤-26.4	PASS
			1000~26500	-6.40	-37.46	≤-26.4	PASS
		2462	30~1000	-6.01	-42.91	≤-26.01	PASS
			1000~26500	-6.01	-37.33	≤-26.01	PASS
11N20SISO	Ant1	2412	30~1000	-7.75	-43.05	≤-27.75	PASS
			1000~26500	-7.75	-37.56	≤-27.75	PASS
		2437	30~1000	-7.01	-43.35	≤-27.01	PASS
			1000~26500	-7.01	-37.62	≤-27.01	PASS
		2462	30~1000	-6.20	-43.42	≤-26.2	PASS
			1000~26500	-6.20	-37.75	≤-26.2	PASS




BUREAU
VERITAS


Test Report No.: W7L-P22060025RF02

TEST GRAPHS

11B_Ant1_2412_30~1000



11B_Ant1_2412_1000~26500



11B_Ant1_2437_30~1000



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11B_Ant1_2437_1000~26500




11B_Ant1_2462_30~1000



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11B_Ant1_2462_1000~26500




11G_Ant1_2412_30~1000



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11G_Ant1_2412_1000~26500




11G_Ant1_2437_30~1000



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11G_Ant1_2437_1000~26500




11G_Ant1_2462_30~1000



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11G_Ant1_2462_1000~26500




11N20SISO_Ant1_2412_30~1000




BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11N20SISO_Ant1_2412_1000~26500




11N20SISO_Ant1_2437_30~1000



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11N20SISO_Ant1_2437_1000~26500




11N20SISO_Ant1_2462_30~1000



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11N20SISO_Ant1_2462_1000~26500



**DUTY CYCLE****TEST RESULT**

TestMode	Antenna	Freq(MHz)	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]	Verdict
11B	Ant1	2412	8.42	8.52	98.83	---
		2437	8.41	8.52	98.71	---
		2462	8.41	8.52	98.71	---
11G	Ant1	2412	1.40	1.50	93.33	---
		2437	1.39	1.50	92.67	---
		2462	1.39	1.50	92.67	---
11N20SISO	Ant1	2412	1.31	1.41	92.91	---
		2437	1.40	1.50	93.33	---
		2462	1.39	1.50	92.67	---




BUREAU
VERITAS


Test Report No.: W7L-P22060025RF02

TEST GRAPHS

11B_Ant1_2412



11B_Ant1_2437




11B_Ant1_2462




BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11G_Ant1_2412




11G_Ant1_2437




BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11G_Ant1_2462




11N20SISO_Ant1_2412




BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



11N20SISO_Ant1_2437




11N20SISO_Ant1_2462



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02





7 Appendix 2 BLE

DTS BANDWIDTH

TEST RESULT

TestMode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.696	2401.648	2402.344	0.5	PASS
		2440	0.700	2439.652	2440.352	0.5	PASS
		2480	0.696	2479.644	2480.340	0.5	PASS



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02

TEST GRAPHS

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



BLE_1M_Ant1_2480





Test Report No.: W7L-P22060025RF02

OCCUPIED CHANNEL BANDWIDTH

TEST RESULT

TestMode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.0544	2401.477	2402.532	---	---
		2440	1.0548	2439.481	2440.536	---	---
		2480	1.0538	2479.485	2480.539	---	---




BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02

TEST GRAPHS

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



BLE_1M_Ant1_2480



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



**MAXIMUM CONDUCTED OUTPUT POWER****TEST RESULT**

TestMod e	Antenn a	Channe l	Averag e power [dBm]	Peak powe r [dBm]	Peak powe r [mw]	Conducte d Limit [dBm]	IC EIRP [dBm]	IC EIR P [mw]	IC EIRP Limit [dBm]	Verdic t	Power Settin g
BLE_1M	Ant1	2402	3.87	6.05	4.03	≤30	7.05	5.07	≤36	PASS	Default
		2440	4.47	6.74	4.72	≤30	7.74	5.94	≤36	PASS	Default
		2480	4.43	6.62	4.59	≤30	7.62	5.78	≤36	PASS	Default
Note:EIRP=Peak Power+Gain;Gain=1dBi											



Test Report No.: W7L-P22060025RF02

MAXIMUM POWER SPECTRAL DENSITY

TEST RESULT

TestMode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-9.81	≤8.00	PASS
		2440	-9.23	≤8.00	PASS
		2480	-9.76	≤8.00	PASS




BUREAU
VERITAS


Test Report No.: W7L-P22060025RF02

TEST GRAPHS

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440




BLE_1M_Ant1_2480



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02





Test Report No.: W7L-P22060025RF02

REFERENCE LEVEL MEASUREMENT

TEST RESULT

TestMode	Antenna	Freq(MHz)	Max.Point[MHz]	Result[dBm]
BLE_1M	Ant1	2402	2402.00	3.88
		2440	2439.99	4.44
		2480	2480.00	4.05



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02

TEST GRAPHS

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



BLE_1M_Ant1_2480



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02





Test Report No.: W7L-P22060025RF02

BAND EDGE MEASUREMENTS

TEST RESULT

TestMode	Antenna	ChName	Frequency [MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	3.88	-45.84	≤ -16.12	PASS
		High	2480	4.05	-45.05	≤ -15.95	PASS




BUREAU
VERITAS


Test Report No.: W7L-P22060025RF02

TEST GRAPHS

BLE_1M_Ant1_Low_2402



BLE_1M_Ant1_High_2480





BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02

CONDUCTED SPURIOUS EMISSION

TEST RESULT

TestMode	Antenna	Frequency[MHz]	FreqRange [MHz]	RefLevel [dBm]	Result [dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	30~1000	3.88	-53.62	≤-16.12	PASS
			1000~26500	3.88	-38.63	≤-16.12	PASS
		2440	30~1000	4.44	-54.69	≤-15.56	PASS
			1000~26500	4.44	-38.34	≤-15.56	PASS
		2480	30~1000	4.05	-54.39	≤-15.95	PASS
			1000~26500	4.05	-38.28	≤-15.95	PASS




BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02

TEST GRAPHS

BLE_1M_Ant1_2402_30~1000



BLE_1M_Ant1_2402_1000~26500



BLE_1M_Ant1_2440_30~1000




BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



BLE_1M_Ant1_2440_1000~26500




BLE_1M_Ant1_2480_30~1000



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



BLE_1M_Ant1_2480_1000~26500





Test Report No.: W7L-P22060025RF02

DUTY CYCLE

TEST RESULT

TestMode	Antenna	Frequency[MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor[dB]
BLE_1M	Ant1	2402	0.39	0.63	61.90	2.08
		2440	0.39	0.63	61.90	2.08
		2480	0.39	0.63	61.90	2.08




BUREAU
VERITAS


Test Report No.: W7L-P22060025RF02

TEST GRAPHS

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440




BLE_1M_Ant1_2480



BUREAU
VERITAS

Test Report No.: W7L-P22060025RF02



---END---