

**CFR 47 FCC PART 22 H
CFR 47 FCC PART 24 E
CFR 47 FCC PART 27
RSS-132, RSS-133, RSS-139**

TEST REPORT

For

UNATTENDED PAYMENT TERMINAL

MODEL NUMBER: IM30

REPORT NUMBER: 4791789077-1-RF-6

ISSUE DATE: June 18, 2026

**FCC ID: V5PIM304GBWLC
IC: 11689A-IM304GBWLC
HVIN: IM30 4GBWLC**

Prepared for

**PAX Technology Limited
FLAT/RM 2504, 25/F, SUN HUNG KAI CENTRE, 30 HARBOUR ROAD, WANCHAI,
HK, China**

Prepared by

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch
Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan,
Guangdong, China**

**Tel: +86 769 22038881
Fax: +86 769 33244054
Website: www.ul.com**

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	June 18, 2026	Initial Issue	\

Note:

1. This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

2. The measurement result for the sample received is <Pass> according to < CFR 47 FCC PART 22 H > < CFR 47 FCC PART 24 E > < CFR 47 FCC PART 27 > < RSS-132, RSS-133, RSS-139 > when < Simple Acceptance > decision rule is applied.

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. CALIBRATION AND UNCERTAINTY	6
4.1. MEASURING INSTRUMENT CALIBRATION.....	6
4.2. MEASUREMENT UNCERTAINTY	6
5. EQUIPMENT UNDER TEST	7
5.1. DESCRIPTION OF EUT	7
5.2. TEST CHANNEL CONFIGURATION	7
5.3. MAXIMUM ERP/EIRP POWER AND EMISSION DESIGNATOR	8
5.4. WORST-CASE CONFIGURATION AND MODE	9
5.5. DESCRIPTION OF AVAILABLE ANTENNAS	10
5.1. DESCRIPTION OF TEST SETUP	11
6. MEASURING INSTRUMENT AND SOFTWARE USED	12
7. ANTENNA TERMINAL TEST RESULTS	13
7.1. EFFECTIVE (ISOTROPIC) RADIATED POWER OF TRANSMITTER.....	13
7.2. PEAK TO AVERAGE RADIO	15
7.3. OCCUPIED BANDWIDTH	16
7.4. BAND EDGE EMISSIONS.....	17
7.5. SPURIOUS EMISSION AT ANTENNA TERMINAL.....	19
7.6. FREQUENCY STABILITY	21
7.7. RADIATED SPURIOUS EMISSIONS	23

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: PAX Technology Limited
Address: FLAT/RM 2504, 25/F, SUN HUNG KAI CENTRE, 30 HARBOUR ROAD, WANCHAI, HK, China

Manufacturer Information

Company Name: PAX Computer Technology (Shenzhen) Co., Ltd.
Address: Room 701, PAX Technology Building, Shanxia Community, Pinghu Sub-district, Longgang District, Shenzhen, China

EUT Information

EUT Name: UNATTENDED PAYMENT TERMINAL
Model: IM30
Brand: Pax
Sample Received Date: May 19, 2026
Sample Status: Normal
Sample ID: 9755003
Date of Tested: May 21, 2026 to June 16, 2026


APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 22 H	PASS
CFR 47 FCC PART 24 E	PASS
CFR 47 FCC PART 27	PASS
RSS-132, RSS-133, RSS-139	PASS

Prepared By:



Daniel Zhang
Project Engineer

Checked By:



Kebo Zhang
Operations Leader

Approved By:



Stephen Guo
Operations Manager

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.26-2015, 971168 D01 Power Meas License Digital Systems v03r01, 971168 D02 Misc Rev Approv License Devices v02r01, 412172 D01 v01r01 Determining ERP and EIRP, CFR 47 FCC Part 2, Part 22 H, Part 24 E, Part 27, RSS-132, RSS-133, RSS-139.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046. VCCI (Registration No.: C-20202, G-20240, R-20248 and T-20202) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the membership No. is 3793. Facility Name: Chamber E, the VCCI registration No. is G-20240 and R-20248 Shielding Room F, the VCCI registration No. is C-20202 and T-20202
---------------------------	--

Note:

1. All tests measurement facilities use to collect the measurement data are located at Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan, Guangdong, China.
2. The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field site and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.
3. Measurements have been performed in an anechoic chamber for below 30 MHz and compared with the measurement result that obtained in an open field site and the measurements result have been corrected to represent the result collected in an OFS.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognize national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 40 GHz)	5.78 dB (1 GHz-18 GHz)
	5.23dB (18 GHz-26 GHz)
	5.64 dB (26 GHz-40 GHz)
Bandwidth	1.1 %
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95 % confidence level using a coverage factor of k=2.	

Remark: For Radiated Emission measurements (200 MHz - 18 GHz), the EUT support table is made of Expanded Polystyrene (EPS). This material is characterized by a low dielectric constant, as recognized in CISPR 16-1-4, to minimize its influence on field strength measurements. This influence has been considered in the uncertainty budget.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	UNATTENDED PAYMENT TERMINAL
Model	IM30
Normal Test Voltage:	AC 120V 60Hz

5.2. TEST CHANNEL CONFIGURATION

Band	Mode	Low	Middle	High
WCDMA Band 2	Rel.99/HSDPA/HSUPA	9262	9400	9538
		1852.4 MHz	1880.0 MHz	1907.6 MHz
WCDMA Band 4	Rel.99/HSDPA/HSUPA	1312	1413	1513
		1712.4 MHz	1732.6 MHz	1752.6 MHz
WCDMA Band 5	Rel.99/HSDPA/HSUPA	4132	4182	4233
		826.4 MHz	836.4 MHz	846.6 MHz

5.3. MAXIMUM ERP/EIRP POWER AND EMISSION DESIGNATOR

WCDMA Band2					
Part 24					
EIRP Limit (W)		2			
Antenna Gain (dBi)		1.69			
Mode	Freq. Range (MHz)	Conducted Average power (dBm)	EIRP (W)	99% OBW (MHz)	Emission Designator
REL. 99	1852.4 ~ 1907.6	23.60	0.338	4.090	4M09F9W
HSDPA		22.53	0.264	4.091	4M09F9W
HSUPA		22.47	0.261	4.123	4M12F9W

WCDMA Band4					
Part 27					
EIRP Limit (W)		1			
Antenna Gain (dBi)		1.49			
Mode	Freq. Range (MHz)	Conducted Average power (dBm)	EIRP (W)	99% OBW (MHz)	Emission Designator
REL. 99	1712.4 ~ 1752.6	24.16	0.367	4.091	4M09F9W
HSDPA		23.20	0.294	4.096	4M10F9W
HSUPA		23.19	0.294	4.131	4M13F9W

WCDMA Band5					
Part 22					
ERP Limit (W) for FCC		7			
Antenna Gain (dBi)		2.82			
Mode	Freq. Range (MHz)	Conducted Average power (dBm)	ERP (W)	99% OBW (MHz)	Emission Designator
REL. 99	826.4 ~ 846.6	23.51	0.262	4.120	4M12F9W
HSDPA		22.53	0.209	4.119	4M12F9W
HSUPA		22.51	0.208	4.147	4M15F9W

5.4. WORST-CASE CONFIGURATION AND MODE

The radiated spurious emissions measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT was investigated in three orthogonal orientations X, Y and Z. It was determined that X orientation was the worst-case orientation.

Radiated spurious emissions were investigated below 30 MHz, 30 MHz - 1 GHz and above 1 GHz. There were no emissions found on below 1GHz and above 18 GHz, the emissions between 1 GHz – 18 GHz were tested at the low, mid, high channel and the worst configuration. Only the worst result is reported.

5.5. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Band	Antenna Type	MAX Antenna Gain (dBi)
Main	WCDMA Band 2	Dipole	1.69
Main	WCDMA Band 4	Dipole	1.49
Main	WCDMA Band 5	Dipole	2.82
Main	WCDMA Band 2	FPC	-0.73
Main	WCDMA Band 4	FPC	-2.24
Main	WCDMA Band 5	FPC	-2.67


Note: All the antennas have been tested, only the worst data for dipole main antenna was recorded in the report.

Band	Transmit and Receive Mode	Description
WCDMA Band 2	☒ 1TX, 2RX	Only one of the two main antennas can be used as a transmitting/receiving antenna, and they cannot work together. The DIV antenna can be used as a receiving antenna
WCDMA Band 4	☒ 1TX, 2RX	Only one of the two main antennas can be used as a transmitting/receiving antenna, and they cannot work together. The DIV antenna can be used as a receiving antenna
WCDMA Band 5	☒ 1TX, 2RX	Only one of the two main antennas can be used as a transmitting/receiving antenna, and they cannot work together. The DIV antenna can be used as a receiving antenna


Note: The value of the antenna gain was declared by customer.

5.1. DESCRIPTION OF TEST SETUP

Conducted



Radiated



6. MEASURING INSTRUMENT AND SOFTWARE USED

Antenna Terminal Test						
Instrument						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
☒	Spectrum Analyzer	R&S	FSW	1312.8000K26-103950-sj	Sep. 12, 2025	Sep. 11, 2026
☒	Wideband Radio Communication Tester	R&S	CMW500	155523	Sep. 12, 2025	Sep. 11, 2026
Software						
Used	Description		Manufacturer	Name		Version
☒	Tonsend Cellular Test System		Tonsend	JS1120 RF Auto Test System		3.1.46
Radiated Test						
Instrument						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
☒	MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Sep. 12, 2025	Sep. 11, 2026
☒	Hybrid Log Periodic Antenna	TDK	HLP-3003C	130959	June.28, 2024	June.27, 2027
☒	Preamplifier	HP	8447D	2944A09099	Sep. 12, 2025	Sep. 11, 2026
☒	EMI Measurement Receiver	R&S	ESR26	101377	Sep. 12, 2025	Sep. 11, 2026
☒	Horn Antenna	TDK	HRN-0118	130940	Dec. 12, 2024	Dece. 11, 2027
☒	Horn Antenna	Schwarzbeck	BBHA9170	697	Jun. 30, 2024	Jun. 29, 2027
☒	Preamplifier	TDK	PA-02-0118	TRS-305-00067	Sep. 12, 2025	Sep. 11, 2026
☒	Preamplifier	TDK	PA-02-2	TRS-307-00003	Sep. 12, 2025	Sep. 11, 2026
☒	Loop antenna	Schwarzbeck	1519B	00008	Dec.09, 2024	Dec.08,2027
☒	High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Sep.12, 2025	Sep.11, 2026
Software						
Used	Description		Manufacturer	Name		Version
☒	Test Software for Radiated disturbance		Farad	EZ-EMC		Ver. UL-3A1

7. ANTENNA TERMINAL TEST RESULTS

7.1. EFFECTIVE (ISOTROPIC) RADIATED POWER OF TRANSMITTER

RULE PART(S)

FCC: §2.1046, §22.913, §24.232, §27.50

RSS-132, RSS-133, RSS-139

LIMITS

22.913(a) The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

24.232(c) Mobile/portable stations are limited to 2 watts e.i.r.p. peak power and the equipment must employ means to limit the power to the minimum necessary for successful communications.

27.50(c) Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

27.50(d) Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watts EIRP.

27.50(h) Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

In addition, when the transmitter power is measured in terms of average value, the peak-to-average ratio of the power shall not exceed 13 dB.

TEST PROCEDURE

Refer to ANSI C63.26:2015 and KDB 971168 D01 Section 5.6

$ERP/ EIRP = P_{Meas} + GT - LC$

where:

ERP or EIRP = effective or equivalent isotropically radiated power, respectively (expressed in the same units as P_{Meas} , typically dBW or dBm);


P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

GT = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

LC = signal attenuation in the connecting cable between the transmitter and antenna, in dB

The transmitter has a maximum output powers as follows and maximum ERP/EIRP is tabulated in section 5.3.

TEST SETUP



TEST ENVIRONMENT

Temperature	22.6°C	Relative Humidity	58.2%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V 60HZ

RESULTS

Band II		Channel No.		
		9262	9400	9538
		Fre. (MHz)		
		1852.4	1880	1907.6
WCDMA	12.2kbps RMC	23.42	23.25	23.6
HSDPA	Subtest 1	22.23	22.17	22.53
	Subtest 2	21.77	21.67	22.01
	Subtest 3	21.69	21.6	21.95
	Subtest 4	21.8	21.61	21.95
HSUPA	Subtest 1	22.28	21.98	22.34
	Subtest 2	20.35	20.11	20.45
	Subtest 3	21.33	20.97	21.44
	Subtest 4	20.37	20.12	20.46
	Subtest 5	22.29	22.05	22.47

Band IV		Channel No.		
		1312	1413	1513
		Fre. (MHz)		
		1712.4	1732.6	1752.6
WCDMA	12.2kbps RMC	24.16	23.91	23.98
HSDPA	Subtest 1	23.2	22.81	22.93
	Subtest 2	22.65	22.37	22.48
	Subtest 3	22.82	22.5	22.43
	Subtest 4	22.73	22.52	22.44
HSUPA	Subtest 1	23.16	22.78	22.91
	Subtest 2	21.18	20.83	21.04
	Subtest 3	22.13	21.86	21.83
	Subtest 4	21.23	20.99	21.08
	Subtest 5	23.19	22.89	22.93

Band V		Channel No.		
		4132	4182	4233
		Fre. (MHz)		
		826.4	836.4	846.6
WCDMA	12.2kbps RMC	23.42	23.51	23.47
HSDPA	Subtest 1	22.31	22.53	22.4
	Subtest 2	21.9	21.94	21.93
	Subtest 3	21.94	21.95	21.94
	Subtest 4	21.97	21.98	21.98
HSUPA	Subtest 1	22.37	22.51	22.41
	Subtest 2	20.46	20.58	20.49
	Subtest 3	21.47	21.51	21.57
	Subtest 4	20.46	20.5	20.52
	Subtest 5	22.4	22.51	22.37

7.2. PEAK TO AVERAGE RADIO

LIMITS


In addition, when the transmitter power is measured in terms of average value, the peak-to-average ratio of the power shall not exceed 13 dB.

TEST PROCEDURE

Refer to KDB 971168 D01 Power Meas License Digital Systems v03r01;

The transmitter output was connected to a CMW500 Test Set and configured to operate at maximum power. The PAR was measured on the Spectrum Analyzer.

TEST SETUP



TEST ENVIRONMENT

Temperature	22.6°C	Relative Humidity	58.2%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V 60HZ

RESULTS

Middle was used to measure as the worst case. The results from all CCDF plots are passed with 13dB peak-to-average power ratio criteria.

Please refer to Appendix WCDMA.

7.3. OCCUPIED BANDWIDTH

RULE PART(S)

FCC: §2.1049

RSS-132, RSS-133, RSS-139

LIMITS


For reporting purposes only.

TEST PROCEDURE

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The occupied bandwidth was measured with the spectrum analyzer at the low, middle and high channel in each band. The -26dB bandwidth was also measured and recorded.

(Refer to KDB 971168 D01 Power Meas License Digital Systems v03r01)

TEST SETUP



TEST ENVIRONMENT

Temperature	22.6°C	Relative Humidity	58.2%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V 60HZ

RESULTS

There is no limit required and power is the same for low, middle and high channel, therefore, only middle channel was tested.

Please refer to Appendix WCDMA.

7.4. BAND EDGE EMISSIONS

RULE PART(S)

FCC §2.1051, §22.917, §24.238, §27.53
RSS-132, RSS-133, RSS-139

LIMITS

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.


TEST PROCEDURE

Refer to KDB 971168 D01 Power Meas License Digital Systems v03r01

The transmitter output was connected to a CMW500 Test Set and configured to operate at maximum power. The band edge emissions were measured at the required operating frequencies in each band on the Spectrum Analyzer.

- a) Set the RBW = 1 ~ 5 % of OBW (Typically limited to a minimum RBW of 1% of the OBW)
- b) Set VBW $\geq 3 \times$ RBW;
- c) Set span ≥ 1.5 times the OBW;
- d) Sweep time = Auto;
- e) Detector = RMS;
- f) Ensure that the number of measurement points $\geq 2 \times$ Span/RBW;
- g) Trace mode = Average (100);

TEST SETUP



TEST ENVIRONMENT

Temperature	22.6°C	Relative Humidity	58.2%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V 60HZ

RESULTS

Please refer to Appendix WCDMA.

7.5. SPURIOUS EMISSION AT ANTENNA TERMINAL

RULE PART(S)

FCC: §2.1051, §22.901, §22.917, §24.238, §27.53

RSS-132, RSS-133, RSS-139

LIMITS

FCC: §22.901, §22.917, §24.238

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.


TEST PROCEDURE

Per KDB 971168 D01 Power Meas License Digital Systems v03r01

The RF output of the transmitter was connected to a spectrum analyzer through a calibrated coaxial cable. Sufficient scans were taken to show the out-of-band Emissions, if any, up to 10th harmonic. Multiple sweeps were recorded in maximum hold mode using a peak detector to ensure that the worst-case emissions were caught.

- a) Set the RBW = 100 kHz for emission below 1GHz and 1MHz for emissions above 1GHz (Tests were performed 1 MHz [Worst case], to sweep 1 time for all frequency range)
- b) Set VBW $\geq 3 \times$ RBW;
- c) Set span ≥ 1.5 times the OBW;
- d) Sweep time = auto couple;
- e) Detector = rms;
- f) Ensure that the number of measurement points 2001 for 30MHz to 1GHz and Max (40001) for above 1GHz;
- g) Trace mode = trace average for continuous emissions, max hold for pulse emissions;

TEST SETUP



TEST ENVIRONMENT

Temperature	22.6°C	Relative Humidity	58.2%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V 60HZ

RESULTS

Please refer to Appendix WCDMA.

7.6. FREQUENCY STABILITY

Rule Part:

FCC: §2.1055, §22.355, §24.235, §27.54

RSS-132, RSS-133, RSS-139

LIMITS

§22.355 - The carrier frequency shall not depart from the reference frequency in excess of ± 2.5 ppm for mobile stations.


§24.235 and §27.54 - The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

TEST PROCEDURE

Refer to KDB 971168 D01 Power Meas License Digital Systems v03r01.

	Normal Test Conditions	Extreme Test Conditions
Relative Humidity	45 % - 75 %	/
Atmospheric Pressure	100 kPa ~102 kPa	/
Temperature	T_N (Normal Temperature): 24.5 °C	T_L (Low Temperature): -20 °C
		T_H (High Temperature): 70 °C
Supply Voltage	V_N (Normal Voltage): AC 120V 60HZ	V_L (Low Voltage): AC 102 V
		V_H (High Voltage): AC 138 V

TEST SETUP



TEST ENVIRONMENT

Temperature	22.6°C	Relative Humidity	58.2%
Atmosphere Pressure	101kPa	Test Voltage	/

RESULTS

The peak frequency error is recorded (worst-case).
Please refer to Appendix WCDMA.

7.7. RADIATED SPURIOUS EMISSIONS

LIMIT

FCC: §24.238(a), (WCDMA Band 2)

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

FCC: §22.917(a), (WCDMA Band 5)


The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

FCC: §27.53(h), (WCDMA Band 4)

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

TEST PROCEDURE

Following the test configuration shown below, radiated emissions measured directly from the EUT and convert the measured field strength or received power to ERP or EIRP, as required, for comparison to the applicable limits. As stated in section 5.5.1 of ANSI C63.26-2015. The field strength measurement method by using a test site validated to the requirement of ANSI C63.4 is an alternative method to the substitution measurement.



Radiated Power Measurement Calculation According to ANSI C63.26-2015


- a) $E \text{ (dB}\mu\text{V/m)} = \text{Measured amplitude level (dB}\mu\text{V)} + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$.
- b) $E \text{ (dB}\mu\text{V/m)} = \text{Measured amplitude level (dBm)} + 107 + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$.
- c) $E \text{ (dB}\mu\text{V/m)} = \text{EIRP (dBm)} - 20\log(D) + 104.8$, where D is the measurement distance (in the far field region) in m.
- d) $\text{EIRP (dBm)} = E \text{ (dB}\mu\text{V/m)} + 20\log(D) - 104.8$, where D is the measurement distance (in the far field region) in m.

So, from d)

The measuring distance is at 3m, then $20 \cdot \log(3) = 9.5424$

Then, $\text{EIRP (dBm)} = E \text{ (dB}\mu\text{V/m)} + 9.5424 - 104.8 = E \text{ (dB}\mu\text{V/m)} - 95.2576$

X axis, Y axis, Z axis positions:




Note: The EUT was investigated in three orthogonal orientations X/Y/Z to determine the worst-case orientation. X orientation is finally determined the worst.

TEST ENVIRONMENT

Temperature	22.5°C	Relative Humidity	62.8%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V 60Hz


RESULTS

Test Mode:	WCDMA Band 2	Frequency(MHz):	1852.4
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1194.000	18.54	27.88	46.42	82.25	-35.83	peak
2	1636.000	18.08	29.64	47.72	82.25	-34.53	peak
3	1852.400	80.27	30.36	110.63	/	/	Fundamental
4	2614.000	21.38	32.80	54.18	82.25	-28.07	peak
5	2832.000	21.03	33.49	54.52	82.25	-27.73	peak
6	2998.000	21.01	34.01	55.02	82.25	-27.23	peak

Test Mode:	WCDMA Band 2	Frequency(MHz):	1852.4
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1402.000	18.47	28.82	47.29	82.25	-34.96	peak
2	1630.000	19.18	29.62	48.80	82.25	-33.45	peak
3	1852.400	83.33	30.36	113.69	/	/	Fundamental
4	1932.000	27.61	30.64	58.25	82.25	-24.00	peak
5	2612.000	21.20	32.80	54.00	82.25	-28.25	peak
6	2998.000	20.37	34.01	54.38	82.25	-27.87	peak

Test Mode:	WCDMA Band 2	Frequency(MHz):	1880
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1460.000	17.81	29.05	46.86	82.25	-35.39	peak
2	1624.000	18.42	29.60	48.02	82.25	-34.23	peak
3	1880.000	79.83	30.45	110.28	/	/	Fundamental
4	2406.000	20.28	32.06	52.34	82.25	-29.91	peak
5	2568.000	21.72	32.65	54.37	82.25	-27.88	peak
6	2996.000	20.84	34.00	54.84	82.25	-27.41	peak

Test Mode:	WCDMA Band 2	Frequency(MHz):	1880
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1448.000	17.81	29.00	46.81	82.25	-35.44	peak
2	1638.000	18.38	29.65	48.03	82.25	-34.22	peak
3	1880.000	84.24	30.46	114.70	/	/	Fundamental
4	1960.000	27.36	30.74	58.10	82.25	-24.15	peak
5	2416.000	20.41	32.10	52.51	82.25	-29.74	peak
6	2958.000	21.00	33.88	54.88	82.25	-27.37	peak

Test Mode:	WCDMA Band 2	Frequency(MHz):	1907.6
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1432.000	18.02	28.94	46.96	82.25	-35.29	peak
2	1742.000	19.26	30.00	49.26	82.25	-32.99	peak
3	1907.600	80.10	30.55	110.65	/	/	Fundamental
4	2258.000	19.77	31.34	51.11	82.25	-31.14	peak
5	2594.000	21.46	32.74	54.20	82.25	-28.05	peak
6	2984.000	20.87	33.96	54.83	82.25	-27.42	peak

Test Mode:	WCDMA Band 2	Frequency(MHz):	1907.6
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1344.000	18.11	28.55	46.66	82.25	-35.59	peak
2	1588.000	18.73	29.48	48.21	82.25	-34.04	peak
3	1907.600	84.05	30.55	114.60	/	/	Fundamental
4	1988.000	25.98	30.83	56.81	82.25	-25.44	peak
5	2580.000	21.53	32.69	54.22	82.25	-28.03	peak
6	2862.000	21.85	33.59	55.44	82.25	-26.81	peak

Test Mode:	WCDMA Band 2	Frequency(MHz):	1852.4
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4545.000	41.47	-0.57	40.90	82.25	-41.35	peak
2	6990.000	39.81	5.97	45.78	82.25	-36.47	peak
3	9390.000	34.99	10.73	45.72	82.25	-36.53	peak
4	10365.000	34.40	13.68	48.08	82.25	-34.17	peak
5	14010.000	27.87	24.00	51.87	82.25	-30.38	peak
6	18000.000	23.63	27.98	51.61	82.25	-30.64	peak

Test Mode:	WCDMA Band 2	Frequency(MHz):	1852.4
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3690.000	48.50	-4.00	44.50	82.25	-37.75	peak
2	6975.000	39.28	5.92	45.20	82.25	-37.05	peak
3	10335.000	34.04	13.59	47.63	82.25	-34.62	peak
4	11895.000	29.76	17.99	47.75	82.25	-34.50	peak
5	13980.000	28.14	23.98	52.12	82.25	-30.13	peak
6	17940.000	23.92	27.61	51.53	82.25	-30.72	peak

Test Mode:	WCDMA Band 2	Frequency(MHz):	1880
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4830.000	41.88	0.26	42.14	82.25	-40.11	peak
2	6975.000	38.95	5.92	44.87	82.25	-37.38	peak
3	10395.000	34.30	13.75	48.05	82.25	-34.20	peak
4	11565.000	31.60	17.03	48.63	82.25	-33.62	peak
5	14025.000	28.52	23.92	52.44	82.25	-29.81	peak
6	18000.000	24.49	27.98	52.47	82.25	-29.78	peak

Test Mode:	WCDMA Band 2	Frequency(MHz):	1880
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3750.000	48.54	-4.01	44.53	82.25	-37.72	peak
2	6945.000	40.06	5.82	45.88	82.25	-36.37	peak
3	10590.000	34.42	14.27	48.69	82.25	-33.56	peak
4	11505.000	32.05	16.84	48.89	82.25	-33.36	peak
5	14100.000	28.53	23.47	52.00	82.25	-30.25	peak
6	18000.000	23.42	27.98	51.40	82.25	-30.85	peak

Test Mode:	WCDMA Band 2	Frequency(MHz):	1907.6
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5715.000	44.28	2.04	46.32	82.25	-35.93	peak
2	6975.000	39.50	5.92	45.42	82.25	-36.83	peak
3	9240.000	35.36	10.25	45.61	82.25	-36.64	peak
4	12015.000	29.42	18.31	47.73	82.25	-34.52	peak
5	13860.000	27.42	23.52	50.94	82.25	-31.31	peak
6	17925.000	23.16	27.50	50.66	82.25	-31.59	peak

Test Mode:	WCDMA Band 2	Frequency(MHz):	1907.6
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3810.000	47.52	-4.00	43.52	82.25	-38.73	peak
2	5715.000	42.12	2.04	44.16	82.25	-38.09	peak
3	8265.000	36.98	8.10	45.08	82.25	-37.17	peak
4	11835.000	31.10	17.84	48.94	82.25	-33.31	peak
5	14025.000	27.95	23.92	51.87	82.25	-30.38	peak
6	18000.000	23.74	27.98	51.72	82.25	-30.53	peak

Test Mode:	WCDMA Band 4	Frequency(MHz):	1712.4
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6990.000	39.56	5.97	45.53	82.25	-36.72	peak
2	8580.000	36.67	8.53	45.20	82.25	-37.05	peak
3	10215.000	34.52	13.31	47.83	82.25	-34.42	peak
4	11895.000	31.23	17.99	49.22	82.25	-33.03	peak
5	13875.000	28.30	23.59	51.89	82.25	-30.36	peak
6	18000.000	24.18	27.98	52.16	82.25	-30.09	peak

Test Mode:	WCDMA Band 4	Frequency(MHz):	1712.4
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6990.000	39.19	5.97	45.16	82.25	-37.09	peak
2	9270.000	35.71	10.34	46.05	82.25	-36.20	peak
3	10545.000	33.34	14.16	47.50	82.25	-34.75	peak
4	12555.000	31.04	19.20	50.24	82.25	-32.01	peak
5	13890.000	28.59	23.64	52.23	82.25	-30.02	peak
6	17940.000	23.91	27.61	51.52	82.25	-30.73	peak

Test Mode:	WCDMA Band 4	Frequency(MHz):	1732.6
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4785.000	41.54	0.15	41.69	82.25	-40.56	peak
2	6990.000	39.64	5.97	45.61	82.25	-36.64	peak
3	8130.000	37.53	8.02	45.55	82.25	-36.70	peak
4	10605.000	33.30	14.31	47.61	82.25	-34.64	peak
5	14040.000	27.51	23.83	51.34	82.25	-30.91	peak
6	18000.000	23.58	27.98	51.56	82.25	-30.69	peak

Test Mode:	WCDMA Band 4	Frequency(MHz):	1732.6
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3450.000	45.02	-4.01	41.01	82.25	-41.24	peak
2	6960.000	39.39	5.88	45.27	82.25	-36.98	peak
3	10605.000	33.43	14.31	47.74	82.25	-34.51	peak
4	12330.000	30.66	18.88	49.54	82.25	-32.71	peak
5	13950.000	26.71	23.87	50.58	82.25	-31.67	peak
6	17985.000	24.22	27.88	52.10	82.25	-30.15	peak

Test Mode:	WCDMA Band 4	Frequency(MHz):	1752.6
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6855.000	40.18	5.53	45.71	82.25	-36.54	peak
2	9210.000	36.63	10.14	46.77	82.25	-35.48	peak
3	10515.000	34.45	14.08	48.53	82.25	-33.72	peak
4	11805.000	31.25	17.76	49.01	82.25	-33.24	peak
5	14010.000	27.56	24.00	51.56	82.25	-30.69	peak
6	17820.000	24.28	26.84	51.12	82.25	-31.13	peak

Test Mode:	WCDMA Band 4	Frequency(MHz):	1752.6
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4635.000	41.56	-0.25	41.31	82.25	-40.94	peak
2	7020.000	39.00	6.08	45.08	82.25	-37.17	peak
3	9210.000	36.51	10.14	46.65	82.25	-35.60	peak
4	11640.000	31.99	17.27	49.26	82.25	-32.99	peak
5	13965.000	27.16	23.93	51.09	82.25	-31.16	peak
6	17955.000	23.00	27.69	50.69	82.25	-31.56	peak

Test Mode:	WCDMA Band 5	Frequency(MHz):	826.4
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1648.000	58.17	-10.11	48.06	82.25	-34.19	peak
2	3007.000	44.97	-6.03	38.94	82.25	-43.31	peak
3	4087.000	43.04	-3.34	39.70	82.25	-42.55	peak
4	5131.000	40.53	0.58	41.11	82.25	-41.14	peak
5	6985.000	39.96	5.86	45.82	82.25	-36.43	peak
6	9325.000	35.88	10.37	46.25	82.25	-36.00	peak

Test Mode:	WCDMA Band 5	Frequency(MHz):	826.4
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1648.000	63.04	-10.11	52.93	82.25	-29.32	peak
2	3007.000	44.60	-6.03	38.57	82.25	-43.68	peak
3	5122.000	41.00	0.58	41.58	82.25	-40.67	peak
4	6976.000	40.20	5.83	46.03	82.25	-36.22	peak
5	8056.000	36.77	8.01	44.78	82.25	-37.47	peak
6	9829.000	33.93	12.14	46.07	82.25	-36.18	peak

Test Mode:	WCDMA Band 5	Frequency(MHz):	836.4
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1666.000	56.10	-10.11	45.99	82.25	-36.26	peak
2	2512.000	48.53	-7.73	40.80	82.25	-41.45	peak
3	4825.000	41.06	-0.13	40.93	82.25	-41.32	peak
4	5392.000	40.09	1.41	41.50	82.25	-40.75	peak
5	6976.000	39.44	5.83	45.27	82.25	-36.98	peak
6	9235.000	36.67	10.11	46.78	82.25	-35.47	peak

Test Mode:	WCDMA Band 5	Frequency(MHz):	836.4
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1666.000	61.96	-10.11	51.85	82.25	-30.40	peak
2	3007.000	44.22	-6.03	38.19	82.25	-44.06	peak
3	4897.000	41.25	0.10	41.35	82.25	-40.90	peak
4	6985.000	39.43	5.86	45.29	82.25	-36.96	peak
5	8245.000	36.93	8.10	45.03	82.25	-37.22	peak
6	9199.000	37.10	10.00	47.10	82.25	-35.15	peak

Test Mode:	WCDMA Band 5	Frequency(MHz):	846.6
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1684.000	54.46	-10.11	44.35	82.25	-37.90	peak
2	2530.000	50.15	-7.66	42.49	82.25	-39.76	peak
3	4690.000	41.55	-0.47	41.08	82.25	-41.17	peak
4	5707.000	40.21	1.81	42.02	82.25	-40.23	peak
5	6976.000	39.73	5.83	45.56	82.25	-36.69	peak
6	9613.000	34.83	11.34	46.17	82.25	-36.08	peak

Test Mode:	WCDMA Band 5	Frequency(MHz):	846.6
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1684.000	63.77	-10.11	53.66	82.25	-28.59	peak
2	2521.000	47.85	-7.69	40.16	82.25	-42.09	peak
3	3745.000	42.87	-4.48	38.39	82.25	-43.86	peak
4	5122.000	41.43	0.58	42.01	82.25	-40.24	peak
5	6967.000	39.90	5.81	45.71	82.25	-36.54	peak
6	9199.000	36.50	10.00	46.50	82.25	-35.75	peak

Remark: All the modulation have been tested at low, middle, high channels, only the worst modulation show in the test report.

END OF REPORT