



Bundesnetzagentur

Test report

AIN17b01

BNetzA-CAB-02/21-01

Product / EUT: RFID reader
Type designation: UDT-100L 17L/UD/U/H/CS1
ARE DT1 – 17L/A/U/H
FCC ID: V7IUUDT100L
FCC ID: V7IAREDT1LF-1
Tested type: UDT-100L 17L/UD/U/H/CS1
EUT authorization: ☒ Certification ☐ Declaration of Conformity
☐ Verification
Production level: 03/2016
S/N: 660
Manufacturer: AEG Identifikationssysteme GmbH
Hörvelsinger Weg 47
89081 Ulm / Germany

Test remit: FCC Rules 47 CFR Part 15 – Subpart C – Intentional radiators
in accordance with the procedures given in
§15.207; 15.209

The standards were: ☒ kept*
☐ not kept*


***Remark:** ☒ Validation covered by the accredited scope
☐ Validation not covered by the accredited scope
according: _____
☐ Validation of the EMC-requirements partly proceeded

Applicant: AEG Identifikationssysteme GmbH
Hörvelsinger Weg 47
89081 Ulm / Germany

EUT-
Date of arrival: 2016-03-08
Test ID: PRN10_15
Date(s) of test: 2016-03-08 – 2016-04-25

Burgrieden, 2016-08-10

Released by:



Principal engineer – Christian Vogelmann

Test laboratory: ☒ EMCE GmbH
Ingenieurbüro für EMV-Prüfungen und Schaltungsentwicklung
Untere Wiesen 1 / 88483 Burgrieden / Germany

DAkkS-Registration No.: D-PL-12122-01-01
CAB-Registration No.: BnetzA-CAB-02/21-01/1
FCC-Registration No.: 219415

Test procedure: ANSI C63.10-2013

Responsible inspector: Mr. Hauser
EMCE GmbH
Ingenieurbüro für EMV-Prüfungen und Schaltungsentwicklung

Contact person : Mr. Köster / AEG Identifikationssysteme GmbH

EUT-

Description: Desktop LF-RFID reader.
Used abbreviations for the options:
UD = specific 3D-front-label for customer UID
U = USB interface
H = HID interface
CSx = customer specific software, sequential number x
L = air coil

Voltage supply: 5VDC via USB-Port

Fundamental frequency: 134kHz,
Frequency list: 17.1776MHz; 20MHz

Temperature range: n/a

Approximate size: (ØxH) / mm - 110x35

**Supplied /
used equipment:**

Designation	Type	Manufacturer	S/N
Laptop	Inspiron 5150	Dell	CN-0W0941-1296136J-2083
AC Adapter (Inspiron 5150)	PA-1131-02D	Dell	CN-9Y819-48010-360-0954
Laptop	Lifebook E8110	Fujitsu Siemens	YK2B046965
AC Adapter (Lifebook E8110)	ADP-80NB A	Fujitsu Siemens	CP293661-01
Transponder (tag)	Tier ISO, 20mm disc	AEG ID	999 000000000000

Configuration:


As-delivered condition*



Modified*

*

Cable designation	Type	Length	Remarks
USB cable	Shielded	1.9m	n/a

Remarks:

n/a

State of revision:

Source document	New Document	Date / Reviser	Modifications
AIN17_01	AIN17a01	2016-06-24 Chr. Vogelmann	List of valid equipment shrink to used equipment. Environmental conditions recorded.
AIN17a01	AIN17b01	2016-08-09 Chr. Vogelmann	Type designation extended with FCC ID number.

Test equipment list of EMCE GmbH:

Inv.-No.	Designation	Type	Manufacturer	S/N	Calibration: Interval /valid until
001	Test receiver	ESS 5Hz - 1000MHz	Rohde & Schwarz	833776/008 Firmware: Main: 1.21 OTP: 02.01 GRA: 02.03	1 Year(s)/ 2016-10-05
003	LISN 1	ESH3-Z5	Rohde & Schwarz	835268/007	1 Year(s)/ 2016-08-31
004	LISN 2	ESH3-Z5	Rohde & Schwarz	835268/003	1 Year(s)/ 2016-11-30
008	Loop antenna 9kHz-30MHz	HFH2-Z2	Rohde & Schwarz	835776/0002	3 Year(s)/ 2016-11-22
009	Antenna 30-300MHz	VHBA9123 / BBA9106	Schwarzbeck	435	3 Year(s)/ 2018-10-27
010	Antenna 250-1200MHz	UHALP 9108A	Schwarzbeck	108	2 Year(s)/ 2016-09-05
011	Antenna 30-300MHz	VHBA9123 / BBA9106	Schwarzbeck	0403/94	2 Year(s)/ 2016-09-05
012	Antenna 250-1200MHz	UHALP 9108A	Schwarzbeck	166	3 Year(s)/ 2018-11-10
014	OATS	3m	EMCE GmbH		3 Year(s)/ 2017-10-31
015	OATS	10m	EMCE GmbH		3 Year(s)/ 2017-10-31
042	AC-Source/ Analyser/ Norm impedance	EMV D 5000/PAS	Spitzenberger+ Spies	A2747 00/0 0501 A2747 07/00501 (ARS16/3)	2 Year(s)/ 2017-08-31
058	Receiver	ESIB 40	Rohde & Schwarz	100200/ Firmware 4.35	1 Year(s)/ 2017-04-07
062	Semi anechoic chamber #2	13.0m x 7.0m x 5.0m	EMC-Technik & Consulting GmbH		1 Year(s)/ 2016-07-31
067	LISN	ESH2-Z5	Rohde&Schwarz	872460/043	1 Year(s)/ 2016-08-31
068	LISN	ESH2-Z5	Rohde&Schwarz	872460/042	1 Year(s)/ 2016-08-31
070	Pulse limiter + 10dB Attenuator	ESH3-Z2	Rohde&Schwarz	n/a	1 Year(s)/ 2016-08-31
175	EMI Test receiver	ESR7	Rohde & Schwarz	101108 Firmware:	1 Year(s)/ 2016-07-14

Inv.- No.	Designation	Type	Manufacturer	S/N	Calibration: Interval /valid until
				FW V2.26	
997	EMC Software	EMC32 Vers. 8.53.0	Rohde& Schwarz	n/a	

Scope:

1	EMC-Test(s).....	7
1.1	Emission according 47 CFR Part 15 Subpart C - 04/2016	7
1.1.1	Terminal voltage according 47 CFR Part 15 Subpart C - 04/2016	7
1.1.1.1	Test set up	8
1.1.1.2	Test.....	10
1.1.2	Radio disturbances according 47 CFR Part 15 Subpart C - 04/2016	16
1.1.2.1	Test set up	17
1.1.2.2	Test – Radiated emission fundamental.....	21
1.1.2.3	Test – Spurious emissions.....	23
1.1.2.4	Restricted bands of operation	34
1.1.2.5	Antenna requirement	37
2	Summary	38

1 EMC-Test(s)

1.1 Emission according 47 CFR Part 15 Subpart C - 04/2016

1.1.1 Terminal voltage according 47 CFR Part 15 Subpart C - 04/2016

- ☒ Full compliance
☐ Precompliance
☐ Test not requested*
☐ Test not carried out*


*

Test location

☒	Inv.-No.	Designation	Type (LxWxH)	Manufacturer	Location
☒	588	Shielded room #2	8.3/5.8 x 5.5/2.9 x 3.4m	EMC-Technik & Consulting GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
	584	Shielded room #3	3.6 x 3.6 x 2.5m	Siemens AG	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
	678	Shielded room #4	4.0 x 4.0 x 3.5m	EMC-Technik & Consulting GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
	062	Semi anechoic chamber #2	13.5 x 6.1 x 5.5m	EMC-Technik & Consulting GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
	679	Full anechoic chamber #3	8.8 x 4.6 x 4.2m	Albatross Projects GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
	014	Open area test site	10m	EMCE GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
	015	Open area test site	3m	EMCE GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
	042	Voltage- / current source test site	0-382VDC 0-270VAC 1x10kW / 3x5kW	Spitzenberger + Spies	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
	n/a	Alternative test site	n/a	n/a	n/a

1.1.1.1 Test set up

According ANSI C63.10-2013



Used test equipment

☒	Inv.-No.	Designation	Type	Manufacturer	S/N
☒	001	Test receiver	ESS 5Hz - 1000 MHz	Rohde & Schwarz	833776/008
	002	Probe	ESH2-Z3	Rohde & Schwarz	
	003	LISN 1	ESH3-Z5	Rohde & Schwarz	835268/007
	004	LISN 2	ESH3-Z5	Rohde & Schwarz	835268/003
	005	LISN 3	NNB 4/32T	Rolf Heine HF-Technik	4/32T-96015
	006	LISN	NNBM 8125	Schwarzbeck	8125371
	007	Absorbing clamp	MDS 21	Schwarzbeck	942436
	025	Current clamp BCI	F-120-2	FCC	47
	026	Coupling device network	CDN 801-M3-25	FCC	92
	030	Coupling device network	CDN-S9	EMCE GmbH	
	031	Coupling device network	CDN-S9	EMCE GmbH	
	036	Coupling device network	CDN-M5-25	EMCE GmbH	
	037	Coupling device network	CDN-S1	EMCE GmbH	
☒	042	AC-Source / Analyser / Norm impedance	EMV D5000/PAS	Spitzenberger + Spies	A274700/ 0 0501
	058	Test receiver	ESIB 40	Rohde & Schwarz	100200
	060	HF-coupling clamp	KEMA 801	Schaffner	20808
☒	067	LISN 5	ESH2-Z5	Rohde & Schwarz	0872460/043
	068	LISN 4	ESH2-Z5	Rohde & Schwarz	0872460/042
	073	Absorbing clamp	MDS 21	Schwarzbeck	881757

All used test equipment are checked resp. calibrated periodically.

☒ Test equipment was checked and complied to the requirements

Test / Measurement uncertainty

The measurement uncertainty in the test met the guideline of CISPR16-4-2 or better.

Measurement uncertainty of the terminal voltage with an extended coverage factor of $k=2$:

Frequency	Measurement uncertainty
9kHz – 150kHz	4.0dB
150kHz – 30MHz	3.6dB

1.1.1.2 Test

Regulation

47 CFR Part 15 Subpart C - 04/2016

☐ 9kHz - 30MHz

☒ 150kHz - 30MHz

Mains supply
Limits:

☒ Section 15.207

☐ __

Operation mode

EUT arrangement:

☒ Tabletop

☐ Floor standing

Power supply:

☒ 120V/60Hz

☐ 240V/60Hz

Rated voltage variation:

☐ 85%

☐ 115%

Port #	Designation	Remarks
#1	AC power line	L1/N/PE
#2		
#3		

Continuous operation of the RFID reader connected to the laptop USB-port.
RFID tag placed at approx. of the half reading distance.

Environmental conditions

Temperature [10 - 40°C]:

21°C

Relative humidity [10 - 90%]:

46%

Environmental conditions during the test:

☒ kept

☐ not kept

Test - / Measurement procedure

Measurements are made with a receiver according CISPR 16 guidelines. A pulse limiter and a 10dB attenuator at the receiver input is used to protect the receiver. The required frequency range is scanned in an automatically operation. When the EUT is arranged the frequency range is monitored. The setup of the equipment and the cables are manipulated within the range to produce the highest emission. Frequency steps of $<0.5 \times$ receiver bandwidth and peak / average detectors are used. If the conducted emission is closer than 20dB to the limits or exceeds, the receiver will retest the emission with quasipeak or average detector. The identified frequency and amplitude of the six highest conducted emissions relative to the limit lines are listed for each current-carrying conductor. If less than six emission frequencies are within the 20dB of the limit, the noise level of the measuring instrument at representative frequencies are reported.

The reported test results are calculated with the following formula:

$$\text{Result (dB}\mu\text{V)} = \text{Reading (dB}\mu\text{V)} + \text{ATF (dB)} + \text{CF (dB)}$$

ATF = Correction factor for the pulse limiter / 10dB attenuator

CF = Correction factor for the cable loss

Test result

Limits for continuous disturbances:

☒ kept
☐ not kept

| Remarks: n/a

Protocol scope

- ☒ Readings - continuous emanation
☒ Diagram - continuous emanation

EMCE GmbH Ing_buero fuer EMV_Pruefungen

Terminal voltage

16. Mar 16 08:29


EUT: UDT-100L 17L / UD / U / H / CS1
Manuf: AEG ID GmbH
Op Cond: Reading tag, 1/2 reading distance
Operator: P. Hauser
Test Spec: 47 CFR Part 15 Subpart C
Comment: Test_ID PRN10_15
AIN11_11, Phase L1

Scan Settings (1 Range)

Frequencies			Receiver Settings					
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
150k	30M	5k	10k	PK+AV	20ms	AUTO	LN	OFF 60dB

Final Measurement: x QP / + AV
Meas Time: 1 s
Subranges: 50
Acc Margin: 6dB

Transducer No.	Start	Stop	Name
3 2	1Hz	1000M	Kabel_6m
20	9k	30M	Lim_#070



EMCE GmbH Ing_buero fuer EMV_Pruefungen Terminal voltage

16. Mar 16 08:29

EUT: UDT-100L 17L / UD / U / H / CS1
Manuf: AEG ID GmbH
Op Cond: Reading tag, 1/2 reading distance
Operator: P. Hauser
Test Spec: 47 CFR Part 15 Subpart C
Comment: Test_ID PRN10_15
AIN11_11, Phase L1

Scan Settings (1 Range)

Frequencies			Receiver Settings					
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
150k	30M	5k	10k	PK+AV	20ms	AUTO	LN	OFF 60dB

Final Measurement Results:

no Results

EMCE GmbH Ing_buero fuer EMV_Pruefungen

Terminal voltage

16. Mar 16 08:45


EUT: UDT-100L 17L / UD / U / H / CS1
Manuf: AEG ID GmbH
Op Cond: Reading tag, 1/2 reading distance
Operator: P. Hauser
Test Spec: 47 CFR Part 15 Subpart C
Comment: Test_ID PRN10_15
AIN11_12, Phase N

Scan Settings (1 Range)

Frequencies			Receiver Settings				
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp OpRge
150k	30M	5k	10k	PK+AV	20ms	AUTO	LN OFF 60dB

Final Measurement: x QP / + AV
Meas Time: 1 s
Subranges: 50
Acc Margin: 6dB

Transducer No.	Start	Stop	Name
3 2	1Hz	1000M	Kabel_6m
20	9k	30M	Lim_#070



EMCE GmbH Ing_buero fuer EMV_Pruefungen Terminal voltage

16. Mar 16 08:45

EUT: UDT-100L 17L / UD / U / H / CS1
Manuf: AEG ID GmbH
Op Cond: Reading tag, 1/2 reading distance
Operator: P. Hauser
Test Spec: 47 CFR Part 15 Subpart C
Comment: Test_ID PRN10_15
AIN11_12, Phase N

Scan Settings (1 Range)

Frequencies			Receiver Settings					
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
150k	30M	5k	10k	PK+AV	20ms	AUTO	LN	OFF 60dB

Final Measurement Results:

no Results

1.1.2 Radio disturbances according 47 CFR Part 15 Subpart C - 04/2016

- ☒ Full compliance
☐ Precompliance
☐ Test not requested*
☐ Test not carried out*


*

Test location

☒	Inv.-No.	Designation	Type (LxWxH)	Manufacturer	Location
	588	Shielded room #2	8.3/5.8 x 5.5/2.9 x 3.4m	EMC-Technik & Consulting GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
	584	Shielded room #3	3.6 x 3.6 x 2.5m	Siemens AG	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
	678	Shielded room #4	4.0 x 4.0 x 3.5m	EMC-Technik & Consulting GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
☒	062	Semi anechoic chamber #2	13.5 x 6.1 x 5.5m	EMC-Technik & Consulting GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
	679	Full anechoic chamber #3	8.8 x 4.6 x 4.2m	Albatross Projects GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
☒	014	Open area test site	10m	EMCE GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
☒	015	Open area test site	3m	EMCE GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
	042	Voltage- / current source test site	0-382VDC 0-270VAC 1x10kW / 3x5kW	Spitzenberger + Spies	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
	n/a	Alternative test site	n/a	n/a	n/a

1.1.2.1 Test set up

According ANSI C63.10-2013





Used test equipment

☒	Inv.-No.	Designation	Type	Manufacturer	S/N
☒	001	Test receiver	ESS 5Hz - 1000 MHz	Rohde & Schwarz	833776/008
	003	LISN 1	ESH3-Z5	Rohde & Schwarz	835268/007
	004	LISN 2	ESH3-Z5	Rohde & Schwarz	835268/003
	005	LISN 3	NNB 4/32T	Rolf Heine HF-Technik	4/32T-96015
	006	LISN	NNBM 8125	Schwarzbeck	8125371
	007	Absorbing clamp	MDS 21	Schwarzbeck	942436
☒	008	Antenna 9kHz – 30MHz	HFH2-Z2	Rohde & Schwarz	835776/0002
☒	009	Antenna 30 – 300MHz	VHBA9123 / BBA9106	Schwarzbeck	435
☒	010	Antenna 250 -1200MHz	UHALP 9108A	Schwarzbeck	108
☒	011	Antenna 30 – 300MHz	VHBA9123 / BBA9106	Schwarzbeck	0408/94
☒	012	Antenna 250 -1200MHz	UHALP 9108A	Schwarzbeck	166
	013	Antenna 9kHz – 30 MHz	Loop antenna 1.5m Ø	EMCE GmbH	
	025	Current clamp BCI	F-120-2	FCC	47
	041	HZ-10	Shielded coil	Rohde & Schwarz	849788/020
	042	AC-Source / Analyser / Norm impedance	EMV D5000/PAS	Spitzenberger + Spies	A274700/ 0 0501
☒	058	Test receiver	ESIB 40	Rohde & Schwarz	100200
	059	Logper. Antenna	HL050	Rohde & Schwarz	100006
	060	HF coupling clamp	KEMA 801	Schaffner	20808
	063	Logper. Antenna	HL023 A2	Rohde & Schwarz	
	067	LISN 5	ESH2-Z5	Rohde & Schwarz	0872460/043
	068	LISN 4	ESH2-Z5	Rohde & Schwarz	0872460/042
	073	Absorbing clamp	MDS 21	Schwarzbeck	881757
	116	Vertical rod antenna	VAMP 9243	Schwarzbeck	9243-205

All used test equipment are checked resp. calibrated periodically.

☒ Test equipment was checked and complied to the requirements

Test / Measurement uncertainty

The measurement uncertainty in the test met the guideline of CISPR16-4-2 or better.

Measurement uncertainty of the radiated emission with an extended coverage factor of $k=2$:

Frequency	Measurement uncertainty
9kHz – 30MHz	on request
30MHz – 300MHz	4.4dB
300MHz – 1GHz	3.4dB
1GHz – 18GHz	on request

1.1.2.2 Test – Radiated emission fundamental

Regulation

47 CFR Part 15 Subpart C - 04/2016

- | | |
|--|--|
| ☒ 9kHz - 30MHz | ☐ 150kHz – 1GHz |
| ☐ 30MHz - 1000MHz | ☐ 1 – 18GHz |

Limits: ☒ Section 15.209* ☐ Section 15.225*

* The limits for frequencies below 30MHz were corrected for a closer measuring distance by using an extrapolation factor of 40 dB/decade..

Test distance: ☐ 3m ☐ 5m
☒ 10m ☐ 30m

Operation mode

EUT arrangement:	☒ Tabletop	☐ Floor standing
Power supply:	☒ 120V/60Hz	☐ 240V/60Hz
Rated voltage variation:	☒ 85%	☒ 115%

Continuous operation of the RFID reader connected to the laptop USB-port.
The emanation was maximized while placing the RFID tag inside the field or without tag.

Environmental conditions

Temperature [10 - 40°C]:	19°C
Relative humidity [10 - 90%]:	52%

Environmental conditions during the test: ☒ kept
☐ not kept

Test - / Measurement procedure

The test was performed at an antenna to EUT distance of 10m in the frequency range $\leq 30\text{MHz}$ and at 3m distance for frequencies $\geq 30\text{MHz}$. Measurements were made with a CISPR receiver with quasi-peak. The average detector is used in the frequency bands 9-90kHz, 110-490kHz and above 1000MHz. For pulse modulated devices with a pulse repetition frequency of 20Hz or less, peak detector is used (15.35a Note). The frequency, the measured value, antenna information and the limit will be printed out.

The reported test results are calculated with the following formula:

$$\text{Field strength (dB}\mu\text{V/m)} = \text{Reading (dB}\mu\text{V)} + \text{AF (dB/m)} + \text{CF (dB)}$$

AF = Correction factor for the antenna

CF = Correction factor for the cable loss

$$\text{Limit}_{10\text{m}} \text{ (dB}\mu\text{V/m)} = \text{Limit (dB}\mu\text{V/m)} + \text{LCF}_{10\text{m}} \text{ (dB)}$$

Limit_{10m} Limit calculated for 10m test distance

LCF_{10m} = Limit Correction factor for 10m test distance

LCF_{10m} for 30m antenna distance = 20dB

LCF_{10m} for 100m antenna distance = 40dB

LCF_{10m} for 300m antenna distance = 60dB

Test result

Frequency	Field strength	Limit _{10m}	Margin	Ant.-	Ant.-	Detector	Receiver	Supply voltage	Remarks
				Distance	Polar.	Peak /	6dB BW		
MHz	dB μ V/m	dB μ V/m	dB	m	H/V	QP / AV	kHz		
0.13422	60.5	85.0	24.5	10.0	V	AV	0.2	120V	n/a
0.13422	60.5	85.0	24.5	10.0	V	AV	0.2	102V	n/a
0.13422	60.5	85.0	24.5	10.0	V	AV	0.2	138V	n/a

Limit_{10m} Limit calculated for 10m test distance

Limits for radiated disturbances:

☒ kept

☐ not kept

Remarks: n/a

1.1.2.3 Test – Spurious emissions

Regulation

47 CFR Part 15 Subpart C - 04/2016

- | | |
|---|--|
| ☒ 9kHz - 30MHz | ☐ 150kHz – 1GHz |
| ☒ 30MHz - 1000MHz | ☐ 1 – 18GHz |

Limits: ☒ Section 15.209 ☐ __

Test distance: ☒ 3m ☐ 5m
☒ 10m ☐ 30m

Operation mode

EUT arrangement:	☒ Tabletop	☐ Floor standing
Power supply:	☒ 120V/60Hz	☐ 240V/60Hz
Rated voltage variation:	☐ 85%	☐ 115%

Continuous operation of the RFID reader connected to the laptop USB-port.
RFID tag placed at approx. of the half reading distance.

Environmental conditions

Temperature [10 - 40°C]:	19°C
Relative humidity [10 - 90%]:	52%

Environmental conditions during the test: ☒ kept
☐ not kept

Test - / Measurement procedure

The test was performed at an antenna to EUT distance of 10m in the frequency range $\leq 30\text{MHz}$ and at 3m distance for frequencies $\geq 30\text{MHz}$. Measurements were made with a CISPR receiver with quasi-peak. The average detector is used in the frequency bands 9-90kHz, 110-490kHz and above 1000MHz. For pulse modulated devices with a pulse repetition frequency of 20Hz or less, peak detector is used (15.35a Note). The frequency, the measured value, antenna information and the limit will be printed out.

The reported test results are calculated with the following formula:

$$\text{Field strength (dB}\mu\text{V/m)} = \text{Reading (dB}\mu\text{V)} + \text{AF (dB/m)} + \text{CF (dB)}$$

AF = Correction factor for the antenna
CF = Correction factor for the cable loss

$$\text{Limit}_{10\text{m}} (\text{dB}\mu\text{V/m}) = \text{Limit (dB}\mu\text{V/m)} + \text{LCF}_{10\text{m}} (\text{dB})$$

Limit_{10m} Limit calculated for 10m test distance
LCF_{10m} = Limit Correction factor for 10m test distance
LCF_{10m} for 30m antenna distance = 20dB
LCF_{10m} for 100m antenna distance = 40dB
LCF_{10m} for 300m antenna distance = 60dB

Test result

Limits for intentional radiators:

☒ kept
☐ not kept

Level of the fundamental > unwanted emission:

☒ kept
☐ not kept

Remarks: Radio disturbances below the limit line with a margin > 10dB to the limit are generally not listed.

Protocol scope

- ☒ Readings - Antenna horizontal polarized.
- ☒ Diagram - Antenna horizontal polarized.
- ☒ Readings - Antenna vertical polarized.
- ☒ Diagram - Antenna vertical polarized.
- ☐ Bandwidth plot – Frequency response vs. supply voltage
- ☐ Precompliance measurement(s).

Readings - Antenna vertical polarized, Antenna loop lowest height 1 m


Frequency	Field strength	Limit _{10m}	Margin	Ant.-	Ant.-	Detector	Receiver	Remarks
				Distance	Polar.	Peak /	6dB BW	
MHz	dB μ V/m	dB μ V/m	dB	m	H/V	QP / AV	kHz	
0.26842	37.0	79.0	42.0	10.0	V	AV	10	Increased ambient noise
0.40263	49.0	75.5	26.5	10.0	V	AV	10	Increased ambient noise
0.53684	31.0	53.0	22.0	10.0	V	QP	10	
0.67105	31.0	51.1	20.1	10.0	V	QP	10	
0.80526	29.0	49.5	20.5	10.0	V	QP	10	
0.93947	30.0	48.1	18.1	10.0	V	QP	10	

Limit_{10m} Limit calculated for 10m test distance

Diagram - Antenna vertical polarized

Limits according FCC Rules CFR 47 Part 15 – Subpart C


☒ Section 15.209 – Corrected to 10m distance EUT-Antenna



EUT Information

EUT Name: UDT-100L – 17L/UD/U/H/CS1
 Test_ID: / SN: PRN10_15
 Customer: AEG ID GmbH
 Operational condition: Reading tag, half reading distance
 Test specification: 47 CFR §15.209
 Antenna information: Distance EUT-Ant.: 3.0m / Polarisation: V / Ant.Height: 1.0m
 Operator: P. Hauser
 File #: AIN11_85

Magnetic Field Strength dB μ V with Sweep_SAC2




15_209_3m [..EMI radiated\] Preview Result 1V-PK+ [Preview Result 1V.Result:2]

EUT Information

EUT Name: UDT-100L – 17L/UD/U/H/CS1
 Test_ID: / SN: PRN10_15
 Customer: AEG ID GmbH
 Operational condition: Reading tag, half reading distance
 Test specification: 47 CFR §15.209
 Antenna information: Distance EUT-Ant.: 3.0m / Polarisation: V / Ant.Height: 1.0m
 Operator: P. Hauser
 File #: AIN11_86

Magnetic Field Strength dB μ V with Sweep_SAC2




15_209_3m [..EMI radiated\] Preview Result 1V-PK+ [Preview Result 1V.Result:2]

Readings - Antenna horizontal polarized

Frequency	Readings	+ AF Antenna correction factor	+ KF Cable correction factor	Field strength	Limit	Margin	Antenna- Height	Antenna- Polarization	Turntable position
MHz	dB μ V	dB/m	dB	dB μ V/m	dB μ V/m	dB	m	hor./ver.	deg.
132.000	28.8	11.3	1.8	42.0	43.5	1.5	2.5	H	120

Diagram radio disturbances – Antenna horizontal polarized

Limits: ☒ Section 15.209* ☐ __




Readings - Antenna vertical polarized

Frequency	Readings	+ AF Antenna correction factor	+ KF Cable correction factor	Field strength	Limit	Margin	Antenna- Height	Antenna- Polarization	Turntable position
MHz	dB μ V	dB/m	dB	dB μ V/m	dB μ V/m	dB	m	hor./ver.	deg.
44.550	16.5	9.0	1.0	26.5	40.0	13.5	1.3	V	40
45.360	17.4	8.9	1.0	27.3	40.0	12.7	1.3	V	40
48.040	16.6	8.7	1.1	26.4	40.0	13.6	1.3	V	52
48.580	9.0	8.7	1.1	18.7	40.0	21.3	1.3	V	52
57.170	16.7	8.4	1.2	26.3	40.0	13.7	1.0	V	104
132.000	28.0	11.3	1.8	41.2	43.5	2.3	1.0	V	190
197.560	5.4	15.3	2.2	23.0	43.5	20.5	1.0	V	192

Diagram radio disturbances – Antenna vertical polarized

Limits: ☒ Section 15.209* ☐ __



1.1.2.4 Restricted bands of operation

Regulation

47 CFR Part 15 Subpart C - 04/2016

Requirement: ☒ Section 15.205(a)

Limit spurious emission: ☒ Section 15.209
☒ CISPR quasi peak detector ($f \leq 1\text{GHz}$)
☐ Average detector ($f > 1\text{GHz}$)

Operation mode

EUT arrangement:	☒ Tabletop	☐ Floor standing
Power supply:	☒ 120V/60Hz	☐ 240V/60Hz
Rated voltage variation:	☐ 85%	☐ 115%

Continuous operation of the RFID reader connected to the laptop USB-port.
RFID tag placed at approx. of the half reading distance.

Environmental conditions

Temperature [10 - 40°C]:	21°C
Relative humidity [10 - 90%]:	46%

Environmental conditions during the test: ☒ kept
☐ not kept

Test - / Measurement procedure

Position the EUT in front of the measuring antenna. The analyzer is set to peak detector and the trace mode to max. hold. Set the analyzer to the identified fundamental and the sweep is continued until the trace is stabilized. The frequencies of the maximum of the envelope and the outermost points attenuated by 20dB to the maximum are noted.

Test result

Measured fundamental: 0.13422MHz
20dB-Emission Bandwidth: 1.008kHz

Fundamental out
of restricted bands:

☒ kept
☐ not kept

Limit spurious emission:


☒ kept
☐ not kept

Remarks: n/a

Protocol scope

☒ Diagram – 20dB-Emission bandwidth.

Occupied bandwidth



PRN10_15, UDT-100L 17L/UD/U/H/CS1

Date: 16.MAR.2016 11:20:05

Occupied bandwidth BW = D1 - D2 = 0.499kHz - -0.509kHz = 1.008kHz

1.1.2.5 Antenna requirement

Regulation

47 CFR Part 15 Subpart C - 04/2016

Requirement: ☒ Section 15.203
☒ Permanent attached
☐ Unique coupling to the intentional radiator

Test result

Requirement: ☒ kept
☐ not kept

Authorized antenna: ☐ Print antenna
☒ Internal antenna
☐ n/a

Remarks: n/a


2 Summary

Regulation	Class / Test level	Result	Remark(s)
FCC Rules 47 CFR Part 15 Subpart C			
Terminal voltage 0.15-30MHz	Section 15.207	Limits kept	
Radiated emissions 0.009-30MHz	Section 15.209	Limit kept	
Radiated emissions 30-1000MHz	Section 15.209	Limit kept	
Occupied bandwidth	Section 15.215(c)	n. r.	
Restricted bands	Section 15.205(a)	Requirement kept	
Antenna requirement	Section 15.203	Requirement kept	

n. r. – not relevant

Burgrieden, 2016-08-10

Report generated by:



Acceptance inspector – Peter Hauser