

TEST REPORT

Product : BE3600 Dual-band 2.5G Ceiling
Access Point
Trade mark : Tenda
Model/Type reference : i33
Report Number : EED32S814143
FCC ID : V7TI33
Date of Issue : September 22, 2026
Test Standards : 47 CFR Part 15 Subpart C
Test result : PASS

Prepared for:

Shenzhen Tenda Technology Co., Ltd.
6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District,
Shenzhen, China. 518052

Prepared by:

Centre Testing International Group Co., Ltd.
Building C, Hongwei Industrial Park Block 70, Bao'an District,
Shenzhen, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385



Compiled by:

Frazer Li

Frazer Li

Approved by:

Aaron Ma

Aaron Ma

Reviewed by:

Tom Chen

Tom Chen

Date:

September 22, 2026

Check No.: 5741220626

1 Content

1 CONTENT	2
2 TEST SUMMARY	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 TEST CONFIGURATION	6
3.4 TEST ENVIRONMENT	7
3.5 DESCRIPTION OF SUPPORT UNITS	7
3.6 TEST LOCATION	7
3.7 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2)	7
4 EQUIPMENT LIST	8
5 TEST RESULTS AND MEASUREMENT DATA	12
5.1 ANTENNA REQUIREMENT	12
5.2 AC POWER LINE CONDUCTED EMISSIONS	13
5.3 MAXIMUM CONDUCTED OUTPUT POWER	17
5.4 DTS BANDWIDTH	18
5.5 MAXIMUM POWER SPECTRAL DENSITY	19
5.6 BAND EDGE MEASUREMENTS AND CONDUCTED SPURIOUS EMISSION	20
5.7 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS	21
6 APPENDIX A	138
7 PHOTOGRAPHS	139

2 Test Summary

Test Item	Test Requirement	Result
Antenna Requirement	47 CFR Part 15 Subpart C Section 15.203/15.247 (c)	PASS
AC Power Line Conducted Emission	47 CFR Part 15 Subpart C Section 15.207	PASS
DTS Bandwidth	47 CFR Part 15 Subpart C Section 15.247 (a)(2)	PASS
Maximum Conducted Output Power	47 CFR Part 15 Subpart C Section 15.247 (b)(3)	PASS
Maximum Power Spectral Density	47 CFR Part 15 Subpart C Section 15.247 (e)	PASS
Band edge measurements	47 CFR Part 15 Subpart C Section 15.247(d)	PASS
Conducted Spurious Emissions	47 CFR Part 15 Subpart C Section 15.247(d)	PASS
Radiated Spurious Emission & Restricted bands	47 CFR Part 15 Subpart C Section 15.205/15.209	PASS

3 General Information

3.1 Client Information

Applicant:	Shenzhen Tenda Technology Co., Ltd.
Address of Applicant:	6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District, Shenzhen, China. 518052
Manufacturer:	Shenzhen Tenda Technology Co., Ltd.
Address of Manufacturer:	6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District, Shenzhen, China. 518052

3.2 General Description of EUT

Product Name:	BE3600 Dual-band 2.5G Ceiling Access Point	
Model No.:	i33	
Test Model No.:	i33	
Trade mark:	Tenda	
Product Type:	☒ Mobile ☐ Portable ☐ Fix Location	
Operation Frequency:	IEEE 802.11b/g/n(HT20)/ax(HE20)/be(EHT20): 2412MHz to 2462MHz IEEE 802.11n(HT40)/ax(HE40)/be(EHT40): 2422MHz to 2452MHz	
Modulation Type:	IEEE for 802.11b:DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g:OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40): OFDM (64QAM, 16QAM,QPSK,BPSK) IEEE for 802.11ax(HE20 and HE40): OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11be(HET20 and HET40): OFDMA (4096QAM, 1024QAM, 64QAM, 16QAM, QPSK, BPSK)	
Number of Channel:	IEEE 802.11b/g, IEEE 802.11n HT20/ax HE20/be EHT20: 11 Channels IEEE 802.11n HT40/ax HE40/be EHT40: 7 Channels	
Channel Separation:	5MHz	
Function	☒ SISO ☒ 2x2 MIMO ☐ 3x3 MIMO ☐ 4x4MIMO	
Antenna Type:	PCB Antenna	
Antenna Gain:	Antenna 1:4.80dBi Antenna 2:4.34dBi	
Power Supply:	Adapter:	Input:AC 100-240V 50/60Hz 1A Output:48.0Vdc 0.8A
Test Voltage:	DC 48V	
Sample Received Date:	Jun. 29, 2026	
Sample tested Date:	Jun. 29, 2026 to Jul. 28, 2026	

Operation Frequency each of channel (802.11b/g/n HT20/ax HE20/be EHT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		
Operation Frequency each of channel (802.11n HT40/ax HE40/be EHT40)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
3	2422MHz	6	2437MHz	9	2452MHz		
4	2427MHz	7	2442MHz				
5	2432MHz	8	2447MHz				

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

802.11b/g/n (HT20)/ax (HE20)/be (EHT20)

Channel	Frequency
The lowest channel	2412MHz
The middle channel	2437MHz
The highest channel	2462MHz

802.11n (HT40)/ax (HE40)/be (EHT40)

Channel	Frequency
The lowest channel	2422MHz
The middle channel	2437MHz
The highest channel	2452MHz

3.3 Test Configuration

EUT Test Software Settings:	
Test Software:	QATool_Dbg.exe
EUT Power Grade:	Default
Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.	
Test Mode:	
We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:	
Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.	
Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(HT20)	MCS0
802.11n(HT40)	MCS0
802.11ax(HE20)	MCS0
802.11ax(HE40)	MCS0
802.11be(EHT20)	MCS0
802.11be(EHT40)	MCS0
According to ANSI C63.10 standards, the test results are both the "worst case" and "worst setup" 1Mbps for 802.11b, 6Mbps for 802.11g, MCS0 for 802.11n(HT20), MCS0 for 802.11n(HT40), MCS0 for 802.11ax(HE20), MCS0 for 802.11ax(HE40), MCS0 for 802.11be(EHT20) and MCS0 for 802.11be(EHT40).	

3.4 Test Environment

Operating Environment:	
Radiated Spurious Emissions:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar
Conducted Emissions:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar
RF Conducted:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar

3.5 Description of Support Units

The EUT has been tested independently.

3.6 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd
Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China
Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385
No tests were sub-contracted.
FCC Designation No.: CN1164, Test Firm Registration No.: 260439

3.7 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.9×10^{-8}
2	RF power, conducted	0.46dB (30MHz-1GHz)
		0.55dB (1GHz-40GHz)
3	Radiated Spurious emission test	3.3dB (9kHz-30MHz)
		4.3dB (30MHz-1GHz)
		4.5dB (1GHz-18GHz)
		3.4dB (18GHz-40GHz)
4	Conduction emission	3.5dB (9kHz to 150kHz)
		3.1dB (150kHz to 30MHz)
5	Temperature test	0.64°C
6	Humidity test	3.8%
7	DC power voltages	0.026%

4 Equipment List

RF test system					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Spectrum Analyzer	Keysight	N9010A	MY54510339	11-25-2025	11-24-2026
Spectrum Analyzer	R&S	FSVS3044	101509	05-14-2026	05-13-2027
Signal Generator	Keysight	N5182B	MY53051549	11-13-2025	11-12-2026
Signal Generator	Agilent	N5181A	MY46240094	11-25-2025	11-24-2026
DC Power	Keysight	E3642A	MY56376072	11-13-2025	11-12-2026
Communication test set	R&S	CMW500	169004	02-06-2026	02-05-2027
RF control unit(power unit)	JS Tonscend	JS0806-2	24I80620925	07-21-2025 07-15-2026	07-20-2026 07-14-2027
Wi-Fi 7GHz Band Extender	JS Tonscend	TS-WF7U2	2206200002	05-09-2026	05-08-2027
high-low temperature test chamber	Dong Guang Qin Zhuo	LK-80GA	QZ20150611879	11-13-2025	11-12-2026
Temperature/ Humidity Indicator	biaozhi	HM10	1804186	05-22-2026	05-21-2027
BT&WI-FI Automatic test software	JS Tonscend	JS1120-3	V3.6.21	---	---
Digital multimeter	FLUKE	17B MAX	59545050WS	10-15-2025	10-14-2026

Conducted disturbance Test					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
				(mm-dd-yyyy)	(mm-dd-yyyy)
Receiver	R&S	ESCI	100435	04-07-2026	04-06-2027
Temperature/ Humidity Indicator	Defu	TH128	/	03-24-2026	03-23-2027
LISN	R&S	ENV216	100098	09-13-2025 09-04-2026	09-12-2026 09-03-2027
Barometer	changchun	DYM3	1188	---	---
Test software	Fara	EZ-EMC	EMC-CON 3A1.1	---	---

3M Semi-anechoic Chamber (2)- Radiated disturbance Test					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
				(mm-dd-yyyy)	(mm-dd-yyyy)
3M Chamber & Accessory Equipment	TDK	SAC-3	---	01/13/2024	01/12/2027
Receiver	R&S	ESCI7	100938-003	09/03/2025	09/02/2026
TRILOG Broadband Antenna	schwarzbeck	VULB 9163	9163-618	05/11/2026	05/10/2027
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-076	03/29/2026	03/28/2027
Microwave Preamplifier	Tonscend	EMC051845SE	980380	11/25/2025	11/24/2026
Horn Antenna	A.H.SYSTEMS	SAS-574	374	07/02/2023 05-16-2026	07/01/2026 05-15-2027
Horn Antenna	ETS-LINGREN	BBHA 9120D	9120D-1869	03/31/2026	03/30/2027
Preamplifier	Agilent	11909A	12-1	02/06/2026	02/05/2027
Preamplifier	CD	PAP-1840-60	6041.6042	05/16/2026	05/15/2027
Test software	Fara	EZ-EMC	EMEC-3A1-Pre	---	---
Cable line	Fulai(7M)	SF106	5219/6A	01/13/2024	01/12/2027
Cable line	Fulai(6M)	SF106	5220/6A	01/13/2024	01/12/2027
Cable line	Fulai(3M)	SF106	5216/6A	01/13/2024	01/12/2027
Cable line	Fulai(3M)	SF106	5217/6A	01/13/2024	01/12/2027


3M full-anechoic Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Fully Anechoic Chamber	TDK	FAC-3	---	01-29-2024	01-28-2027
Receiver	Keysight	N9038A	MY57290136	12-22-2025	12-21-2026
Spectrum Analyzer	Keysight	N9020B	MY57111112	12-21-2025	12-20-2026
Spectrum Analyzer	Keysight	N9030B	MY57140871	12-21-2025	12-20-2026
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	9163-1148	03-29-2026	03-28-2027
Horn Antenna	Schwarzbeck	BBHA 9170	9170-832	04-03-2026	04-02-2027
Horn Antenna	ETS-LINDGREN	3117	57407	05-10-2026	05-09-2027
Preamplifier	EMCI	EMC001330	980563	02-06-2026	02-05-2027
Preamplifier	EMCI	EMC051845SE	980380	11-25-2025	11-24-2026
Preamplifier	Tonscend	TAP-011858	AP21B806112	07-07-2025 06-22-2026	07-06-2026 06-21-2027
Communication test set	R&S	CMW500	104466	11-25-2025	11-24-2026
Temperature/ Humidity Indicator	biaozhi	GM1360	EE1186631	03-24-2026	03-23-2027
RSE Automatic test software	JS Tonscend	JS36-RSE	V5.0.0.1	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0001	01-29-2024	01-28-2027
Cable line	Times	SFT205-NMSM-2.50M	394812-0002	01-29-2024	01-28-2027
Cable line	Times	SFT205-NMSM-2.50M	394812-0003	01-29-2024	01-28-2027
Cable line	Times	SFT205-NMSM-2.50M	393495-0001	01-29-2024	01-28-2027
Cable line	Times	EMC104-NMNM-1000	SN160710	01-29-2024	01-28-2027
Cable line	Times	SFT205-NMSM-3.00M	394813-0001	01-29-2024	01-28-2027
Cable line	Times	SFT205-NMNM-1.50M	381964-0001	01-29-2024	01-28-2027
Cable line	Times	SFT205-NMSM-7.00M	394815-0001	01-29-2024	01-28-2027
Cable line	Times	HF160-KMKM-3.00M	393493-0001	01-29-2024	01-28-2027

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)						
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.							
EUT Antenna:	Please see Internal photos						
FCC KDB 662911 D01 Multiple Transmitter Output v02r01 Unequal antenna gains, with equal transmit powers. For antenna gains given by G1, G2, ..., GN dBi ☐ (1)If transmit signals are correlated, then Directional gain = 10 log[(10^{G1/20} + 10^{G2/20} + ... + 10^{GN/20})² /N_{ANT}] dBi [Note the “20”s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.] ☒ (2)If all transmit signals are completely uncorrelated, then Directional gain = 10 log[(10^{G1/10} + 10^{G2/10} + ... + 10^{GN/10}) /N_{ANT}] dBi <table><tr><td>Ant.1(dBi)</td><td>Ant.1(dBi)</td><td>DG(dBi)</td></tr><tr><td>4.80</td><td>4.34</td><td>4.58</td></tr></table>		Ant.1(dBi)	Ant.1(dBi)	DG(dBi)	4.80	4.34	4.58
Ant.1(dBi)	Ant.1(dBi)	DG(dBi)					
4.80	4.34	4.58					


5.2 AC Power Line Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10-2020		
Test Frequency Range:	150kHz to 30MHz		
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Setup:			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane. 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10-2020 on conducted measurement.		
Test Mode:	All modes were tested, only the worse case lowest channel of 1Mbps for 802.11b was recorded in the report.		

Test Results: Pass

Measurement Data

Live line:




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.1740	41.75	10.25	52.00	64.77	-12.77	QP	
2		0.2490	23.38	10.17	33.55	51.79	-18.24	AVG	
3		0.3570	33.07	10.11	43.18	58.80	-15.62	QP	
4		0.3615	24.16	10.11	34.27	48.69	-14.42	AVG	
5		0.4740	10.25	10.08	20.33	46.44	-26.11	AVG	
6		0.9105	6.33	10.17	16.50	46.00	-29.50	AVG	
7		1.4505	17.55	10.18	27.73	56.00	-28.27	QP	
8		4.6635	19.13	10.07	29.20	56.00	-26.80	QP	
9		5.9955	11.82	10.05	21.87	50.00	-28.13	AVG	
10		10.3784	23.87	9.94	33.81	60.00	-26.19	QP	
11		10.7565	17.12	9.94	27.06	50.00	-22.94	AVG	
12		11.7465	24.62	9.92	34.54	60.00	-25.46	QP	

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. Margin=Measurement-Limit.

- 4. Measurement=Reading Level+Correct Factor.
- 5. In the test results, an asterisk (*) indicates Maximum Data, a cross (X) indicates over Limit.
- 6. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:
80.0 dBuV




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.1545	45.37	10.28	55.65	65.75	-10.10	QP	
2		0.1905	21.46	10.22	31.68	54.01	-22.33	AVG	
3		0.3480	30.38	10.11	40.49	59.01	-18.52	QP	
4		0.6540	5.76	10.12	15.88	46.00	-30.12	AVG	
5		0.8025	15.52	10.18	25.70	56.00	-30.30	QP	
6		1.5405	8.22	10.17	18.39	46.00	-27.61	AVG	
7		3.1155	15.81	10.13	25.94	56.00	-30.06	QP	
8		3.6195	6.17	10.11	16.28	46.00	-29.72	AVG	
9		8.6280	15.63	9.99	25.62	60.00	-34.38	QP	
10		14.1540	4.65	9.88	14.53	50.00	-35.47	AVG	
11		21.6735	14.86	9.80	24.66	60.00	-35.34	QP	
12		23.8560	5.89	9.81	15.70	50.00	-34.30	AVG	


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. Margin = Measurement - Limit.
4. Measurement = Reading Level + Correct Factor.
5. In the test results, an asterisk (*) indicates Maximum Data, a cross (X) indicates over Limit.
6. If the Peak value under Average limit, the Average value is not recorded in the report.


5.3 Maximum Conducted Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10-2020
Test Setup:	
Test Procedure:	1. PKPM1 Peak power meter measurement The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector. 2. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01. Method (a): Measure and sum the spectra across the outputs. The total final Power Spectral Density is from a device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points, the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.
Limit:	30dBm
Test Mode:	Refer to clause 3.3
Test Results:	Refer to Appendix A


5.4 DTS Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10-2020
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	a) Set RBW = 100 kHz. b) Set the VBW $\geq [3 \times \text{RBW}]$. c) Detector = peak. d) Trace mode = max hold. e) Sweep = auto couple. f) Allow the trace to stabilize. g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
Limit:	$\geq 500 \text{ kHz}$
Test Mode:	Refer to clause 3.3
Test Results:	Refer to Appendix A

5.5 Maximum Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10-2020
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	a) Set analyzer center frequency to DTS channel center frequency. b) Set the span to 1.5 times the DTS bandwidth. c) Set the RBW to $3 \text{ kHz} < \text{RBW} < 100 \text{ kHz}$. d) Set the VBW $> [3 \times \text{RBW}]$. e) Detector = power averaging (rms) or sample detector (when rms not available). f) Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / \text{RBW}]$. g) Sweep time = auto couple. h) Employ trace averaging (rms) mode over a minimum of 100 traces.. i) Use the peak marker function to determine the maximum amplitude level. j) If the measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat (note that this might require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced). K) For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01. Method (a): Measure and sum the spectra across the outputs.The total final Power Spectral Density is from a device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points, the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.
Limit:	$\leq 8.00 \text{ dBm}/3 \text{ kHz}$
Test Mode:	Refer to clause 3.3
Test Results:	Refer to Appendix A

5.6 Band Edge Measurements and Conducted Spurious Emission

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10-2020
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	a) Set RBW = 100KHz. b) Set VBW = 300KHz. c) Sweep time = auto couple. d) Detector = peak. e) Trace mode = max hold. f) Allow trace to fully stabilize. g) Use peak marker function to determine the peak amplitude level.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Refer to clause 3.3
Test Results:	Refer to Appendix A

5.7 Radiated Spurious Emission & Restricted bands

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10-2020				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10kHz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 - 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- Note: For the radiated emission test above 1GHz:
- Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
 - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both

	horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel (2402MHz),the middle channel (2440MHz),the Highest channel (2480MHz) h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete.
Test Mode:	Refer to clause 3.3
Test Results:	Pass


Radiated Spurious Emission below 1GHz:

During the test, the Radiates Emission from 30MHz to 1GHz was performed in all modes, only the worst case lowest channel of 1Mbps for 802.11b was recorded in the report.

Test Graph

Horizontal:


72.0 dBuV/m



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Antenna Height cm	Table Degree	Comment
1		55.9909	2.16	13.96	16.12	40.00	-23.88	QP	100	35	
2		113.9738	15.31	13.09	28.40	43.50	-15.10	QP	100	302	
3		178.8524	23.04	10.98	34.02	43.50	-9.48	QP	100	328	
4	*	201.6756	23.33	12.66	35.99	43.50	-7.51	QP	100	345	
5		269.2394	21.69	15.24	36.93	46.00	-9.07	QP	100	345	
6		330.1948	14.14	17.34	31.48	46.00	-14.52	QP	100	78	

Remark:

1. $\text{Margin} = \text{Measurement}(\text{Level}) - \text{Limit}$.
2. $\text{Measurement}(\text{Level}) = \text{Reading Level} + \text{Correct Factor}$.
3. In the test results, an asterisk (*) indicates Maximum Data, a cross (X) indicates over Limit, an exclamation mark (!) indicates over -6dB margin Limit.



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1		35.2450	14.66	12.86	27.52	40.00	-12.48	QP 100	284
2		70.9930	15.25	10.90	26.15	40.00	-13.85	QP 100	345
3		114.0938	20.46	13.06	33.52	43.50	-9.98	QP 100	58
4	*	168.8868	24.18	10.99	35.17	43.50	-8.33	QP 100	345
5		339.7674	9.98	17.66	27.64	46.00	-18.36	QP 100	5
6		623.2177	2.11	23.28	25.39	46.00	-20.61	QP 100	258

Remark:

1. Margin=Measurement(Level)-Limit.
2. Measurement(Level)=Reading Level+Correct Factor.
3. In the test results, an asterisk (*) indicates Maximum Data, a cross (X) indicates over Limit, an exclamation mark (!) indicates over -6dB margin Limit.


Radiated Spurious Emission above 1GHz:

Remark: Through Pre-scan, for 20MHz Occupied Bandwidth, 802.11 b mode was the worst case; for 40MHz Occupied Bandwidth, 802.11 n(HT40) mode was the worst case; only the worst case of was recorded in the report.

SISO:

Test_Mode	802.11 b Transmitting	Test_Frequency	2412MHz
Tset_Engineer	\	Test_Date	2026/7/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1534.83	13.47	41.97	55.44	74.00	18.56	PASS	Horizontal	PK
2	2852.92	17.30	37.37	54.67	74.00	19.33	PASS	Horizontal	PK
3	5000.13	-8.15	63.37	55.22	74.00	18.78	PASS	Horizontal	PK
4	10377.4	1.87	50.16	52.03	74.00	21.97	PASS	Horizontal	PK
5	13738.7	7.19	50.53	57.72	74.00	16.28	PASS	Horizontal	PK
6	16287.8	10.84	49.46	60.30	74.00	13.70	PASS	Horizontal	PK
7	1517.10	13.29	27.34	40.63	54.00	13.37	PASS	Horizontal	AV
8	2838.92	17.49	19.56	37.05	54.00	16.95	PASS	Horizontal	AV
9	4990.13	-8.12	47.36	39.24	54.00	14.76	PASS	Horizontal	AV
10	13760.7	7.29	39.91	47.20	54.00	6.80	PASS	Horizontal	AV
11	16337.8	11.44	37.25	48.69	54.00	5.31	PASS	Horizontal	AV

Test_Mode	802.11 b Transmitting	Test_Frequency	2412MHz
Tset_Engineer	\	Test_Date	2026/7/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1511.36	13.29	43.04	56.33	74.00	17.67	PASS	Vertical	PK
2	2934.66	17.71	37.83	55.54	74.00	18.46	PASS	Vertical	PK
3	5000.13	-8.15	63.61	55.46	74.00	18.54	PASS	Vertical	PK
4	10209.4	1.61	50.26	51.87	74.00	22.13	PASS	Vertical	PK
5	13667.7	7.38	50.77	58.15	74.00	15.85	PASS	Vertical	PK
6	16330.8	11.35	50.06	61.41	74.00	12.59	PASS	Vertical	PK
7	1505.36	13.31	31.14	44.45	54.00	9.55	PASS	Vertical	AV
8	2970.39	17.94	19.30	37.24	54.00	16.76	PASS	Vertical	AV
9	4993.13	-8.14	47.08	38.94	54.00	15.06	PASS	Vertical	AV
10	13684.7	7.31	40.00	47.31	54.00	6.69	PASS	Vertical	AV
11	16497.8	11.90	37.00	48.90	54.00	5.10	PASS	Vertical	AV

Test_Mode	802.11 b Transmitting	Test_Frequency	2412MHz
Tset_Engineer	\	Test_Date	2026/7/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18562.7	-26.69	62.81	36.12	74.00	37.88	PASS	Horizontal	PK
2	19894.5	-24.94	60.72	35.78	74.00	38.22	PASS	Horizontal	PK
3	21718.7	-25.62	61.06	35.44	74.00	38.56	PASS	Horizontal	PK
4	22830.5	-25.14	59.40	34.26	74.00	39.74	PASS	Horizontal	PK
5	24585.0	-21.86	58.12	36.26	74.00	37.74	PASS	Horizontal	PK
6	26045.4	-21.00	57.08	36.08	74.00	37.92	PASS	Horizontal	PK

Test_Mode	802.11 b Transmitting	Test_Frequency	2412MHz
Tset_Engineer	\	Test_Date	2026/7/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18718.4	-26.45	62.92	36.47	74.00	37.53	PASS	Vertical	PK
2	19823.4	-25.16	61.14	35.98	74.00	38.02	PASS	Vertical	PK
3	21159.7	-25.80	61.00	35.20	74.00	38.80	PASS	Vertical	PK
4	22921.6	-25.44	60.18	34.74	74.00	39.26	PASS	Vertical	PK
5	24645.9	-21.89	56.74	34.85	74.00	39.15	PASS	Vertical	PK
6	25939.3	-20.87	56.86	35.99	74.00	38.01	PASS	Vertical	PK

Test_Mode	802.11 b Transmitting	Test_Frequency	2437MHz
Tset_Engineer	\	Test_Date	2026/7/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1534.03	13.47	41.55	55.02	74.00	18.98	PASS	Horizontal	PK
2	2887.05	17.55	37.40	54.95	74.00	19.05	PASS	Horizontal	PK
3	4982.13	-8.11	62.68	54.57	74.00	19.43	PASS	Horizontal	PK
4	9169.41	0.13	51.65	51.78	74.00	22.22	PASS	Horizontal	PK
5	13748.7	7.17	50.78	57.95	74.00	16.05	PASS	Horizontal	PK
6	16502.9	11.93	49.11	61.04	74.00	12.96	PASS	Horizontal	PK
7	1538.30	13.49	26.43	39.92	54.00	14.08	PASS	Horizontal	AV
8	2859.05	17.35	19.34	36.69	54.00	17.31	PASS	Horizontal	AV
9	4990.13	-8.12	46.53	38.41	54.00	15.59	PASS	Horizontal	AV
10	13681.7	7.33	39.66	46.99	54.00	7.01	PASS	Horizontal	AV
11	16342.8	11.50	37.98	49.48	54.00	4.52	PASS	Horizontal	AV

Test_Mode	802.11 b Transmitting	Test_Frequency	2437MHz
Tset_Engineer	\	Test_Date	2026/7/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1495.63	13.34	43.40	56.74	74.00	17.26	PASS	Vertical	PK
2	2971.33	17.93	37.29	55.22	74.00	18.78	PASS	Vertical	PK
3	5000.13	-8.15	65.41	57.26	74.00	16.74	PASS	Vertical	PK
4	9309.42	0.85	51.22	52.07	74.00	21.93	PASS	Vertical	PK
5	13699.7	7.26	51.59	58.85	74.00	15.15	PASS	Vertical	PK
6	16501.9	11.94	49.08	61.02	74.00	12.98	PASS	Vertical	PK
7	1508.83	13.29	31.75	45.04	54.00	8.96	PASS	Vertical	AV
8	2975.99	17.90	18.85	36.75	54.00	17.25	PASS	Vertical	AV
9	4990.13	-8.12	48.32	40.20	54.00	13.80	PASS	Vertical	AV
10	13685.7	7.31	39.45	46.76	54.00	7.24	PASS	Vertical	AV
11	16331.8	11.37	37.71	49.08	54.00	4.92	PASS	Vertical	AV

Test_Mode	802.11 b Transmitting	Test_Frequency	2437MHz
Tset_Engineer	\	Test_Date	2026/7/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18638.8	-26.61	62.68	36.07	74.00	37.93	PASS	Horizontal	PK
2	19949.6	-24.77	60.68	35.91	74.00	38.09	PASS	Horizontal	PK
3	21050.9	-25.94	60.82	34.88	74.00	39.12	PASS	Horizontal	PK
4	22613.3	-25.00	59.82	34.82	74.00	39.18	PASS	Horizontal	PK
5	24805.7	-21.96	57.34	35.38	74.00	38.62	PASS	Horizontal	PK
6	25920.6	-20.87	56.70	35.83	74.00	38.17	PASS	Horizontal	PK

Test_Mode	802.11 b Transmitting	Test_Frequency	2437MHz
Tset_Engineer	\	Test_Date	2026/7/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	18690.9	-26.51	62.63	36.12	74.00	37.88	PASS	Vertical	PK
2	19723.8	-25.37	60.95	35.58	74.00	38.42	PASS	Vertical	PK
3	20846.2	-25.73	61.10	35.37	74.00	38.63	PASS	Vertical	PK
4	23207.6	-24.25	59.21	34.96	74.00	39.04	PASS	Vertical	PK
5	24519.7	-21.79	57.08	35.29	74.00	38.71	PASS	Vertical	PK
6	25786.6	-20.81	57.32	36.51	74.00	37.49	PASS	Vertical	PK

Test_Mode	802.11 b Transmitting	Test_Frequency	2462MHz
Tset_Engineer	\	Test_Date	2026/7/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1495.76	13.34	41.42	54.76	74.00	19.24	PASS	Horizontal	PK
2	2873.85	17.42	37.68	55.10	74.00	18.90	PASS	Horizontal	PK
3	4988.13	-8.12	62.09	53.97	74.00	20.03	PASS	Horizontal	PK
4	10276.4	1.93	50.64	52.57	74.00	21.43	PASS	Horizontal	PK
5	13682.7	7.33	51.34	58.67	74.00	15.33	PASS	Horizontal	PK
6	16289.8	10.86	50.56	61.42	74.00	12.58	PASS	Horizontal	PK
7	1506.30	13.31	26.27	39.58	54.00	14.42	PASS	Horizontal	AV
8	2857.05	17.34	19.73	37.07	54.00	16.93	PASS	Horizontal	AV
9	4989.13	-8.12	46.55	38.43	54.00	15.57	PASS	Horizontal	AV
10	13745.7	7.18	39.74	46.92	54.00	7.08	PASS	Horizontal	AV
11	16334.8	11.40	37.66	49.06	54.00	4.94	PASS	Horizontal	AV

Test_Mode	802.11 b Transmitting	Test_Frequency	2462MHz
Tset_Engineer	\	Test_Date	2026/7/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1512.83	13.29	43.16	56.45	74.00	17.55	PASS	Vertical	PK
2	2820.92	17.14	38.35	55.49	74.00	18.51	PASS	Vertical	PK
3	4977.13	-8.09	65.34	57.25	74.00	16.75	PASS	Vertical	PK
4	8313.35	-1.04	52.50	51.46	74.00	22.54	PASS	Vertical	PK
5	13742.7	7.18	50.83	58.01	74.00	15.99	PASS	Vertical	PK
6	16331.8	11.37	49.24	60.61	74.00	13.39	PASS	Vertical	PK
7	1511.50	13.29	31.44	44.73	54.00	9.27	PASS	Vertical	AV
8	2844.78	17.41	19.74	37.15	54.00	16.85	PASS	Vertical	AV
9	4982.13	-8.11	47.71	39.60	54.00	14.40	PASS	Vertical	AV
10	13680.7	7.34	39.72	47.06	54.00	6.94	PASS	Vertical	AV
11	16414.8	10.27	38.58	48.85	54.00	5.15	PASS	Vertical	AV

Test_Mode	802.11 b Transmitting	Test_Frequency	2462MHz
Tset_Engineer	\	Test_Date	2026/7/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18970.0	-26.27	61.74	35.47	74.00	38.53	PASS	Horizontal	PK
2	20124.0	-25.17	60.25	35.08	74.00	38.92	PASS	Horizontal	PK
3	21490.5	-25.81	61.05	35.24	74.00	38.76	PASS	Horizontal	PK
4	22732.3	-25.03	59.20	34.17	74.00	39.83	PASS	Horizontal	PK
5	24368.4	-21.83	57.86	36.03	74.00	37.97	PASS	Horizontal	PK
6	25519.7	-21.01	57.14	36.13	74.00	37.87	PASS	Horizontal	PK

Test_Mode	802.11 b Transmitting	Test_Frequency	2462MHz
Tset_Engineer	\	Test_Date	2026/7/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18825.8	-26.29	61.90	35.61	74.00	38.39	PASS	Vertical	PK
2	20452.1	-25.63	60.86	35.23	74.00	38.77	PASS	Vertical	PK
3	21741.5	-25.59	60.63	35.04	74.00	38.96	PASS	Vertical	PK
4	23228.3	-24.17	59.21	35.04	74.00	38.96	PASS	Vertical	PK
5	24803.3	-21.96	56.97	35.01	74.00	38.99	PASS	Vertical	PK
6	26098.4	-21.13	57.26	36.13	74.00	37.87	PASS	Vertical	PK

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	2422MHz
Tset_Engineer	\	Test_Date	2026/7/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1514.70	13.30	41.71	55.01	74.00	18.99	PASS	Horizontal	PK
2	2809.32	17.26	38.36	55.62	74.00	18.38	PASS	Horizontal	PK
3	4984.13	-8.11	62.48	54.37	74.00	19.63	PASS	Horizontal	PK
4	8533.36	-0.51	52.02	51.51	74.00	22.49	PASS	Horizontal	PK
5	13738.7	7.19	51.15	58.34	74.00	15.66	PASS	Horizontal	PK
6	16332.8	11.38	50.29	61.67	74.00	12.33	PASS	Horizontal	PK
7	1511.23	13.29	25.06	38.35	54.00	15.65	PASS	Horizontal	AV
8	2838.12	17.47	19.75	37.22	54.00	16.78	PASS	Horizontal	AV
9	4991.13	-8.13	46.19	38.06	54.00	15.94	PASS	Horizontal	AV
10	13717.7	7.22	39.89	47.11	54.00	6.89	PASS	Horizontal	AV
11	16347.8	11.56	37.78	49.34	54.00	4.66	PASS	Horizontal	AV

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	2422MHz
Tset_Engineer	\	Test_Date	2026/7/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1516.96	13.29	43.72	57.01	74.00	16.99	PASS	Vertical	PK
2	2810.92	17.26	38.00	55.26	74.00	18.74	PASS	Vertical	PK
3	5000.13	-8.15	65.52	57.37	74.00	16.63	PASS	Vertical	PK
4	10262.4	1.96	51.38	53.34	74.00	20.66	PASS	Vertical	PK
5	13672.7	7.36	51.09	58.45	74.00	15.55	PASS	Vertical	PK
6	16347.8	11.56	49.52	61.08	74.00	12.92	PASS	Vertical	PK
7	1505.23	13.31	31.01	44.32	54.00	9.68	PASS	Vertical	AV
8	2796.11	17.26	19.55	36.81	54.00	17.19	PASS	Vertical	AV
9	4989.13	-8.12	48.12	40.00	54.00	14.00	PASS	Vertical	AV
10	13695.7	7.27	39.58	46.85	54.00	7.15	PASS	Vertical	AV
11	16335.8	11.41	37.35	48.76	54.00	5.24	PASS	Vertical	AV

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	2422MHz
Tset_Engineer	\	Test_Date	2026/7/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18603.1	-26.68	63.33	36.65	74.00	37.35	PASS	Horizontal	PK
2	19477.6	-25.60	61.76	36.16	74.00	37.84	PASS	Horizontal	PK
3	20844.8	-25.73	61.04	35.31	74.00	38.69	PASS	Horizontal	PK
4	23103.6	-24.95	59.50	34.55	74.00	39.45	PASS	Horizontal	PK
5	24575.1	-21.85	57.18	35.33	74.00	38.67	PASS	Horizontal	PK
6	25795.1	-20.82	56.77	35.95	74.00	38.05	PASS	Horizontal	PK

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	2422MHz
Tset_Engineer	\	Test_Date	2026/7/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18870.7	-26.28	62.10	35.82	74.00	38.18	PASS	Vertical	PK
2	19842.5	-25.10	60.69	35.59	74.00	38.41	PASS	Vertical	PK
3	21090.7	-25.88	60.95	35.07	74.00	38.93	PASS	Vertical	PK
4	22472.1	-25.07	60.57	35.50	74.00	38.50	PASS	Vertical	PK
5	23854.0	-22.23	58.46	36.23	74.00	37.77	PASS	Vertical	PK
6	25451.3	-21.25	56.55	35.30	74.00	38.70	PASS	Vertical	PK

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	2437MHz
Tset_Engineer	\	Test_Date	2026/7/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	1533.36	13.46	40.49	53.95	74.00	20.05	PASS	Horizontal	PK
2	2850.12	17.29	37.60	54.89	74.00	19.11	PASS	Horizontal	PK
3	4996.13	-8.14	63.06	54.92	74.00	19.08	PASS	Horizontal	PK
4	9245.41	0.59	52.23	52.82	74.00	21.18	PASS	Horizontal	PK
5	13686.7	7.31	50.51	57.82	74.00	16.18	PASS	Horizontal	PK
6	16323.8	11.26	50.34	61.60	74.00	12.40	PASS	Horizontal	PK
7	2860.92	17.37	19.38	36.75	54.00	17.25	PASS	Horizontal	AV
8	4985.13	-8.11	46.40	38.29	54.00	15.71	PASS	Horizontal	AV
9	13676.7	7.35	39.53	46.88	54.00	7.12	PASS	Horizontal	AV
10	16346.8	11.54	37.97	49.51	54.00	4.49	PASS	Horizontal	AV

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	2437MHz
Tset_Engineer	\	Test_Date	2026/7/23

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1512.43	13.29	43.37	56.66	74.00	17.34	PASS	Vertical	PK
2	2867.19	17.41	37.38	54.79	74.00	19.21	PASS	Vertical	PK
3	4983.13	-8.11	65.50	57.39	74.00	16.61	PASS	Vertical	PK
4	10179.4	1.53	50.68	52.21	74.00	21.79	PASS	Vertical	PK
5	13761.7	7.30	51.22	58.52	74.00	15.48	PASS	Vertical	PK
6	16501.9	11.94	48.86	60.80	74.00	13.20	PASS	Vertical	PK
7	1511.76	13.29	30.91	44.20	54.00	9.80	PASS	Vertical	AV
8	2846.52	17.37	19.38	36.75	54.00	17.25	PASS	Vertical	AV
9	4992.13	-8.13	48.09	39.96	54.00	14.04	PASS	Vertical	AV
10	13680.7	7.34	39.76	47.10	54.00	6.90	PASS	Vertical	AV
11	16336.8	11.43	37.26	48.69	54.00	5.31	PASS	Vertical	AV