

FCC PART 15.247 TEST REPORT

For

SHENZHEN TENDA TECHNOLOGY CO.,LTD.

6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District, Shenzhen, China. 518052

FCC ID: V7TO1

Report Type: Original Report	Product Name: 500m Outdoor Point to Point CPE
Report Number: RDG180123003-00B	
Report Date: 2018-02-07	
Reviewed By:	Jerry Zhang EMC Manager
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	6
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	9
SUPPORT CABLE LIST AND DETAILS	9
BLOCK DIAGRAM OF TEST SETUP	10
SUMMARY OF TEST RESULTS	11
FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	12
APPLICABLE STANDARD	12
FCC §15.203 - ANTENNA REQUIREMENT.....	13
APPLICABLE STANDARD	13
ANTENNA CONNECTOR CONSTRUCTION	13
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	14
APPLICABLE STANDARD	14
EUT SETUP	14
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE	15
CORRECTED AMPLITUDE & MARGIN CALCULATION	15
TEST EQUIPMENT LIST AND DETAILS.....	15
TEST DATA	16
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	20
APPLICABLE STANDARD	20
EUT SETUP	20
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	21
TEST PROCEDURE	21
CORRECTED AMPLITUDE & MARGIN CALCULATION	21
TEST EQUIPMENT LIST AND DETAILS.....	22
TEST DATA	22
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	31
APPLICABLE STANDARD	31
TEST PROCEDURE	31
TEST EQUIPMENT LIST AND DETAILS.....	31
TEST DATA	31
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	39
APPLICABLE STANDARD	39
TEST PROCEDURE	39
TEST EQUIPMENT LIST AND DETAILS.....	39

TEST DATA	40
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	41
APPLICABLE STANDARD	41
TEST PROCEDURE	41
TEST EQUIPMENT LIST AND DETAILS.....	41
TEST DATA	42
FCC §15.247(e) - POWER SPECTRAL DENSITY	51
APPLICABLE STANDARD	51
TEST PROCEDURE	51
TEST EQUIPMENT LIST AND DETAILS.....	51
TEST DATA	51

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:		500m Outdoor Point to Point CPE
EUT Model:		O1
FCC ID:		V7TO1
Rated Input Voltage:		DC 9V from adapter or DC 48V from POE port
Adapter Information	Model:	BN049-A05009U
	Input:	100-240V~ 50/60Hz 0.3A
	Output:	9V, 600mA
External Dimension:		Length (19.4 cm)*Width (8 cm)*High (6.7 cm)
Serial Number:		180123003
EUT Received Date:		2018.01.23

Objective

This report is prepared on behalf of **SHENZHEN TENDA TECHNOLOGY CO.,LTD.** in accordance with Part 2, Subpart J, Part 15, Subparts A, and C of the Federal Communications Commission's rules.

The tests were performed in order to determine the compliance of the EUT with FCC Rules Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

N/A

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and KDB 558074 D01 DTS Meas Guidance v04.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.58 dB for Horizontal, 4.59 dB for Vertical 200M~1GHz: 4.83 dB for Horizontal, 5.85 dB for Vertical 1G~6GHz: 4.45 dB, 6G~26.5GHz: 5.23 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218,the FCC Designation No. : CN1220.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062D.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in Engineering Mode, which was provided by the manufacturer.

The device has 2 internal antennas for 2.4GHz. For 2.4GHz band, 11 channels are provided:

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were test with channel 1,6,11.

For 802.11n ht40 mode was test with channel 3,6, 9.

The device supports SISO and MIMO mode at 802.11n ht20 and 802.11n ht40 mode, per pre-test, MIMO mode was the worst and reported.

Equipment Modifications

No modification was made to the EUT tested.


EUT Exercise Software

The software “MP-Test” was used for testing, which was provided by manufacturer. The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations. The maximum power was configured as below table, that provided by the manufacturer:

Antenna 0/Antenna 1				
Test Mode	Test Software Version	MP-Test		
802.11b	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	1Mbps	1Mbps	1Mbps
	Power Level Setting	53/52	53/50	53/48
802.11g	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	6Mbps	6Mbps	6Mbps
	Power Level Setting	54/53	57/54	58/54
802.11n ht20	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	MCS8	MCS8	MCS8
	Power Level Setting	54/54	54/54	52/52
802.11n ht40	Test Frequency	2422MHz	2437MHz	2452MHz
	Data Rate	MCS8	MCS8	MCS8
	Power Level Setting	54/54	54/54	53/53


The duty cycle as below:

Mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
802.11b	100	100	100
802.11g	100	100	100
802.11n ht20	100	100	100
802.11n ht40	100	100	100




Date: 5.FEB.2018 10:37:41

802.11g




Date: 5.FEB.2018 10:34:43

802.11n ht20



Date: 5.FEB.2018 10:35:11

802.11n ht40



Date: 5.FEB.2018 10:35:30

Local Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	Laptop	PP11L	QDS-BRCM1017

Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
RJ45 Cable	Yes	No	10	RJ45 Port of Laptop	EUT/POE Adapter
Adapter Cable	No	No	1.21	Adapter	EUT
RJ45 Cable	Yes	No	1.0	POE Adapter	EUT

Block Diagram of Test Setup

Adapter Mode:



POE Mode:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum conducted output power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2412-2462	8	6.31	28	630.96	20.00	0.7924	1.0

Result: The device meet FCC MPE at 20 cm distance

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT have 2 internal antennas, which was permanently attached to the Unit, both antenna gains are 8dBi. Please refer to the EUT photo.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The EUT was connected to the main lisn with AC 120 V/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the EUT was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2017-12-08	2018-12-08
R&S	L.I.S.N	ESH2-Z5	892107/021	2017-09-25	2018-09-25
R&S	Two-line V-network	ENV 216	3560.6550.12	2017-12-08	2018-12-08
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A
N/A	Coaxial Cable	C-NJNJ-50	C-0200-01	2017-09-05	2018-09-05

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Temperature:	23.4 °C
Relative Humidity:	41 %
ATM Pressure:	101.1 kPa

The testing was performed by Jim Zhang on 2018-01-25.

Test Mode: Transmitting


Adapter Mode:

AC120 V, 60 Hz, Line:




Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.154858	42.5	9.000	L1	11.1	23.2	65.7	Compliance
0.167702	44.3	9.000	L1	10.9	20.8	65.1	Compliance
0.519918	27.6	9.000	L1	9.9	28.4	56.0	Compliance
0.676289	28.9	9.000	L1	9.8	27.1	56.0	Compliance
1.108371	35.2	9.000	L1	9.8	20.8	56.0	Compliance
1.289541	36.2	9.000	L1	9.8	19.8	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.349066	28.6	9.000	L1	10.0	20.4	49.0	Compliance
0.372042	29.9	9.000	L1	10.0	18.6	48.5	Compliance
0.396530	29.0	9.000	L1	10.0	19.0	47.9	Compliance
0.432855	24.7	9.000	L1	9.9	22.5	47.2	Compliance
1.108371	30.3	9.000	L1	9.8	15.7	46.0	Compliance
1.289541	28.4	9.000	L1	9.8	17.6	46.0	Compliance

AC120 V, 60 Hz, Neutral:


Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.167702	45.5	9.000	N	10.9	19.6	65.1	Compliance
0.372042	36.8	9.000	N	10.0	21.7	58.5	Compliance
0.511698	31.6	9.000	N	9.9	24.4	56.0	Compliance
0.709407	33.4	9.000	N	9.8	22.6	56.0	Compliance
1.023481	37.9	9.000	N	9.8	18.1	56.0	Compliance
1.289541	37.6	9.000	N	9.8	18.4	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.169044	35.0	9.000	N	10.9	20.0	55.0	Compliance
0.372042	31.6	9.000	N	10.0	16.9	48.5	Compliance
0.396530	29.8	9.000	N	10.0	18.1	47.9	Compliance
0.436318	30.2	9.000	N	9.9	16.9	47.1	Compliance
1.048242	31.9	9.000	N	9.8	14.1	46.0	Compliance
1.289541	32.0	9.000	N	9.8	14.0	46.0	Compliance

POE Mode:**AC120 V, 60 Hz, Line:**

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.173134	41.5	9.000	L1	10.9	23.3	64.8	Compliance
0.609741	29.1	9.000	L1	9.8	26.9	56.0	Compliance
0.676289	28.9	9.000	L1	9.8	27.1	56.0	Compliance
0.774393	29.0	9.000	L1	9.8	27.0	56.0	Compliance
1.031669	34.0	9.000	L1	9.8	22.0	56.0	Compliance
1.289541	36.7	9.000	L1	9.8	19.3	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.346296	29.1	9.000	L1	10.0	20.0	49.1	Compliance
0.372042	30.8	9.000	L1	10.0	17.7	48.5	Compliance
0.396530	28.9	9.000	L1	10.0	19.0	47.9	Compliance
0.419276	26.1	9.000	L1	10.0	21.4	47.5	Compliance
1.239175	29.5	9.000	L1	9.8	16.5	46.0	Compliance
1.289541	28.9	9.000	L1	9.8	17.1	46.0	Compliance



AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.177322	41.9	9.000	N	10.8	22.7	64.6	Compliance
0.372042	36.8	9.000	N	10.0	21.7	58.5	Compliance
0.443327	35.1	9.000	N	9.9	21.9	57.0	Compliance
0.609741	32.5	9.000	N	9.8	23.5	56.0	Compliance
1.135185	36.3	9.000	N	9.8	19.7	56.0	Compliance
1.289541	37.9	9.000	N	9.8	18.1	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.167702	34.7	9.000	N	10.9	20.4	55.1	Compliance
0.372042	30.2	9.000	N	10.0	18.3	48.5	Compliance
0.396530	29.6	9.000	N	10.0	18.3	47.9	Compliance
0.436318	30.5	9.000	N	9.9	16.6	47.1	Compliance
1.023481	32.7	9.000	N	9.8	13.3	46.0	Compliance
1.289541	32.5	9.000	N	9.8	13.5	46.0	Compliance

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

EUT Setup**Below 1GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2017-09-01	2018-08-31
Sunol Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10
HP	Amplifier	8447D	2727A05902	2017-09-05	2018-09-05
Agilent	Spectrum Analyzer	E4440A	SG43360054	2017-12-08	2018-12-08
ETS-Lindgren	Horn Antenna	3115	000 527 35	2016-01-05	2019-01-04
MITEQ	Amplifier	AFS42-00101800-25-S-42	2001271	2017-09-05	2018-09-05
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2016-11-18	2019-11-18
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2017-06-27	2018-06-27
Chengdu Ouli	Band Rejection Filter	2400-2483.5	002	2017-09-05	2018-09-05
N/A	Coaxial Cable	C-NJNJ-50	C-0400-01	2017-09-05	2018-09-05
N/A	Coaxial Cable	C-NJNJ-50	C-0075-01	2017-09-05	2018-09-05
N/A	Coaxial Cable	C-NJNJ-50	C-1000-01	2017-09-05	2018-09-05
N/A	Coaxial Cable	C-SJSJ-50	C-0800-01	2017-09-05	2018-09-05
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Temperature:	23.3~23.8 °C
Relative Humidity:	40~50 %
ATM Pressure:	101.1~101.2 kPa

* The testing was performed by Blake Yang&Steven Zuo from 2018-01-25 to 2018-01-26.


Test Mode: Transmitting(POE mode was the worst)

1) Below 1GHz(802.11b mode middle channel was the worst):

Horizontal



Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
42.6100	42.75	QP	-8.05	34.70	40.00	5.30
77.5300	45.28	QP	-11.08	34.20	40.00	5.80
142.5200	35.44	QP	-6.34	29.10	43.50	14.40
290.9300	30.84	QP	-4.04	26.80	46.00	19.20
326.8200	32.45	QP	-3.85	28.60	46.00	17.40
696.3900	25.88	QP	2.42	28.30	46.00	17.70

Vertical

Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
49.4000	43.44	QP	-11.34	32.10	40.00	7.90
110.5100	34.83	QP	-6.03	28.80	43.50	14.70
148.3400	36.90	QP	-6.50	30.40	43.50	13.10
165.8000	36.38	QP	-6.98	29.40	43.50	14.10
226.9100	35.60	QP	-6.70	28.90	46.00	17.10
243.4000	35.48	QP	-6.28	29.20	46.00	16.80

802.11b(Chain 0 was the worst)

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	77.57	PK	H	28.12	1.81	0.00	107.50	N/A	N/A
2412.00	73.31	AV	H	28.12	1.81	0.00	103.24	N/A	N/A
2412.00	68.78	PK	V	28.12	1.81	0.00	98.71	N/A	N/A
2412.00	64.29	AV	V	28.12	1.81	0.00	94.22	N/A	N/A
2390.00	31.42	PK	H	28.08	1.80	0.00	61.30	74.00	12.70
2390.00	22.63	AV	H	28.08	1.80	0.00	52.51	54.00	1.49
4824.00	55.55	PK	H	32.95	3.19	37.20	54.49	74.00	19.51
4824.00	52.38	AV	H	32.95	3.19	37.20	51.32	54.00	2.68
7236.00	46.61	PK	H	35.81	4.77	37.27	49.92	74.00	24.08
7236.00	33.31	AV	H	35.81	4.77	37.27	36.62	54.00	17.38
2921.50	49.54	PK	H	29.82	2.13	37.09	44.40	74.00	29.60
2921.50	43.62	AV	H	29.82	2.13	37.09	38.48	54.00	15.52
Middle Channel: 2437 MHz									
2437.00	78.39	PK	H	28.17	1.82	0.00	108.38	N/A	N/A
2437.00	74.08	AV	H	28.17	1.82	0.00	104.07	N/A	N/A
2437.00	71.74	PK	V	28.17	1.82	0.00	101.73	N/A	N/A
2437.00	67.26	AV	V	28.17	1.82	0.00	97.25	N/A	N/A
4874.00	54.47	PK	H	33.05	3.26	37.21	53.57	74.00	20.43
4874.00	50.57	AV	H	33.05	3.26	37.21	49.67	54.00	4.33
7311.00	46.55	PK	H	36.01	4.64	37.36	49.84	74.00	24.16
7311.00	33.26	AV	H	36.01	4.64	37.36	36.55	54.00	17.45
1642.00	50.24	PK	H	25.80	1.66	36.07	41.63	74.00	32.37
1642.00	36.86	AV	H	25.80	1.66	36.07	28.25	54.00	25.75
High Channel: 2462 MHz									
2462.00	77.82	PK	H	28.22	1.83	0.00	107.87	N/A	N/A
2462.00	73.44	AV	H	28.22	1.83	0.00	103.49	N/A	N/A
2462.00	71.39	PK	V	28.22	1.83	0.00	101.44	N/A	N/A
2462.00	66.75	AV	V	28.22	1.83	0.00	96.80	N/A	N/A
2483.50	31.65	PK	H	28.27	1.84	0.00	61.76	74.00	12.24
2483.50	22.14	AV	H	28.27	1.84	0.00	52.25	54.00	1.75
4924.00	52.32	PK	H	33.15	3.27	37.22	51.52	74.00	22.48
4924.00	47.85	AV	H	33.15	3.27	37.22	47.05	54.00	6.95
7386.00	46.71	PK	H	36.20	4.51	37.46	49.96	74.00	24.04
7386.00	33.27	AV	H	36.20	4.51	37.46	36.52	54.00	17.48
2561.00	50.32	PK	H	28.52	1.87	36.38	44.33	74.00	29.67
2561.00	36.95	AV	H	28.52	1.87	36.38	30.96	54.00	23.04

802.11g(Chain 0 was the worst)

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	77.05	PK	H	28.12	1.81	0.00	106.98	N/A	N/A
2412.00	68.08	AV	H	28.12	1.81	0.00	98.01	N/A	N/A
2412.00	71.54	PK	V	28.12	1.81	0.00	101.47	N/A	N/A
2412.00	62.20	AV	V	28.12	1.81	0.00	92.13	N/A	N/A
2390.00	41.09	PK	H	28.08	1.80	0.00	70.97	74.00	3.03
2390.00	22.44	AV	H	28.08	1.80	0.00	52.32	54.00	1.68
4824.00	50.81	PK	H	32.95	3.19	37.20	49.75	74.00	24.25
4824.00	35.99	AV	H	32.95	3.19	37.20	34.93	54.00	19.07
7236.00	46.53	PK	H	35.81	4.77	37.27	49.84	74.00	24.16
7236.00	33.19	AV	H	35.81	4.77	37.27	36.50	54.00	17.50
1963.00	48.96	PK	H	27.14	1.70	36.16	41.64	74.00	32.36
1963.00	36.49	AV	H	27.14	1.70	36.16	29.17	54.00	24.83
Middle Channel: 2437 MHz									
2437.00	77.14	PK	H	28.17	1.82	0.00	107.13	N/A	N/A
2437.00	68.12	AV	H	28.17	1.82	0.00	98.11	N/A	N/A
2437.00	72.68	PK	V	28.17	1.82	0.00	102.67	N/A	N/A
2437.00	63.91	AV	V	28.17	1.82	0.00	93.90	N/A	N/A
4874.00	51.42	PK	H	33.05	3.26	37.21	50.52	74.00	23.48
4874.00	36.17	AV	H	33.05	3.26	37.21	35.27	54.00	18.73
7311.00	45.97	PK	H	36.01	4.64	37.36	49.26	74.00	24.74
7311.00	32.49	AV	H	36.01	4.64	37.36	35.78	54.00	18.22
3159.00	50.12	PK	H	30.48	2.22	36.99	45.83	74.00	28.17
3159.00	37.41	AV	H	30.48	2.22	36.99	33.12	54.00	20.88
High Channel: 2462 MHz									
2462.00	77.74	PK	H	28.22	1.83	0.00	107.79	N/A	N/A
2462.00	68.73	AV	H	28.22	1.83	0.00	98.78	N/A	N/A
2462.00	72.82	PK	V	28.22	1.83	0.00	102.87	N/A	N/A
2462.00	64.01	AV	V	28.22	1.83	0.00	94.06	N/A	N/A
2483.50	40.15	PK	H	28.27	1.84	0.00	70.26	74.00	3.74
2483.50	22.69	AV	H	28.27	1.84	0.00	52.80	54.00	1.20
4924.00	51.07	PK	H	33.15	3.27	37.22	50.27	74.00	23.73
4924.00	35.92	AV	H	33.15	3.27	37.22	35.12	54.00	18.88
7386.00	46.37	PK	H	36.20	4.51	37.46	49.62	74.00	24.38
7386.00	33.02	AV	H	36.20	4.51	37.46	36.27	54.00	17.73
2819.00	51.34	PK	H	29.45	1.98	36.67	46.10	74.00	27.90
2819.00	37.88	AV	H	29.45	1.98	36.67	32.64	54.00	21.36

802.11n ht20(2Tx was the worst)

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	78.56	PK	H	28.12	1.81	0.00	108.49	N/A	N/A
2412.00	68.27	AV	H	28.12	1.81	0.00	98.20	N/A	N/A
2412.00	71.77	PK	V	28.12	1.81	0.00	101.70	N/A	N/A
2412.00	61.03	AV	V	28.12	1.81	0.00	90.96	N/A	N/A
2390.00	38.44	PK	H	28.08	1.80	0.00	68.32	74.00	5.68
2390.00	22.95	AV	H	28.08	1.80	0.00	52.83	54.00	1.17
4824.00	48.99	PK	H	32.95	3.19	37.20	47.93	74.00	26.07
4824.00	36.27	AV	H	32.95	3.19	37.20	35.21	54.00	18.79
7236.00	46.27	PK	H	35.81	4.77	37.27	49.58	74.00	24.42
7236.00	33.40	AV	H	35.81	4.77	37.27	36.71	54.00	17.29
2043.00	48.95	PK	H	27.39	1.72	36.22	41.84	74.00	32.16
2043.00	36.28	AV	H	27.39	1.72	36.22	29.17	54.00	24.83
Middle Channel: 2437 MHz									
2437.00	79.76	PK	H	28.17	1.82	0.00	109.75	N/A	N/A
2437.00	68.86	AV	H	28.17	1.82	0.00	98.85	N/A	N/A
2437.00	72.66	PK	V	28.17	1.82	0.00	102.65	N/A	N/A
2437.00	62.63	AV	V	28.17	1.82	0.00	92.62	N/A	N/A
4874.00	48.76	PK	H	33.05	3.26	37.21	47.86	74.00	26.14
4874.00	36.14	AV	H	33.05	3.26	37.21	35.24	54.00	18.76
7311.00	46.19	PK	H	36.01	4.64	37.36	49.48	74.00	24.52
7311.00	33.52	AV	H	36.01	4.64	37.36	36.81	54.00	17.19
2637.00	48.73	PK	H	28.79	1.88	36.41	42.99	74.00	31.01
2637.00	36.82	AV	H	28.79	1.88	36.41	31.08	54.00	22.92
High Channel: 2462 MHz									
2462.00	79.04	PK	H	28.22	1.83	0.00	109.09	N/A	N/A
2462.00	68.13	AV	H	28.22	1.83	0.00	98.18	N/A	N/A
2462.00	71.71	PK	V	28.22	1.83	0.00	101.76	N/A	N/A
2462.00	61.49	AV	V	28.22	1.83	0.00	91.54	N/A	N/A
2483.50	39.12	PK	H	28.27	1.84	0.00	69.23	74.00	4.77
2483.50	22.07	AV	H	28.27	1.84	0.00	52.18	54.00	1.82
4924.00	48.57	PK	H	33.15	3.27	37.22	47.77	74.00	26.23
4924.00	36.01	AV	H	33.15	3.27	37.22	35.21	54.00	18.79
7386.00	46.72	PK	H	36.20	4.51	37.46	49.97	74.00	24.03
7386.00	36.58	AV	H	36.20	4.51	37.46	39.83	54.00	14.17
1769.00	50.22	PK	H	26.33	1.65	35.97	42.23	74.00	31.77
1769.00	37.48	AV	H	26.33	1.65	35.97	29.49	54.00	24.51




802.11n ht40(2Tx was the worst)

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB/m)					
Low Channel: 2422 MHz									
2422.00	75.81	PK	H	28.14	1.81	0.00	105.76	N/A	N/A
2422.00	65.05	AV	H	28.14	1.81	0.00	95.00	N/A	N/A
2422.00	68.94	PK	V	28.14	1.81	0.00	98.89	N/A	N/A
2422.00	58.11	AV	V	28.14	1.81	0.00	88.06	N/A	N/A
2390.00	38.44	PK	H	28.08	1.80	0.00	68.32	74.00	5.68
2390.00	22.41	AV	H	28.08	1.80	0.00	52.29	54.00	1.71
4844.00	47.21	PK	H	32.99	3.22	37.20	46.22	74.00	27.78
4844.00	34.19	AV	H	32.99	3.22	37.20	33.20	54.00	20.80
7266.00	46.85	PK	H	35.89	4.72	37.31	50.15	74.00	23.85
7266.00	33.72	AV	H	35.89	4.72	37.31	37.02	54.00	16.98
3286.00	49.52	PK	H	30.79	2.17	36.93	45.55	74.00	28.45
3286.00	37.08	AV	H	30.79	2.17	36.93	33.11	54.00	20.89
Middle Channel: 2437 MHz									
2437.00	76.05	PK	H	28.17	1.82	0.00	106.04	N/A	N/A
2437.00	66.04	AV	H	28.17	1.82	0.00	96.03	N/A	N/A
2437.00	69.07	PK	V	28.17	1.82	0.00	99.06	N/A	N/A
2437.00	57.96	AV	V	28.17	1.82	0.00	87.95	N/A	N/A
4874.00	46.92	PK	H	33.05	3.26	37.21	46.02	74.00	27.98
4874.00	33.83	AV	H	33.05	3.26	37.21	32.93	54.00	21.07
7311.00	46.43	PK	H	36.01	4.64	37.36	49.72	74.00	24.28
7311.00	33.29	AV	H	36.01	4.64	37.36	36.58	54.00	17.42
1909.00	50.14	PK	H	26.92	1.67	36.09	42.64	74.00	31.36
1909.00	38.27	AV	H	26.92	1.67	36.09	30.77	54.00	23.23
High Channel: 2452 MHz									
2452.00	76.09	PK	H	28.20	1.83	0.00	106.12	N/A	N/A
2452.00	66.10	AV	H	28.20	1.83	0.00	96.13	N/A	N/A
2452.00	69.42	PK	V	28.20	1.83	0.00	99.45	N/A	N/A
2452.00	58.77	AV	V	28.20	1.83	0.00	88.80	N/A	N/A
2483.50	37.57	PK	H	28.27	1.84	0.00	67.68	74.00	6.32
2483.50	22.23	AV	H	28.27	1.84	0.00	52.34	54.00	1.66
4904.00	47.02	PK	H	33.11	3.30	37.21	46.22	74.00	27.78
4904.00	33.62	AV	H	33.11	3.30	37.21	32.82	54.00	21.18
7356.00	46.38	PK	H	36.13	4.56	37.42	49.65	74.00	24.35
7356.00	33.26	AV	H	36.13	4.56	37.42	36.53	54.00	17.47
2640.00	49.22	PK	H	28.80	1.88	36.41	43.49	74.00	30.51
2640.00	36.76	AV	H	28.80	1.88	36.41	31.03	54.00	22.97

Worst plots(802.11b Chain 0 Middle channel)




Horizontal

Fundamental
Test with Band
Rejection Filter



Vertical

Fundamental
Test with Band
Rejection Filter



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH


Applicable Standard

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2018-1-4	2019-1-4
N/A	Coaxial Cable	C-SJ00-0010	C0010/03	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	22.7 °C
Relative Humidity:	40 %
ATM Pressure:	102.2 kPa

* The testing was performed by Nami Quan on 2018-01-29.


Test Mode: Transmitting

Test Result: Compliant

Test performed at chain 0, please refer to the following table and plots.


Test mode	Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	9.94	≥ 0.5
	Middle	2437	9.86	≥ 0.5
	High	2462	9.86	≥ 0.5
802.11g	Low	2412	16.35	≥ 0.5
	Middle	2437	16.51	≥ 0.5
	High	2462	16.51	≥ 0.5
802.11n ht20	Low	2412	17.72	≥ 0.5
	Middle	2437	17.8	≥ 0.5
	High	2462	17.8	≥ 0.5
802.11n ht40	Low	2422	36.23	≥ 0.5
	Middle	2437	36.23	≥ 0.5
	High	2452	36.39	≥ 0.5

802.11b –Low Channel




Date: 29.JAN.2018 10:21:22

802.11b- Middle Channel




Date: 29.JAN.2018 10:23:13

802.11b -High Channel




Date: 29.JAN.2018 10:24:38

802.11g- Low Channel




Date: 29.JAN.2018 10:30:54

802.11g - Middle Channel




Date: 29.JAN.2018 10:29:04

802.11g- High Channel




Date: 29.JAN.2018 10:27:07

802.11n ht20- Low Channel




Date: 29.JAN.2018 10:33:24

802.11n ht20- Middle Channel




Date: 29.JAN.2018 10:39:06

802.11n ht20- High Channel




Date: 29.JAN.2018 11:01:14

802.11n ht40- Low Channel




Date: 29.JAN.2018 10:48:41

802.11n ht40 - Middle Channel



Date: 29.JAN.2018 10:51:27

802.11n ht40 - High Channel




Date: 29.JAN.2018 10:58:46

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER**Applicable Standard**

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.
4. Set the power Meter to test Peak output power, record the result as peak power.
5. Set the power meter to test average output power, record the result as average power.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Wideband Power Sensor	N1921A	MY54210016	2017-11-03	2018-11-03
Agilent	P-Series Power Meter	N1912A	MY5000448	2017-11-03	2018-11-03
N/A	Coaxial Cable	C-SJ00-0010	C0010/03	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	22.7 °C
Relative Humidity:	40 %
ATM Pressure:	102.2 kPa

* The testing was performed by Nami Quan on 2018-01-29.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table.

Test mode	Channel	Frequency (MHz)	Max Peak Conducted Output Power (dBm)			Limit (dBm)
			Chain 0	Chain 1	Total	
802.11b	Low	2412	25.24	25.74	/	28
	Middle	2437	24.57	24.97	/	28
	High	2462	24.08	24.21	/	28
802.11g	Low	2412	26.63	26.92	/	28
	Middle	2437	27.28	27.58	/	28
	High	2462	27.08	27.58	/	28
802.11n ht20	Low	2412	24.19	24.46	27.34	28
	Middle	2437	24.47	24.72	27.61	28
	High	2462	24.48	24.2	27.35	28
802.11n ht40	Low	2422	24.12	24	27.07	28
	Middle	2437	24.01	24.06	27.05	28
	High	2452	24.39	24	27.21	28

Note: the maximum antenna gain is 8 dBi, the device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on IEEE 802.11 devices:

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

So:

Directional gain = $G_{ANT} + \text{Array Gain} = 8\text{dBi}$

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**Applicable Standard**

According to FCC§15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2018-1-4	2019-1-4
N/A	Coaxial Cable	C-SJ00-0010	C0010/03	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Temperature:	22.7 °C
Relative Humidity:	40 %
ATM Pressure:	102.2 kPa

* The testing was performed by Nami Quan on 2018-01-29.

Test mode: Transmitting


Test Result: Compliant. Please refer to following plots.

Chain 0:

802.11b: Band Edge, Left Side


Date: 29.JAN.2018 10:22:30

802.11b: Band Edge, Right Side




Date: 29.JAN.2018 10:26:04

802.11g: Band Edge, Left Side




Date: 29.JAN.2018 10:32:14

802.11g: Band Edge, Right Side




Date: 29.JAN.2018 10:28:21

802.11n ht20 Band Edge, Left Side




Date: 29.JAN.2018 10:34:40

802.11n ht20 Band Edge, Right Side




Date: 29.JAN.2018 11:03:16

802.11n ht40 Band Edge, Left Side



Date: 29.JAN.2018 10:50:14


802.11n ht40 Band Edge, Right Side



Date: 29.JAN.2018 11:00:11


Chain 1:

802.11b: Band Edge, Left Side




Date: 29.JAN.2018 11:31:54

802.11b: Band Edge, Right Side




Date: 29.JAN.2018 11:11:38

802.11g: Band Edge, Left Side




Date: 29.JAN.2018 11:29:36

802.11g: Band Edge, Right Side




Date: 29.JAN.2018 11:14:01

802.11n ht20 Band Edge, Left Side




Date: 29.JAN.2018 10:36:41

802.11n ht20 Band Edge, Right Side




Date: 29.JAN.2018 11:05:25

802.11n ht40 Band Edge, Left Side



Date: 29.JAN.2018 10:48:01

802.11n ht40 Band Edge, Right Side



Date: 29.JAN.2018 10:57:44

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the RBW = 3 kHz, VBW = 10 kHz, Set the span to 1.5 times the DTS bandwidth.
4. Use the peak marker function to determine the maximum amplitude level.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2018-1-4	2019-1-4
N/A	Coaxial Cable	C-SJ00-0010	C0010/03	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	22.7 °C
Relative Humidity:	40 %
ATM Pressure:	102.2 kPa

* The testing was performed by Nami Quan on 2018-01-29.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots

Test mode	Channel	Frequency (MHz)	PSD (dBm/3kHz)		Total (dBm/3kHz)	Limit (dBm/3kHz)
			Chain 0	Chain 1		
802.11b	Low	2412	-7.97	-4.96	/	≤6
	Middle	2437	-8.71	-4.39	/	≤6
	High	2462	-9.18	-4.86	/	≤6
802.11g	Low	2412	-8.81	-4.91	/	≤6
	Middle	2437	-9.14	-4.63	/	≤6
	High	2462	-9.21	-4.61	/	≤6
802.11n ht20	Low	2412	-9.13	-5.69	-4.07	≤6
	Middle	2437	-9.35	-5.34	-3.89	≤6
	High	2462	-9.94	-5.06	-3.84	≤6
802.11n ht40	Low	2422	-9.55	-5.6	-4.13	≤6
	Middle	2437	-9.54	-6.37	-4.66	≤6
	High	2452	-9.72	-5.99	-4.46	≤6

Note: the maximum antenna gain is 8 dBi, the device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices:

$$\text{Array Gain} = 10 \log(N_{\text{ANT}}/N_{\text{SS}}) \text{ dB.}$$


So:

$$\text{Directional gain} = G_{\text{ANT}} + \text{Array Gain} = 8 + 10 \cdot \log(2/2) = 8 \text{ dBi}$$

The limit should be reduced by 2dB.


Chain 0:

Power Spectral Density, 802.11b, Low Channel




Date: 29.JAN.2018 10:22:13

Power Spectral Density, 802.11b, Middle Channel




Date: 29.JAN.2018 10:24:05

Power Spectral Density, 802.11b, High Channel




Date: 29.JAN.2018 10:25:46

Power Spectral Density, 802.11g, Low Channel




Date: 29.JAN.2018 10:31:51

Power Spectral Density, 802.11g, Middle Channel




Date: 29.JAN.2018 10:30:04

Power Spectral Density, 802.11g, High Channel




Date: 29.JAN.2018 10:28:04

Power Spectral Density, 802.11n ht20, Low Channel




Date: 29.JAN.2018 10:34:22

Power Spectral Density, 802.11n ht20, Middle Channel




Date: 29.JAN.2018 10:40:36

Power Spectral Density, 802.11n ht20, High Channel




Date: 29.JAN.2018 11:02:52

Power Spectral Density, 802.11n ht40 Low Channel




Date: 29.JAN.2018 10:49:51

Power Spectral Density, 802.11n ht40 Middle Channel



Date: 29.JAN.2018 10:52:46


Power Spectral Density, 802.11n ht40 High Channel



Date: 29.JAN.2018 10:59:54


Chain 1:

Power Spectral Density, 802.11b, Low Channel




Date: 29.JAN.2018 11:31:31

Power Spectral Density, 802.11b, Middle Channel




Date: 29.JAN.2018 11:09:45

Power Spectral Density, 802.11b, High Channel




Date: 29.JAN.2018 11:11:20

Power Spectral Density, 802.11g, Low Channel




Date: 29.JAN.2018 11:29:19

Power Spectral Density, 802.11g, Middle Channel




Date: 29.JAN.2018 11:15:33

Power Spectral Density, 802.11g, High Channel




Date: 29.JAN.2018 11:13:44

Power Spectral Density, 802.11n ht20, Low Channel




Date: 29.JAN.2018 10:36:17

Power Spectral Density, 802.11n ht20, Middle Channel




Date: 29.JAN.2018 10:38:12

Power Spectral Density, 802.11n ht20, High Channel




Date: 29.JAN.2018 11:05:07

Power Spectral Density, 802.11n ht40 Low Channel




Date: 29.JAN.2018 10:47:38

Power Spectral Density, 802.11n ht40 Middle Channel



Date: 29.JAN.2018 10:54:49

Power Spectral Density, 802.11n ht40 High Channel



Date: 29.JAN.2018 10:57:27

***** END OF REPORT *****