



**中认信通**

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



# TEST REPORT

**Applicant:** SHENZHEN TENDA TECHNOLOGY CO.,LTD.

**Address:** 6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District, Shenzhen, China. 518052

**FCC ID:** V7TO3V3

**Product Name:** 2.4G Long Range Outdoor Access Point

**Model Number:** O3

**Standard(s):** 47 CFR Part 15, Subpart C(15.247)  
ANSI C63.10-2013  
KDB 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

**Report Number:** CR22060010-00A

**Date Of Issue:** 2022-07-15

**Reviewed By:** Sun Zhong

*Sun Zhong*

**Title:** Manager

**Test Laboratory:** China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,  
Guangdong, China  
Tel: +86-769-82016888

**Test Facility**

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

**Declarations**

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

# CONTENTS

|                                                                     |           |
|---------------------------------------------------------------------|-----------|
| <b>TEST FACILITY .....</b>                                          | <b>2</b>  |
| <b>DECLARATIONS.....</b>                                            | <b>2</b>  |
| <b>1. GENERAL INFORMATION .....</b>                                 | <b>5</b>  |
| <b>1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....</b> | <b>5</b>  |
| <b>1.2 DESCRIPTION OF TEST CONFIGURATION.....</b>                   | <b>7</b>  |
| 1.2.1 EUT Operation Condition:.....                                 | 7         |
| 1.2.2 Support Equipment List and Details .....                      | 7         |
| 1.2.3 Support Cable List and Details .....                          | 7         |
| 1.2.4 Block Diagram of Test Setup.....                              | 8         |
| <b>1.3 MEASUREMENT UNCERTAINTY .....</b>                            | <b>9</b>  |
| <b>2. SUMMARY OF TEST RESULTS .....</b>                             | <b>10</b> |
| <b>3. REQUIREMENTS AND TEST PROCEDURES .....</b>                    | <b>11</b> |
| <b>3.1 AC LINE CONDUCTED EMISSIONS.....</b>                         | <b>11</b> |
| 3.1.1 Applicable Standard.....                                      | 11        |
| 3.1.2 EUT Setup.....                                                | 12        |
| 3.1.3 EMI Test Receiver Setup .....                                 | 12        |
| 3.1.4 Test Procedure .....                                          | 13        |
| 3.1.5 Corrected Amplitude & Margin Calculation.....                 | 13        |
| <b>3.2 RADIATION SPURIOUS EMISSIONS.....</b>                        | <b>14</b> |
| 3.2.1 Applicable Standard.....                                      | 14        |
| 3.2.2 EUT Setup.....                                                | 14        |
| 3.2.3 EMI Test Receiver & Spectrum Analyzer Setup .....             | 15        |
| 3.2.4 Test Procedure .....                                          | 15        |
| 3.2.5 Corrected Amplitude & Margin Calculation.....                 | 15        |
| <b>3.3 6 DB EMISSION BANDWIDTH:.....</b>                            | <b>16</b> |
| 3.3.1 Applicable Standard.....                                      | 16        |
| 3.3.2 EUT Setup.....                                                | 16        |
| 3.3.3 Test Procedure .....                                          | 16        |
| <b>3.4 MAXIMUM PEAK CONDUCTED OUTPUT POWER:.....</b>                | <b>17</b> |
| 3.4.1 Applicable Standard.....                                      | 17        |
| 3.4.2 EUT Setup.....                                                | 17        |
| 3.4.3 Test Procedure .....                                          | 17        |
| <b>3.5 MAXIMUM POWER SPECTRAL DENSITY: .....</b>                    | <b>18</b> |
| 3.5.1 Applicable Standard.....                                      | 18        |
| 3.5.2 EUT Setup.....                                                | 18        |
| 3.5.3 Test Procedure .....                                          | 18        |
| <b>3.6 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE: .....</b>          | <b>19</b> |
| 3.6.1 Applicable Standard.....                                      | 19        |
| 3.6.2 EUT Setup.....                                                | 19        |
| 3.6.3 Test Procedure .....                                          | 19        |
| <b>3.7 DUTY CYCLE:.....</b>                                         | <b>20</b> |

|                                                     |           |
|-----------------------------------------------------|-----------|
| 3.7.1 EUT Setup.....                                | 20        |
| 3.7.2 Test Procedure .....                          | 20        |
| <b>3.8 ANTENNA REQUIREMENT.....</b>                 | <b>20</b> |
| 3.8.1 Applicable Standard.....                      | 20        |
| 3.8.2 Judgment.....                                 | 20        |
| <b>4. Test DATA AND RESULTS .....</b>               | <b>21</b> |
| 4.1 AC LINE CONDUCTED EMISSIONS.....                | 21        |
| 4.2 RADIATION SPURIOUS EMISSIONS .....              | 24        |
| 4.3 6 dB EMISSION BANDWIDTH:.....                   | 37        |
| 4.4 MAXIMUM PEAK CONDUCTED OUTPUT POWER:.....       | 42        |
| 4.5 MAXIMUM POWER SPECTRAL DENSITY: .....           | 43        |
| 4.6 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE: ..... | 52        |
| 4.7 DUTY CYCLE:.....                                | 61        |
| <b>5. RF EXPOSURE EVALUATION .....</b>              | <b>64</b> |
| 5.1 APPLICABLE STANDARD.....                        | 64        |
| 5.2 PROCEDURE.....                                  | 64        |
| 5.3 MEASUREMENT RESULT .....                        | 64        |

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment under Test (EUT)

|                                               |                                                                           |
|-----------------------------------------------|---------------------------------------------------------------------------|
| <b>EUT Name:</b>                              | 2.4G Long Range Outdoor Access Point                                      |
| <b>EUT Model:</b>                             | O3                                                                        |
| <b>Operation Frequency:</b>                   | 2412-2462 MHz(802.11b/g/n ht20)<br>2422-2452 MHz(802.11n ht40)            |
| <b>Maximum Peak Output Power (Conducted):</b> | 22.30 dBm                                                                 |
| <b>Modulation Type:</b>                       | 802.11b:DSSS-DBPSK, DQPSK, CCK<br>802.11g/n:OFDM-BPSK, QPSK, 16QAM, 64QAM |
| <b>Rated Input Voltage:</b>                   | DC 12V from POE                                                           |
| <b>Serial Number:</b>                         | CR22060010-RF-S1                                                          |
| <b>EUT Received Date:</b>                     | 2022.06.12                                                                |
| <b>EUT Received Status:</b>                   | Good                                                                      |

#### Operation Frequency Detail: For 802.11b/g/n ht20:

| Channel                                                                       | Frequency (MHz) | Channel         | Frequency (MHz) |
|-------------------------------------------------------------------------------|-----------------|-----------------|-----------------|
| 1                                                                             | 2412            | 7               | 2442            |
| 2                                                                             | 2417            | 8               | 2447            |
| 3                                                                             | 2422            | 9               | 2452            |
| 4                                                                             | 2427            | 10              | 2457            |
| 5                                                                             | 2432            | 11              | 2462            |
| 6                                                                             | 2437            | /               | /               |
| Per section 15.31(m), the below frequencies were performed the test as below: |                 |                 |                 |
| Test Channel                                                                  |                 | Frequency (MHz) |                 |
| Lowest                                                                        |                 | 2412            |                 |
| Middle                                                                        |                 | 2437            |                 |
| Highest                                                                       |                 | 2462            |                 |

#### For 802.11n ht40:

| Channel                                                                       | Frequency (MHz) | Channel         | Frequency (MHz) |
|-------------------------------------------------------------------------------|-----------------|-----------------|-----------------|
| 3                                                                             | 2422            | 7               | 2442            |
| 4                                                                             | 2427            | 8               | 2447            |
| 5                                                                             | 2432            | 9               | 2452            |
| 6                                                                             | 2437            | /               | /               |
| Per section 15.31(m), the below frequencies were performed the test as below: |                 |                 |                 |
| Test Channel                                                                  |                 | Frequency (MHz) |                 |
| Lowest                                                                        |                 | 2422            |                 |
| Middle                                                                        |                 | 2437            |                 |
| Highest                                                                       |                 | 2452            |                 |

**Antenna Information Detail ▲:**

| Antenna Chain | Manufacturer        | Antenna Type | input impedance (Ohm) | Antenna Gain /Frequency Range | §15.203 Requirement |
|---------------|---------------------|--------------|-----------------------|-------------------------------|---------------------|
| 0             | SHENZHEN TENDA      | metal        | 50                    | 11.43dBi/<br>2.4~2.5GHz       | Compliance          |
| 1             | TECHNOLOGY CO.,LTD. | metal        | 50                    | 10.89dBi/<br>2.4~2.5GHz       | Compliance          |

The Method of §15.203 Compliance:

- ☒ Antenna must be permanently attached to the unit.  
☐ Antenna must use a unique type of connector to attach to the EUT.  
☐ Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

**Accessory Information:**

| Accessory Description | Manufacturer                                           | Model         | Parameters                                        |
|-----------------------|--------------------------------------------------------|---------------|---------------------------------------------------|
| Adapter               | SHEN ZHEN<br>HEWISHUN NETWORK<br>TECHNOLOGY<br>CO.,LTD | BN073-A12012U | Input: 100-240V~50/60Hz<br>0.4A<br>Output: 12V~1A |
| PoE                   | SHENZHEN TENDA<br>TECHNOLOGY<br>CO.,LTD.               | Unknown       | Input: DC 12V<br>Output: DC 12V                   |

## 1.2 Description of Test Configuration

### 1.2.1 EUT Operation Condition:

| <b>EUT Operation Mode:</b>                                                                                                                                                                                                           |         | The system was configured for testing in Engineering Mode, which was provided by the manufacturer. |           |                     |         |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|----------------------------------------------------------------------------------------------------|-----------|---------------------|---------|
| <b>Equipment Modifications:</b>                                                                                                                                                                                                      |         | No                                                                                                 |           |                     |         |
| <b>EUT Exercise Software:</b>                                                                                                                                                                                                        |         | MP_Tool                                                                                            |           |                     |         |
| The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:                                                                                                        |         |                                                                                                    |           |                     |         |
| Mode                                                                                                                                                                                                                                 | Channel | Frequency (MHz)                                                                                    | Data Rate | Power Level Setting |         |
|                                                                                                                                                                                                                                      |         |                                                                                                    |           | Chain 0             | Chain 1 |
| 802.11b                                                                                                                                                                                                                              | Lowest  | 2412                                                                                               | 1Mbps     | 28                  | 28      |
|                                                                                                                                                                                                                                      | Middle  | 2437                                                                                               | 1Mbps     | 28                  | 28      |
|                                                                                                                                                                                                                                      | Highest | 2462                                                                                               | 1Mbps     | 28                  | 28      |
| 802.11g                                                                                                                                                                                                                              | Lowest  | 2412                                                                                               | 6Mbps     | 25                  | 25      |
|                                                                                                                                                                                                                                      | Middle  | 2437                                                                                               | 6Mbps     | 25                  | 25      |
|                                                                                                                                                                                                                                      | Highest | 2462                                                                                               | 6Mbps     | 25                  | 25      |
| 802.11n ht20                                                                                                                                                                                                                         | Lowest  | 2412                                                                                               | 6.5Mbps   | 25                  | 25      |
|                                                                                                                                                                                                                                      | Middle  | 2437                                                                                               | 6.5Mbps   | 25                  | 25      |
|                                                                                                                                                                                                                                      | Highest | 2462                                                                                               | 6.5Mbps   | 25                  | 25      |
| 802.11n ht40                                                                                                                                                                                                                         | Lowest  | 2422                                                                                               | 13Mbps    | 25                  | 25      |
|                                                                                                                                                                                                                                      | Middle  | 2437                                                                                               | 13Mbps    | 25                  | 25      |
|                                                                                                                                                                                                                                      | Highest | 2452                                                                                               | 13Mbps    | 25                  | 25      |
| The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations. The device only supports SISO mode. |         |                                                                                                    |           |                     |         |

### 1.2.2 Support Equipment List and Details


| Manufacturer | Description | Model     | Serial Number    |
|--------------|-------------|-----------|------------------|
| Lenovo       | Laptop      | E480      | PF-1QQYYYP 19/06 |
| Unknown      | Load        | RJ45 Load | RJ45 Load-1      |

### 1.2.3 Support Cable List and Details


| Cable Description | Shielding Type | Ferrite Core | Length (m) | From Port | To     |
|-------------------|----------------|--------------|------------|-----------|--------|
| RJ45 Cable        | yes            | No           | 10         | EUT       | Laptop |
| RJ45 Cable        | yes            | No           | 10         | PoE       | Load   |
| RJ45 Cable        | No             | No           | 1.2        | PoE       | EUT    |

### 1.2.4 Block Diagram of Test Setup

AC line conducted emissions:



Spurious Emissions:



### 1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

| Parameter                         | Measurement Uncertainty                                                                                                 |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Occupied Channel Bandwidth        | ±5 %                                                                                                                    |
| RF output power, conducted        | ±0.61dB                                                                                                                 |
| Power Spectral Density, conducted | ±0.61 dB                                                                                                                |
| Unwanted Emissions, radiated      | 30M~200MHz: 4.15 dB, 200M~1GHz: 5.61 dB, 1G~6GHz: 5.14 dB,<br>6G~18GHz: 5.93 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB |
| Unwanted Emissions, conducted     | ±1.26 dB                                                                                                                |
| Temperature                       | ±1℃                                                                                                                     |
| Humidity                          | ±5%                                                                                                                     |
| DC and low frequency voltages     | ±0.4%                                                                                                                   |
| Duty Cycle                        | 1%                                                                                                                      |
| AC Power Lines Conducted Emission | 2.8 dB (150 kHz to 30 MHz)                                                                                              |

## 2. SUMMARY OF TEST RESULTS

| Standard(s) Section             | Test Items                               | Result    |
|---------------------------------|------------------------------------------|-----------|
| §15.207(a)                      | AC line conducted emissions              | Compliant |
| §15.205, §15.209,<br>§15.247(d) | Spurious Emissions                       | Compliant |
| §15.247 (a)(2)                  | 6 dB Bandwidth                           | Compliant |
| §15.247(b)(3)                   | Maximum Conducted Output Power           | Compliant |
| §15.247(d)                      | 100 kHz Bandwidth of Frequency Band Edge | Compliant |
| §15.247(e)                      | Power Spectral Density                   | Compliant |
| §15.203                         | Antenna Requirement                      | Compliant |
| §15.247 (i) & §1.1307           | RF Exposure Evaluation                   | Compliant |

### 3. REQUIREMENTS AND TEST PROCEDURES

#### 3.1 AC Line Conducted Emissions

##### 3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

| Frequency of emission (MHz) | Conducted limit (dB $\mu$ V) |           |
|-----------------------------|------------------------------|-----------|
|                             | Quasi-peak                   | Average   |
| 0.15-0.5                    | 66 to 56*                    | 56 to 46* |
| 0.5-5                       | 56                           | 46        |
| 5-30                        | 60                           | 50        |

\*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000  $\mu$ V within the frequency band 535-1705 kHz, as measured using a 50  $\mu$ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

### 3.1.2 EUT Setup



Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

### 3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range  | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz  |

### 3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

### 3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

## 3.2 Radiation Spurious Emissions

### 3.2.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 3.2.2 EUT Setup

**Below 1GHz:**



**Above 1GHz:**



The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

### 3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

| Measurement | RBW     | Video B/W | IF B/W |
|-------------|---------|-----------|--------|
| QP          | 120 kHz | 300 kHz   | 120kHz |

1GHz- 25GHz:

| Measurement | Duty cycle | RBW  | Video B/W |
|-------------|------------|------|-----------|
| PK          | Any        | 1MHz | 3 MHz     |
| AV          | >98%       | 1MHz | 10 Hz     |
|             | <98%       | 1MHz | 1/T       |

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

### 3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

### 3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result


### 3.3 6 dB Emission Bandwidth:

#### 3.3.1 Applicable Standard

FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

#### 3.3.2 EUT Setup



#### 3.3.3 Test Procedure

According to ANSI C63.10-2013 Section 11.8

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times \text{RBW}$ .
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


### 3.4 Maximum peak conducted output power:

#### 3.4.1 Applicable Standard

FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

#### 3.4.2 EUT Setup



#### 3.4.3 Test Procedure

According to ANSI C63.10-2013 Section 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

- a) Set the EUT in transmitting mode.
- b) Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
- c) Add a correction factor to the display.
- d) Set the power meter to test peak output power, record the result.


### 3.5 Maximum power spectral density:

#### 3.5.1 Applicable Standard

FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

#### 3.5.2 EUT Setup



#### 3.5.3 Test Procedure

According to ANSI C63.10-2013 Section 11.10.2

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set the VBW  $\geq [3 \cdot \text{RBW}]$ .
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.


### 3.6 100 kHz Bandwidth of Frequency Band Edge:

#### 3.6.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### 3.6.2 EUT Setup



#### 3.6.3 Test Procedure


According to ANSI C63.10-2013 Section 11.11

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq [3 \times \text{RBW}]$ .
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

### 3.7 Duty Cycle:

#### 3.7.1 EUT Setup



#### 3.7.2 Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set  $RBW \geq OBW$  if possible; otherwise, set RBW to the largest available value.
- 3) Set  $VBW \geq RBW$ . Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are  $> 50/T$  and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if  $T \leq 16.7 \mu s$ .)

### 3.8 Antenna Requirement

#### 3.8.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

#### 3.8.2 Judgment

Please refer to the Antenna Information detail in Section 1.

## 4. Test DATA AND RESULTS

### 4.1 AC Line Conducted Emissions

|                |                  |              |                                                                |
|----------------|------------------|--------------|----------------------------------------------------------------|
| Serial Number: | CR22060010-RF-S1 | Test Date:   | 2022-06-20                                                     |
| Test Site:     | CE               | Test Mode:   | Transmitting<br>(802.11b Chain 0 Middle channel was the worst) |
| Tester:        | Vic Du           | Test Result: | Pass                                                           |

#### Environmental Conditions:


|                      |      |                              |    |                        |       |
|----------------------|------|------------------------------|----|------------------------|-------|
| Temperature:<br>(°C) | 28.2 | Relative<br>Humidity:<br>(%) | 71 | ATM Pressure:<br>(kPa) | 100.1 |
|----------------------|------|------------------------------|----|------------------------|-------|

#### Test Equipment List and Details:

| Manufacturer | Description       | Model   | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|---------|---------------|------------------|----------------------|
| R&S          | LISN              | ENV216  | 101134        | 2022-04-01       | 2023-03-31           |
| R&S          | EMI Test Receiver | ESR3    | 102726        | 2021-07-22       | 2022-07-21           |
| MICRO-COAX   | Coaxial Cable     | UTIFLEX | C-0200-01     | 2021-08-08       | 2022-08-07           |
| Audix        | Test Software     | E3      | 190306 (V9)   | N/A              | N/A                  |


*\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Line:



| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB) | Result<br>(dBμV) | Limit<br>(dBμV) | Margin<br>(dB) | Detector |
|-----|--------------------|-------------------|----------------|------------------|-----------------|----------------|----------|
| 1   | 0.150              | 25.37             | 9.61           | 34.98            | 66.00           | 31.02          | QP       |
| 2   | 0.150              | 8.75              | 9.61           | 18.36            | 56.00           | 37.64          | Average  |
| 3   | 0.433              | 27.51             | 9.61           | 37.12            | 57.19           | 20.07          | QP       |
| 4   | 0.433              | 15.61             | 9.61           | 25.22            | 47.19           | 21.97          | Average  |
| 5   | 0.500              | 26.31             | 9.61           | 35.92            | 56.01           | 20.09          | QP       |
| 6   | 0.500              | 12.92             | 9.61           | 22.53            | 46.01           | 23.47          | Average  |
| 7   | 1.156              | 37.09             | 9.62           | 46.71            | 56.00           | 9.29           | QP       |
| 8   | 1.156              | 27.73             | 9.62           | 37.35            | 46.00           | 8.65           | Average  |
| 9   | 1.550              | 26.02             | 9.63           | 35.65            | 56.00           | 20.35          | QP       |
| 10  | 1.550              | 15.03             | 9.63           | 24.66            | 46.00           | 21.34          | Average  |
| 11  | 11.313             | 26.03             | 9.67           | 35.70            | 60.00           | 24.30          | QP       |
| 12  | 11.313             | 16.09             | 9.67           | 25.76            | 50.00           | 24.24          | Average  |

Neutral:



| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB) | Result<br>(dBμV) | Limit<br>(dBμV) | Margin<br>(dB) | Detector |
|-----|--------------------|-------------------|----------------|------------------|-----------------|----------------|----------|
| 1   | 0.155              | 25.29             | 9.61           | 34.90            | 65.74           | 30.84          | QP       |
| 2   | 0.155              | 15.63             | 9.61           | 25.24            | 55.74           | 30.50          | Average  |
| 3   | 0.484              | 36.82             | 9.61           | 46.43            | 56.26           | 9.83           | QP       |
| 4   | 0.484              | 27.76             | 9.61           | 37.37            | 46.26           | 8.89           | Average  |
| 5   | 1.167              | 39.81             | 9.62           | 49.43            | 56.00           | 6.57           | QP       |
| 6   | 1.167              | 31.11             | 9.62           | 40.73            | 46.00           | 5.27           | Average  |
| 7   | 2.874              | 28.45             | 9.65           | 38.10            | 56.00           | 17.90          | QP       |
| 8   | 2.874              | 18.45             | 9.65           | 28.10            | 46.00           | 17.90          | Average  |
| 9   | 4.147              | 29.48             | 9.65           | 39.13            | 56.00           | 16.87          | QP       |
| 10  | 4.147              | 18.71             | 9.65           | 28.36            | 46.00           | 17.64          | Average  |
| 11  | 12.265             | 34.42             | 9.67           | 44.09            | 60.00           | 15.91          | QP       |
| 12  | 12.265             | 22.27             | 9.67           | 31.94            | 50.00           | 18.06          | Average  |

## 4.2 Radiation Spurious Emissions

|                |                  |              |              |
|----------------|------------------|--------------|--------------|
| Serial Number: | CR22060010-RF-S1 | Test Date:   | 2022-06-22   |
| Test Site:     | 966-1,966-2      | Test Mode:   | Transmitting |
| Tester:        | Mack Huang       | Test Result: | Pass         |

### Environmental Conditions:

|                      |      |                              |    |                        |       |
|----------------------|------|------------------------------|----|------------------------|-------|
| Temperature:<br>(°C) | 23.9 | Relative<br>Humidity:<br>(%) | 63 | ATM Pressure:<br>(kPa) | 100.3 |
|----------------------|------|------------------------------|----|------------------------|-------|


### Test Equipment List and Details:

| Manufacturer    | Description           | Model                 | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-----------------------|-----------------------|---------------|------------------|----------------------|
| Sunol Sciences  | Antenna               | JB6                   | A082520-5     | 2020-10-19       | 2023-10-18           |
| R&S             | EMI Test Receiver     | ESR3                  | 102724        | 2021-07-22       | 2022-07-21           |
| TIMES MICROWAVE | Coaxial Cable         | LMR-600-UltraFlex     | C-0470-02     | 2021-07-18       | 2022-07-17           |
| TIMES MICROWAVE | Coaxial Cable         | LMR-600-UltraFlex     | C-0780-01     | 2021-07-18       | 2022-07-17           |
| Sonoma          | Amplifier             | 310N                  | 186165        | 2021-07-18       | 2022-07-17           |
| Audix           | Test Software         | E3                    | 201021 (V9)   | N/A              | N/A                  |
| ETS-Lindgren    | Horn Antenna          | 3115                  | 9912-5985     | 2020-10-13       | 2023-10-12           |
| R&S             | Spectrum Analyzer     | FSV40                 | 101591        | 2021-07-22       | 2022-07-21           |
| MICRO-COAX      | Coaxial Cable         | UFA210A-1-1200-70U300 | 217423-008    | 2021-08-08       | 2022-08-07           |
| MICRO-COAX      | Coaxial Cable         | UFA210A-1-2362-300300 | 235780-001    | 2021-08-08       | 2022-08-07           |
| Mini            | Pre-amplifier         | ZVA-183-S+            | 5969001149    | 2021-11-10       | 2022-11-09           |
| PASTERNAK       | Horn Antenna          | PE9852/2F-20          | 112002        | 2021-02-05       | 2024-02-04           |
| AH              | Preamplifier          | PAM-1840VH            | 190           | 2021-11-19       | 2022-11-18           |
| MICRO-COAX      | Coaxial Cable         | UFB142A-1-2362-200200 | 235772-001    | 2021-08-08       | 2022-08-07           |
| E-Microwave     | Band Rejection Filter | 2400-2483.5MHz        | OE01902424    | 2021-08-08       | 2022-08-07           |
| Mini Circuits   | High Pass Filter      | VHF-6010+             | 31119         | 2021-08-08       | 2022-08-07           |


\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data:

Please refer to the below table and plots.

**1) 30MHz-1GHz(802.11b Chain 0 Low channel was the worst)****Horizontal:**

| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|----------|
| 1   | 30.000          | 28.51          | -3.79         | 24.72           | 40.00          | 15.28       | Peak     |
| 2   | 67.202          | 38.42          | -16.97        | 21.45           | 40.00          | 18.55       | Peak     |
| 3   | 97.456          | 38.71          | -15.21        | 23.50           | 43.50          | 20.00       | Peak     |
| 4   | 107.134         | 40.54          | -13.13        | 27.41           | 43.50          | 16.09       | Peak     |
| 5   | 156.227         | 53.18          | -12.32        | 40.87           | 43.50          | 2.63        | QP       |
| 6   | 312.179         | 49.65          | -10.81        | 38.84           | 46.00          | 7.16        | Peak     |

**Vertical:**

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|----------|
| 1   | 30.317          | 38.11          | -4.03         | 34.08           | 40.00          | 5.92        | Peak     |
| 2   | 38.212          | 36.35          | -10.08        | 26.27           | 40.00          | 13.73       | Peak     |
| 3   | 45.535          | 41.35          | -14.78        | 26.58           | 40.00          | 13.42       | Peak     |
| 4   | 96.099          | 42.31          | -15.57        | 26.75           | 43.50          | 16.75       | Peak     |
| 5   | 156.458         | 43.40          | -12.31        | 31.08           | 43.50          | 12.42       | Peak     |
| 6   | 312.179         | 46.24          | -10.81        | 35.43           | 46.00          | 10.57       | Peak     |

**2) 1-25GHz:****Chain 0****802.11b Mode:**

| Frequency<br>(MHz)       | Receiver          |          | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBµV/m) | Limit<br>(dBµV/m) | Margin<br>(dB) |
|--------------------------|-------------------|----------|----------------|------------------|--------------------|-------------------|----------------|
|                          | Reading<br>(dBµV) | Detector |                |                  |                    |                   |                |
| Low Channel: 2412 MHz    |                   |          |                |                  |                    |                   |                |
| 2412.00                  | 75.08             | PK       | H              | 31.53            | 106.61             | N/A               | N/A            |
| 2412.00                  | 67.28             | AV       | H              | 31.53            | 98.81              | N/A               | N/A            |
| 2412.00                  | 71.57             | PK       | V              | 31.53            | 103.10             | N/A               | N/A            |
| 2412.00                  | 63.09             | AV       | V              | 31.53            | 94.62              | N/A               | N/A            |
| 2390.00                  | 37.78             | PK       | H              | 31.46            | 69.24              | 74.00             | 4.76           |
| 2390.00                  | 14.89             | AV       | H              | 31.46            | 46.35              | 54.00             | 7.65           |
| 4824.00                  | 43.31             | PK       | H              | 10.94            | 54.25              | 74.00             | 19.75          |
| 4824.00                  | 39.46             | AV       | H              | 10.94            | 50.40              | 54.00             | 3.60           |
| 7236.00                  | 34.67             | PK       | H              | 14.44            | 49.11              | 74.00             | 24.89          |
| 7236.00                  | 28.33             | AV       | H              | 14.44            | 42.77              | 54.00             | 11.23          |
| Middle Channel: 2437 MHz |                   |          |                |                  |                    |                   |                |
| 2437.00                  | 73.81             | PK       | H              | 31.60            | 105.41             | N/A               | N/A            |
| 2437.00                  | 65.69             | AV       | H              | 31.60            | 97.29              | N/A               | N/A            |
| 2437.00                  | 70.65             | PK       | V              | 31.60            | 102.25             | N/A               | N/A            |
| 2437.00                  | 62.81             | AV       | V              | 31.60            | 94.41              | N/A               | N/A            |
| 4874.00                  | 43.37             | PK       | H              | 11.05            | 54.42              | 74.00             | 19.58          |
| 4874.00                  | 39.60             | AV       | H              | 11.05            | 50.65              | 54.00             | 3.35           |
| 7311.00                  | 33.25             | PK       | H              | 14.80            | 48.05              | 74.00             | 25.95          |
| 7311.00                  | 27.66             | AV       | H              | 14.80            | 42.46              | 54.00             | 11.54          |
| High Channel: 2462MHz    |                   |          |                |                  |                    |                   |                |
| 2462.00                  | 72.24             | PK       | H              | 31.63            | 103.87             | N/A               | N/A            |
| 2462.00                  | 63.79             | AV       | H              | 31.63            | 95.42              | N/A               | N/A            |
| 2462.00                  | 68.44             | PK       | V              | 31.63            | 100.07             | N/A               | N/A            |
| 2462.00                  | 60.05             | AV       | V              | 31.63            | 91.68              | N/A               | N/A            |
| 2483.50                  | 37.57             | PK       | H              | 31.64            | 69.21              | 74.00             | 4.79           |
| 2483.50                  | 15.36             | AV       | H              | 31.64            | 47.00              | 54.00             | 7.00           |
| 4924.00                  | 43.07             | PK       | H              | 11.18            | 54.25              | 74.00             | 19.75          |
| 4924.00                  | 39.26             | AV       | H              | 11.18            | 50.44              | 54.00             | 3.56           |
| 7386.00                  | 33.14             | PK       | H              | 14.89            | 48.03              | 74.00             | 25.97          |
| 7386.00                  | 26.58             | AV       | H              | 14.89            | 41.47              | 54.00             | 12.53          |

**802.11g Mode:**

02.F1g Mode.

| Frequency<br>(MHz)       | Receiver          |          | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------------|-------------------|----------|----------------|------------------|--------------------|-------------------|----------------|
|                          | Reading<br>(dBμV) | Detector |                |                  |                    |                   |                |
| Low Channel: 2412 MHz    |                   |          |                |                  |                    |                   |                |
| 2412.00                  | 72.31             | PK       | H              | 31.53            | 103.84             | N/A               | N/A            |
| 2412.00                  | 62.44             | AV       | H              | 31.53            | 93.97              | N/A               | N/A            |
| 2412.00                  | 66.10             | PK       | V              | 31.53            | 97.63              | N/A               | N/A            |
| 2412.00                  | 56.19             | AV       | V              | 31.53            | 87.72              | N/A               | N/A            |
| 2390.00                  | 30.51             | PK       | H              | 31.46            | 61.97              | 74.00             | 12.03          |
| 2390.00                  | 14.99             | AV       | H              | 31.46            | 46.45              | 54.00             | 7.55           |
| 4824.00                  | 41.11             | PK       | H              | 10.94            | 52.05              | 74.00             | 21.95          |
| 4824.00                  | 37.69             | AV       | H              | 10.94            | 48.63              | 54.00             | 5.37           |
| 7236.00                  | 33.61             | PK       | H              | 14.44            | 48.05              | 74.00             | 25.95          |
| 7236.00                  | 27.30             | AV       | H              | 14.44            | 41.74              | 54.00             | 12.26          |
| Middle Channel: 2437 MHz |                   |          |                |                  |                    |                   |                |
| 2437.00                  | 69.97             | PK       | H              | 31.60            | 101.57             | N/A               | N/A            |
| 2437.00                  | 60.16             | AV       | H              | 31.60            | 91.76              | N/A               | N/A            |
| 2437.00                  | 65.48             | PK       | V              | 31.60            | 97.08              | N/A               | N/A            |
| 2437.00                  | 55.56             | AV       | V              | 31.60            | 87.16              | N/A               | N/A            |
| 4874.00                  | 43.72             | PK       | H              | 11.05            | 54.77              | 74.00             | 19.23          |
| 4874.00                  | 39.25             | AV       | H              | 11.05            | 50.30              | 54.00             | 3.70           |
| 7311.00                  | 34.85             | PK       | H              | 14.80            | 49.65              | 74.00             | 24.35          |
| 7311.00                  | 29.36             | AV       | H              | 14.80            | 44.16              | 54.00             | 9.84           |
| High Channel: 2462MHz    |                   |          |                |                  |                    |                   |                |
| 2462.00                  | 69.94             | PK       | H              | 31.63            | 101.57             | N/A               | N/A            |
| 2462.00                  | 60.04             | AV       | H              | 31.63            | 91.67              | N/A               | N/A            |
| 2462.00                  | 66.40             | PK       | V              | 31.63            | 98.03              | N/A               | N/A            |
| 2462.00                  | 56.51             | AV       | V              | 31.63            | 88.14              | N/A               | N/A            |
| 2483.50                  | 30.36             | PK       | H              | 31.64            | 62.00              | 74.00             | 12.00          |
| 2483.50                  | 15.74             | AV       | H              | 31.64            | 47.38              | 54.00             | 6.62           |
| 4924.00                  | 43.06             | PK       | H              | 11.18            | 54.24              | 74.00             | 19.76          |
| 4924.00                  | 39.46             | AV       | H              | 11.18            | 50.64              | 54.00             | 3.36           |
| 7386.00                  | 34.25             | PK       | H              | 14.89            | 49.14              | 74.00             | 24.86          |
| 7386.00                  | 28.54             | AV       | H              | 14.89            | 43.43              | 54.00             | 10.57          |

**802.11n ht20 Mode:**

| Frequency<br>(MHz)       | Receiver          |          | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------------|-------------------|----------|----------------|------------------|--------------------|-------------------|----------------|
|                          | Reading<br>(dBμV) | Detector |                |                  |                    |                   |                |
| Low Channel: 2412 MHz    |                   |          |                |                  |                    |                   |                |
| 2412.00                  | 73.67             | PK       | H              | 31.53            | 105.20             | N/A               | N/A            |
| 2412.00                  | 63.23             | AV       | H              | 31.53            | 94.76              | N/A               | N/A            |
| 2412.00                  | 68.54             | PK       | V              | 31.53            | 100.07             | N/A               | N/A            |
| 2412.00                  | 58.07             | AV       | V              | 31.53            | 89.60              | N/A               | N/A            |
| 2390.00                  | 32.85             | PK       | H              | 31.46            | 64.31              | 74.00             | 9.69           |
| 2390.00                  | 13.10             | AV       | H              | 31.46            | 44.56              | 54.00             | 9.44           |
| 4824.00                  | 42.63             | PK       | H              | 10.94            | 53.57              | 74.00             | 20.43          |
| 4824.00                  | 38.76             | AV       | H              | 10.94            | 49.70              | 54.00             | 4.30           |
| 7236.00                  | 34.34             | PK       | H              | 14.44            | 48.78              | 74.00             | 25.22          |
| 7236.00                  | 29.42             | AV       | H              | 14.44            | 43.86              | 54.00             | 10.14          |
| Middle Channel: 2437 MHz |                   |          |                |                  |                    |                   |                |
| 2437.00                  | 73.90             | PK       | H              | 31.60            | 105.50             | N/A               | N/A            |
| 2437.00                  | 63.41             | AV       | H              | 31.60            | 95.01              | N/A               | N/A            |
| 2437.00                  | 68.80             | PK       | V              | 31.60            | 100.40             | N/A               | N/A            |
| 2437.00                  | 58.15             | AV       | V              | 31.60            | 89.75              | N/A               | N/A            |
| 4874.00                  | 43.64             | PK       | H              | 11.05            | 54.69              | 74.00             | 19.31          |
| 4874.00                  | 39.27             | AV       | H              | 11.05            | 50.32              | 54.00             | 3.68           |
| 7311.00                  | 34.68             | PK       | H              | 14.80            | 49.48              | 74.00             | 24.52          |
| 7311.00                  | 28.45             | AV       | H              | 14.80            | 43.25              | 54.00             | 10.75          |
| High Channel: 2462MHz    |                   |          |                |                  |                    |                   |                |
| 2462.00                  | 72.99             | PK       | H              | 31.63            | 104.62             | N/A               | N/A            |
| 2462.00                  | 62.66             | AV       | H              | 31.63            | 94.29              | N/A               | N/A            |
| 2462.00                  | 69.58             | PK       | V              | 31.63            | 101.21             | N/A               | N/A            |
| 2462.00                  | 59.37             | AV       | V              | 31.63            | 91.00              | N/A               | N/A            |
| 2483.50                  | 35.18             | PK       | H              | 31.64            | 66.82              | 74.00             | 7.18           |
| 2483.50                  | 13.36             | AV       | H              | 31.64            | 45.00              | 54.00             | 9.00           |
| 4924.00                  | 42.76             | PK       | H              | 11.18            | 53.94              | 74.00             | 20.06          |
| 4924.00                  | 38.36             | AV       | H              | 11.18            | 49.54              | 54.00             | 4.46           |
| 7386.00                  | 34.83             | PK       | H              | 14.89            | 49.72              | 74.00             | 24.28          |
| 7386.00                  | 28.40             | AV       | H              | 14.89            | 43.29              | 54.00             | 10.71          |

**802.11n ht40 Mode:**

402.1MHz Mode:

| Frequency<br>(MHz)       | Receiver          |          | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------------|-------------------|----------|----------------|------------------|--------------------|-------------------|----------------|
|                          | Reading<br>(dBμV) | Detector |                |                  |                    |                   |                |
| Low Channel: 2422 MHz    |                   |          |                |                  |                    |                   |                |
| 2422.00                  | 68.08             | PK       | H              | 31.56            | 99.64              | N/A               | N/A            |
| 2422.00                  | 56.86             | AV       | H              | 31.56            | 88.42              | N/A               | N/A            |
| 2422.00                  | 62.55             | PK       | V              | 31.56            | 94.11              | N/A               | N/A            |
| 2422.00                  | 51.59             | AV       | V              | 31.56            | 83.15              | N/A               | N/A            |
| 2390.00                  | 38.29             | PK       | H              | 31.46            | 69.75              | 74.00             | 4.25           |
| 2390.00                  | 17.74             | AV       | H              | 31.46            | 49.20              | 54.00             | 4.80           |
| 4844.00                  | 40.55             | PK       | H              | 10.96            | 51.51              | 74.00             | 22.49          |
| 4844.00                  | 36.25             | AV       | H              | 10.96            | 47.21              | 54.00             | 6.79           |
| 7266.00                  | 34.28             | PK       | H              | 14.63            | 48.91              | 74.00             | 25.09          |
| 7266.00                  | 28.36             | AV       | H              | 14.63            | 42.99              | 54.00             | 11.01          |
| Middle Channel: 2437 MHz |                   |          |                |                  |                    |                   |                |
| 2437.00                  | 71.72             | PK       | H              | 31.60            | 103.32             | N/A               | N/A            |
| 2437.00                  | 60.52             | AV       | H              | 31.60            | 92.12              | N/A               | N/A            |
| 2437.00                  | 68.17             | PK       | V              | 31.60            | 99.77              | N/A               | N/A            |
| 2437.00                  | 56.42             | AV       | V              | 31.60            | 88.02              | N/A               | N/A            |
| 4874.00                  | 42.83             | PK       | H              | 11.05            | 53.88              | 74.00             | 20.12          |
| 4874.00                  | 38.36             | AV       | H              | 11.05            | 49.41              | 54.00             | 4.59           |
| 7311.00                  | 35.26             | PK       | H              | 14.80            | 50.06              | 74.00             | 23.94          |
| 7311.00                  | 30.47             | AV       | H              | 14.80            | 45.27              | 54.00             | 8.73           |
| High Channel: 2452MHz    |                   |          |                |                  |                    |                   |                |
| 2452.00                  | 69.87             | PK       | H              | 31.63            | 101.50             | N/A               | N/A            |
| 2452.00                  | 58.19             | AV       | H              | 31.63            | 89.82              | N/A               | N/A            |
| 2452.00                  | 66.64             | PK       | V              | 31.63            | 98.27              | N/A               | N/A            |
| 2452.00                  | 54.21             | AV       | V              | 31.63            | 85.84              | N/A               | N/A            |
| 2483.50                  | 39.20             | PK       | H              | 31.64            | 70.84              | 74.00             | 3.16           |
| 2483.50                  | 18.15             | AV       | H              | 31.64            | 49.79              | 54.00             | 4.21           |
| 4904.00                  | 42.47             | PK       | H              | 11.14            | 53.61              | 74.00             | 20.39          |
| 4904.00                  | 38.12             | AV       | H              | 11.14            | 49.26              | 54.00             | 4.74           |
| 7356.00                  | 33.54             | PK       | H              | 14.80            | 48.34              | 74.00             | 25.66          |
| 7356.00                  | 29.36             | AV       | H              | 14.80            | 44.16              | 54.00             | 9.84           |

**Chain 1****802.11b Mode:**

| Frequency<br>(MHz)       | Receiver          |          | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------------|-------------------|----------|----------------|------------------|--------------------|-------------------|----------------|
|                          | Reading<br>(dBμV) | Detector |                |                  |                    |                   |                |
| Low Channel: 2412 MHz    |                   |          |                |                  |                    |                   |                |
| 2412.00                  | 74.15             | PK       | V              | 31.53            | 105.68             | N/A               | N/A            |
| 2412.00                  | 65.54             | AV       | V              | 31.53            | 97.07              | N/A               | N/A            |
| 2412.00                  | 69.85             | PK       | H              | 31.53            | 101.38             | N/A               | N/A            |
| 2412.00                  | 60.63             | AV       | H              | 31.53            | 92.16              | N/A               | N/A            |
| 2390.00                  | 40.47             | PK       | V              | 31.46            | 71.93              | 74.00             | 2.07           |
| 2390.00                  | 16.54             | AV       | V              | 31.46            | 48.00              | 54.00             | 6.00           |
| 4824.00                  | 43.21             | PK       | V              | 10.94            | 54.15              | 74.00             | 19.85          |
| 4824.00                  | 38.80             | AV       | V              | 10.94            | 49.74              | 54.00             | 4.26           |
| 7236.00                  | 34.88             | PK       | V              | 14.44            | 49.32              | 74.00             | 24.68          |
| 7236.00                  | 29.40             | AV       | V              | 14.44            | 43.84              | 54.00             | 10.16          |
| Middle Channel: 2437 MHz |                   |          |                |                  |                    |                   |                |
| 2437.00                  | 72.47             | PK       | V              | 31.60            | 104.07             | N/A               | N/A            |
| 2437.00                  | 63.97             | AV       | V              | 31.60            | 95.57              | N/A               | N/A            |
| 2437.00                  | 66.13             | PK       | H              | 31.60            | 97.73              | N/A               | N/A            |
| 2437.00                  | 57.79             | AV       | H              | 31.60            | 89.39              | N/A               | N/A            |
| 4874.00                  | 43.05             | PK       | V              | 11.05            | 54.10              | 74.00             | 19.90          |
| 4874.00                  | 39.25             | AV       | V              | 11.05            | 50.30              | 54.00             | 3.70           |
| 7311.00                  | 34.58             | PK       | V              | 14.80            | 49.38              | 74.00             | 24.62          |
| 7311.00                  | 28.36             | AV       | V              | 14.80            | 43.16              | 54.00             | 10.84          |
| High Channel: 2462MHz    |                   |          |                |                  |                    |                   |                |
| 2462.00                  | 73.45             | PK       | V              | 31.63            | 105.08             | N/A               | N/A            |
| 2462.00                  | 64.43             | AV       | V              | 31.63            | 96.06              | N/A               | N/A            |
| 2462.00                  | 68.35             | PK       | H              | 31.63            | 99.98              | N/A               | N/A            |
| 2462.00                  | 59.36             | AV       | H              | 31.63            | 90.99              | N/A               | N/A            |
| 2483.50                  | 39.35             | PK       | V              | 31.64            | 70.99              | 74.00             | 3.01           |
| 2483.50                  | 15.21             | AV       | V              | 31.64            | 46.85              | 54.00             | 7.15           |
| 4924.00                  | 42.40             | PK       | V              | 11.18            | 53.58              | 74.00             | 20.42          |
| 4924.00                  | 38.45             | AV       | V              | 11.18            | 49.63              | 54.00             | 4.37           |
| 7386.00                  | 34.27             | PK       | V              | 14.89            | 49.16              | 74.00             | 24.84          |
| 7386.00                  | 29.33             | AV       | V              | 14.89            | 44.22              | 54.00             | 9.78           |

**802.11g Mode:**

02.Fig Mode.

| Frequency<br>(MHz)       | Receiver          |          | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------------|-------------------|----------|----------------|------------------|--------------------|-------------------|----------------|
|                          | Reading<br>(dBμV) | Detector |                |                  |                    |                   |                |
| Low Channel: 2412 MHz    |                   |          |                |                  |                    |                   |                |
| 2412.00                  | 73.69             | PK       | V              | 31.53            | 105.22             | N/A               | N/A            |
| 2412.00                  | 63.75             | AV       | V              | 31.53            | 95.28              | N/A               | N/A            |
| 2412.00                  | 67.03             | PK       | H              | 31.53            | 98.56              | N/A               | N/A            |
| 2412.00                  | 57.35             | AV       | H              | 31.53            | 88.88              | N/A               | N/A            |
| 2390.00                  | 35.74             | PK       | V              | 31.46            | 67.20              | 74.00             | 6.80           |
| 2390.00                  | 17.78             | AV       | V              | 31.46            | 49.24              | 54.00             | 4.76           |
| 4824.00                  | 40.65             | PK       | V              | 10.94            | 51.59              | 74.00             | 22.41          |
| 4824.00                  | 36.45             | AV       | V              | 10.94            | 47.39              | 54.00             | 6.61           |
| 7236.00                  | 34.43             | PK       | V              | 14.44            | 48.87              | 74.00             | 25.13          |
| 7236.00                  | 29.32             | AV       | V              | 14.44            | 43.76              | 54.00             | 10.24          |
| Middle Channel: 2437 MHz |                   |          |                |                  |                    |                   |                |
| 2437.00                  | 75.55             | PK       | V              | 31.60            | 107.15             | N/A               | N/A            |
| 2437.00                  | 65.34             | AV       | V              | 31.60            | 96.94              | N/A               | N/A            |
| 2437.00                  | 69.58             | PK       | H              | 31.60            | 101.18             | N/A               | N/A            |
| 2437.00                  | 59.45             | AV       | H              | 31.60            | 91.05              | N/A               | N/A            |
| 4874.00                  | 43.01             | PK       | V              | 11.05            | 54.06              | 74.00             | 19.94          |
| 4874.00                  | 39.12             | AV       | V              | 11.05            | 50.17              | 54.00             | 3.83           |
| 7311.00                  | 34.25             | PK       | V              | 14.80            | 49.05              | 74.00             | 24.95          |
| 7311.00                  | 29.41             | AV       | V              | 14.80            | 44.21              | 54.00             | 9.79           |
| High Channel: 2462MHz    |                   |          |                |                  |                    |                   |                |
| 2462.00                  | 74.86             | PK       | V              | 31.63            | 106.49             | N/A               | N/A            |
| 2462.00                  | 64.98             | AV       | V              | 31.63            | 96.61              | N/A               | N/A            |
| 2462.00                  | 69.46             | PK       | H              | 31.63            | 101.09             | N/A               | N/A            |
| 2462.00                  | 59.31             | AV       | H              | 31.63            | 90.94              | N/A               | N/A            |
| 2483.50                  | 32.66             | PK       | V              | 31.64            | 64.30              | 74.00             | 9.70           |
| 2483.50                  | 16.83             | AV       | V              | 31.64            | 48.47              | 54.00             | 5.53           |
| 4924.00                  | 43.66             | PK       | V              | 11.18            | 54.84              | 74.00             | 19.16          |
| 4924.00                  | 38.56             | AV       | V              | 11.18            | 49.74              | 54.00             | 4.26           |
| 7386.00                  | 34.86             | PK       | V              | 14.89            | 49.75              | 74.00             | 24.25          |
| 7386.00                  | 28.56             | AV       | V              | 14.89            | 43.45              | 54.00             | 10.55          |

**802.11n ht20 Mode:**


02-FH n20 Mode:


| Frequency<br>(MHz)       | Receiver          |          | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------------|-------------------|----------|----------------|------------------|--------------------|-------------------|----------------|
|                          | Reading<br>(dBμV) | Detector |                |                  |                    |                   |                |
| Low Channel: 2412 MHz    |                   |          |                |                  |                    |                   |                |
| 2412.00                  | 72.56             | PK       | V              | 31.53            | 104.09             | N/A               | N/A            |
| 2412.00                  | 62.28             | AV       | V              | 31.53            | 93.81              | N/A               | N/A            |
| 2412.00                  | 66.26             | PK       | H              | 31.53            | 97.79              | N/A               | N/A            |
| 2412.00                  | 56.25             | AV       | H              | 31.53            | 87.78              | N/A               | N/A            |
| 2390.00                  | 36.71             | PK       | V              | 31.46            | 68.17              | 74.00             | 5.83           |
| 2390.00                  | 19.84             | AV       | V              | 31.46            | 51.30              | 54.00             | 2.70           |
| 4824.00                  | 40.82             | PK       | V              | 10.94            | 51.76              | 74.00             | 22.24          |
| 4824.00                  | 36.72             | AV       | V              | 10.94            | 47.66              | 54.00             | 6.34           |
| 7236.00                  | 34.36             | PK       | V              | 14.44            | 48.80              | 74.00             | 25.20          |
| 7236.00                  | 28.12             | AV       | V              | 14.44            | 42.56              | 54.00             | 11.44          |
| Middle Channel: 2437 MHz |                   |          |                |                  |                    |                   |                |
| 2437.00                  | 73.28             | PK       | V              | 31.60            | 104.88             | N/A               | N/A            |
| 2437.00                  | 65.09             | AV       | V              | 31.60            | 96.69              | N/A               | N/A            |
| 2437.00                  | 67.14             | PK       | H              | 31.60            | 98.74              | N/A               | N/A            |
| 2437.00                  | 59.07             | AV       | H              | 31.60            | 90.67              | N/A               | N/A            |
| 4874.00                  | 41.27             | PK       | V              | 11.05            | 52.32              | 74.00             | 21.68          |
| 4874.00                  | 37.45             | AV       | V              | 11.05            | 48.50              | 54.00             | 5.50           |
| 7311.00                  | 34.57             | PK       | V              | 14.80            | 49.37              | 74.00             | 24.63          |
| 7311.00                  | 25.45             | AV       | V              | 14.80            | 40.25              | 54.00             | 13.75          |
| High Channel: 2462MHz    |                   |          |                |                  |                    |                   |                |
| 2462.00                  | 76.48             | PK       | V              | 31.63            | 108.11             | N/A               | N/A            |
| 2462.00                  | 65.90             | AV       | V              | 31.63            | 97.53              | N/A               | N/A            |
| 2462.00                  | 70.34             | PK       | H              | 31.63            | 101.97             | N/A               | N/A            |
| 2462.00                  | 60.58             | AV       | H              | 31.63            | 92.21              | N/A               | N/A            |
| 2483.50                  | 35.12             | PK       | V              | 31.64            | 66.76              | 74.00             | 7.24           |
| 2483.50                  | 19.41             | AV       | V              | 31.64            | 51.05              | 54.00             | 2.95           |
| 4924.00                  | 38.40             | PK       | V              | 11.18            | 49.58              | 74.00             | 24.42          |
| 4924.00                  | 34.58             | AV       | V              | 11.18            | 45.76              | 54.00             | 8.24           |
| 7386.00                  | 34.70             | PK       | V              | 14.89            | 49.59              | 74.00             | 24.41          |
| 7386.00                  | 27.56             | AV       | V              | 14.89            | 42.45              | 54.00             | 11.55          |

**802.11n ht40 Mode:**

2422 MHz Mode:

| Frequency<br>(MHz)       | Receiver          |          | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------------|-------------------|----------|----------------|------------------|--------------------|-------------------|----------------|
|                          | Reading<br>(dBμV) | Detector |                |                  |                    |                   |                |
| Low Channel: 2422 MHz    |                   |          |                |                  |                    |                   |                |
| 2422.00                  | 70.58             | PK       | V              | 31.56            | 102.14             | N/A               | N/A            |
| 2422.00                  | 59.47             | AV       | V              | 31.56            | 91.03              | N/A               | N/A            |
| 2422.00                  | 64.25             | PK       | H              | 31.56            | 95.81              | N/A               | N/A            |
| 2422.00                  | 54.36             | AV       | H              | 31.56            | 85.92              | N/A               | N/A            |
| 2390.00                  | 41.32             | PK       | V              | 31.46            | 72.78              | 74.00             | 1.22           |
| 2390.00                  | 19.15             | AV       | V              | 31.46            | 50.61              | 54.00             | 3.39           |
| 4844.00                  | 35.61             | PK       | V              | 10.96            | 46.57              | 74.00             | 27.43          |
| 4844.00                  | 30.36             | AV       | V              | 10.96            | 41.32              | 54.00             | 12.68          |
| 7266.00                  | 34.33             | PK       | V              | 14.63            | 48.96              | 74.00             | 25.04          |
| 7266.00                  | 28.34             | AV       | V              | 14.63            | 42.97              | 54.00             | 11.03          |
| Middle Channel: 2437 MHz |                   |          |                |                  |                    |                   |                |
| 2437.00                  | 71.51             | PK       | V              | 31.60            | 103.11             | N/A               | N/A            |
| 2437.00                  | 60.42             | AV       | V              | 31.60            | 92.02              | N/A               | N/A            |
| 2437.00                  | 65.31             | PK       | H              | 31.60            | 96.91              | N/A               | N/A            |
| 2437.00                  | 55.25             | AV       | H              | 31.60            | 86.85              | N/A               | N/A            |
| 4874.00                  | 34.67             | PK       | V              | 11.05            | 45.72              | 74.00             | 28.28          |
| 4874.00                  | 30.45             | AV       | V              | 11.05            | 41.50              | 54.00             | 12.50          |
| 7311.00                  | 35.34             | PK       | V              | 14.80            | 50.14              | 74.00             | 23.86          |
| 7311.00                  | 26.42             | AV       | V              | 14.80            | 41.22              | 54.00             | 12.78          |
| High Channel: 2452MHz    |                   |          |                |                  |                    |                   |                |
| 2452.00                  | 72.84             | PK       | V              | 31.63            | 104.47             | N/A               | N/A            |
| 2452.00                  | 61.83             | AV       | V              | 31.63            | 93.46              | N/A               | N/A            |
| 2452.00                  | 63.41             | PK       | H              | 31.63            | 95.04              | N/A               | N/A            |
| 2452.00                  | 53.64             | AV       | H              | 31.63            | 85.27              | N/A               | N/A            |
| 2483.50                  | 41.15             | PK       | V              | 31.64            | 72.79              | 74.00             | 1.21           |
| 2483.50                  | 18.63             | AV       | V              | 31.64            | 50.27              | 54.00             | 3.73           |
| 4904.00                  | 34.03             | PK       | V              | 11.14            | 45.17              | 74.00             | 28.83          |
| 4904.00                  | 30.48             | AV       | V              | 11.14            | 41.62              | 54.00             | 12.38          |
| 7356.00                  | 33.94             | PK       | V              | 14.80            | 48.74              | 74.00             | 25.26          |
| 7356.00                  | 28.42             | AV       | V              | 14.80            | 43.22              | 54.00             | 10.78          |

**Worst Test plots(802.11b Chain 0 Middle channel was the worst)**



**4.3 6 dB Emission Bandwidth:**

|                |                  |              |              |
|----------------|------------------|--------------|--------------|
| Serial Number: | CR22060010-RF-S1 | Test Date:   | 2022-06-23   |
| Test Site:     | RF               | Test Mode:   | Transmitting |
| Tester:        | George Chen      | Test Result: | Pass         |

**Environmental Conditions:**

|                      |      |                              |    |                        |       |
|----------------------|------|------------------------------|----|------------------------|-------|
| Temperature:<br>(°C) | 25.5 | Relative<br>Humidity:<br>(%) | 53 | ATM Pressure:<br>(kPa) | 100.5 |
|----------------------|------|------------------------------|----|------------------------|-------|

**Test Equipment List and Details:**




| Manufacturer | Description       | Model   | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|---------|---------------|------------------|----------------------|
| R&S          | Spectrum Analyzer | FSV40   | 101474        | 2021-07-22       | 2022-07-21           |
| zhuoxiang    | Coaxial Cable     | SMA-178 | 211001        | Each time        | N/A                  |

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).




**Test Data:**

| Test Modes                                | Test Frequency (MHz) | 6 dB Bandwidth (MHz) | Limit (MHz) |
|-------------------------------------------|----------------------|----------------------|-------------|
| 802.11b                                   | 2412                 | 10.08                | $\geq 0.5$  |
|                                           | 2437                 | 9.68                 | $\geq 0.5$  |
|                                           | 2462                 | 9.68                 | $\geq 0.5$  |
| 802.11g                                   | 2412                 | 16.48                | $\geq 0.5$  |
|                                           | 2437                 | 16.48                | $\geq 0.5$  |
|                                           | 2462                 | 16.48                | $\geq 0.5$  |
| 802.11n ht20                              | 2412                 | 17.44                | $\geq 0.5$  |
|                                           | 2437                 | 17.60                | $\geq 0.5$  |
|                                           | 2462                 | 17.60                | $\geq 0.5$  |
| 802.11n ht40                              | 2422                 | 36.00                | $\geq 0.5$  |
|                                           | 2437                 | 36.00                | $\geq 0.5$  |
|                                           | 2452                 | 35.84                | $\geq 0.5$  |
| Note: Test only was performed at Chain 0. |                      |                      |             |




## 6dB Emission Bandwidth

802.11b  
Lowest Channel802.11b  
Middle Channel802.11b  
Highest Channel


## 6dB Emission Bandwidth

802.11g  
Lowest Channel802.11g  
Middle Channel802.11g  
Highest Channel


## 6dB Emission Bandwidth

802.11n ht20  
Lowest Channel802.11n ht20  
Middle Channel802.11n ht20  
Highest Channel


## 6dB Emission Bandwidth

802.11n ht40  
Lowest Channel

Date: 23, JUN, 2022 11:30:51

802.11n ht40  
Middle Channel

Date: 23, JUN, 2022 11:33:09

802.11n ht40  
Highest Channel

Date: 23, JUN, 2022 11:36:21

**4.4 Maximum peak conducted output power:**

|                |                  |              |              |
|----------------|------------------|--------------|--------------|
| Serial Number: | CR22060010-RF-S1 | Test Date:   | 2022-06-23   |
| Test Site:     | RF               | Test Mode:   | Transmitting |
| Tester:        | George Chen      | Test Result: | Pass         |

**Environmental Conditions:**

|                      |      |                              |    |                        |       |
|----------------------|------|------------------------------|----|------------------------|-------|
| Temperature:<br>(°C) | 25.5 | Relative<br>Humidity:<br>(%) | 53 | ATM Pressure:<br>(kPa) | 100.5 |
|----------------------|------|------------------------------|----|------------------------|-------|

**Test Equipment List and Details:**

| Manufacturer | Description               | Model         | Serial Number | Calibration Date | Calibration Due Date |
|--------------|---------------------------|---------------|---------------|------------------|----------------------|
| zhuoxiang    | Coaxial Cable             | SMA-178       | 211001        | Each time        | N/A                  |
| eastsheep    | Coaxial Attenuator        | 2W-SMA-JK-18G | 21060301      | Each time        | N/A                  |
| Agilent      | USB Wideband Power Sensor | U2021XA       | MY54080015    | 2021/7/22        | 2022/7/21            |

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data:**

| Test Modes   | Test Channel | Test Frequency (MHz) | Maximum Conducted Peak Output Power(dBm) |         | Limit (dBm) |
|--------------|--------------|----------------------|------------------------------------------|---------|-------------|
|              |              |                      | Chain 0                                  | Chain 1 |             |
| 802.11b      | Lowest       | 2412                 | 21.1                                     | 20.9    | ≤24.57      |
|              | Middle       | 2437                 | 20.39                                    | 20.5    | ≤24.57      |
|              | Highest      | 2462                 | 20.06                                    | 20.1    | ≤24.57      |
| 802.11g      | Lowest       | 2412                 | 22.1                                     | 22.3    | ≤24.57      |
|              | Middle       | 2437                 | 21.76                                    | 21.8    | ≤24.57      |
|              | Highest      | 2462                 | 21.19                                    | 21.3    | ≤24.57      |
| 802.11n ht20 | Lowest       | 2412                 | 21.5                                     | 21.6    | ≤24.57      |
|              | Middle       | 2437                 | 21.09                                    | 21.2    | ≤24.57      |
|              | Highest      | 2462                 | 20.86                                    | 20.9    | ≤24.57      |
| 802.11n ht40 | Lowest       | 2422                 | 21.13                                    | 21.2    | ≤24.57      |
|              | Middle       | 2437                 | 20.86                                    | 20.9    | ≤24.57      |
|              | Highest      | 2452                 | 20.51                                    | 20.6    | ≤24.57      |

Note: the maximum Gain is 11.43dBi.

**4.5 Maximum power spectral density:**

|                |                  |              |                       |
|----------------|------------------|--------------|-----------------------|
| Serial Number: | CR22060010-RF-S1 | Test Date:   | 2022-06-23~2022-07-15 |
| Test Site:     | RF               | Test Mode:   | Transmitting          |
| Tester:        | George Chen      | Test Result: | Pass                  |

**Environmental Conditions:**

|                      |           |                           |       |                        |             |
|----------------------|-----------|---------------------------|-------|------------------------|-------------|
| Temperature:<br>(°C) | 25.5~27.5 | Relative Humidity:<br>(%) | 53~56 | ATM Pressure:<br>(kPa) | 100.1~100.5 |
|----------------------|-----------|---------------------------|-------|------------------------|-------------|

**Test Equipment List and Details:**

| Manufacturer | Description       | Model   | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|---------|---------------|------------------|----------------------|
| R&S          | Spectrum Analyzer | FSV40   | 101474        | 2021-07-22       | 2022-07-21           |
| zhuoxiang    | Coaxial Cable     | SMA-178 | 211001        | Each time        | N/A                  |

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).




**Test Data:**

| Test Channel | Test Frequency<br>(MHz) | Maximum Power Spectral Density<br>(dBm/3kHz) |         | Limit<br>(dBm/3kHz) |
|--------------|-------------------------|----------------------------------------------|---------|---------------------|
|              |                         | Chain 0                                      | Chain 1 |                     |
| 802.11b      | 2412                    | -7.93                                        | -7.95   | $\leq 2.57$         |
|              | 2437                    | -7.96                                        | -6.83   | $\leq 2.57$         |
|              | 2462                    | -7.81                                        | -6.74   | $\leq 2.57$         |
| 802.11g      | 2412                    | -14.13                                       | -14.42  | $\leq 2.57$         |
|              | 2437                    | -14.36                                       | -14.51  | $\leq 2.57$         |
|              | 2462                    | -14.11                                       | -14.51  | $\leq 2.57$         |
| 802.11n ht20 | 2412                    | -14.86                                       | -15.06  | $\leq 2.57$         |
|              | 2437                    | -14.97                                       | -15     | $\leq 2.57$         |
|              | 2462                    | -14.99                                       | -15.1   | $\leq 2.57$         |
| 802.11n ht40 | 2422                    | -17.58                                       | -17.18  | $\leq 2.57$         |
|              | 2437                    | -16.98                                       | -17.03  | $\leq 2.57$         |
|              | 2452                    | -17.61                                       | -17.43  | $\leq 2.57$         |


Note: the maximum Gain is 11.43dBi.

Chain 0:


## Maximum power spectral density

802.11b  
Lowest Channel802.11b  
Middle Channel802.11b  
Highest Channel


## Maximum power spectral density

802.11g  
Lowest Channel

Date: 23, JUN, 2022 11:10:43


802.11g  
Middle Channel

Date: 23, JUN, 2022 11:20:39


802.11g  
Highest Channel

Date: 23, JUN, 2022 11:22:53


802.11n ht20  
Lowest Channel




802.11n ht20  
Middle Channel




802.11n ht20  
Highest Channel




## Maximum power spectral density

802.11n ht40  
Lowest Channel

Date: 23, JUN, 2022 11:31:42

802.11n ht40  
Middle Channel




Date: 23, JUN, 2022 11:34:00

802.11n ht40  
Highest Channel




Date: 23, JUN, 2022 11:37:15

Chain 1:


## Maximum power spectral density

802.11b  
Lowest Channel802.11b  
Middle Channel802.11b  
Highest Channel


## Maximum power spectral density

802.11g  
Lowest Channel802.11g  
Middle Channel802.11g  
Highest Channel


## Maximum power spectral density

802.11n ht20  
Lowest Channel

Date: 23, JUN, 2022 10:26:59




802.11n ht20  
Middle Channel

Date: 23, JUN, 2022 10:28:15

802.11n ht20  
Highest Channel

Date: 23, JUN, 2022 10:29:23

## Maximum power spectral density

802.11n ht40  
Lowest Channel802.11n ht40  
Middle Channel802.11n ht40  
Highest Channel

**4.6 100 kHz Bandwidth of Frequency Band Edge:**

|                |                  |              |              |
|----------------|------------------|--------------|--------------|
| Serial Number: | CR22060010-RF-S1 | Test Date:   | 2022-06-23   |
| Test Site:     | RF               | Test Mode:   | Transmitting |
| Tester:        | George Chen      | Test Result: | Pass         |

**Environmental Conditions:**



|                      |      |                              |    |                        |       |
|----------------------|------|------------------------------|----|------------------------|-------|
| Temperature:<br>(°C) | 25.5 | Relative<br>Humidity:<br>(%) | 53 | ATM Pressure:<br>(kPa) | 100.5 |
|----------------------|------|------------------------------|----|------------------------|-------|

**Test Equipment List and Details:**

| Manufacturer | Description          | Model   | Serial<br>Number | Calibration<br>Date | Calibration<br>Due Date |
|--------------|----------------------|---------|------------------|---------------------|-------------------------|
| R&S          | Spectrum<br>Analyzer | FSV40   | 101474           | 2021-07-22          | 2022-07-21              |
| zhuoxiang    | Coaxial Cable        | SMA-178 | 211001           | Each time           | N/A                     |


*\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Chain 0:


**100 kHz Bandwidth of Frequency Band Edge**802.11b  
Lowest Band edge802.11b  
Highest Band edge

**100 kHz Bandwidth of Frequency Band Edge**

802.11g  
Lowest Band edge




802.11g  
Highest Band edge




**100 kHz Bandwidth of Frequency Band Edge**

802.11n ht20  
Lowest Band edge



Date: 23, JUN, 2022 11:25:41



802.11n ht20  
Highest Band edge



Date: 23, JUN, 2022 11:30:08




Chain 1:


**100 kHz Bandwidth of Frequency Band Edge**802.11b  
Lowest Band edge802.11b  
Highest Band edge

**100 kHz Bandwidth of Frequency Band Edge**

802.11g  
Lowest Band edge




802.11g  
Highest Band edge




**100 kHz Bandwidth of Frequency Band Edge**

802.11n ht20  
Lowest Band edge




802.11n ht20  
Highest Band edge




**100 kHz Bandwidth of Frequency Band Edge**

802.11n ht40  
Lowest Band edge



802.11n ht40  
Highest Band edge



**4.7 Duty Cycle:**

|                |                  |              |              |
|----------------|------------------|--------------|--------------|
| Serial Number: | CR22060010-RF-S1 | Test Date:   | 2022-06-23   |
| Test Site:     | RF               | Test Mode:   | Transmitting |
| Tester:        | George Chen      | Test Result: | N/A          |

**Environmental Conditions:**

|                      |      |                              |    |                        |       |
|----------------------|------|------------------------------|----|------------------------|-------|
| Temperature:<br>(°C) | 25.5 | Relative<br>Humidity:<br>(%) | 53 | ATM Pressure:<br>(kPa) | 100.5 |
|----------------------|------|------------------------------|----|------------------------|-------|

**Test Equipment List and Details:**

| Manufacturer | Description          | Model   | Serial<br>Number | Calibration<br>Date | Calibration<br>Due Date |
|--------------|----------------------|---------|------------------|---------------------|-------------------------|
| R&S          | Spectrum<br>Analyzer | FSV40   | 101474           | 2021-07-22          | 2022-07-21              |
| zhuoxiang    | Coaxial Cable        | SMA-178 | 211001           | Each time           | N/A                     |


*\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

**Test Data:****Horizontal Polarization**


| Test Modes                               | Ton<br>(ms) | Ton+off<br>(ms) | Duty cycle<br>(%) |
|------------------------------------------|-------------|-----------------|-------------------|
| 802.11b                                  | 8.509       | 8.552           | 99.50             |
| 802.11g                                  | 1.436       | 1.564           | 91.82             |
| 802.11n ht20                             | 1.323       | 1.372           | 96.43             |
| 802.11n ht40                             | 0.654       | 0.738           | 88.62             |
| Note: test only was performed at chain 0 |             |                 |                   |

## Duty Cycle


802.11b




802.11g



802.11n ht20





## 5. RF EXPOSURE EVALUATION

### 5.1 Applicable Standard

FCC §15.247 (i)

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §1.1307(b)(1) of this chapter.

### 5.2 Procedure

According to §1.1307(b)(3)(i)

(B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);

### 5.3 Measurement Result

| Frequency (MHz) | Distance (mm) | $P_{th}$ |       | Maximum Conducted Power including Tune-up Tolerance (dBm) | Antenna Gain (dBi) | ERP (dBm) | Exemption |
|-----------------|---------------|----------|-------|-----------------------------------------------------------|--------------------|-----------|-----------|
|                 |               | (mW)     | (dBm) |                                                           |                    |           |           |
| 2412-2462       | 200           | 3060     | 34.86 | 23                                                        | 11.43              | 32.28     | Compliant |

Result: The device compliant the Exemption at 20cm distances.

===== END OF REPORT =====