



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM180200114703
Page: 1 of 37

TEST REPORT

Application No.: SZEM1802001147CR(SGS SZ No.:T51810200006EM)
Applicant: Toy State International Ltd.
Address of Applicant: Unit 905, 9/F, West Wing, Tsim Sha Tsui Centre, 66 Mody Road, TST East,
Kowloon, Hong Kong

Equipment Under Test (EUT):

EUT Name: Mini FPV Racer
Model No.: 22615
Country of Origin: China
FCC ID: V9Q-22615X58
Standard(s) : 47 CFR Part 15, Subpart C 15.249
Date of Receipt: 2018-02-05
Date of Test: 2018-03-15 to 2018-04-04
Date of Issue: 2018-04-10

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2018-04-10		Original

Authorized for issue by:				
				
		Gebin Sun /Project Engineer		
				
		Eric Fu /Reviewer		



2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.249	N/A	47 CFR Part 15, Subpart C 15.203	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
20dB Bandwidth	47 CFR Part 15, Subpart C 15.249	ANSI C63.10 (2013) Section 6.9	47 CFR Part 15, Subpart C 15.215	Pass
Field Strength of the Fundamental Signal (15.249(a))	47 CFR Part 15, Subpart C 15.249	ANSI C63.10 (2013) Section 6.5&6.6	47 CFR Part 15, Subpart C 15.249(a)	Pass
Restricted Band Around Fundamental Frequency	47 CFR Part 15, Subpart C 15.249	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.249(d) & 15.209	Pass
Radiated Emissions	47 CFR Part 15, Subpart C 15.249	ANSI C63.10 (2013) Section 6.4&6.5&6.6	47 CFR Part 15, Subpart C 15.209 & 15.249 (a),(d)	Pass



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 DETAILS OF E.U.T.	5
4.2 DESCRIPTION OF SUPPORT UNITS	5
4.3 MEASUREMENT UNCERTAINTY	5
4.4 TEST LOCATION	6
4.5 TEST FACILITY	6
4.6 DEVIATION FROM STANDARDS	6
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	6
5 EQUIPMENT LIST	7
6 RADIO SPECTRUM TECHNICAL REQUIREMENT	9
6.1 ANTENNA REQUIREMENT	9
6.1.1 Test Requirement:	9
6.1.2 Conclusion	9
7 RADIO SPECTRUM MATTER TEST RESULTS	10
7.1 20dB BANDWIDTH	10
7.1.1 E.U.T. Operation	10
7.1.2 Test Setup Diagram	10
7.1.3 Measurement Procedure and Data	10
7.2 FIELD STRENGTH OF THE FUNDAMENTAL SIGNAL (15.249(A))	13
7.2.1 E.U.T. Operation	14
7.2.2 Test Setup Diagram	14
7.2.3 Measurement Procedure and Data	14
7.3 RESTRICTED BAND AROUND FUNDAMENTAL FREQUENCY	21
7.3.1 E.U.T. Operation	22
7.3.2 Test Setup Diagram	22
7.3.3 Measurement Procedure and Data	22
7.4 RADIATED EMISSIONS	27
7.4.1 E.U.T. Operation	28
7.4.2 Test Setup Diagram	28
7.4.3 Measurement Procedure and Data	28-37

4 General Information

4.1 Details of E.U.T.

Operating Frequency:	2.4GHz(2420MHz-2461MHz)
Frequency spacing	1 MHz
Channel Number:	42
Modulation Type:	GFSK
Sample Type:	Portable production
Antenna Type:	Integral
Antenna Gain:	2dBi
Power supply:	Rechargeable battery DC3.7V for Drone
Cable:	Charging Cable:60cm unshielded

4.2 Description of Support Units

The EUT has been tested as an independent unit.

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.25×10^{-8}
2	Duty cycle	0.37%
3	Occupied Bandwidth	3%
4	RF conducted power	0.75dB
5	RF power density	2.84dB
6	Conducted Spurious emissions	0.75dB
7	RF Radiated power	4.5dB (below 1GHz)
		4.8dB (above 1GHz)
8	Radiated Spurious emission test	4.5dB (Below 1GHz)
		4.8dB (Above 1GHz)
9	Temperature test	1 °C
10	Humidity test	3%
11	Supply voltages	1.5%
12	Time	3%



4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



5 Equipment List

20dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2018-04-02	2019-04-01
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2017-07-13	2018-07-12
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26

Field Strength of the Fundamental Signal (15.249(a))					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2017-05-02	2020-05-01
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2017-07-13	2018-07-12
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2018-04-02	2019-04-01
BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-01	2017-06-27	2020-06-26
Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-13
Horn Antenna (15GHz-40GHz)	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16
Pre-amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2017-09-27	2018-09-26
Low Noise Amplifier (100MHz-18GHz)	Black Diamond Series	BDLNA-0118- 352810	SEM005-05	2017-09-27	2018-09-27
Pre-amplifier(18-26GHz)	Rohde & Schwarz	CH14-H052	SEM005-17	2018-04-02	2019-04-01
Pre-amplifier (26GHz-40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2018-04-02	2019-04-01
DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2017-09-27	2018-09-26
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21
Band filter	N/A	N/A	SEM023-01	N/A	N/A



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180200114703

Page: 8 of 37

Restricted Band Around Fundamental Frequency					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2017-05-02	2020-05-01
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2017-07-13	2018-07-12
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2018-04-02	2019-04-01
BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-01	2017-06-27	2020-06-26
Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-13
Horn Antenna (15GHz-40GHz)	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16
Pre-amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2017-09-27	2018-09-26
Low Noise Amplifier (100MHz-18GHz)	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2017-09-27	2018-09-27
Pre-amplifier(18-26GHz)	Rohde & Schwarz	CH14-H052	SEM005-17	2018-04-02	2019-04-01
Pre-amplifier (26GHz-40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2018-04-02	2019-04-01
DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2017-09-27	2018-09-26
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21
Band filter	N/A	N/A	SEM023-01	N/A	N/A

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2017-09-29	2018-09-28
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2017-09-29	2018-09-28
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2017-09-29	2018-09-28
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2017-04-18	2018-04-17

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

Limit:

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2dBi.

Antenna location: Refer to Appendix (Internal photos)

7 Radio Spectrum Matter Test Results

7.1 20dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.215

Test Method: ANSI C63.10 (2013) Section 6.9

Limit: N/A


7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 22.6 °C Humidity: 43.9 % RH Atmospheric Pressure: 1015 mbar

Test mode: c:2.4G TX mode_Keep the EUT(Drone) in transmitting with modulation mode.

7.1.2 Test Setup Diagram




7.1.3 Measurement Procedure and Data


Test channel	20dB bandwidth (MHz)	Results
Lowest	0.477	Pass
Middle	0.472	Pass
Highest	0.472	Pass



Mode:c; Channel:Low




Mode:c; Channel:middle





Mode:c; Channel:High





7.2 Field Strength of the Fundamental Signal (15.249(a))

Test Requirement 47 CFR Part 15, Subpart C 15.249(a)

Test Method: ANSI C63.10 (2013) Section 6.5&6.6

Measurement Distance: 3m

Limit:

Frequency	Limit (dBUV/m @3m)	Remark
2400MHz-2483.5MHz	94.0	Average Value
	114.0	Peak Value


7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 21.1 °C Humidity: 64.2 % RH Atmospheric Pressure: 1015 mbar

Test mode: c:2.4G TX mode_Keep the EUT(Drone) in transmitting with modulation mode.

7.2.2 Test Setup Diagram




7.2.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor



Mode:c; Polarization:Horizontal; Modulation:GFSK; Channel:Low



Condition: 3m HORIZONTAL

Job No : 01147CR


Mode : 2420 Field Strength

Note : Plane

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2420.000	5.52	29.17	41.88	86.62	79.43	94.00	-14.57 Average
2 pk	2420.000	5.52	29.17	41.88	100.14	92.95	114.00	-21.05 peak



Mode:c; Polarization:Vertical; Modulation:GFSK; Channel:Low



Condition: 3m VERTICAL

Job No : 01147CR


Mode : 2420 Field Strength

Note : Plane

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2420.000	5.52	29.17	41.88	86.95	79.76	94.00	-14.24 Average
2 pk	2420.000	5.52	29.17	41.88	100.47	93.28	114.00	-20.72 peak



Mode:c; Polarization:Horizontal; Modulation:GFSK; Channel:middle



Condition: 3m VERTICAL

Job No : 01147CR


Mode : 2440 Field Strength

Note : Plane

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2440.000	5.54	29.23	41.89	86.72	79.60	94.00	-14.40 Average
2 pk	2440.000	5.54	29.23	41.89	100.24	93.12	114.00	-20.88 Peak



Mode:c; Polarization:Vertical; Modulation:GFSK; Channel:middle



Condition: 3m HORIZONTAL

Job No : 01147CR


Mode : 2440 Field Strength

Note : Plane

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2440.000	5.54	29.23	41.89	86.38	79.26	94.00	-14.74 Average
2 pk	2440.000	5.54	29.23	41.89	99.90	92.78	114.00	-21.22 Peak



Mode:c; Polarization:Horizontal; Modulation:GFSK; Channel:High



Condition: 3m HORIZONTAL

Job No : 01147CR


Mode : 2461 Field Strength

Note : Plane

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2461.000	5.57	29.29	41.90	85.71	78.67	94.00	-15.33 Average
2 pk	2461.000	5.57	29.29	41.90	99.23	92.19	114.00	-21.81 peak



Mode:c; Polarization:Vertical; Modulation:GFSK; Channel:High



Condition: 3m VERTICAL

Job No : 01147CR

Mode : 2461 Field Strength

Note : Plane

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2461.000	5.57	29.29	41.90	84.02	76.98	94.00	-17.02 Average
2 pk	2461.000	5.57	29.29	41.90	97.54	90.50	114.00	-23.50 peak

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only above measurement data were shown in the report.



7.3 Restricted Band Around Fundamental Frequency

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.249(d) & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency	Limit (dBuV/m @3m)	Remark
30MHz-88MHz	40.0	Quasi-peak Value
88MHz-216MHz	43.5	Quasi-peak Value
216MHz-960MHz	46.0	Quasi-peak Value
960MHz-1GHz	54.0	Quasi-peak Value
Above 1GHz	54.0	Average Value
Above 1GHz	74.0	Peak Value

Emission radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.


7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 21.4 °C Humidity: 65.8 % RH Atmospheric Pressure: 1015 mbar

Test mode: c:2.4G TX mode_Keep the EUT(Drone) in transmitting with modulation mode.

7.3.2 Test Setup Diagram




7.3.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor



Mode:c; Polarization:Horizontal; Modulation:GFSK; Channel:Low



Condition: 3m HORIZONTAL

Job No : 01147CR


Mode : 2420 Band edge

Note : Plane

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2400.000	5.49	29.11	41.88	60.22	52.94	74.00	-21.06 peak
2 pp	2420.000	5.52	29.17	41.88	86.62	79.43	94.00	-14.57 Average
3 pk	2420.000	5.52	29.17	41.88	100.14	92.95	114.00	-21.05 peak



Mode:c; Polarization:Vertical; Modulation:GFSK; Channel:Low



Condition: 3m VERTICAL

Job No : 01147CR


Mode : 2420 Band edge

Note : Plane

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pk	2399.063	5.49	29.10	41.88	60.95	53.66	74.00	-20.34 peak
2	2400.000	5.49	29.11	41.88	60.69	53.41	114.00	-60.59 peak
3 pp	2420.000	5.52	29.17	41.88	86.95	79.76	94.00	-14.24 Average
4	2420.000	5.52	29.17	41.88	100.47	93.28	114.00	-20.72 peak



Mode:c; Polarization:Horizontal; Modulation:GFSK; Channel:High



Condition: 3m HORIZONTAL

Job No : 01147CR


Mode : 2461 Band edge

Note : Plane

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2461.000	5.57	29.29	41.90	85.71	78.67	94.00	-15.33 Average
2 pk	2461.000	5.57	29.29	41.90	99.23	92.19	114.00	-21.81 peak
3	2483.500	5.60	29.35	41.91	55.80	48.84	74.00	-25.16 peak
4	2484.743	5.60	29.36	41.91	57.48	50.53	74.00	-23.47 peak



Mode:c; Polarization:Vertical; Modulation:GFSK; Channel:High



Condition: 3m VERTICAL

Job No : 01147CR

Mode : 2461 Band edge

Note : Plane

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2461.000	5.57	29.29	41.90	84.02	76.98	94.00	-17.02 Average
2	2461.000	5.57	29.29	41.90	97.54	90.50	114.00	-23.50 peak
3	2483.500	5.60	29.35	41.91	56.97	50.01	74.00	-23.99 peak
4 pk	2484.241	5.60	29.35	41.91	57.58	50.62	74.00	-23.38 peak

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

2) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only above measurement data were shown in the report.



7.4 Radiated Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.249 (a),(d)

Test Method: ANSI C63.10 (2013) Section 6.4&6.5&6.6

Limit:

Frequency(MHz)	Field strength (microvolts/meter)	Limit (dBuV/m)	Detector	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	-	-	300
0.490-1.705	24000/F(kHz)	-	-	30
1.705-30	30	-	-	30
30-88	100	40.0	QP	3
88-216	150	43.5	QP	3
216-960	200	46.0	QP	3
960-1000	500	54.0	QP	3
Above 1000	500	54.0	AV	3


7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 22.7 °C Humidity: 43.5 % RH Atmospheric Pressure: 1015 mbar

Test mode: c:2.4G TX mode_Keep the EUT(Drone) in transmitting with modulation mode.

7.4.2 Test Setup Diagram




7.4.3 Measurement Procedure and Data

For testing performed with the loop antenna, the center of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane. Only the worst position of vertical was shown in the report.

below 1GHz

Mode:b; Polarization:Horizontal




Condition: 3m HORIZONTAL

Job No. : 01147CR

Test mode: c

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	599.32	2.70	26.59	27.70	35.37	36.96	46.00	-9.04
2	636.13	2.78	27.09	27.64	33.49	35.72	46.00	-10.28
3	774.16	3.13	28.35	27.45	33.71	37.74	46.00	-8.26
4	839.18	3.36	29.03	27.28	32.43	37.54	46.00	-8.46
5 pp	857.02	3.44	29.26	27.22	34.19	39.67	46.00	-6.33
6	989.54	3.69	30.25	26.80	31.13	38.27	54.00	-15.73

Mode:b; Polarization:Vertical



Condition: 3m VERTICAL

Job No. : 01147CR


Test mode: c

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	595.13	2.70	26.51	27.71	33.40	34.90	46.00	-11.10
2	699.30	2.90	27.89	27.55	28.76	32.00	46.00	-14.00
3	776.88	3.14	28.37	27.45	29.42	33.48	46.00	-12.52
4	839.18	3.36	29.03	27.28	30.90	36.01	46.00	-9.99
5 pp	893.86	3.58	29.72	27.10	29.88	36.08	46.00	-9.92
6	968.93	3.67	30.15	26.86	29.13	36.09	54.00	-17.91



above 1GHz

Mode:c; Polarization:Horizontal; Modulation:GFSK; Channel:Low



Condition: 3m HORIZONTAL


Job No : 01147CR

Mode : 2420 TX RSE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1354.577	4.99	25.20	41.30	49.73	38.62	74.00	-35.38	peak
2	4218.186	7.24	33.60	42.37	49.93	48.40	74.00	-25.60	peak
3	4840.000	7.93	34.22	42.47	51.30	50.98	74.00	-23.02	peak
4 pp	6795.879	10.69	35.94	41.00	47.59	53.22	74.00	-20.78	peak
5	7260.000	10.06	36.39	40.67	46.52	52.30	74.00	-21.70	peak
6	9680.000	10.78	37.54	37.64	41.64	52.32	74.00	-21.68	peak



Mode:c; Polarization:Vertical; Modulation:GFSK; Channel:Low



Condition: 3m VERTICAL


Job No : 01147CR

Mode : 2420 TX RSE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1096.904	3.99	23.95	41.09	53.03	39.88	74.00	-34.12	peak
2	4379.699	7.43	33.60	42.40	47.25	45.88	74.00	-28.12	peak
3	pp 4840.000	7.93	34.23	42.48	43.42	43.10	54.00	-10.90	Average
4	pk 4840.000	7.93	34.22	42.47	55.22	54.90	74.00	-19.10	peak
5	6835.278	10.58	36.05	40.97	47.77	53.43	74.00	-20.57	peak
6	7260.000	10.06	36.39	40.67	47.27	53.05	74.00	-20.95	peak
7	9680.000	10.78	37.54	37.64	41.15	51.83	74.00	-22.17	peak



Mode:c; Polarization:Horizontal; Modulation:GFSK; Channel:middle



Condition: 3m HORIZONTAL


Job No : 01147CR

Mode : 2440 TX RSE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1315.985	4.86	25.03	41.27	51.63	40.25	74.00	-33.75	peak
2	4218.186	7.24	33.60	42.37	49.60	48.07	74.00	-25.93	peak
3	4880.000	7.97	34.29	42.48	50.96	50.74	74.00	-23.26	peak
4	6602.265	11.24	35.39	41.14	47.70	53.19	74.00	-20.81	peak
5 pp	7320.000	10.05	36.37	40.63	38.06	43.85	54.00	-10.15	Average
6 pk	7320.000	10.05	36.37	40.63	49.86	55.65	74.00	-18.35	peak
7	9760.000	10.82	37.55	37.53	41.36	52.20	74.00	-21.80	peak



Mode:c; Polarization:Vertical; Modulation:GFSK; Channel:middle



Condition: 3m VERTICAL


Job No : 01147CR

Mode : 2440 TX RSE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1315.985	4.86	25.03	41.27	51.83	40.45	74.00	-33.55	peak
2	4443.453	7.50	33.60	42.41	47.85	46.54	74.00	-27.46	peak
3	4880.000	7.97	34.29	42.48	52.77	52.55	74.00	-21.45	peak
4	6602.265	11.24	35.39	41.14	48.35	53.84	74.00	-20.16	peak
5 pp	7320.000	10.05	36.37	40.63	37.43	43.22	54.00	-10.78	Average
6 pk	7320.000	10.05	36.37	40.63	49.23	55.02	74.00	-18.98	peak
7	9760.000	10.82	37.55	37.53	41.60	52.44	74.00	-21.56	peak



Mode:c; Polarization:Horizontal; Modulation:GFSK; Channel:High



Condition: 3m HORIZONTAL


Job No : 01147CR

Mode : 2461 TX RSE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1315.985	4.86	25.03	41.27	51.13	39.75	74.00	-34.25	peak
2	4443.453	7.50	33.60	42.41	48.64	47.33	74.00	-26.67	peak
3	4922.000	8.01	34.37	42.49	47.80	47.69	74.00	-26.31	peak
4	6698.373	10.97	35.67	41.07	47.61	53.18	74.00	-20.82	peak
5 pp	7383.000	10.03	36.35	40.59	39.44	45.23	54.00	-8.77	Average
6 pk	7383.000	10.03	36.35	40.59	51.24	57.03	74.00	-16.97	peak
7	9844.000	10.86	37.57	37.41	41.26	52.28	74.00	-21.72	peak



Mode:c; Polarization:Vertical; Modulation:GFSK; Channel:High



Condition: 3m VERTICAL

Job No : 01147CR

Mode : 2461 TX RSE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1374.295	5.06	25.28	41.32	49.82	38.84	74.00	-35.16	peak
2	4218.186	7.24	33.60	42.37	49.38	47.85	74.00	-26.15	peak
3	4922.000	8.01	34.37	42.49	51.30	51.19	74.00	-22.81	peak
4	6488.754	11.52	35.09	41.22	47.59	52.98	74.00	-21.02	peak
5 pp	7383.000	10.03	36.35	40.59	40.13	45.92	54.00	-8.08	Average
6 pk	7383.000	10.03	36.35	40.59	51.93	57.72	74.00	-16.28	peak
7	9844.000	10.86	37.57	37.41	42.86	53.88	74.00	-20.12	peak



Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

- 2) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only above measurement data were shown in the report.

- End of the Report -