



Compliance Certification Services Inc.

Report No: C150420Z02-RP1_MPE FCC ID: VEPGL-GSMGXW01 Date of Issue: May 7, 2015

RADIO FREQUENCY EXPOSURE

LIMIT

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §15.247(b)(4) and §1.1307(b)(1) of this chapter.

Conducted Power Results

Mode	Channel	Frequency(MHz)	Peak Conducted Output Power (dBm)
HSDPA (BAND II)	9262	1852.40	24.61
	9400	1880.00	24.79
	9538	1907.60	24.31



Compliance Certification Services Inc.

Report No: C150420Z02-RP1_MPE FCC ID: VEPGL-GSMGXW01 Date of Issue: May 7, 2015

EUT Specification

EUT	GXW Wireless Camera
Frequency band (Operating)	☐ WLAN: 2.412GHz ~ 2.462GHz ☐ WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz ☐ WLAN: 5.745GHz ~ 5825GHz ☐ Bluetooth: 2.402GHz~ 2.480GHz ☒ UMTS Band II/GSM1900: 1850MHz~1910MHz ☐ UMTS Band V/GSM850: 824MHz~849MHz ☐ Others _
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others _____
Exposure classification	☐ Occupational/Controlled exposure ($S = 5mW/cm^2$) ☒ General Population/Uncontrolled exposure ($S=1mW/cm^2$)
Duty Cycle	100%
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☒ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power (Including turn tolerance)	24.0dBm (251.189mW)
Antenna gain (Max)	2.00dBi (Numeric gain:1.58)
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Note:

1. The maximum output power (including turn tolerance) is 24.0dBm (251.189mW) and maximum antenna gain is 2dBi
2. For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20 cm, even if the calculations indicate that the MPE distance would be lesser.



Compliance Certification Services Inc.

Report No: C150420Z02-RP1_MPE FCC ID: VEPGL-GSMGXW01 Date of Issue: May 7, 2015

TEST RESULT

No non-compliance noted.

Calculation

Given $S = \frac{P \times G}{4\pi d^2}$ ***Equation 1***

Where d = distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power Density in mW / cm²

Maximum Permissible Exposure

EUT Output Power=251.189mW

Numeric antenna gain=1.58

Substituting the MPE safe distance using d=20 cm into ***Equation 1***:

Fields

The power density $S = 251.189 \times 1.58 / (4\pi \times 400) \text{ cm}^2 = 7.90 \times 10^{-2} \text{ mW/cm}^2$

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm^2 even if the calculation indicates that the power density would be larger.)