FCC PART18 TEST REPORT

Report No.: SET2022-07702

Product Name: Microwave Oven

Trade Name: Midea, Panasonic

Model No. : AM134A##-P, AM134A###-P, NN-SD67NS

FCC ID : VG8AM134AYYP

Applicant: Guangdong Midea Kitchen Appliances Manufacturing Co., Ltd.

Received Date: 2022.06.13

Test Data: 2022.06.13-2022.06.20

Issued by: CCIC Southern Testing Co., Ltd.

Lab Location: Electronic Testing Building, No.43Shahe Road, Xili Street, Nanshan District, Shenzhen, Guangdong, China
Tel: 86 755 26627338 **Fax:** 86 755 26627238

This test report consists of **21** pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.

Test Report

Product Name.....: Microwave Oven

Model No. .....: AM134A##-P, AM134A###-P, NN-SD67NS

Trade name ..... Midea, Panasonic

Applicant.....: Guangdong Midea Kitchen Appliances Manufacturing Co., Ltd.

Applicant Address.....: No.6, Yong An Road, Beijiao, Shunde, Foshan, China

Manufacturer .....: Guangdong Midea Kitchen Appliances Manufacturing Co., Ltd.

Manufacturer Address ...: No.6, Yong An Road, Beijiao, Shunde, Foshan, China

Test Standards .....: 47 CFR Part 18

Test Result.....: PASS

Tested by .....: Ruihong Xie

Ruihong Xie Test Engineer 2022.06.20

Reviewed by .....: Chris You

Chris You Senior Engineer 2022.06.20

Approved by .....: Shuangwen Zhang

2022.06.20

Shuangwen Zhang, Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION 5

1.1 GENERAL DESCRIPTION OF EUT 5

1.2 Test Standards and Results 6

1.3 Facilities and Accreditations 7

1.3.1 Facilities 7

1.3.2 Test Environment Conditions 7

1.3.3 Measurement Uncertainty 7

2. EQUIPMENTS LIST 8

3. EMC EMISSION TEST 9

3.1 Test Procedure 9

3.1.1 Frequency For Normal Voltage 9

3.1.2 Frequency For Line Voltage 9

3.1.3 Measurement data 10

3.2 RADIATION HAZARD TEST 10

3.2.1 Test Setup 10

3.2.2 Limit 10

3.2.3 Test results 10

3.3 RF OUTPUT POWER MEASUREMENT 11

3.3.1 Test Standard 11

3.3.2 EUT Operating mode 11

3.3.3 Test Data 11

4. CONDUCTED EMISSION 12

4.1.1 Conducted Emission Limit 12

4.1.2 Test Procedure 12

4.1.3 Test Setup 12

5. RADIATED EMISSION 15

5.1.1 Radiated Emission Limits 15

5.1.2 Test Setup 15

5.1.3 Test Procedure 16

APPENDIX I: PHOTOGRAPHS OF EMC TEST CONFIGURATION 20

Change History		
Issue	Date	Reason for change
1.0	2022.06.20	First edition

1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF EUT

EUT Name ..... :	Microwave Oven
Trade Name……..:	Midea, Panasonic
Model……..:	AM134A##-P, AM134A###-P, NN-SD67NS model designations as follow: First "A": Mechanical keypad; M: Indicates microwave function; 134: "1" indicates the microwave output power is 1100W, "34" indicate cavity capacity is 34 liters; Second "A": indicates the design No.; ## or ###: "#" may be 0~9, A~Z or blank, indicates different appearance; -P: Indicates Painted (Steel) Cavity, Stand for transduction function; Customer model as "NN-SD67NS" for trade mark "Panasonic" which is identical to Midea model "AM134A2DN-P". Model of AM134A2DN-P was selected for final testing.
Power Supply ..... :	120V AC/60Hz
Rated input Power(microwave):	1500W
Rated output Power(microwave):	1100W
Frequency..... :	2450MHz (Class B/Group 2)
Magnetron Model..... :	2M392J
Magnetron Manufacturer ... :	WITOL
Description of Support Units :	-Load for power output measurement: 1100 milliliters of water in the beaker located in the center of the oven. -Load for frequency measurement: 1100 milliliters of water in the beaker located in the center of the oven. -Load for measurement of radiation on second and third harmonic: Two loads, one of 770 and the other of 330 milliliters, of water are used. Each load is tested both with the beaker located in the center of the oven and with it in the right front corner. -Load for all other measurements: 770 milliliters of water, with the beaker located in the center of the oven.

Note 1: The EUT have the following typical setups during the test:

Setup1: Microwave heating mode (According to FCC PART 18);

Note 2: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 18:

No.	Identity	Document Title
1	47 CFR Part 18	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

Emission			
Standard	Item	Class / Severity	Result
47 CFR PART 18	Conducted Emission (150 kHz to 30 MHz)	18.307(b)	PASS
	Radiated Emission (30 MHz to1 GHz)	18.305(b)	PASS

1.3 Facilities and Accreditations

1.3.1 Facilities

CNAS-Lab Code: L1659

CCIC-SET is a third party testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L1659.

FCC-Registration No.: CN1283

CCIC Southern Testing Co., Ltd EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Designation Number: CN1283, valid time is until April 19th, 2023.

ISED Registration: 11185A-1

CCIC Southern Testing Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 11185A-1 on Aug. 04, 2016, valid time is until April 19th, 2023.

A2LA Code: 5721.01

CCIC-
SET is a third party testing organization accredited by A2LA according to ISO/IEC 17025. T he accreditation certificate number is 5721.01.

1.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15°C- 35°C
Relative Humidity (%):	25% -75%
Atmospheric Pressure (kPa):	86kPa-106kPa

1.3.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission:	Uc = 3.2 dB (k=2)
Uncertainty of Radiated Emission:(30MHz~1GHz)	Uc = 5.8 dB (k=2)
Uncertainty of Radiated Emission:(1~18GHz)	Uc = 5.1 dB (k=2)

2. EQUIPMENTS LIST

A. Equipment List:

Description	Manufacturer	Model	Serial No.	Calibration Date	Calibration Due. Date
Test Receiver	KEYSIGHT	ESR3	A181103297	2021.07.14	2022.06.24
LISN	ROHDE&SCHWARZ	NSLK 8127	A210803670	2021.04.03	2022.08.10
Shield Room	Xinju Electronics	L9000*W4500*H3100	A181003230	2021.09.05	2024.07.29
EMI Test Receiver	ROHDE&SCHWARZ	ESIB7	A0501375	2022.05.23	2023.04.17
Broadband Ant.	ETC	MCTD2786	A150402240	2021.03.05	2024.03.03
3M Anechoic Chamber	Albatross	SAC-3MAC 9*6*6m	A0412375	2019.03.26	2023.03.25
EMI Test Receiver	ROHDE&SCHWARZ	ESW26	A180502935	2021.08.12	2022.08.01
5M Anechoic Chamber	Albatross	SAC-5MAC 12.8x6.8x6.4m	A0304210	2019.03.25	2023.03.24
EMI Horn Ant.	ETC	1209	A150402241	2021.01.02	2024.01.01
Spectrum Analyzer	ROHDE&SCHWARZ	ESW26	A180502935	2021.08.12	2022.08.02

3. EMC EMISSION TEST

3.1 Test Procedure

Test Requirement: 47 CFR PART 18
Test Method: FCC/OST MP-5:1986
Power Supply: AC 120V/ 60Hz
Frequency Range: 2441-2482MHz
Detector: Peak
Limit: ISM equipment may be operated at any frequency above 9KHz and the frequency band 2400-2500MHz is allocated for use by ISM equipment

ISM frequency	Tolerance
6.78 MHz	±15.0 kHz
13.56 MHz	±7.0 kHz
27.12 MHz	±163.0 kHz
40.68 MHz	±20.0 kHz
915 MHz	±13.0 MHz
2,450 MHz	±50.0 MHz
5,800 MHz	±75.0 MHz
24,125 MHz	±125.0 MHz
61.25 GHz	±250.0 MHz
122.50 GHz	±500.0 MHz
245.00 GHz	±1.0 GHz

3.1.1 Frequency For Normal Voltage

The operating frequency was measured using a spectrum analyzer. Starting with the EUT at room temperature, a 1100mL water load was placed in the center of the oven and the oven was operated at maximum output power. The fundamental operating frequency was monitored until the water load was reduced to 20 percent of the original load.

3.1.2 Frequency For Line Voltage

The EUT was operated / warmed by at least 10 minutes of use with a 1100mL water load at room temperature at the beginning of the test. Then the operating frequency was monitored as the input voltage was varied between 80 and 125 percent of the nominal rating.

3.1.3 Measurement data

Operating Mode	Frequency (MHz)
Normal Voltage	2435.0-2469.5
Line Voltage	2448.6-2473.8

3.2 RADIATION HAZARD TEST

3.2.1 Test Setup

The EUT was set-up according to the FCC MP-5 and FCC Part 18 for radiation Hazard measurement. The measurement was using a microwave leakage meter to measure the radiation leakage in the as-received condition with the oven door closed A 770mL water load in a breaker was located in the center of the oven and the microwave oven was set to maximum power. While the oven operating, the microwave meter will check the leakage and then record the maximum leakage.

3.2.2 Limit

A maximum of 1.0mW/cm^{2}is allowed in according with the applicable FCC standards

3.2.3 Test results

There was no microwave leakage exceeding a power level of 0.51 m W/cm^{2}Observed at any point 5cm or more from the external surface of the oven

3.3 RF OUTPUT POWER MEASUREMENT

3.3.1 Test Standard

Test Requirement	47 CFR PART 18
Test Method	FCC/OST MP-5:1986
Power Supply	AC120/60Hz

3.3.2 EUT Operating mode

Test the EUT in microwave mode with full power.

3.3.3 Test Data

Mass of Water(g)	Mass of the container(g)	ambient temperature (℃)	Initial temperature(℃)	Final temperature(℃)	Heating Time(S)	Output Power (Watt)
1100	280	21.1	9.7	31.0	120	840.84

Formula:

$$P = \frac{4.2 \times m_w(T_2 - T_1) + 0.9 \times m_c(T_2 - T_0)}{t}$$

P is the microwave power output, in watts

Mw is the mass of the water, in grams

Mc is the mass of the container, in grams

T0 is the ambient temperature, in degrees Celsius

T1 is Initial temperature of the water, in degrees Celsius

T2 is final temperature of the water, in degrees Celsius

T is heating time, in seconds, excluding the magnetron filament heating-up time

4. CONDUCTED EMISSION

4.1.1 Conducted Emission Limit

Frequency range (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

a) The limit decreases linearly with the logarithm of the frequency in therange 0.05 MHz to 0.5 MHz.

b) The lower limit is applicable at the transition frequency.

4.1.2 Test Procedure

The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides 50Ω/50μH of coupling impedance for the measuring instrument. The Common Antenna is used for the call between the EUT and the System Simulator (SS). A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.

4.1.3 Test Setup



A. Test Result:

Mains terminal disturbance voltage, Setup1,L phase



(Plot A: L Phase)

Frequency (MHz)	Quasi Peak (dBµV)	Average (dBµV)	Cabel Loss (dB)	Corr. (dB)	Margin - QPK	Limit - QPK	Margin - AV	Limit - AV (dBµV)
0.181500	47.98	23.19	0.1	10.3	16.44	64.4	31.23	54.4
0.370500	44.81	17.99	0.2	10.3	13.68	58.5	30.50	48.5
0.564000	38.69	13.79	0.1	10.2	17.31	56.0	32.21	46.0
14.910000	31.42	11.72	0.1	10.9	28.58	60.0	38.28	50.0
17.313000	31.78	11.06	0.2	11.1	28.22	60.0	38.94	50.0
19.653000	31.54	11.76	0.1	11.2	28.46	60.0	38.24	50.0

Mains terminal disturbance voltage, Setup 1, N phase



(Plot B: N Phase)

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Cabel Loss (dB)	Corr. (dB)	Margin - QPK	Limit - QPK	Margin - AV	Limit - AV (dBµV)
0.154500	49.40	26.06	0.1	10.2	16.35	65.8	29.69	55.8
0.177000	45.33	21.05	0.1	10.3	19.30	64.6	33.58	54.6
0.235500	38.49	16.15	0.1	10.3	23.76	62.3	36.10	52.3
0.397500	31.72	10.35	0.2	10.3	26.19	57.9	37.56	47.9
1.212000	26.92	8.88	0.2	10.2	29.08	56.0	37.12	46.0
19.693500	28.40	8.49	0.2	11.2	31.60	60.0	41.51	50.0

Test Result: PASS

5. RADIATED EMISSION

5.1.1 Radiated Emission Limits

(a) ISM equipment operation on a frequency specified in §18.301 is permitted unlimited radiated energy in the band specified for that frequency.

(b) The field strength levels of emissions which lie outside the bands specified in §18.301,unless otherwise indicated, shall not exceed the following:

RF Power generated by equipment(watts)	Field strength limit(uV/m) @300m
Below 500	25
500or more	25*SQRT(power/500)

Power =840.84W

Limit=20lg(25*SQRT(power/500))+20lg(300/3) @ 3m distance.

5.1.2 Test Setup

For radiated emissions from 30MHz to1GHz



For radiated emissions above 1GHz



5.1.3 Test Procedure

a.The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.

b.The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.

c.The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement

d.The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.

e.If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.

f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note: Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

Test Result:

Radiation disturbances, antenna polarization:Setup1,Horizontal



(Plot A: Test Antenna Vertical30M - 1G)

Frequency (MHz)	Quasi Peak (dBµV/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dBµV/m)	Margin (dB)	Antenna	Verdict
43.68	25.10	120.000	100.0	70.22	45.12	Horizontal	Pass
51.25	26.27	120.000	100.0	70.22	43.95	Horizontal	Pass
129.39	34.20	120.000	100.0	70.22	36.02	Horizontal	Pass
169.37	27.60	120.000	100.0	70.22	42.62	Horizontal	Pass
696.22	37.62	120.000	100.0	70.22	32.60	Horizontal	Pass
786.09	30.20	120.000	100.0	70.22	40.02	Horizontal	Pass

Radiation disturbances, antenna polarization:Setup1,Vertical



(Plot B: Test Antenna Horizontal30M - 1G)

Frequency (MHz)	Quasi Peak (dBµV/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dBµV/m)	Margin (dB)	Antenna	Horizontal
30.00	21.85	120.000	100.0	70.22	48.37	Vertical	Pass
92.49	24.61	120.000	100.0	70.22	45.61	Vertical	Pass
166.51	27.51	120.000	100.0	70.22	42.71	Vertical	Pass
173.63	24.60	120.000	100.0	70.22	45.62	Vertical	Pass
687.03	34.52	120.000	100.0	70.22	35.70	Vertical	Pass
926.54	27.62	120.000	100.0	70.22	42.60	Vertical	Pass

Above 1GHz Setup1

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1204.05	46.07	-15.01	70.22	24.15	100	219	Horizontal
2	1858.71	46.47	-12.67	70.22	23.75	100	253	Horizontal
3	2317.82	52.57	-11.43	70.22	17.65	100	55	Horizontal
4	2483.62	51.10	-10.82	70.22	19.12	100	29	Horizontal
5	4260.56	57.22	-3.39	70.22	13.00	100	274	Horizontal
6	8303.32	52.05	3.17	70.22	18.17	100	78	Horizontal

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1229.55	41.62	-14.87	70.22	28.60	100	205	Vertical
2	1858.71	43.74	-12.67	70.22	26.48	100	293	Vertical
3	2462.36	53.76	-10.79	70.22	16.46	100	330	Vertical
4	2768.44	55.52	-9.52	70.22	14.70	100	57	Vertical
5	3669.66	53.73	-6.22	70.22	16.49	100	12	Vertical
6	4596.39	54.06	-1.85	70.22	16.16	100	341	Vertical

APPENDIX I: PHOTOGRAPHS OF EMC TEST CONFIGURATION

1. Radiated Emission Measurement below 1GHz



2. Radiated Emission Measurement above 1GHz



3. Conducted emission at AC mains input/output port Measurement

APPENDIX II: PHOTOGRAPHS OF PRODUCT PHOTO

External Photo



Internal Photo




ECXXXQQ-21-K(F)-P
BCK19-D1829
AMCAADU-S1-K-P
220427-12
Midea
STAINLESS STEEL


STAINLESS STEEL


Midea
NC(IN)
NC(OUT)
GND
L(IN)
L(OUT)
C3
FUSE
20A/125V
MDFLT12B-2
YK20090108





※※※ End of Report ※※※