www.ecmg-global.net

EMI TEST REPORT

On Model Name: Microwave Oven

Model Numbers: XM142AYY-P(S)

Brand Name: Midea

FCC ID Number: VG8EAM142AYY

Prepared for Guangdong Midea Kitchen Appliances Manufacturing Co.,Ltd.

According to
FCC Part 18(2015)
Industrial, Scientific and Medical Equipment
FCC/OST MP-5(1986)
FCC methods of measurements of radio noise emission from industrial, scientific and medical equipment

Test Report #: GUA-1602-11421-FCC

Prepared by: _____ *ECMG*
ViVi Huang/Assistant *Company Name*

Reviewed by: _____ *ECMG*
Jawen Yin/Senior Engineer *Company Name*

QC Manager: _____ *ECMG*
Swall Zhang/QC Manager *Company Name*

Test Report Released by: _____ *March 15th, 2016*
Swall Zhang *Date*

Revision History

Rev.	*Issue date*	*Revision*	*Revised by*
Rev.A	*04/27/2011*	*Initial*	*Jawen Yin*
Rev.B	*06/13/2013*	*Revised mother-Board*	*Jawen Yin*
Rev.C	*03/15/2016*	*Revised mother-Board*	*Jawen Yin*

Test Location

Tests performed in a Certified ANSI Semi-Anechoic Chamber and Shielded Room.

Test Site Location	*: GD WITOL VACUUM ELECTRONIC EMC TEST LABORATORY*
	BeiJiao,ShunDe,FoShan,GuangDong, 528311, China
Tel	*: (86)-757-26326917*
Fax	*: (86)-757- 22607341*

Test Facility

The test facility was recognized, certified, or accredited by the following organizations:

FCC – Registration No.: 910385

GD WITOL VACUUM ELECTRONIC EMC TEST LABORATORY has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC was maintained in our files

Table of Contents

GOVERNMENT DISCLAIMER NOTICE _____ 2

REPRODUCTION CLAUSE _____ 2

OPINIONS AND INTERPRETATIONS _____ 2

STATEMENT OF MEASUREMENT UNCERTAINTY _____ 2

ADMINISTRATIVE DATA _____ 3

EUT DESCRIPTION _____ 4

EUT MODEL DERIVED _____ 4

TEST SUMMARY _____ 5

LOAD FOR MICROWAVE OVEN _____ 6

EUT EXERCISE SOFTWARE _____ 6

EQUIPMENT MODIFICATION _____ 6

EUT SAMPLE PHOTOS FOR MODEL EM142ANV-P _____ 7

TEST SYSTEM DETAILS _____ 12

CONFIGURATION OF TESTED SYSTEM _____ 13

ATTACHMENT 1 –RADIATION HAZARD TEST _____ 14

ATTACHMENT 2 – INPUT POWER MEASUREMENT _____ 16

ATTACHMENT 3 – RF OUTPUT POWER MEASUREMENT _____ 18

ATTACHMENT 4 – OPERATING FREQUENCY MEASUREMENT _____ 20

ATTACHMENT 5 – CONDUCTED EMISSION TEST RESULTS _____ 23

ATTACHMENT 6 - RADIATED EMISSION TEST RESULTS _____ 28

List Attached Files

Exhibit Type	***File Description***	***File Name***
Test Report	*Test Report*	*VG8EAM142AYY_Test Report.pdf*
Operation Description	*Technical Description*	*VG8EAM142AYY_Operation Description.pdf*
External Photos	*External Photos*	*VG8EAM142AYY_External Photos.pdf*
Internal Photos	*Internal Photos*	*VG8EAM142AYY _Internal Photos.pdf*
Block Diagram	*Block Diagram*	*VG8EAM142AYY _Block Diagram.pdf*
Schematics	*Circuit Diagram*	*VG8EAM142AYY_Schematics.pdf*
ID Label/Location	*Label and Location*	*VG8EAM142AYY_Label & Location.pdf*
User Manual	*User Manual*	*VG8EAM142AYY_User's Manual.pdf*
Test set-up photos	*Test set-up photos*	*VG8EAM142AYY _Test Set-up Photos*

Government Disclaimer Notice

When government drawing, specification, or other data are used for any purpose other than in connection with a definitely related government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawing, specifications, or other data, is not to be regarded by implication or otherwise in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell patented invention that may in any way be related thereto. This report must not be used to claim product endorsement by NVLAP or any agency of the U.S. Government.

Reproduction Clause

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from ECMG Electronic Technical Testing Corp (Shenzhen).

Opinions and Interpretations

This test report relates to the abovementioned equipment under test (EUT).Without the permission of ECMG Electronic Technical Testing Corp (Shenzhen) Test Lab this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark on this or similar products. The manufacturer has sole responsibility of continued compliance of the device.

Statement of Measurement Uncertainty

The data and results referenced in the document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities that can account for a nominal measurement error. Furthermore, component and process variability of devices similar to that tested may result in additional deviation.

Administrative Data

Test Sample	*: Microwave Oven*
Model Numbers	*: XM142AYY-P(S)*
Model Tested	*: EM142ANV-P*
Brand Name	*:* Midea
Receipt Date	*: March 5th, 2016*
Date Tested	*: March 7th, 2016*
Applicant	*: Guangdong Midea Kitchen Appliances Manufacturing Co.,Ltd.*
Address	*No.6, Yong An Road, Beijiao, Shunde, Foshan.*
Telephone	*: (86)-757-23606480*
Fax	*: (86)-757-22607341*
Manufacturer	*: Guangdong Midea Kitchen Appliances Manufacturing Co.,Ltd.*
Address	*No.6, Yong An Road, Beijiao, Shunde, Foshan.*
Telephone	*: (86)-757-23606480*
Fax	*: (86)-757-22607341*
Factory	*: Guangdong Midea Kitchen Appliances Manufacturing Co.,Ltd.*
Address	*No.6, Yong An Road, Beijiao, Shunde, Foshan.*
Telephone	*: (86)-757-23606480*
Fax	*: (86)-757-22607341*

EUT Description

Guangdong Midea Kitchen Appliances Manufacturing Co.,Ltd. model tested EM142ANV-P (referred to as the EUT in this report) is a Microwave Oven.

The technical specifications of EUT are as below:

Power Supply	120V AC/60Hz
Rated Input Power (Microwave)	1550W
Rated Output Power (Microwave)	1100W
Frequency	2450 MHz(Class B/Group 2)
Magnetron Model	2M319J
Magnetron Manufacturer	WITOL

Note: For more detailed information or features please refer to user's manual of EUT.

EUT Model Derived

XM142AYY-P(S) model designations as follows:
X=E or A ;
M: Indicate Microwave;
142: "1" indicate the microwave output power is 1100W, "42" indicate cavity capacity is 42 liters;
YY= 0-9 or A-Z, indicate different appearance;
-P(S): "-P" indicate painted cavity, "-S" indicate Steel Cavity;
Model EM142ANV-P was chosen for the final testing.

Test Summary

The electromagnetic compatibility requirements on model EM142ANV-P for this test are stated below. all results listed in this report relate exclusively to this above-mentioned model as the equipment under test. this report confers no approval or endorsement upon any other component, host or subsystem used in the test set-up.

Emission Tests				
Specifications	***Description***	***Test Results***	***Test Point***	***Remark***
FCC Part 18:2015 FCC/OST MP-5:1986 ANSI C63.4-2014	*Radiation Hazard Measurement*	*Passed*	*Enclosure*	*Attachment 1*
FCC Part 18:2015 FCC/OST MP-5:1986 ANSI C63.4-2014	*Input Power Measurement*	*Passed*	*AC Input Port*	*Attachment 2*
FCC Part 18:2015 FCC/OST MP-5:1986 ANSI C63.4-2014	*RF Output power Measurement*	*Passed*	*EUT*	*Attachment 3*
FCC Part 18:2015 FCC/OST MP-5:1986 ANSI C63.4-2014	*Operating Frequency Measurement*	*Passed*	*EUT*	*Attachment 4*
FCC Part 18:2015 FCC/OST MP-5:1986 ANSI C63.4-2014	*Conducted Emission*	*Passed*	*AC Input Port*	*Attachment 5*
FCC Part 18:2015 FCC/OST MP-5:1986 ANSI C63.4-2014	*Radiated Emission*	*Passed*	*Enclosure*	*Attachment 6*

Load for Microwave Oven

For all measurements the energy developed by the oven was absorbed by a dummy load consisting of a quantity of tag water in a beaker. If the oven was provided with a shelf or other utensil support, this support was in its initial normal position. For ovens rated at 1000watts or less power output, the beaker contained quantities of water as listed in the following subparagraphs. For ovens rated at more than 1000watts output, each quantity was increased by 50% for each 500watts or fraction thereof in excess of 1000 watts. Additional beakers were used if necessary.

-Load for power output measurement: 1100 milliliters of water in the beaker located in the center of the oven.

-Load for frequency measurement: 1100 milliliters of water in the beaker located in the center of the oven.

-Load for measurement of radiation on second and third harmonic: Two loads, one of 770 and the other of 330 milliliters, of water are used. Each load is tested both with the beaker located in the center of the oven and with it in the right front corner.

-Load for all other measurements: 770 milliliters of water, with the beaker located in the center of the oven.

Note: *Rated output power of EUT is 1100 watts.*

EUT Exercise Software

No Test sofware support this test.

Equipment Modification

Any modifications installed previous to testing by Guangdong Midea Kitchen Appliances Manufacturing Co.,Ltd., will be incorporated in each production model sold or leased in United States.

There were no modifications installed by ECMG Electronic Technical Testing Corp (Shenzhen) test personnel.

EUT Sample Photos for Model EM142ANV-P

EUT Front View

EUT Back View

EUT Uncovered View-01



EUT Uncovered View-02

EUT Uncovered View-03

Magnetron Front View



Power Filter Board Top View



Power Filter Board Bottom View



Mother board - Top View



Mother board - Bottom View

Test System Details

EUT	
Model Number:	XM142AYY-P(S)
Model Tested:	EM142ANV-P
Description:	Microwave Oven
Input:	AC 120V/60Hz
Manufacturer:	Guangdong Midea Kitchen Appliances Manufacturing Co.,Ltd.

Support Equipment			
Description	**Model Number**	**Serial Number**	**Manufacturer**
N/A			

Cable Description					
Description	**From**	**To**	**Length (Meters)**	**Shielded (Y/N)**	**Ferrite (Y/N)**
Power Cable	EUT	Plug	1.2	N	N

Note:The "EUT" means "Microwave Oven".

Note:

The EUT has been tested as an independent unit together with other necessary accessories or support units. The above support units or accessories were used to form a representative test configuration during the test tests.

Configuration of Tested System



ATTACHMENT 1 –RADIATION HAZARD TEST

CLIENT:	Guangdong Midea Kitchen Appliances Manufacturing Co.,Ltd.	**TEST STANDERD:**	FCC Part 18
MODEL NUMBERS:	XM142AYY-P(S)	**PRODUCT:**	Microwave Oven
MODEL TESTED:	EM142ANV-P	**EUT DESIGNATION:**	Home or Office
TEMPERATURE:	23°C	**HUMIDITY:**	51%
ATM PRESSURE:	103kPa	**GROUNDING:**	Through AC Power Cord
TESTED BY:	Yang Dongmei	**DATE OF TEST:**	March 7th,2015
TEST REFERENCE:	ANSI C63.4-2014, FCC/OST MP-5:1986		
TEST PROCEDURE:	The EUT was set-up according to the FCC MP-5 and FCC Part 18 for Radiation Hazard Measurement. The measurement was using a microwave leakage meter to measure the Radiation leakage in the as-received condition with the oven door closed. A 770ml water load in a beaker was located in the center of the oven and the Microwave Oven was set to maximum power. While the oven operating, the microwavemeter will check the leakage and then record the maximum leakage.		
TESTED RANGE:	N/A		
TEST VOLTAGE:	AC 120V/60Hz		
RESULTS:	There was no microwave leakage exceeding a power level of 0.19 mW/cm^2 observed at any point 5cm or more from the external surface of the oven. A maximum of 1.0 mW/cm^2 is allowed in accordance with the applicable FCC standards. Hence, microwave leakage in the as-received condition with the oven door closed was below the maximum allowed. The test results relate only to the equipment under test provided by client.		
CHANGES OR MODIFICATIONS:	There were no modifications installed by ECMG Electronic Technical Testing Corp (Shenzhen) test personnel.		
M. UNCERTAINTY:	0.0001 mW/cm^2		

Test Equipment List:

Test Equipment	Manufacturer	Model	Serial No.	Cal. Due Date
Microwave Measurement	HOLADAY	HI-1710A	00122261	2017.1.03

TESTED BY: _____ **REVIEWED BY:** _____

ENGINEER **SENIOR ENGINEER**

Radiation Hazard Test Set up:

ATTACHMENT 2 – INPUT POWER MEASUREMENT

CLIENT:	Guangdong Midea Kitchen Appliances Manufacturing Co.,Ltd.	**TEST STANDERD:**	FCC Part 18
MODEL NUMBERS:	XM142AYY-P(S)	**PRODUCT:**	Microwave Oven
MODEL TESTED:	EM142ANV-P	**EUT DESIGNATION:**	Home or Office
TEMPERATURE:	22℃	**HUMIDITY:**	59%
ATM PRESSURE:	103.1kPa	**GROUNDING:**	Through AC Power Cord
TESTED BY:	Yang Dongmei	**DATE OF TEST:**	March 7th,2015
TEST REFERENCE:	ANSI C63.4-2014, FCC/OST MP-5:1986		
TEST PROCEDURE:	The EUT was set up according to the FCC MP-5 and FCC Part 18 for input power measurement. The input power and current was measured using a power analyzer. A 770ml water load in a beaker was located in the center of the oven and the Microwave Oven was set to maximum power. While the oven is operating, use a voltmeter and an ampmeter to test the AC input voltage and current.		
TESTED RANGE:	N/A		
TEST VOLTAGE:	120VAC / 60Hz		
RESULTS :	Based on the measured input power, the EUT was found to be operating within the intended specifications. The test results relate only to the equipment under test provided by client.		
CHANGES OR MODIFICATIONS:	There were no modifications installed by ECMG Electronic Technical Testing Corp (Shenzhen) test personnel.		
M. UNCERTAINTY :	± 5W		

Test Data:

Input voltage (V)	*Input Current (A)*	*Measured Input Power (W)*	*Rated input Power (W)*
120.5	*13.37*	*1541*	*1550*

Test Equipments List:

Test Equipment	*Manufacturer*	*Model*	*Serial No.*	*Cal. Due Date*
Power Meter	*Ainuo*	*AN8726C*	*058704200*	*2017.01.12*

TESTED BY: _____ ***REVIEWED BY:*** _____

ENGINEER ***SENIOR ENGINEER***

Input power Test Set up:

ATTACHMENT 3 – RF OUTPUT POWER MEASUREMENT

CLIENT:	Guangdong Midea Kitchen Appliances Manufacturing Co.,Ltd.	**TEST STANDERD:**	FCC Part 18
MODEL NUMBERS:	XM142AYY-P(S)	**PRODUCT:**	Microwave Oven
MODEL TESTED:	EM142ANV-P	**EUT DESIGNATION:**	Home or Office
TEMPERATURE:	22 ℃	**HUMIDITY:**	60%RH
ATM PRESSURE:	103kPa	**GROUNDING:**	Through AC Power Cord
TESTED BY:	Yang Dongmei	**DATE OF TEST:**	March 7th,2015
TEST REFERENCE:	ANSI C63.4-2014, FCC/OST MP-5:1986		
TEST PROCEDURE:	The EUT was set up according to the FCC MP-5 and FCC Part 18 for RF output power Measurement. The Caloric Method was used to determine maximum RF output power. The initial temperature of the water load was measured. A 1100ml water load in a beaker was located in the center of the oven. The oven was operated at maximum output power for 120 seconds, the temperature of the water was re-measured. RF Output Power = (4.2joules/calorie)(volume in milliliters)(temperature rise) / (time in seconds) = 4.2 joules/calorie × 1100 × (Final Temp - Initial Temp) / 120		
TESTED RANGE:	N/A		
TEST VOLTAGE:	120VAC / 60Hz		
RESULTS:	RF Output Power =808.5 watts. The test results relate only to the equipment under test provided by client.		
CHANGES OR MODIFICATIONS:	There were no modifications installed by ECMG Electronic Technical Testing Corp (Shenzhen) test personnel.		
M. UNCERTAINTY:	± 0.3℃		

Test Result:

Quality of Water(ml)	Initial Temp (℃)	Final Temp (℃)	Measured Times (s)	Measured out put Power(W)
1100	20.0	41.0	120S	808.5

RF Output Power (W) = 4.2 x 1000 x (Final Temp – Initial Temp) / 120 =808.5watts

Test Equipments list:

Test Equipment	Manufacturer	Model	Serial No.	Cal. Due Date
Digit Thermometer	Fluke Corporation	Fluke 51 II	15940197	2016.08.12
Stopwatch	CASIO	HS-3	CF-004	2016.07.13

TESTED BY: _____ ***REVIEWED BY:*** _____

ENGINEER ***SENIOR ENGINEER***

RF Output power Test Set up:

ATTACHMENT 4 – OPERATING FREQUENCY MEASUREMENT

CLIENT:	Guangdong Midea Kitchen Appliances Manufacturing Co.,Ltd.	**TEST STANDERD:**	FCC Part 18
MODEL NUMBERS:	XM142AYY-P(S)	**PRODUCT:**	Microwave Oven
MODEL TESTED:	EM142ANV-P	**EUT DESIGNATION:**	Home or Office
TEMPERATURE:	22℃	**HUMIDITY:**	60%RH
ATM PRESSURE:	101.1kPa	**GROUNDING:**	Through AC Power Cord
TESTED BY:	Yang Dongmei	**DATE OF TEST:**	March 7th,2015
TEST REFERENCE:	ANSI C63.4-2014, FCC/OST MP-5:1986		
TEST PROCEDURE:	The EUT was set up according to the FCC MP-5 and FCC Part 18 for Operating Frequency Measurement. 1) The variation of frequency with time. The operating frequency was measured using a spectrum analyzer. Starting with the EUT at room temperature, a 1100ml water load in a beaker was located in the center of the oven. Set a spectrum analyzer with antenna at 3 meters distance form the oven and the oven was operated at maximum output power. The fundamental operating frequency was monitored until the water load was reduced to 20 percent of the original load. 2) The variation of frequency with Line Voltage. The operating frequency was measured using a spectrum analyzer. The EUT was operated/warmed by at least 10 minutes of use with a 1100ml water load at room temperature at the beginning of the test. Then the operating frequency was monitored as the input voltage was varied between 80 and 125 percent of the nominal rating.		
TESTED RANGE:	2450 ± 50MHz		
TEST VOLTAGE:	120VAC / 60Hz		
RESULTS:	Please refer to following pages for details of the variation in operating frequency with time & line voltage measurement. The test results relate only to the equipment under test provided by client.		
CHANGES OR MODIFICATIONS:	There were no modifications installed by ECMG Electronic Technical Testing Corp (Shenzhen) test personnel.		
M. UNCERTAINTY:	Freq. ±10kHz		

Variation in Operating Frequency with Time:

Minimum Frequency (MHz)	*Maximum Frequency (MHz)*
2454.2	*2459.7*

Variation in Operating Frequency with Line Voltage:

Minimum Frequency (MHz)	*Maximum Frequency (MHz)*
2447.2	*2452.3*
Note: Line voltage varied from 96Vac to 150Vac.	

Test Equipments List:

Test Equipment	Manufacturer	Model	Serial No.	Last Cal.	Cal. Due
EMI test receiver	R&S	ESIB-26	100174	11/18/2015	11/17/2016
Horn Antenna	R&S	HF906	100311	11/20/2015	11/21/2016
Note: All testing were performed using internationally recognized standards. All test instruments were calibrated and traceable to the National Institute of Standards and Technology (NIST).					

TESTED BY: _____ **REVIEWED BY:** _____

ENGINEER **SENIOR ENGINEER**

Operating Frequency Test Set-up:

ATTACHMENT 5 – CONDUCTED EMISSION TEST RESULTS

CLIENT:	Guangdong Midea Kitchen Appliances Manufacturing Co.,Ltd.	**TEST STANDERD:**	FCC Part 18
MODEL NUMBERS:	EM142ANV-P	**PRODUCT:**	Microwave Oven
MODEL TESTED:	EM142ANV-P	**EUT DESIGNATION:**	Home or Office
TEMPERATURE:	22℃	**HUMIDITY:**	60%RH
ATM PRESSURE:	101.1kPa	**GROUNDING:**	Through AC Power Cord
TESTED BY:	Yang Dongmei	**DATE OF TEST:**	March 7th,2015
TEST REFERENCE:	ANSI C63.4-2014, FCC/OST MP-5:1986		
TEST PROCEDURE:	The EUT was set up according to the guideline of ANSI C63.4-2014 & FCC MP-5 for conducted emissions. The measurement was using a AMN on each line and an EMI receiver peak scan was made at the frequency measurement range. The six highest significant peaks were then marked, and these signals were then quasi-peaked and averaged. The frequency range investigated was from 150kHz to 30MHz.		
TESTED RANGE:	150kHz to 30MHz		
TEST VOLTAGE:	120VAC / 60Hz		
RESULTS:	The EUT meets the requirements of test reference for Conducted Emissions.The test results relate only to the equipment under test provided by client.		
CHANGES OR MODIFICATIONS:	There were no modifications installed by ECMG Electronic Technical Testing Corp (Shenzhen) test personnel.		
M. UNCERTAINTY:	The maximum measurement uncertainty is evaluated as : 150KHz~ 30MHz: 3.0dB		

Conducted Emission Test Set up:





Line L Conducted Emission Graph



Line N Conducted Emission Graph

Test Data:

Lines (L/N)	Frequency (MHz)	Corrected QP Level (dBuV)	Limits QP (dBuV)	Margin QP (dB)	Frequency (MHz)	Corrected AV Level (dBuV)	Limits AV (dBuV)	Margin QP (dB)
L	0.360	50.5	58.7	-8.2	0.360	/	48.7	/
L	0.695	36.5	56	-19.5	0.695	/	46	/
L	1.970	33.4	56	-22.6	1.970	/	46	/
N	0.370	52.1	58.5	-6.4	0.370	/	48.5	/
N	0.620	39.9	56	-16.1	0.620	/	46	/
N	1.150	36.1	56	-19.9	1.150	/	46	/

Note :
1) All readings are using a bandwidth of 9 kHz, with a 500 ms sweep time. A video filter was not used.
2) "QP" means "Quasi-Peak" values, "AV" means "Average" values.
3) The other reading are too low against official limits that are not be recorded.

Test Equipments List:

Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due
EMI test receiver	R&S	ESIB-26	100174	11/19/2015	11/18/2016
LISN	R&S	ESH2-Z5	100091	11/19/2015	11/18/2016
Transient Limiter	Agilent	11947A	3107A03648	11/19/2015	11/18/2016
Shielding Room	TDK	8m×4m×3m	N/A	04/17/2015	04/16/2017

Note: All testing were performed using internationally recognized standards. All test instruments were calibrated and traceable to the National Institute of Standards and Technology (NIST).

TESTED BY: _____ **ENGINEER**

REVIEWED BY: _____ **SENIOR ENGINEER**

Conducted Emission Test Set-up:

ATTACHMENT 6 - RADIATED EMISSION TEST RESULTS

CLIENT:	Guangdong Midea Kitchen Appliances Manufacturing Co.,Ltd.	**TEST STANDERD:**	FCC Part 18
MODEL NUMBERS:	XM142AYY-P(S)	**PRODUCT:**	Microwave Oven
MODEL TESTED:	EM142ANV-P	**EUT DESIGNATION:**	Home or Office
TEMPERATURE:	22 ℃	HUMIDITY:	63%RH
ATM PRESSURE:	103.0kPa	GROUNDING:	Through AC Power Cord
TESTED BY:	Yang Dongmei	DATE OF TEST:	March 7th,2015
TEST REFERENCE:	ANSI C63.4-2014, FCC/OST MP-5:1986		
TEST PROCEDURE:	The EUT was set up according to the guidelines of ANSI C63.4-2014& FCC MP-5 for radiated emissions. Microwave Oven was placed on a 1m *1.5m nonconductive table. The top of the table is 1.0 m above the ground. The table is placed on a flush mounted metal turntable. An EMI receiver peak scan was made at the frequency measurement range (pre-scan) in an Anechoic chamber. Signal discrimination was then performed and the significant peaks marked. All data was recorded in Quasi-peak detection mode from 30 MHz to 1GHz and average detector mode above 1GHz. The following data lists the significant emission frequencies, measured levels, correction factors (including cable and antenna correction factors), and the corrected readings against the limits. Explanation of the Correction Factor are given as follows: FS= RA + AF + CF - AG Where: FS = Field Strength RA = Receiver Amplitude AF = Antenna Factor CF = Cable Attenuation Factor AG = Amplifier Gain		
TESTED RANGE:	30MHz to 24.5GHz		
TEST VOLTAGE:	120VAC / 60Hz		
RESULTS:	The EUT meet the requirements of test reference for radiated emissions. The test results relate only to the equipment under test provided by client.		
CHANGES OR MODIFICATIONS:	There were no modifications installed by ECMG Electronic Technical Testing Corp (Shenzhen) test personnel.		
M. UNCERTAINTY:	The maximum measurement uncertainty is evaluated as : 30~1000MHz: 4.76dB; 1~25GHz: 4.5dB		

For radiated emissions from 30MHz to1GHz



For radiated emissions above 1GHz



Field strength limits for out-of-band emissions :

For RF output power <500W, Limit at 300m = 27.96dBuV/m

*For RF output power>500W, Limit at 300m=20log [25*SQRT(Power/500)]dBuV/m*

Test Data :

30MHz – 1GHz						
Frequency [MHz]	Antenna Polarization [V/H]	Corrected Reading [dBμV/m]	Factor (dB)	Field Strength [dBμV/m]	Delta, QP [dB]	3 Meters Limits [dBμV/m]
504.309	V	12.8	17.5	30.30	-39.7	70.0
257.435	V	11.76	12.9	24.66	-45.34	70.0
737.575	V	8.21	23.6	31.81	-38.19	70.0
257.435	H	32.77	12.9	45.67	-24.33	70.0
490.701	H	27.55	17.3	44.85	-25.15	70.0
492.645	H	25.3	17.3	43.60	-26.4	70.0
Note: 1) All readings are quasi-peak unless stated otherwise, using a bandwidth of 120kHz, with a 60s sweep time. A video filter was not used. 2) Field Strength = Read Level + Factor, Factor = Antenna Factor + Cable Loss - Preamp Factor.						
1GHz – 25GHz						
Frequency [GHz]	Antenna Polarization [V/H]	Corrected Reading [dBμV/m]	Factor (dB)	Field Strength [dBμV/m]	Delta, AV [dB]	3 Meters Limits [dBμV/m]
14.814	V	18.79	35.34	54.13	-15.87	70.0
14.513	V	13.65	35.86	49.51	-20.49	70.0
9.854	V	13.89	28.07	41.96	-28.04	70.0
14.483	H	16	35.86	51.86	-18.14	70.0
14.723	H	18.59	35.34	53.93	-16.07	70.0
9.824	H	22.76	28.07	50.83	-19.17	70.0
Note: 1) All readings are average unless stated otherwise, using a bandwidth of 1MHz, with a 60s sweep time. A video filter was not used. 2) Field Strength = Read Level + Factor, Factor = Antenna Factor + Cable Loss - Preamp Factor.						

Test Equipments List:

Test Equipment	Manufacturer	Model	Serial No.	Last Cal.	Cal. Due
EMI Test Receiver	R&S	ESIB-26	100174	11/19/2015	11/18/2016
Horn Antenna	R&S	HF906	100311	11/21/2015	11/20/2016
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130144	11/21/2015	11/20/2016
Loop Antenna	ETS	ETS-6152	24934	11/21/2015	11/20/2016
Anechoic Chamber	TDK	9m×6 m×5.7m	N/A	04/17/2015	04/16/2017
Note: All testing were performed using internationally recognized standards. All test instruments were calibrated and traceable to the National Institute of Standards and Technology (NIST).					

TESTED BY: _____ **ENGINEER**

REVIEWED BY: _____ **SENIOR ENGINEER**

Radiated Emission Test Set-up (30-1000MHz):

Radiated Emission Test Set-up (1-25GHz):

※※※ End Of Report ※※※