



Test report No. : 4788854906-US-R2-V0  
Page : 1 of 10  
Issued date : Mar. 9, 2020  
FCC ID : VGY2915

## **Maximum Permissible Exposure Report**

**Product** : Gigabit Broadband Router

**Model Name** : Vigor 2915ac, Vigor 2915Fac

**FCC ID** : VGY2915

**Test Regulation** : 47 CFR FCC Part 2.1091

**Received Date** : Feb. 25, 2019

**Issued Date** : Mar. 09, 2020

**Applicant** : DrayTek Corp.  
No.26 Fu Shing Rd., HuKou County, Hsin-Chu Industrial Park,  
Hsin-Chu, Taiwan 303 R.O.C

**Issued By** : Underwriters Laboratories Taiwan Co., Ltd.  
Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd.,  
Zhudong Township, Hsinchu County, Taiwan



The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report are responsible of the test sample(s) provided by the client only and are not to be used to indicate applicability to other similar products.

### **Underwriters Laboratories Taiwan Co., Ltd.**

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan  
Telephone : +886-2-7737-3000  
Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0864 / 2.0



Test report No. : 4788854906-US-R2-V0  
Page : 2 of 10  
Issued date : Mar. 9, 2020  
FCC ID : VGY2915

## REVISION HISTORY

**Original Test Report No.: 4788854906-US-R2-V0**

[illegible]

**Underwriters Laboratories Taiwan Co., Ltd.**

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0864 / 2.0



## Table Of Contents

|                                                               |           |
|---------------------------------------------------------------|-----------|
| <b>1. Attestation of Test Results.....</b>                    | <b>4</b>  |
| <b>2. Test Methodology .....</b>                              | <b>5</b>  |
| <b>3. Facilities and Accreditation .....</b>                  | <b>5</b>  |
| <b>4. Equipment Under Test .....</b>                          | <b>6</b>  |
| 4.1. Description of EUT.....                                  | 6         |
| 4.2. Description Of Available Antennas .....                  | 8         |
| <b>5. Requirement .....</b>                                   | <b>9</b>  |
| <b>6. Radio Frequency Radiation Exposure Evaluation .....</b> | <b>10</b> |

### **Underwriters Laboratories Taiwan Co., Ltd.**

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan  
Telephone :+886-2-7737-3000  
Facsimile (FAX) :+886-3-583-7948



Test report No. : 4788854906-US-R2-V0  
Page : 4 of 10  
Issued date : Mar. 9, 2020  
FCC ID : VGY2915

## 1. Attestation of Test Results

**APPLICANT:** DrayTek Corp.  
No.26 Fu Shing Rd., HuKou County, Hsin-Chu Industrial Park,  
Hsin-Chu, Taiwan 303 R.O.C

**MANUFACTURER** DrayTek Corp.  
No.26 Fu Shing Rd., HuKou County, Hsin-Chu Industrial Park,  
Hsin-Chu, Taiwan 303 R.O.C

**EUT DESCRIPTION:** Gigabit Broadband Router

**BRAND:** DrayTek

**MODEL:** Vigor2915ac, Vigor2915Fac

**SAMPLE STAGE:** Production Unit

| APPLICABLE STANDARDS   |              |
|------------------------|--------------|
| STANDARD               | Test Results |
| 47 CFR FCC PART 2.1091 | PASS         |

Underwriters Laboratories Taiwan Co., Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by Underwriters Laboratories Taiwan Co., Ltd. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Underwriters Laboratories Taiwan Co., Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Underwriters Laboratories Taiwan Co., Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Prepared By:

Cindy Hsin  
Project Handler

Date : Mar. 9, 2020

Approved and Authorized By:

Stanley Wu  
Senior Project Engineer

Date : Mar. 9, 2020

### Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan  
Telephone : +886-2-7737-3000  
Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0864 / 2.0



## 2. Test Methodology

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06.

## 3. Facilities and Accreditation

|                                  |                                                                                                                                                                                                                                                                                                                                 |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Location</b>             | Underwriters Laboratories Taiwan Co., Ltd.                                                                                                                                                                                                                                                                                      |
| <b>Address</b>                   | Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan                                                                                                                                                                                                                           |
| <b>Accreditation Certificate</b> | Underwriters Laboratories Taiwan Co., Ltd. is accredited by TAF, Laboratory Code 3398. The full scope of accreditation can be viewed at <a href="http://accreditation.taftw.org.tw/taf/public/basic/viewApplyItems.action?unitNo=3398">http://accreditation.taftw.org.tw/taf/public/basic/viewApplyItems.action?unitNo=3398</a> |

### Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan  
Telephone :+886-2-7737-3000  
Facsimile (FAX) :+886-3-583-7948



## 4. Equipment Under Test

### 4.1. Description of EUT

|                            |                                                                                                                                                                                                                                                                                                                                          |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product Name</b>        | Gigabit Broadband Router                                                                                                                                                                                                                                                                                                                 |
| <b>Brand Name</b>          | DrayTek                                                                                                                                                                                                                                                                                                                                  |
| <b>Model Name</b>          | Vigor2915ac, Vigor2915Fac                                                                                                                                                                                                                                                                                                                |
| <b>Operating Frequency</b> | 2.4GHz: 2412MHz ~ 2462MHz<br>5GHz: 5180MHz ~ 5240MHz<br>5745MHz ~ 5825MHz                                                                                                                                                                                                                                                                |
| <b>Modulation</b>          | CCK, DQPSK, DBPSK for DSSS<br>64QAM, 16QAM, QPSK, BPSK for OFDM<br>256QAM, 64QAM, 16QAM, QPSK, BPSK                                                                                                                                                                                                                                      |
| <b>Number of Channel</b>   | 2.4GHz:<br>802.11b, 802.11g, 802.11n (HT20): 11<br>802.11n (HT40): 7<br>5.18 ~ 5.24GHz:<br>802.11a, 802.11n (HT20), 802.11ac (VHT20): 4<br>802.11n (HT40), 802.11ac (VHT40): 2<br>802.11ac (VHT80): 1<br>5.745 ~ 5.825GHz:<br>802.11a, 802.11n (HT20), 802.11ac (VHT20): 5<br>802.11n (HT40), 802.11ac (VHT40): 2<br>802.11ac (VHT80): 1 |
| <b>Normal Voltage</b>      | 12Vdc from Adapter                                                                                                                                                                                                                                                                                                                       |
| <b>Hardware Version</b>    | V2915 V0A                                                                                                                                                                                                                                                                                                                                |
| <b>Software Version</b>    | r79916_beta                                                                                                                                                                                                                                                                                                                              |

### Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan  
Telephone :+886-2-7737-3000  
Facsimile (FAX) :+886-3-583-7948



Note:

1. The models difference table as below:

| Main Model   | Function |       |
|--------------|----------|-------|
|              | WAN1     |       |
|              | RJ45     | Fiber |
| Vigor2915ac  | V        | -     |
| Vigor2915Fac | -        | V     |

- The above models are market segmented by customer statements. The difference between models is the combination of hardware design and appearance, and there are no changes in RF-related parts.

2. The EUT contains following accessory devices.

| Product     | Brand | Model      | Description                                                                                           |
|-------------|-------|------------|-------------------------------------------------------------------------------------------------------|
| Adapter     | APD   | WA-24Q12FG | Input: 100-40Vac, 0.7A,<br>Output: 12Vdc, 2A<br>1.7meter, non-shielded cable, without<br>ferrite core |
| RJ-45 Cable | N/A   | N/A        | Length:3m                                                                                             |

3. The above EUT information is declared by manufacturer and for more detailed features description, please refer the manufacturer's or user's manual.

**Underwriters Laboratories Taiwan Co., Ltd.**

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan  
Telephone :+886-2-7737-3000  
Facsimile (FAX) :+886-3-583-7948



## 4.2. Description Of Available Antennas

| For 2.4GHz |             |                   |              |                   |
|------------|-------------|-------------------|--------------|-------------------|
| Antenna    | Brand Name  | Model Name        | Antenna Type | Antenna Gain(dBi) |
| Chain(0)   | MAG. LAYERS | EDA-1313-25GR2-A9 | Dipole       | 1.95              |
| Chain(1)   | MAG. LAYERS | EDA-1313-25GR2-A9 | Dipole       | 1.95              |
| For 5GHz   |             |                   |              |                   |
| Antenna    | Brand Name  | Model Name        | Antenna Type | Antenna Gain(dBi) |
| Chain(0)   | MAG. LAYERS | EDA-1313-25GR2-A9 | Dipole       | 4.12              |
| Chain(1)   | MAG. LAYERS | EDA-1313-25GR2-A9 | Dipole       | 4.12              |

Note: The above antenna information was provided from customer and for more detailed features description, please refer the manufacturer's specification or user's manual.

### Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan  
Telephone :+886-2-7737-3000  
Facsimile (FAX) :+886-3-583-7948



## 5. Requirement

### Limits for General Population/Uncontrolled Exposure

| Limits for General Population/Uncontrolled Exposure                                                                                                                                                                                                                                              |                                   |                                   |                                         |                                                                   |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|-----------------------------------|-----------------------------------------|-------------------------------------------------------------------|
| Frequency Range (MHz)                                                                                                                                                                                                                                                                            | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes) |
| 0.3-1.34                                                                                                                                                                                                                                                                                         | 614                               | 1.63                              | *100                                    | 30                                                                |
| 1.34-30                                                                                                                                                                                                                                                                                          | 824/f                             | 2.19/f                            | *180/f <sup>2</sup>                     | 30                                                                |
| 30-300                                                                                                                                                                                                                                                                                           | 27.5                              | 0.073                             | 0.2                                     | 30                                                                |
| 300-1500                                                                                                                                                                                                                                                                                         | --                                | --                                | f/1500                                  | 30                                                                |
| 1500-100,000                                                                                                                                                                                                                                                                                     | --                                | --                                | 1.0                                     | 30                                                                |
| Note 1: f = frequency in MHz, * means Plane-wave equivalent power density                                                                                                                                                                                                                        |                                   |                                   |                                         |                                                                   |
| Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure. |                                   |                                   |                                         |                                                                   |

Power Density (S) is calculated by the following formula:

$$S=(P*G)/4\pi R^2$$

where: S = power density (in appropriate units, e.g. mW/ cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

### Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0864 / 2.0



## 6. Radio Frequency Radiation Exposure Evaluation

### CDD Mode

#### WLAN 2.4GHz

| WLAN 2.4GHz          |                    |                  |           |           |                       |                       |
|----------------------|--------------------|------------------|-----------|-----------|-----------------------|-----------------------|
| Evaluation Frequency | Max. Average Power | Directional Gain | Max. EIRP | Max. EIRP | Power density @ 20 cm | Limit                 |
| (MHz)                | (dBm)              | (dBi)            | (dBm)     | (mW)      | (mW/cm <sup>2</sup> ) | (mW/cm <sup>2</sup> ) |
| 2412 ~ 2462          | 23.96              | 4.96             | 28.92     | 779.830   | 0.155                 | 1                     |

#### WLAN 5GHz

| WLAN 5GHz            |                    |                  |           |           |                       |                       |
|----------------------|--------------------|------------------|-----------|-----------|-----------------------|-----------------------|
| Evaluation Frequency | Max. Average Power | Directional Gain | Max. EIRP | Max. EIRP | Power density @ 20 cm | Limit                 |
| (MHz)                | (dBm)              | (dBi)            | (dBm)     | (mW)      | (mW/cm <sup>2</sup> ) | (mW/cm <sup>2</sup> ) |
| 5180 ~ 5240          | 27.45              | 7.13             | 34.58     | 2870.781  | 0.571                 | 1                     |
| 5745 ~ 5825          | 25.63              | 7.13             | 32.76     | 1887.991  | 0.376                 | 1                     |

### Beamforming Mode

#### WLAN 5GHz

| WLAN 5GHz            |                    |                  |           |           |                       |                       |
|----------------------|--------------------|------------------|-----------|-----------|-----------------------|-----------------------|
| Evaluation Frequency | Max. Average Power | Directional Gain | Max. EIRP | Max. EIRP | Power density @ 20 cm | Limit                 |
| (MHz)                | (dBm)              | (dBi)            | (dBm)     | (mW)      | (mW/cm <sup>2</sup> ) | (mW/cm <sup>2</sup> ) |
| 5180 ~ 5240          | 27.53              | 7.13             | 34.66     | 2924.152  | 0.582                 | 1                     |
| 5745 ~ 5825          | 26.47              | 7.13             | 33.60     | 2290.868  | 0.456                 | 1                     |

Note:

1. Max. EIRP (dBm) = Max. Average power (dBm) + Antenna Gain (dBi)
2. Max. EIRP (mW) =  $10^{(\text{Max. EIRP (dBm)} / 10)}$
3. Power density (mW/cm<sup>2</sup>) = Max. EIRP (mW) /  $[4 \times \pi \times (\text{calculated distance})^2]$ , the calculated distance is 20 cm.

### Conclusion:

The formula of calculated the MPE is:

$$\text{CPD1} / \text{LPD1} + \text{CPD2} / \text{LPD2} + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + WLAN 5GHz=0.155+0.582=0.737, therefore the maximum calculations of above situations are less than the “1” limit.

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

### Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0864 / 2.0