



12. Radio Frequency Exposure

12.1.Applicable Standards

☐ §1.1307(b)(3)(i)(A)	The available maximum time-averaged power is no more than 1 mW, regardless of separation distance.																																																	
☐ §1.1307(b)(3)(i)(c)	ERP is below a threshold calculated based on the distance , R between the person and t antenna / radiating structure, where $R > \lambda / 2 \pi$. TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION <table><tr><th colspan="3">RF Source Frequency</th><th colspan="3">Minimum Distance</th><th>Threshold ERP</th></tr><tr><th>f_L MHz</th><th></th><th>f_H MHz</th><th>$\lambda_L / 2\pi$</th><th></th><th>$\lambda_H / 2\pi$</th><th>W</th></tr><tr><td>0.3</td><td>–</td><td>1.34</td><td>159 m</td><td>–</td><td>35.6 m</td><td>1,920 R²</td></tr><tr><td>1.34</td><td>–</td><td>30</td><td>35.6 m</td><td>–</td><td>1.6 m</td><td>3,450 R²/f²</td></tr><tr><td>30</td><td>–</td><td>300</td><td>1.6 m</td><td>–</td><td>159 mm</td><td>3.83 R²</td></tr><tr><td>300</td><td>–</td><td>1,500</td><td>159 mm</td><td>–</td><td>31.8 mm</td><td>0.0128 R²f</td></tr><tr><td>1,500</td><td>–</td><td>100,000</td><td>31.8 mm</td><td>–</td><td>0.5 mm</td><td>19.2R²</td></tr></table> Subscripts L and H are low and high; λ is wavelength. From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.	RF Source Frequency			Minimum Distance			Threshold ERP	f_L MHz		f_H MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W	0.3	–	1.34	159 m	–	35.6 m	1,920 R ²	1.34	–	30	35.6 m	–	1.6 m	3,450 R ² /f ²	30	–	300	1.6 m	–	159 mm	3.83 R ²	300	–	1,500	159 mm	–	31.8 mm	0.0128 R ² f	1,500	–	100,000	31.8 mm	–	0.5 mm	19.2R ²
RF Source Frequency			Minimum Distance			Threshold ERP																																												
f_L MHz		f_H MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W																																												
0.3	–	1.34	159 m	–	35.6 m	1,920 R ²																																												
1.34	–	30	35.6 m	–	1.6 m	3,450 R ² /f ²																																												
30	–	300	1.6 m	–	159 mm	3.83 R ²																																												
300	–	1,500	159 mm	–	31.8 mm	0.0128 R ² f																																												
1,500	–	100,000	31.8 mm	–	0.5 mm	19.2R ²																																												
☒ § 1.1307(b)(3)(i)(B).	Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, $\leq P_{th}$ $P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$ Where $x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$ and $ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$ d = the separation distance (cm);																																																	



12.2.EUT Specification

Frequency band (Operating)	☐ WLAN: 2412MHz ~ 2462MHz ☒ WLAN: 5150MHz ~ 5250MHz ☐ WLAN: 5250MHz ~ 5350MHz ☐ WLAN: 5470MHz ~ 5725MHz ☒ WLAN: 5725MHz ~ 5850MHz ☐ Bluetooth: 2402MHz ~ 2480MHz
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation)
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm ²) ☒ General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	☐ Single antenna ☒ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☒ Tx/Rx diversity
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A
Remark: Non-Beamforming The maximum conducted output power is <u>26.92dBm (492.459mW)</u> at <u>5795MHz</u> (with <u>4.40dBi antenna gain.</u>) Beamforming The maximum conducted output power is <u>25.34dBm (342.031mW)</u> at <u>5775MHz</u> (with <u>6.49dBi antenna gain.</u>)	

**12.3. Test Results****Non-BeamForming**

Channel Frequency (MHz)	Max. Conducted output power(dBm)	Max. Tune up power (dBm)	Antenna Gain(dBi)	Max.Tune up e.r.p. Power (dBm)	Max. Tune up e.r.p. Power (mW)	Limit (mW)
5230	26.74	27.24	3.52	28.61	726.11	3060
5795	26.92	27.42	4.40	29.67	927.62	3060

BeamForming

Channel Frequency (MHz)	Max. Conducted output power(dBm)	Max. Tune up power (dBm)	Antenna Gain(dBi)	Max.Tune up e.r.p. Power (dBm)	Max. Tune up e.r.p. Power (mW)	Limit (mW)
5180-5240	23.45	23.95	5.01	26.81	479.73	3060
5745-5825	25.34	25.84	6.49	30.18	1042.32	3060

No non-compliance noted.

Maximum Permissible Exposure (Co-location)**Non-Beamforming**

Modulation Type	Channel Frequency (MHz)	Max. Conducted output power (dBm)	Max. Tune up power (dBm)	Antenna Gain(dBi)	Distance (cm)	Max. Tune up e.r.p. Power (mW)	Limit (mW)	MPE Ratio
11ax HE20	2437	26.70	27.20	6.03	20	1282.073	3060	0.419
11ax HE40	5795	26.92	27.42	4.40	20	927.620	3060	0.303
Co-location Total								0.722
Σ MPE ratios Limit								1

-----THE END OF REPORT-----