



시험 성적서

TEST REPORT

페이지(page) : (1) / 총(Total) (21)

성적서 번호 Report No.		ICRT-TR-E252174-0A	
신청자 Client	기관명 Name	AISOLUTION CO., LTD	
	주 소 Address	28-4, Samyang-ro 29gil, Gangbuk-gu, Seoul, 01194, Republic of Korea	
시험대상품목 Sample description		KOAMTAC SLED UHF 1.0W RFID READER	
모델명 Type description		KSLED-UHF1.0W	
정 격 Ratings		DC 3.7 V	
시험장소 Place of test		☒ 고정시험실(Permanent Testing Lab) ☐ 현장시험(On Site Testing) 주소지(Address): 112, 113 Hwanggeum 3-ro 7beon-gil, Hagun-ri, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea	
시험기간 Date of test		09. Jul. 2025 ~ 10. Jul. 2025	
시험방법/항목 Test Method/Item		FCC Part 15 Subpart C	
시험결과 Test Results		Refer to 3. Test Summary	
확 인 Affirmation	작성자 Tested by	기술책임자 Technical Manager	
	성명 Name Eun-Hye, Kwak	성명 Name Yong-Min, Won	
		(Signature)	
☐ 위 성적서는 고객이 제공한 시료에 대한 시험결과입니다. ☐ The above test report is certified that the above mentioned products have been tested for the sample. ☐ 위 성적서는 KS Q ISO/IEC 17025 및 한국인정기구(KOLAS)인정과 관련이 없습니다. ☐ The above test report is not related to accreditation by KS Q ISO/IEC 17025 and Korea Laboratory Accreditation scheme. ☐ 위 성적서는 주식회사 아이씨알의 승인 없이는 일부 복제에 대해 금지됩니다. ☐ The test report is prohibited for some reproduction without the approval of the ICR.			
2025. 07. 11 주식회사 아이씨알 대표이사 The head of INTERNATIONAL CERTIFICATION REGISTRAR			

본 성적서의 진위 확인은 G4B 혹은 ICR 홈페이지에서 가능합니다.

The authenticity of the test report can be checked on the G4B or ICR website.

경기도 김포시 양촌읍 황금3로7번길 112 / Tel: 02-6351-9001 ~ 6

112, Hwanggeum3-ro 7beon-gil, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea / Tel: 02-6351-9001 ~ 6



Contents

1. Applicant & Manufacturer & Test Laboratory Information	<u>4</u>
2. Equipment under Test(EUT) Information	<u>5</u>
3. Test Summary	<u>6</u>
4. Test Result	<u>9</u>
5. Used equipment	<u>21</u>



Revision History

Issued Report No.	Issued Date	Revisions	Effect Section
ICRT-TR-E252174-0A	2025.07.11	Initial Issue	All



1. Applicant & Manufacturer & Test Laboratory Information

1.1 Applicant information

Applicant	AISOLUTION CO., LTD
Address	28-4, Samyang-ro 29gil, Gangbuk-gu, Seoul, 01194, Republic of Korea

1.2 Manufacturer Information

Applicant	AISOLUTION CO., LTD
Address	28-4, Samyang-ro 29gil, Gangbuk-gu, Seoul, 01194, Republic of Korea

1.3 Test Laboratory Information

Laboratory	ICR Co., Ltd.
Address	112, Hwanggeum 3-ro 7beon-gil, Hagun-ri, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea
Telephone No.	+82-2-6351-9002
Fax No.	+82-2-6351-9007
KOLAS No.	KT652
KC & FCC	KR0165

1.4 Measurement Uncertainty

Parameter	Uncertainty	Limit
Occupied Channel Bandwidth	0.14%	±5 %
RF output power, conducted	0.85 dB	±1.5 dB
Power Spectral Density, conducted	1.44 dB	±3 dB
Unwanted Emissions, conducted	1.35 dB	±3 dB
Supply voltages	0.02%	±3 %
Time	0.58%	±5 %
All emissions, radiated (Under the 30 MHz)	2.10 dB	±6 dB
All emissions, radiated (Range 30 MHz ~ 1 GHz)	1.95 dB	±6 dB
All emissions, radiated (Above the 1 GHz)	2.47 dB	±6 dB



2. Equipment under Test(EUT) Information

2.1 General Information

Product Name	KOAMTAC SLED UHF 1.0W RFID READER
Model Name	KSLED-UHF1.0W
Additional Model Name	-
FCC ID	VH9-KSLEDUHF10-PL
Power Supply	DC 3.7 V

2.2 Additional Information

Equipment Class	DSS - Frequency Hopping Spread Spectrum system
Device Type	Stand-alone
Operating Frequency	902.75 MHz ~ 927.25 MHz
RF Output Power	29.77 dBm
Number of Channel	50
Modulation Type	ASK
Antenna Type	PCB ANTENNA
Antenna Gain	1.48 dBi

2.3 Modifications of EUT

- None



3. Test Summary

3.1 Test standards and results

FCC Part 15 Subpart C			
Clause	Test items	Applied	Results
§15.247 (a)(1)(i)	20 dB Bandwidth	■	N/A(Note 1)
§15.247 (a)(1)(i)	Carrier Frequency Separation	■	N/A(Note 1)
§15.247 (a)(1)(i)	Number of Hopping Frequencies	■	N/A(Note 1)
§15.247 (a)(1)(i)	Time of Occupancy (dwell Time)	■	N/A(Note 1)
§15.247 (b)(2)	Maximum Conducted Output Power	■	N/A(Note 1)
§15.247 (d)	Conducted Spurious Emission & Band edge	■	N/A(Note 1)
§15.247 (d) & §15.209 & §15.205	Radiated Spurious Emission & Band edge	■	PASS
§15.207	Power Line Conducted Emission	■	PASS

Note 1 : Not applicable because the EUT uses a certified RFID module.

※Compared the x, y, and z axes and test on the x-axis with the higher output value.

3.2 Purpose of the test

- To determine whether the equipment under test fulfills the requirements of the standards stated in section 3.1 and the provision of Article 3.2 of Directive 2014/53/EU

3.3 Test Methodology

- Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2013. Radiated testing was performed at a distance of 3 m from EUT to the antenna.

3.4 Configuration of Test System

- Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2013. Radiated testing was performed at a distance of 3 m from EUT to the antenna.

3.4.1 Radiated emission test

- Preliminary radiated emissions test were conducted using the procedure in ANSI C63.10: 2013 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 m Semi Anechoic Chamber.

The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization.



3.5 Antenna requirement

- According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section.

The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi.

Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Result: Pass

The transmitter has a **PCB ANTENNA**. The directional gain of the antenna is **1.48 dBi**.



4. Test Result

4.1. 20 dB Bandwidth

4.1.1 Test procedure

ANSI C63.10-2013 Clause 6.9.2

4.1.2 Limit

§15.247 (a)(1)(i)

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

4.1.3 Test data

Result : Pass

Test Result : Report Number [CTK-2023-02000]



4.2 Carrier Frequency Separation

4.2.1 Test procedure

ANSI C63.10-2013 Clause 7.8.2

4.2.2 Limit

§15.247 (a)(1)(i)

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

4.2.3 Test data

Result : Pass

Test Result : Report Number [CTK-2023-02000]



4.3 Number of Hopping Frequency

4.3.1 Test procedure

ANSI C63.10-2013 Clause 7.8.3

4.3.2 Limit

15.247 (a)(1)(i)

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

4.3.3 Test data

Result : Pass

Test Result : Report Number [CTK-2023-02000]



4.4 Time of Occupancy (dwell Time)

4.4.1 Test procedure

ANSI C63.10-2013 Clause 7.8.4

4.4.2 Limit

15.247 (a)(1)(i)

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

4.4.3 Test data

Result : Pass

Test Result : Report Number [CTK-2023-02000]



4.5 Maximum Conducted Output Power

4.5.1 Test procedure

ANSI C63.10-2013 Clause 7.8.5

4.5.2 Limit

§15.247 (b)(2)

For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

4.5.3 Test data

Result : Pass

Test Result : Report Number [CTK-2023-02000]



4.6 Conducted Spurious Emission

4.6.1 Test procedure

ANSI C63.10-2013 Clause 7.8.8, 6.10.4

4.6.2 Limit

§15.247 (d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

4.6.3 Test data

Result : Pass

Test Result : Report Number [CTK-2023-02000]



4.7 Radiated Spurious Emission

4.7.1 Test procedure

ANSI C63.10-2013 Clause 6.4, 6.5, 6.6

4.7.2 Limit

§15.247 (d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

§15.209 Radiated emission limits; general requirements.(a)

Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009–0.490	2400/F(kHz)	300
0.490–1.705	24000/F(kHz)	30
1.705–30.0	30	30
30–88	100 **	3
88–216	150 **	3
216–960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.



§15.205 Restricted bands of operation.(a),(b)

MHz	MHz	MHz	GHz
0.090–0.110	16.42–16.423	399.9–410	4.5–5.15
¹ 0.495–0.505	16.69475–16.69525	608–614	5.35–5.46
2.1735–2.1905	16.80425–16.80475	960–1240	7.25–7.75
4.125–4.128	25.5–25.67	1300–1427	8.025–8.5
4.17725–4.17775	37.5–38.25	1435–1626.5	9.0–9.2
4.20725–4.20775	73–74.6	1645.5–1646.5	9.3–9.5
6.215–6.218	74.8–75.2	1660–1710	10.6–12.7
6.26775–6.26825	108–121.94	1718.8–1722.2	13.25–13.4
6.31175–6.31225	123–138	2200–2300	14.47–14.5
8.291–8.294	149.9–150.05	2310–2390	15.35–16.2
8.362–8.366	156.52475–156.52525	2483.5–2500	17.7–21.4
8.37625–8.38675	156.7–156.9	2690–2900	22.01–23.12
8.41425–8.41475	162.0125–167.17	3260–3267	23.6–24.0
12.29–12.293	167.72–173.2	3332–3339	31.2–31.8
12.51975–12.52025	240–285	3345.8–3358	36.43–36.5
12.57675–12.57725	322–335.4	3600–4400	(²)
13.36–13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490–0.510 MHz.

² Above 38.6

Except as provided in paragraphs (d) and (e) of this section, the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in § 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in § 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in § 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in § 15.35 apply to these measurements.



4.7.3 Test data

Result : Pass

- Below 30 MHz_Low ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	note
1.475	29.28	QP	H	19.90	49.18	64.25	15.07	
1.514	30.73	QP	H	19.90	50.63	64.00	13.37	
1.628	29.9	QP	H	20.00	49.90	63.39	13.49	
1.753	25.74	QP	H	20.00	45.74	69.54	23.80	

- Below 30 MHz_Mid ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	note
1.514	31.67	QP	H	19.90	51.57	64.00	12.43	
1.553	31.05	QP	H	20.00	51.05	63.79	12.74	
1.628	29.62	QP	H	20.00	49.62	63.39	13.77	
1.699	26.61	QP	H	20.00	46.61	63.00	16.39	

- Below 30 MHz_High ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	note
1.535	31.66	QP	H	19.90	51.56	63.89	12.33	
1.571	31.88	QP	H	19.90	51.78	63.70	11.92	
1.592	32.09	QP	H	20.00	52.09	63.58	11.49	
1.657	29.74	QP	H	20.00	49.74	63.23	13.49	

- Below 30 MHz_Hop ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	note
1.469	28.45	QP	H	19.90	48.35	64.30	15.95	
1.580	31.86	QP	H	20.00	51.86	63.65	11.79	
1.601	31.89	QP	H	20.00	51.89	63.53	11.64	
1.738	24.74	QP	H	20.00	44.74	69.54	24.80	



- 30 MHz ~ 1 GHz_Low ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	note
33.589	39.47	QP	V	-17.40	22.07	40.00	17.93	
40.088	38.88	QP	H	-15.40	23.48	40.00	16.52	
43.580	37.99	QP	V	-14.60	23.39	40.00	16.61	
44.938	37.95	QP	V	-14.50	23.45	40.00	16.55	
45.811	37.97	QP	H	-14.30	23.67	40.00	16.33	
49.497	37.23	QP	V	-14.30	22.93	40.00	17.07	

- 30 MHz ~ 1 GHz_Mid ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	note
38.633	38.75	QP	H	-15.90	22.85	40.00	17.15	
43.968	38.39	QP	V	-14.60	23.79	40.00	16.21	
49.303	37.21	QP	H	-14.30	22.91	40.00	17.09	
578.535	45.02	QP	H	-6.90	38.12	46.00	7.88	
628.587	30.59	QP	V	-5.90	24.69	46.00	21.31	
650.800	22.94	QP	H	-5.60	17.34	46.00	28.66	

- 30 MHz ~ 1 GHz_High ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	note
37.760	38.41	QP	H	-16.20	22.21	40.00	17.79	
39.700	38.68	QP	V	-15.50	23.18	40.00	16.82	
43.289	37.89	QP	V	-14.70	23.19	40.00	16.81	
44.550	38.24	QP	V	-14.50	23.74	40.00	16.26	
49.982	37.25	QP	V	-14.30	22.95	40.00	17.05	
615.201	26.22	QP	V	-5.70	20.52	46.00	25.48	

- 30 MHz ~ 1 GHz_hop ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	note
38.148	39.13	QP	V	-16.10	23.03	40.00	16.97	
39.797	39.03	QP	V	-15.50	23.53	40.00	16.47	
43.192	38.26	QP	V	-14.70	23.56	40.00	16.44	
44.453	38.34	QP	V	-14.50	23.84	40.00	16.16	
48.915	37.51	QP	H	-14.30	23.21	40.00	16.79	
564.47	25.82	QP	H	-7.00	18.82	46.00	27.18	



- 1 GHz Above_Low ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	note
1 805.500	58.59	PK	H	-14.60	43.99	74.00	30.01	2nd Harmonic
	53.27	AVG	H		38.67	54.00	15.33	
2 424.500	56.33	PK	H	-7.80	48.53	74.00	25.47	Spurious Emission
	30.36	AVG	H		22.56	54.00	31.44	
2 708.500	55.08	PK	V	-7.80	47.28	74.00	26.72	3rd Harmonic
	52.76	AVG	V		44.96	54.00	9.04	

- 1 GHz Above_Mid ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	note
1 829.500	56.56	PK	V	-14.60	41.96	74.00	32.04	2nd Harmonic
	53.08	AVG	V		38.48	54.00	15.52	
2 401.750	58.09	PK	V	-8.10	49.99	74.00	24.01	Spurious Emission
	30.27	AVG	V		22.17	54.00	31.83	
2 744.250	60.17	PK	V	-8.10	52.07	74.00	21.93	3rd Harmonic
	55.11	AVG	V		47.01	54.00	6.99	

- 1 GHz Above_High ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	note
1 854.500	58.76	PK	V	-17.80	40.96	74.00	33.04	2nd Harmonic
	54.99	AVG	V		37.19	54.00	16.81	
2 480.250	68.30	PK	H	-14.60	53.70	74.00	20.30	Spurious Emission
	37.98	AVG	H		23.38	54.00	30.62	
2 781.750	59.68	PK	V	-8.80	50.88	74.00	23.12	3rd Harmonic
	57.81	AVG	V		49.01	54.00	4.99	



4.8 Power Line Conducted Emission

4.8.1 Test procedure

ANSI C63.10-2013 Clause 6.2

4.8.2 Limit

§15.207 (a)

Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

*Decreases with the logarithm of the frequency.



4.8.3 Test data

Result : Pass

L-Line Conducted Emission

Frequency (MHz)	Reading (dBuV/m)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	note
0.161	41.48	QP	9.90	51.38	65.40	14.02	-
	20.59	AVG		30.49	55.40	24.91	
0.191	38.15	QP	9.90	48.05	64.02	15.97	-
	23.62	AVG		33.52	54.02	20.50	
0.233	33.56	QP	9.70	43.26	62.33	19.07	-
	22.75	AVG		32.45	52.33	19.88	
0.670	41.34	QP	9.90	51.24	56.00	4.76	-
	33.30	AVG		43.20	46.00	2.80	
0.677	41.98	QP	9.90	51.88	56.00	4.12	-
	30.32	AVG		40.22	46.00	5.78	
1.012	35.22	QP	9.80	45.02	56.00	10.98	-
	24.56	AVG		34.36	46.00	11.64	

N-Line Conducted Emission

Frequency (MHz)	Reading (dBuV/m)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	note
0.161	41.85	QP	9.90	51.75	65.40	13.65	-
	14.89	AVG		24.79	55.40	30.61	
0.195	40.15	QP	9.90	50.05	63.82	13.77	-
	15.99	AVG		25.89	53.82	27.93	
0.263	33.72	QP	9.70	43.42	61.35	17.93	-
	14.61	AVG		24.31	51.35	27.04	
0.321	31.52	QP	9.80	41.32	59.68	18.36	-
	15.56	AVG		25.36	49.68	24.32	
0.346	30.00	QP	9.90	39.90	59.06	19.16	-
	13.95	AVG		23.85	49.06	25.21	
0.674	36.15	QP	9.90	46.05	56.00	9.95	-
	20.98	AVG		30.88	46.00	15.12	



5. Used equipment

	Description	Model Name	Manufacturer	Serial Number	Next Cal
■	LOOP ANTENNA	HFH2-Z2	ROHDE & SCHWARZ	100271	2027-03-04
■	BAND REJECTION FILTER	CTF-912M-S1	RF ONE ELECTRONICS	BRF1805C001	2026-02-24
■	DC POWER SUPPLY	XDL35-5P	XANTREX	J00385373	2026-02-24
■	TRILOG BROADBAND ANTENNA	VULB 9162	SCHWARZBECK	142	2027-03-01
■	EMI TEST RECEIVER	ESR26	ROHDE & SCHWARZ	101462	2026-03-24
■	SIGNAL CONDITIONING UNIT	SCU 08	ROHDE & SCHWARZ	100746	2026-03-24
■	DOUBLE-RIDGED HORN ANTENNA	HF907	ROHDE & SCHWARZ	102556	2025-07-25
■	SIGNAL CONDITIONING UNIT	SCU18	ROHDE & SCHWARZ	102342	2026-03-24
■	EMI TEST RECEIVER	ESR26	ROHDE & SCHWARZ	101461	2026-03-24
■	TWO-LINE V-NETWORK	ENV216	ROHDE & SCHWARZ	102195	2025-09-12
■	EMI TEST RECEIVER	ESR7	ROHDE & SCHWARZ	102034	2026-03-24

- END OF REPORT.