

Safety Human Exposure

1.1 Radio Frequency Exposure Compliance

1.1.1 Electromagnetic Fields

RESULT:

Pass

Report No.	: CN241RMT 003
Test Specification	
Test item	: Bluetooth speaker
Identification / Type No.	: X3D MAX
Trademark	: BlueAnt
FCC ID:	VHFBLUEANTX3DM
IC:	7252A-X3DMAX
HVIN:	X3D MAX
Test standard	: CFR47 FCC Part 2: Section 2.1093 FCC KDB Publication 447498 v06 RSS-102 Issue 5 February 2021

Measurement Record:

The minimum distance for the EUT is less than 5mm.

For FCC:

Since maximum peak output power of the transmitter is 2.70 dBm $\approx$ 1.86 mW <

specified. $\frac{3 * d}{\sqrt{f}} = 9.52$ mW.

Hence the EUT is excluded from SAR evaluation according to FCC KDB Publication 447498 D01 General RF Exposure Guidance v06.

For IC:

The maximum e.i.r.p. of the transmitter is 3.70 dBm $\approx$ 2.34 mW, which is below the SAR exclusion threshold level 4 mW $\approx$ 6.02 dBm.

Hence the EUT is exempted from routine evaluation limits (SAR Evaluation) according to clause 2.5.1 of RSS-102 Issue 5.