

MPE Report

Applicant : Rajant Corporation

Product Name : Radio Module

Trade Name : VIZMONET

Model Number : RJ-1705

Applicable Standard : 47 CFR § 2.1091

Received Date : Jul. 27, 2021

Issue Date : May 06, 2022

Issued by

Approved By :



(Kris Pan)

A Test Lab Techno Corp.

No. 140-1, Changan Street, Bade District,

Taoyuan City 334025, Taiwan (R.O.C.)

Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330

Test Firm MRA designation number: TW0010

Note:

- 1.The test results are valid only for samples provided by customers and under the test conditions described in this report.
- 2.This report shall not be reproduced except in full, without the written approval of A Test Lab Technology Corporation.
- 3.The relevant information is provided by customers in this test report. According to the correctness, appropriateness or completeness of the information provided by the customer, if there is any doubt or error in the information which affects the validity of the test results, the laboratory does not take the responsibility.

Revision History

Rev.	Issued Date	Revisions	Revised By
00	May 06, 2022	Initial Issue	Nicole Chu

Contents

1.	General Information	4
2.	Description of Equipment under Test (EUT)	5
3.	Human Exposure Assessment	5
4.	Power Density Limit – RF Exposure Evaluation	7
5.	Conducted Power.....	8
6.	Test Result	9

1. General Information

1.1 Reference Applicable Standard

Standard	Description	Version
47 CFR Part §1.1310	Radiofrequency radiation exposure limits.	-
47 CFR Part §2.1091	Radiofrequency radiation exposure evaluation: mobile devices.	-
IEEE C95.1	American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300 KHz to 100 GHz, New York.	1992
KDB 447498 D04	RF exposure procedures and equipment authorization policies for mobile and portable devices	v01

2. Description of Equipment under Test (EUT)

Applicant	Rajant Corporation 200 Chesterfield Parkway, Malvern, Pennsylvania 19355-3258, United States
Product Name	Radio Module
Trade Name	VIZMONET
Model Number	RJ-1705
FCC ID	VJA-RJ1705
Frequency Range	WLAN 4.9 GHz Band : 4942.5 - 4978.5 MHz WLAN 5.2 GHz Band : 5180 - 5320 MHz WLAN 5.6 GHz Band : 5500 - 5720 MHz WLAN 5.8 GHz Band : 5745 - 5825 MHz
Supported Modulations	WLAN 4.9 GHz : 802.11a / n HT20
	WLAN 5 GHz : 802.11a / n HT20 / HT40

Note:

The above information of DUT was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Antenna Information				
Model	Type	Frequency	Max. Gain (dBi)	Directional
KMA-4800-6-NM	External type ((Omni-directional))	4.8~5.0 GHz	6	9.01
KMA-5250-7-NM	External type ((Omni-directional))	5150~5250 MHz	7	10.01
		5250~5350 MHz	7	10.01
KMA-5550-6-NM		5470~5725 MHz	6	9.01
KMA-5800-6-NM		5725~5900 MHz	6	9.01
Antenna Diversity	WLAN 4.9 GHz : 1TX (Diversity) / 2TX (MIMO) IEEE 802.11a : 1TX (Diversity) / 2TX (STBC) IEEE 802.11n 5 GHz 20 MHz : 1TX (Diversity) / 2TX (STBC) IEEE 802.11n 5 GHz 40 MHz : 1TX (Diversity) / 2TX (STBC)			

3. Human Exposure Assessment

Due to the design and installation of this product, it is not possible to conduct SAR evaluation. This is because client either manufactures or supplies the antenna(s) that will be used in the installation of this product. Therefore, this product will be evaluated as a mobile device per 47 CFR § 1.1310 titled "Radiofrequency radiation exposure limits", generally referred to as MPE limits.

In 47 CFR § 2.1091, paragraph (b) defines a mobile device as "a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 cm is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons." This product is intended to be installed into a vehicle such that the unit is physically secured at one location. In the installation guide supplied with the product,

Client has made the following statement: "IMPORTANT: To meet the FCC's RF Exposure Guidelines, the antenna should be installed so there is at least 20 cm of separation between the body of the user and nearby persons and the antenna". Based on the installation of the transceiver and the antenna, the transmitters radiating structure is more than 20 cm from the user. Thus, this product is a "mobile device" as defined in section § 2.1091 paragraph (b).

Exposure evaluation

$$S_{eirp} = \frac{EIRP}{4\pi d^2} = \frac{PG}{4\pi d^2} (W / m^2)$$

Where

S: is the input power (W);

G: is the antenna gain;

d : is the distance between antennas and evaluation point (m).

4. Power Density Limit – RF Exposure Evaluation

In 47 CFR § 1.1310, use of the device as based upon the user's awareness and ability to exercise control over human exposure. The two categories defined are Occupational / Controlled Exposure and General Population / Uncontrolled.

These two categories are defined as follow:

Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824 / f	2.19 / f	(180 / f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F / 1,500	30
1,500-100,000	-	-	1.0	30
Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1,842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1,500	-	-	F / 300	6
1,500-100,000	-	-	5	6

5. Maximum Tune-up Power

Operate Band	Frequency (MHz)	ANT 0	ANT 1	MIMO
4.9 GHz	4942.5 - 4987.5	24.5	24.5	27
5.2 GHz	5150 - 5250	19.5	19.5	22
5.3 GHz	5250 - 5350	20.5	20.5	20.5
5.6 GHz	5470 - 5725	21	21	21.5
5.8 GHz	5725 - 5850	24.5	24	26.5

6. Test Result

Band	Frequency (MHz)	Distance (cm) [R]	Tune-up Power (dBm) [P]	ANT Gain (dBi)	Numeric Gain [G]	Duty Cycle	Power with Duty cycle (mW) [P]x[G]	Power Density (mW/cm ²) [S]	Standalone Limit (mW/cm ²)	Antenna
4.9 GHz	4942.5 - 4987.5	26.0	24.50	9.01	7.96	1	2243.43	0.26	1.00	ANT 0
5.2 GHz	5150 - 5250	26.0	19.50	10.01	10.02	1	893.03	0.11	1.00	ANT 0
5.3 GHz	5250 - 5350	26.0	20.50	10.01	10.02	1	1124.26	0.13	1.00	ANT 0
5.6 GHz	5470 - 5725	26.0	21.00	9.01	7.96	1	1002.10	0.12	1.00	ANT 0
5.8 GHz	5725 - 5850	26.0	24.50	9.01	7.96	1	2243.43	0.26	1.00	ANT 0
4.9 GHz	4942.5 - 4987.5	26.0	24.50	9.01	7.96	1	2243.43	0.26	1.00	ANT 1
5.2 GHz	5150 - 5250	26.0	19.50	10.01	10.02	1	893.03	0.11	1.00	ANT 1
5.3 GHz	5250 - 5350	26.0	20.50	10.01	10.02	1	1124.26	0.13	1.00	ANT 1
5.6 GHz	5470 - 5725	26.0	21.00	9.01	7.96	1	1002.10	0.12	1.00	ANT 1
5.8 GHz	5725 - 5850	26.0	24.00	9.01	7.96	1	1999.46	0.24	1.00	ANT 1

Note:

1. The maximum power and gain were applied to evaluate MPE.
2. The Numeric Gain calculated by $10^{(\text{ant. Gain(dBi)} / 10)}$.

Simultaneous Transmission :

Total MPE: 0.52 mW/cm²

TER = 0.52 < 1

7. Conclusion

The result shows that this device is compliance with the exposure limits in 47 CFR §1.1310.

---END---