

## TEST REPORT

|           |                                                                        |
|-----------|------------------------------------------------------------------------|
| Applicant | Asian Express Holdings Limited                                         |
| Address   | RM1702, Sino Centre, 582-592 Nathan Road, Mongkok ,Kowloon, Hong Kong. |

|                                     |                                                                                                                                                 |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Manufacturer or Supplier            | Asian Express Holdings Limited                                                                                                                  |
| Address                             | RM1702, Sino Centre, 582-592 Nathan Road, Mongkok ,Kowloon, Hong Kong.                                                                          |
| Product                             | 720P camera                                                                                                                                     |
| Brand Name                          | PROPEL                                                                                                                                          |
| Model                               | PL-1540                                                                                                                                         |
| Additional Model & Model Difference | PL-1541, PL-1542, PL-1543, PL-1544, PL-1545, PL-1546, PL-1547, PL-1548, PL-1549, HS-2407, HS-2408, HS-2409, HS-2410, HS-2411, See item 3.1 note |
| Date of tests                       | Jul. 26, 2016 ~ Aug. 02, 2016                                                                                                                   |

The tests have been carried out according to the requirements of the following standard:

☒ **FCC Part 15, Subpart C, Section 15.247**

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

|                                                                                     |                                                                                      |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| Tested by Breeze Jiang<br>Project Engineer / EMC Department                         | Approved by Glyn He<br>Supervisor / EMC Department                                   |
|  |  |
|                                                                                     | Date: Aug. 06, 2016                                                                  |

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

## TABLE OF CONTENTS

|                                                              |           |
|--------------------------------------------------------------|-----------|
| <b>RELEASE CONTROL RECORD .....</b>                          | <b>4</b>  |
| <b>1 SUMMARY OF TEST RESULTS.....</b>                        | <b>5</b>  |
| <b>2 MEASUREMENT UNCERTAINTY .....</b>                       | <b>5</b>  |
| <b>3 GENERAL INFORMATION .....</b>                           | <b>6</b>  |
| 3.1 GENERAL DESCRIPTION OF EUT.....                          | 6         |
| 3.2 DESCRIPTION OF TEST MODES.....                           | 7         |
| 3.2.1 CONFIGURATION OF SYSTEM UNDER TEST .....               | 7         |
| 3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL..... | 7         |
| 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS.....            | 10        |
| 3.4 DESCRIPTION OF SUPPORT UNITS.....                        | 10        |
| <b>4 TEST TYPES AND RESULTS.....</b>                         | <b>11</b> |
| 4.1 RADIATED EMISSION MEASUREMENT .....                      | 11        |
| 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT .....          | 11        |
| 4.2.2 TEST INSTRUMENTS.....                                  | 12        |
| 4.2.3 TEST PROCEDURES .....                                  | 13        |
| 4.2.4 DEVIATION FROM TEST STANDARD .....                     | 13        |
| 4.2.5 TEST SETUP .....                                       | 14        |
| 4.2.6 EUT OPERATING CONDITIONS .....                         | 14        |
| 4.2.7 TEST RESULTS .....                                     | 15        |
| 4.2 6dB BANDWIDTH MEASUREMENT .....                          | 20        |
| 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT .....              | 20        |
| 4.3.2 TEST INSTRUMENTS.....                                  | 20        |
| 4.3.3 TEST PROCEDURE.....                                    | 20        |
| 4.3.4 DEVIATION FROM TEST STANDARD .....                     | 20        |
| 4.3.5 TEST SETUP .....                                       | 21        |
| 4.3.6 EUT OPERATING CONDITIONS .....                         | 21        |
| 4.3.7 TEST RESULTS .....                                     | 22        |
| 4.4 CONDUCTED OUTPUT POWER.....                              | 25        |
| 4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT .....     | 25        |
| 4.4.2 TEST SETUP .....                                       | 25        |
| 4.4.3 TEST INSTRUMENTS.....                                  | 25        |
| 4.4.4 TEST PROCEDURES .....                                  | 26        |
| 4.4.5 DEVIATION FROM TEST STANDARD .....                     | 26        |



|         |                                                                                                     |           |
|---------|-----------------------------------------------------------------------------------------------------|-----------|
| 4.4.6   | EUT OPERATING CONDITIONS .....                                                                      | 26        |
| 4.4.7   | TEST RESULTS .....                                                                                  | 27        |
| 4.4.7.1 | MAXIMUM PEAK OUTPUT POWER .....                                                                     | 27        |
| 4.4.7.2 | AVERAGE OUTPUT POWER (FOR REFERENCE) .....                                                          | 28        |
| 4.5     | POWER SPECTRAL DENSITY MEASUREMENT .....                                                            | 29        |
| 4.5.1   | LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....                                                  | 29        |
| 4.5.2   | TEST SETUP .....                                                                                    | 29        |
| 4.5.3   | TEST INSTRUMENTS.....                                                                               | 29        |
| 4.5.4   | TEST PROCEDURE.....                                                                                 | 29        |
| 4.5.5   | DEVIATION FROM TEST STANDARD .....                                                                  | 29        |
| 4.5.6   | EUT OPERATING CONDITION .....                                                                       | 30        |
| 4.5.7   | TEST RESULTS .....                                                                                  | 30        |
| 4.6     | OUT OF BAND EMISSION MEASUREMENT .....                                                              | 33        |
| 4.6.1   | LIMITS OF OUT OF BAND EMISSION MEASUREMENT .....                                                    | 33        |
| 4.6.2   | TEST SETUP.....                                                                                     | 33        |
| 4.6.3   | TEST INSTRUMENTS.....                                                                               | 33        |
| 4.6.4   | TEST PROCEDURE.....                                                                                 | 33        |
| 4.6.5   | DEVIATION FROM TEST STANDARD .....                                                                  | 34        |
| 4.6.6   | EUT OPERATING CONDITION .....                                                                       | 34        |
| 4.6.7   | TEST RESULTS .....                                                                                  | 35        |
| 5       | <b>PHOTOGRAPHS OF THE TEST CONFIGURATION .....</b>                                                  | <b>37</b> |
| 6       | <b>APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT<br/>BY THE LAB .....</b> | <b>38</b> |



Test Report No.: RF160722N064-1

## RELEASE CONTROL RECORD

| ISSUE NO.      | REASON FOR CHANGE | DATE ISSUED   |
|----------------|-------------------|---------------|
| RF160722N064-1 | Original release  | Aug. 06, 2016 |

## 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247) |                             |        |                                  |
|-----------------------------------------------------------|-----------------------------|--------|----------------------------------|
| STANDARD SECTION                                          | TEST TYPE AND LIMIT         | RESULT | REMARK                           |
| 15.207                                                    | AC Power Conducted Emission | N/A    | Powered from Battery             |
| 15.247(d)<br>15.209                                       | Radiated Emissions          | PASS   | Meet the requirement of limit.   |
| 15.247(d)                                                 | Band Edge Measurement       | PASS   | Meet the requirement of limit.   |
| 15.247(a)(2)                                              | 6dB bandwidth               | PASS   | Meet the requirement of limit.   |
| 15.247(b)                                                 | Conducted Output power      | PASS   | Meet the requirement of limit.   |
| 15.247(e)                                                 | Power Spectral Density      | PASS   | Meet the requirement of limit.   |
| 15.203                                                    | Antenna Requirement         | PASS   | Unique antenna connector is used |

## 2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| MEASUREMENT        | FREQUENCY     | UNCERTAINTY |
|--------------------|---------------|-------------|
| Radiated emissions | 9KHz ~ 30MHz  | 2.90dB      |
|                    | 30MHz ~ 1GMHz | 3.83dB      |
|                    | 1GHz ~ 18GHz  | 4.93dB      |
|                    | 18GHz ~ 40GHz | 4.80dB      |

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .



### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

|                              |                                                                                                                                    |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| <b>PRODUCT</b>               | 720P camera                                                                                                                        |
| <b>MODEL NO.</b>             | PL-1540                                                                                                                            |
| <b>ADDITIONAL MODELS</b>     | PL-1541, PL-1542, PL-1543, PL-1544, PL-1545,<br>PL-1546, PL-1547, PL-1548, PL-1549, HS-2407,<br>HS-2408, HS-2409, HS-2410, HS-2411 |
| <b>FCC ID</b>                | VLEPL1540R                                                                                                                         |
| <b>NOMINAL VOLTAGE</b>       | DC7.4V from Li-ion Battery with Host Unit                                                                                          |
| <b>MODULATION TYPE</b>       | CCK, DQPSK, DBPSK for DSSS<br>64QAM, 16QAM, QPSK, BPSK for OFDM                                                                    |
| <b>MODULATION TECHNOLOGY</b> | DSSS, OFDM                                                                                                                         |
| <b>OPERATING FREQUENCY</b>   | 2417MHz for 802.11b/g/n(HT20)                                                                                                      |
| <b>PEAK POWER</b>            | WLAN: 16.64dBm (Maximum)                                                                                                           |
| <b>ANTENNA TYPE</b>          | Wire Antenna, 2.5dBi Gain                                                                                                          |
| <b>I/O PORTS</b>             | Refer to user's manual                                                                                                             |
| <b>CABLE SUPPLIED</b>        | N/A                                                                                                                                |

**NOTE:**

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions, but only the worst case was shown in test report.
3. Please refer to the EUT photo document (Reference No.: 160722N064-1) for detailed product photo.
4. Additional models are identical with the test model PL-1540 except the model no. for trading purpose.
5. The EUT provides completed transmitters and receivers.

| <b>MODULATION MODE</b> | <b>TX FUNCTION</b> |
|------------------------|--------------------|
| <b>802.11b</b>         | 1TX/1RX            |
| <b>802.11g</b>         | 1TX/1RX            |
| <b>802.11n(20MHz)</b>  | 1TX/1RX            |

### 3.2 DESCRIPTION OF TEST MODES

1 channels are provided for 802.11b, 802.11g and 802.11n(HT20):

| CHANNEL | FREQUENCY |
|---------|-----------|
| 2       | 2417 MHz  |

#### 3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

#### 3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on X axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

| EUT<br>CONFIGURE<br>MODE | APPLICABLE TO |       |     |      | MODE                                        |
|--------------------------|---------------|-------|-----|------|---------------------------------------------|
|                          | RE<1G         | RE≥1G | PLC | APCM |                                             |
| A                        | √             | √     | -   | √    | Powered by fully battery with WIFI function |

Where **RE<1G**: Radiated Emission below 1GHz **RE≥1G**: Radiated Emission above 1GHz  
**PLC**: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

#### RADIATED EMISSION TEST (BELOW 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT<br>CONFIGURE<br>MODE | MODE    | AVAILABLE<br>CHANNEL | TESTED<br>CHANNEL | MODULATION<br>TECHNOLOGY | MODULATION<br>TYPE | DATA<br>RATE<br>(Mbps) | AXIS |
|--------------------------|---------|----------------------|-------------------|--------------------------|--------------------|------------------------|------|
| A                        | 802.11g | 2                    | 2                 | OFDM                     | BPSK               | 6.0                    | X    |

**RADIATED EMISSION TEST (ABOVE 1GHz):**

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT<br>CONFIGURE<br>MODE | MODE         | AVAILABLE<br>CHANNEL | TESTED<br>CHANNEL | MODULATION<br>TECHNOLOGY | MODULATION<br>TYPE | DATA<br>RATE<br>(Mbps) | AXIS |
|--------------------------|--------------|----------------------|-------------------|--------------------------|--------------------|------------------------|------|
| A                        | 802.11b      | 2                    | 2                 | CCK                      | DBPSK              | 1.0                    | X    |
| A                        | 802.11g      | 2                    | 2                 | OFDM                     | BPSK               | 6.0                    | X    |
| A                        | 802.11n HT20 | 2                    | 2                 | OFDM                     | BPSK               | 6.5                    | X    |

**BANDEDGE MEASUREMENT:**

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT<br>CONFIGURE<br>MODE | MODE         | AVAILABLE<br>CHANNEL | TESTED<br>CHANNEL | MODULATION<br>TECHNOLOGY | MODULATION<br>TYPE | DATA RATE<br>(Mbps) |
|--------------------------|--------------|----------------------|-------------------|--------------------------|--------------------|---------------------|
| B                        | 802.11b      | 2                    | 2                 | CCK                      | DBPSK              | 1.0                 |
| B                        | 802.11g      | 2                    | 2                 | OFDM                     | BPSK               | 6.0                 |
| B                        | 802.11n HT20 | 2                    | 2                 | OFDM                     | BPSK               | 6.5                 |

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT<br>CONFIGURE<br>MODE | MODE         | AVAILABLE<br>CHANNEL | TESTED<br>CHANNEL | MODULATION<br>TECHNOLOGY | MODULATION<br>TYPE | DATA RATE<br>(Mbps) |
|--------------------------|--------------|----------------------|-------------------|--------------------------|--------------------|---------------------|
| B                        | 802.11b      | 2                    | 2                 | CCK                      | DBPSK              | 1.0                 |
| B                        | 802.11g      | 2                    | 2                 | OFDM                     | BPSK               | 6.0                 |
| B                        | 802.11n HT20 | 2                    | 2                 | OFDM                     | BPSK               | 6.5                 |

**TEST CONDITION:**

| APPLICABLE<br>TO | ENVIRONMENTAL CONDITIONS | TEST VOLTAGE         | TESTED BY    |
|------------------|--------------------------|----------------------|--------------|
| RE<1G            | 26deg. C, 50%RH          | DC 7.4V From Battery | Breeze Jiang |
| RE≥1G            | 26deg. C, 50%RH          | DC 7.4V From Battery | Breeze Jiang |
| PLC              | ---                      | ---                  | ---          |
| APCM             | 25deg. C, 55%RH          | DC 7.4V From Battery | Breeze Jiang |

### 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C, Section 15.247**

**558074 D01 DTS Meas Guidance v03r05**

**ANSI C63.10-2013**

All test items have been performed and recorded as per the above standards.

**NOTE:** It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B(VoC). The test report has been issued separately.

### 3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| NO. | PRODUCT | BRAND  | MODEL NO. | SERIAL NO. | FCC ID |
|-----|---------|--------|-----------|------------|--------|
| 1   | Plane   | PROPEL | PL-1540   | N/A        | N/A    |

| NO. | SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS |
|-----|-----------------------------------------------------|
| 1   | N/A                                                 |

## 4 TEST TYPES AND RESULTS

### 4.1 RADIATED EMISSION MEASUREMENT

#### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

| FREQUENCIES<br>(MHz) | FIELD STRENGTH<br>(microvolts/meter) | MEASUREMENT DISTANCE<br>(meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009 ~ 0.490        | 2400/F(kHz)                          | 300                              |
| 0.490 ~ 1.705        | 24000/F(kHz)                         | 30                               |
| 1.705 ~ 30.0         | 30                                   | 30                               |
| 30 ~ 88              | 100                                  | 3                                |
| 88 ~ 216             | 150                                  | 3                                |
| 216 ~ 960            | 200                                  | 3                                |
| Above 960            | 500                                  | 3                                |

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



#### 4.2.2 TEST INSTRUMENTS

| Equipment                    | Manufacturer  | Model No.                | Serial No.  | Last Cal.   | Next Cal.   |
|------------------------------|---------------|--------------------------|-------------|-------------|-------------|
| EMI Test Receiver            | Rohde&Schwarz | ESR7                     | 101494      | Apr. 05,16  | Apr. 04,17  |
| Signal and Spectrum Analyzer | Rohde&Schwarz | FSV7                     | 102331      | Nov. 09,15  | Nov. 08,16  |
| Bilog Antenna                | Teseq         | CBL 6111D                | 30643       | Jul. 16, 16 | Jul. 15, 17 |
| Horn Antenna (1GHz -18GHz)   | ETS -Lindgren | 3117                     | 00062558    | May 18,16   | May 17,17   |
| GPS Generator+ Antenna       | TOJOIN        | GNSS-5000A               | E1-010119   | Aug. 08, 15 | Aug. 07, 17 |
| 3m Semi-anechoic Chamber     | ETS-LINDGREN  | 9m*6m*6m                 | NSEMC003    | Mar. 12,16  | Mar. 11,18  |
| Test Software                | ADT           | ADT_Radiated_V7.6.15.9.2 | N/A         | N/A         | N/A         |
| Horn Antenna                 | SCHWARZBECK   | BBHA 9170                | BBHA9170242 | Mar. 12,16  | Mar. 11,17  |
| Amplifier (9kHz-1GHz)        | SONOMA        | 310D                     | 186955      | Mar. 04,16  | Mar. 03, 17 |
| Pre-Amplifier(1-18G)         | HP            | 8449B                    | 3008A00409  | Apr. 25,16  | Apr. 24,17  |
| Pre-Amplifier (18GHz-40GHz)  | EMCI          | EMC 184045               | 980102      | Nov. 20,15  | Nov. 19,16  |
| Test Software                | ADT           | ADT_Radiated_V7.6.15.9.2 | N/A         | N/A         | N/A         |
| BLUETOOTH TESTER             | Rohde&Schwarz | CBT32                    | 100811      | Sep. 01,15  | Aug. 31,16  |

**NOTE:**

1. The test was performed in 966 Chamber.
2. The calibration interval of the above test instruments are 12, 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 494399.

#### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

**NOTE:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. For WiFi, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle < 98%) or 10Hz (Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The testing of the EUT was performed on all 3 orthogonal axes; the worst-case test configuration was reported on the file Test Setup Photo.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation.



#### 4.2.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



## 4.2.7 TEST RESULTS

## BELOW 1GHz WORST-CASE DATA:


802.11g

|                 |              |                      |                 |
|-----------------|--------------|----------------------|-----------------|
| CHANNEL         | Channel 2    | DETECTOR<br>FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 30MHz ~ 1GHz |                      |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                           |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|---------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 96.07          | 18.6 QP                       | 43.5              | -24.9          | 2.00 H                    | 0                          | 38.04                  | -19.40                         |
| 2                                                   | 191.67         | 20.6 QP                       | 43.5              | -22.9          | 2.00 H                    | 0                          | 40.66                  | -20.04                         |
| 3                                                   | 239.46         | 22.5 QP                       | 46.0              | -23.5          | 2.00 H                    | 0                          | 39.73                  | -17.24                         |
| 4                                                   | 287.26         | 34.4 QP                       | 46.0              | -11.6          | 2.00 H                    | 0                          | 49.14                  | -14.71                         |
| 5                                                   | 382.86         | 30.2 QP                       | 46.0              | -15.8          | 2.00 H                    | 0                          | 41.36                  | -11.15                         |
| 6                                                   | 671.04         | 28.7 QP                       | 46.0              | -17.3          | 2.00 H                    | 0                          | 32.04                  | -3.36                          |

## REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.




|                        |              |                              |                 |
|------------------------|--------------|------------------------------|-----------------|
| <b>CHANNEL</b>         | Channel 2    | <b>DETECTOR<br/>FUNCTION</b> | Quasi-Peak (QP) |
| <b>FREQUENCY RANGE</b> | 30MHz ~ 1GHz |                              |                 |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                |                               |                   |                |                           |                            |                        |                                |
|---------------------------------------------------|----------------|-------------------------------|-------------------|----------------|---------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                               | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                 | 94.67          | 23.8 QP                       | 43.5              | -19.7          | 1.00 V                    | 0                          | 43.25                  | -19.49                         |
| 2                                                 | 143.87         | 22.7 QP                       | 43.5              | -20.8          | 1.00 V                    | 0                          | 40.45                  | -17.71                         |
| 3                                                 | 191.67         | 25.8 QP                       | 43.5              | -17.7          | 1.00 V                    | 0                          | 45.81                  | -20.04                         |
| 4                                                 | 239.46         | 26.0 QP                       | 46.0              | -20.0          | 1.00 V                    | 0                          | 43.22                  | -17.24                         |
| 5                                                 | 287.26         | 32.9 QP                       | 46.0              | -13.1          | 1.00 V                    | 0                          | 47.59                  | -14.71                         |
| 6                                                 | 382.86         | 23.5 QP                       | 46.0              | -22.6          | 1.00 V                    | 0                          | 34.60                  | -11.15                         |

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



**ABOVE 1GHz DATA**

**802.11b**

|                        |              |                              |              |
|------------------------|--------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 2 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 52.23 PK                      | 74.0              | -21.77         | 1.68 H                   | 291                        | 49.70                  | 2.53                           |
| 2                                                   | 2390.00        | 38.02 AV                      | 54.0              | -15.98         | 1.68 H                   | 291                        | 35.49                  | 2.53                           |
| 3                                                   | *2417.00       | 74.30 PK                      |                   |                | 1.68 H                   | 291                        | 71.71                  | 2.59                           |
| 4                                                   | *2417.00       | 55.02 AV                      |                   |                | 1.68 H                   | 291                        | 52.43                  | 2.59                           |
| 5                                                   | 4834.00        | 57.09 PK                      | 74.0              | -16.91         | 1.28 H                   | 302                        | 49.30                  | 7.79                           |
| 6                                                   | 4834.00        | 41.95 AV                      | 54.0              | -12.05         | 1.28 H                   | 302                        | 34.16                  | 7.79                           |
| 7                                                   | 7251.00        | 58.40 PK                      | 74.0              | -15.60         | 1.12 H                   | 278                        | 44.92                  | 13.48                          |
| 8                                                   | 7251.00        | 46.25 AV                      | 54.0              | -7.75          | 1.12 H                   | 278                        | 32.77                  | 13.48                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 50.26 PK                      | 74.0              | -23.74         | 1.56 V                   | 230                        | 47.73                  | 2.53                           |
| 2                                                   | 2390.00        | 37.08 AV                      | 54.0              | -16.92         | 1.56 V                   | 230                        | 34.55                  | 2.53                           |
| 3                                                   | *2417.00       | 72.97 PK                      |                   |                | 1.56 V                   | 230                        | 70.38                  | 2.59                           |
| 4                                                   | *2417.00       | 54.31 AV                      |                   |                | 1.56 V                   | 230                        | 51.72                  | 2.59                           |
| 5                                                   | 4834.00        | 54.15 PK                      | 74.0              | -19.85         | 1.63 V                   | 238                        | 46.36                  | 7.79                           |
| 6                                                   | 4834.00        | 42.32 AV                      | 54.0              | -11.68         | 1.63 V                   | 238                        | 34.53                  | 7.79                           |
| 7                                                   | 7251.00        | 58.73 PK                      | 74.0              | -15.27         | 1.68 V                   | 152                        | 45.25                  | 13.48                          |
| 8                                                   | 7251.00        | 46.48 AV                      | 54.0              | -7.52          | 1.68 V                   | 152                        | 33.00                  | 13.48                          |

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.

802.11g

|                        |              |                              |              |
|------------------------|--------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 2 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 49.97 PK                      | 74.0              | -24.03         | 1.96 H                   | 295                        | 47.44                  | 2.53                           |
| 2                                                   | 2390.00        | 36.81 AV                      | 54.0              | -17.19         | 1.96 H                   | 295                        | 34.28                  | 2.53                           |
| 3                                                   | *2417.00       | 74.14 PK                      |                   |                | 1.96 H                   | 295                        | 71.55                  | 2.59                           |
| 4                                                   | *2417.00       | 45.22 AV                      |                   |                | 1.96 H                   | 295                        | 42.63                  | 2.59                           |
| 5                                                   | 4834.00        | 56.25 PK                      | 74.0              | -17.75         | 1.85 H                   | 102                        | 48.46                  | 7.79                           |
| 6                                                   | 4834.00        | 39.19 AV                      | 54.0              | -14.81         | 1.85 H                   | 102                        | 31.40                  | 7.79                           |
| 7                                                   | 7251.00        | 58.76 PK                      | 74.0              | -15.24         | 1.00 H                   | 201                        | 45.28                  | 13.48                          |
| 8                                                   | 7251.00        | 44.16 AV                      | 54.0              | -9.84          | 1.00 H                   | 201                        | 30.68                  | 13.48                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 50.53 PK                      | 74.0              | -23.47         | 1.54 V                   | 230                        | 48.00                  | 2.53                           |
| 2                                                   | 2390.00        | 40.06 AV                      | 54.0              | -13.94         | 1.54 V                   | 230                        | 37.53                  | 2.53                           |
| 3                                                   | *2417.00       | 74.22 PK                      |                   |                | 1.69 V                   | 253                        | 71.63                  | 2.59                           |
| 4                                                   | *2417.00       | 44.91 AV                      |                   |                | 1.69 V                   | 253                        | 42.32                  | 2.59                           |
| 5                                                   | 4834.00        | 56.15 PK                      | 74.0              | -17.85         | 1.59 V                   | 84                         | 48.36                  | 7.79                           |
| 6                                                   | 4834.00        | 41.82 AV                      | 54.0              | -12.18         | 1.59 V                   | 84                         | 34.03                  | 7.79                           |
| 7                                                   | 7251.00        | 59.03 PK                      | 74.0              | -14.97         | 1.48 V                   | 295                        | 45.55                  | 13.48                          |
| 8                                                   | 7251.00        | 44.45 AV                      | 54.0              | -9.55          | 1.48 V                   | 295                        | 30.97                  | 13.48                          |

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.

802.11n (20MHz)

|                        |              |                              |              |
|------------------------|--------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 2 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 50.71 PK                      | 74.0              | -23.29         | 1.85 H                   | 203                        | 48.18                  | 2.53                           |
| 2                                                   | 2390.00        | 38.47 AV                      | 54.0              | -15.53         | 1.85 H                   | 203                        | 35.94                  | 2.53                           |
| 3                                                   | *2417.00       | 72.75 PK                      |                   |                | 1.85 H                   | 261                        | 70.16                  | 2.59                           |
| 4                                                   | *2417.00       | 40.42 AV                      |                   |                | 1.85 H                   | 261                        | 37.83                  | 2.59                           |
| 5                                                   | 4834.00        | 55.42 PK                      | 74.0              | -18.58         | 1.34 H                   | 306                        | 47.63                  | 7.79                           |
| 6                                                   | 4834.00        | 41.06 AV                      | 54.0              | -12.94         | 1.34 H                   | 306                        | 33.27                  | 7.79                           |
| 7                                                   | 7251.00        | 58.72 PK                      | 74.0              | -15.28         | 1.56 H                   | 321                        | 45.24                  | 13.48                          |
| 8                                                   | 7251.00        | 45.84 AV                      | 54.0              | -8.16          | 1.56 H                   | 321                        | 32.36                  | 13.48                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 50.03 PK                      | 74.0              | -23.97         | 1.85 V                   | 142                        | 47.50                  | 2.53                           |
| 2                                                   | 2390.00        | 36.89 AV                      | 54.0              | -17.11         | 1.85 V                   | 142                        | 34.36                  | 2.53                           |
| 3                                                   | *2417.00       | 74.81 PK                      |                   |                | 1.85 V                   | 142                        | 72.22                  | 2.59                           |
| 4                                                   | *2417.00       | 41.10 AV                      |                   |                | 1.85 V                   | 142                        | 38.51                  | 2.59                           |
| 5                                                   | 4834.00        | 53.88 PK                      | 74.0              | -20.12         | 1.96 V                   | 295                        | 46.09                  | 7.79                           |
| 6                                                   | 4834.00        | 41.09 AV                      | 54.0              | -12.91         | 1.96 V                   | 295                        | 33.30                  | 7.79                           |
| 7                                                   | 7251.00        | 58.53 PK                      | 74.0              | -15.47         | 1.14 V                   | 102                        | 45.05                  | 13.48                          |
| 8                                                   | 7251.00        | 44.50 AV                      | 54.0              | -9.50          | 1.14 V                   | 102                        | 31.02                  | 13.48                          |

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.

## 4.2 6dB BANDWIDTH MEASUREMENT

### 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

### 4.3.2 TEST INSTRUMENTS

| Equipment                        | Manufacturer    | Model No. | Serial No. | Last Cal.   | Next Cal.   |
|----------------------------------|-----------------|-----------|------------|-------------|-------------|
| Power Sensor                     | Keysight        | U2021XA   | MY55060016 | May 04,16   | May 03,17   |
| Power Sensor                     | Keysight        | U2021XA   | MY55060018 | May 04,16   | May 03,17   |
| Digital Multimeter               | FLUKE           | 15B       | A1220010DG | Oct. 12, 15 | Oct.11, 16  |
| Humid & Temp Programmable Tester | Haida           | HD-2257   | 110807201  | Sep.07,15   | Sep. 06,16  |
| Oscilloscope                     | Agilent         | DSO9254A  | MY51260160 | Nov. 28,15  | Nov. 27,16  |
| Signal Analyzer                  | Rohde & Schwarz | FSV7      | 102331     | Nov. 09,15  | Nov. 08,16  |
| Signal Generator                 | Agilent         | N5183A    | MY50140980 | Nov. 09,15  | Nov. 08,16  |
| ESG Vector Signal Generator      | Agilent         | E4438C    | MY49072505 | Apr. 22, 16 | Apr. 21, 17 |
| BLUETOOTH TESTER                 | Rohde&Schwarz   | CBT32     | 100811     | Sep. 01,15  | Aug. 31,16  |

#### NOTE:

1. The test was performed in RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRG/CHINA and NIM/CHINA.

### 4.3.3 TEST PROCEDURE


1. Set resolution bandwidth (RBW) = 100KHz
2. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

### 4.3.4 DEVIATION FROM TEST STANDARD

No deviation.



#### 4.3.5 TEST SETUP




#### 4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.3.7 TEST RESULTS


##### 802.11b

| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | 6dB<br>BANDWIDTH<br>(MHz) | MINIMUM LIMIT<br>(MHz) | PASS / FAIL |
|---------|-------------------------------|---------------------------|------------------------|-------------|
| 2       | 2417                          | 10.06                     | 0.5                    | PASS        |




802.11g

| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | 6dB<br>BANDWIDTH<br>(MHz) | MINIMUM LIMIT<br>(MHz) | PASS / FAIL |
|---------|-------------------------------|---------------------------|------------------------|-------------|
| 2       | 2417                          | 16.49                     | 0.5                    | PASS        |



802.11n (20MHz)

| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | 6dB<br>BANDWIDTH<br>(MHz) | MINIMUM LIMIT<br>(MHz) | PASS / FAIL |
|---------|-------------------------------|---------------------------|------------------------|-------------|
| 2       | 2417                          | 17.68                     | 0.5                    | PASS        |




#### 4.4 CONDUCTED OUTPUT POWER

##### 4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm).

##### 4.4.2 TEST SETUP



##### 4.4.3 TEST INSTRUMENTS

| Equipment                        | Manufacturer    | Model No. | Serial No. | Last Cal.   | Next Cal.   |
|----------------------------------|-----------------|-----------|------------|-------------|-------------|
| Power Sensor                     | Keysight        | U2021XA   | MY55060016 | May 04,16   | May 03,17   |
| Power Sensor                     | Keysight        | U2021XA   | MY55060018 | May 04,16   | May 03,17   |
| Digital Multimeter               | FLUKE           | 15B       | A1220010DG | Oct. 12, 15 | Oct.11, 16  |
| Humid & Temp Programmable Tester | Haida           | HD-2257   | 110807201  | Sep.07,15   | Sep. 06,16  |
| Oscilloscope                     | Agilent         | DSO9254A  | MY51260160 | Nov. 28,15  | Nov. 27,16  |
| Signal Analyzer                  | Rohde & Schwarz | FSV7      | 102331     | Nov. 09,15  | Nov. 08,16  |
| Signal Generator                 | Agilent         | N5183A    | MY50140980 | Nov. 09,15  | Nov. 08,16  |
| ESG Vector Signal Generator      | Agilent         | E4438C    | MY49072505 | Apr. 22, 16 | Apr. 21, 17 |
| BLUETOOTH TESTER                 | Rohde&Schwarz   | CBT32     | 100811     | Sep. 01,15  | Aug. 31,16  |

**NOTE:**

1. The test was performed in RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



#### 4.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A peak power meter was used to read the response of the peak power sensor. Record the peak power level.

#### 4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



#### 4.4.7 TEST RESULTS

##### 4.4.7.1 MAXIMUM PEAK OUTPUT POWER

###### 802.11b

| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | PEAK<br>POWER<br>(dBm) | PEAK<br>POWER<br>(mW) | PEAK<br>POWER LIMIT<br>(W) | PASS/FAIL |
|---------|-------------------------------|------------------------|-----------------------|----------------------------|-----------|
| 2       | 2417                          | 16.64                  | 46.132                | 1                          | PASS      |

###### 802.11g

| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | PEAK<br>POWER<br>(dBm) | PEAK<br>POWER<br>(mW) | PEAK<br>POWER LIMIT<br>(W) | PASS/FAIL |
|---------|-------------------------------|------------------------|-----------------------|----------------------------|-----------|
| 2       | 2417                          | 15.81                  | 38.107                | 1                          | PASS      |

###### 802.11n (20MHz)

| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | PEAK<br>POWER<br>(dBm) | PEAK<br>POWER<br>(mW) | PEAK<br>POWER LIMIT<br>(W) | PASS/FAIL |
|---------|-------------------------------|------------------------|-----------------------|----------------------------|-----------|
| 2       | 2417                          | 16.07                  | 40.458                | 1                          | PASS      |

#### 4.4.7.2 AVERAGE OUTPUT POWER (FOR REFERENCE)

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

##### 802.11b

| CHANNEL | CHANNEL<br>FREQUENCY (MHz) | AVERAGE<br>POWER (dBm) | AVG. POWER<br>(mW) |
|---------|----------------------------|------------------------|--------------------|
| 2       | 2417                       | 9.11                   | 8.147              |

##### 802.11g

| CHANNEL | CHANNEL<br>FREQUENCY (MHz) | AVERAGE<br>POWER (dBm) | AVG. POWER<br>(mW) |
|---------|----------------------------|------------------------|--------------------|
| 2       | 2417                       | 8.51                   | 7.096              |

##### 802.11n (20MHz)


| CHANNEL | CHANNEL<br>FREQUENCY (MHz) | AVERAGE<br>POWER (dBm) | AVG. POWER<br>(mW) |
|---------|----------------------------|------------------------|--------------------|
| 2       | 2417                       | 8.16                   | 6.546              |

## 4.5 POWER SPECTRAL DENSITY MEASUREMENT

### 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

### 4.5.2 TEST SETUP



### 4.5.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

### 4.5.4 TEST PROCEDURE

- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to: 3 kHz
- Set VBW  $\geq 3 \times$  RBW.
- Detector = peak.
- Sweep time = auto couple.
- Use the peak marker function to determine the maximum amplitude level.

### 4.5.5 DEVIATION FROM TEST STANDARD

No deviation.


#### 4.5.6 EUT OPERATING CONDITION

Same as item 4.3.6

#### 4.5.7 TEST RESULTS


802.11b

| Channel | FREQ.<br>(MHz) | PSD<br>(dBm/3kHz) | Limit<br>(dBm/3kHz) | PASS<br>/FAIL |
|---------|----------------|-------------------|---------------------|---------------|
| 2       | 2417           | -14.58            | 8                   | PASS          |




802.11g

| Channel | FREQ.<br>(MHz) | PSD<br>(dBm/3kHz) | Limit<br>(dBm/3kHz) | PASS<br>/FAIL |
|---------|----------------|-------------------|---------------------|---------------|
| 2       | 2417           | -17.46            | 8                   | PASS          |



802.11n (20MHz)

| Channel | FREQ.<br>(MHz) | PSD<br>(dBm/3kHz) | Limit<br>(dBm/3kHz) | PASS<br>/FAIL |
|---------|----------------|-------------------|---------------------|---------------|
| 2       | 2417           | -18.96            | 8                   | PASS          |




## 4.6 OUT OF BAND EMISSION MEASUREMENT

### 4.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.6.2 TEST SETUP



### 4.6.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

### 4.6.4 TEST PROCEDURE

#### Measurement Procedure - Reference Level

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



### Measurement Procedure –Unwanted Emission Level

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

#### 4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.6.6 EUT OPERATING CONDITION


Same as item 4.3.6



BUREAU  
VERITAS

Test Report No.: RF160722N064-1

## 4.6.7 TEST RESULTS







BUREAU  
VERITAS

Test Report No.: RF160722N064-1


### 802.11b CH 2 Band edge



### 802.11g CH 2 Band edge



### 802.11n (20MHz) CH 2 Band edge





Test Report No.: RF160722N064-1

## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.: RF160722N064-1

## **6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No any modifications are made to the EUT by the lab during the test.

**---END---**