

FCC/IC - TEST REPORT

Report Number : **68.950.16.547.02** Date of Issue: **May 22, 2017**

Model : **MBP49PU, MBP50PU**

Product Type : **Digital Video Baby monitor**

Applicant : **Binatone Electronics International Limited**

Address : **Floor 23A, 9 Des Voeux Road West, Sheung Wan, Hong Kong**

Manufacturer : **Binatone Electronics International Limited**

Address : **Floor 23A, 9 Des Voeux Road West, Sheung Wan, Hong Kong**

Test Result : ☒ **Positive** ☐ **Negative**

Total pages including
Appendices : **36**

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval

1 Table of Contents

1	Table of Contents	2
2	Details about the Test Laboratory.....	3
3	Description of the Equipment Under Test	4
4	Summary of Test Standards	5
5	Summary of Test Results.....	6
6	General Remarks	7
7	Test Setups	8
8	Systems test configuration	9
9	Technical Requirement	10
9.1	Conducted Emission.....	10
9.2	Conducted peak output power	13
9.3	20 dB bandwidth and 99% bandwidth	15
9.4	Carrier Frequency Separation	18
9.5	Number of hopping frequencies	20
9.6	Dwell Time	22
9.7	Spurious RF conducted emissions.....	24
9.8	Band edge testing.....	28
9.9	Spurious radiated emissions for transmitter	31
10	Test Equipment List	35
11	System Measurement Uncertainty.....	36



2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12&13, Zhiheng Wisdomland Business Park,
Nantou Checkpoint Road 2, Nanshan District,
Shenzhen City, 518052,
P. R. China

FCC Registration No.: 502708

IC Registration No: 10320A-1

Telephone: 86 755 8828 6998

Fax: 86 755 8828 5299

3 Description of the Equipment Under Test

Product: Digital Video Baby monitor

Model no.: MBP49PU, MBP50PU

Brand Name: motorola

FCC ID: VLJ-MBP50PU

IC ID: 4522A-MBP50PU

Options and accessories: NIL

Rating: DC 3.7V 2000mAh Li-ion Battery or 5VDC, 1A Powered by external power supply
Adapter Model: S006AKU0500100
Adaptor Input: 100-240VAC, 50/60Hz; 200mA
Adaptor Output: 5.0VDC, 1000mA

RF Transmission Frequency: 2402-2479MHz

No. of Operated Channel: 23

Modulation: GFSK

Antenna Type: Integral Antenna

Antenna Gain: 1.0dBi

Description of the EUT: The Equipment Under Test (EUT) is a baby monitor operated at 2.4GHz

Channel List:

CH1=2402MHz	CH2=2404MHz	CH3=2406MHz
CH4=2408MHz	CH5=2410MHz	CH6=2415MHz
CH7=2420MHz	CH8=2425MHz	CH9=2430MHz
CH10=2435MHz	CH11=2440MHz	CH12=2445MHz
CH13=2450MHz	CH14=2455MHz	CH15=2460MHz
CH16=2465MHz	CH17=2467MHz	CH18=2469MHz
CH19=2471MHz	CH20=2473MHz	CH21=2475MHz
CH22=2477MHz	CH23=2479MHz	

Remark: The product will only use 22 Channels (from Channel 1 to Channel 22) under normal operating condition. The last one Channel (Channel 23) is only used in matching mode.

4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2016 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators
RSS-Gen Issue 4 November 2014	General Requirements for the Certification of Radio Apparatus
RSS-247 Issue 2 May 2017	RSS-247 —Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

All the test methods were according to Public Notice DA 00-705 -Frequency Hopper Spread Spectrum Test Procedure released by FCC on March 30, 2000 and C63.10 (2014).

5 Summary of Test Results

Technical Requirements					
FCC Part 15 Subpart C					
Test Condition			Pages	Test Site	Test Result
§15.207	RSS-GEN A8.8	Conducted emission AC power port	10	Site 1	Pass
§15.247 (b) (1)	RSS-247 5.4(b)	Conducted peak output power	13	Site 1	Pass
§15.247(a)(1)	RSS-247 5.1(a)	20dB bandwidth&99% bandwidth	15	Site 1	Pass
§15.247(a)(1)	RSS-247 5.1(b)	Carrier frequency separation	18	Site 1	Pass
§15.247(a)(1)(iii)	RSS-247 5.1(d)	Number of hopping frequencies	20	Site 1	Pass
§15.247(a)(1)(iii)	RSS-247 5.1(d)	Dwell Time	22	Site 1	Pass
§15.247(a)(2)	RSS-247 5.2 (a)	6dB bandwidth	---	---	N/A
§15.247(e)	RSS-247 5.2 (b)	Power spectral density	---	---	N/A
§15.247(d)	RSS-247 5.5	Spurious RF conducted emissions	26	Site 1	Pass
§15.247(d)	RSS-247 5.5	Band edge	30	Site 1	Pass
§15.247(d) & §15.209	RSS-247 5.5 & RSSGEN 6.13	Spurious radiated emissions for transmitter	35	Site 1	Pass
§15.203	RSSGEN 8.3	Antenna requirement	See note 2		Pass

Note 1: N/A=Not Applicable.

Note 2: The EUT uses an integral antenna, which gain is 1.0dBi. In accordance to §15.203 and §RSSGEN 8.3, It is considered sufficiently to comply with the provisions of this section.

6 General Remarks

Remarks

This submittal(s) (test report) is update base on report 68.950.16.547.01, MBP49 & MBP50 PU: Change the battery, and PCB, but he PCB material is totally same as before, and the RF module including it's antenna gain, output power, hardware and software is totally same as before, so only Spurious radiated emissions for transmitter update in this report, and this report is intended for FCC ID: VLJ-MBP50PU and IC: 4522A-MBP50PU complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules and RSS-Gen and RSS-247.

SUMMARY:

All tests according to the regulations cited on page 5 were

☒ - Performed

☐ - **Not** Performed

The Equipment Under Test

☒ - **Fulfills** the general approval requirements.

☐ - **Does not** fulfill the general approval requirements.

Sample Received Date: January 21, 2017

Testing Start Date: January 21, 2017

Testing End Date: May 18, 2017

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch

Reviewed by:

Prepared by:




John Zhi
EMC Project Manager



Leon Zhang
EMC Project Engineer


7 Test Setups

7.1 AC Power Line Conducted Emission test setups




7.2 Radiated test setups


Below 1GHz:



Above 1GHz:



7.3 Conducted RF test setups



8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
Notebook	Lenovo	X240	---

The system was configured to hopping mode and non-hopping mode.

Hopping mode: typical working mode (normal hopping status)

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power

9 Technical Requirement

9.1 Conducted Emission

Test Method

1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through an Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line


Limit

According to §15.207 & RSS-GEN A8.8, conducted emissions limit as below:

Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50


Decreasing linearly with logarithm of the frequency

Product Type : Digital Video Baby monitor
 M/N : MBP49 PU
 Operating Condition : Normal Working
 Test Specification : Line
 Comment : AC 120V/60Hz



Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.378000	46.88	---	58.32	11.44	L1	9.7
0.382000	---	35.15	48.24	13.08	L1	9.7
0.534000	38.52	---	56.00	17.48	L1	9.7
0.654000	40.20	---	56.00	15.80	L1	9.7
0.782000	41.76	---	56.00	14.24	L1	9.7
1.062000	38.44	---	56.00	17.56	L1	9.7
1.814000	40.26	---	56.00	15.74	L1	9.7

Product Type : Digital Video Baby monitor
 M/N : MBP49 PU
 Operating Condition : Normal Working
 Test Specification : Neutral
 Comment : AC 120V/60Hz



Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.378000	41.70	---	58.32	16.62	N	9.7
0.534000	38.68	---	56.00	17.32	N	9.7
0.682000	---	27.78	46.00	18.22	N	9.7
0.718000	41.54	---	56.00	14.46	N	9.7
0.878000	40.44	---	56.00	15.56	N	9.7
1.726000	39.66	---	56.00	16.34	N	9.7
3.354000	37.16	---	56.00	18.84	N	9.8

9.2 Conducted peak output power

Test Method

1. Use the following spectrum analyzer settings:
Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
RBW > the 20 dB bandwidth of the emission being measured, VBW ≥ RBW,
Sweep = auto, Detector function = peak, Trace = max hold
2. Add a correction factor to the display.
3. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power

Limits

According to §15.247 (b) (1) & RSS-247 5.4(b), conducted peak output power limit as below:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤1	≤30

Conducted peak output power

GFSK modulation Test Result

Frequency MHz	Conducted Peak Output Power dBm	Result
Low channel 2402MHz	15.88	Pass
Middle channel 2440MHz	16.30	Pass
High channel 2477MHz	16.39	Pass

9.3 20 dB bandwidth and 99% bandwidth

Test Method

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Limit


Limit [kHz]

N/A


20 dB bandwidth and 99% bandwidth

GFSK Modulation test result

Frequency MHz	20 dB Bandwidth kHz	99% bandwidth kHz	Limit kHz	Result
2402	2663.0	2445.7	--	Pass
2440	2721.0	2474.7	--	Pass
2477	2751.0	2518.1	--	Pass




Date: 18.OCT.2016 15:00:51



Date: 18.OCT.2016 14:59:14



20 dB bandwidth and 99% bandwidth



Date: 18.OCT.2016 14:58:07

9.4 Carrier Frequency Separation

Test Method

1. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels, RBW $\geq$ 1% of the span, VBW $\geq$ RBW, Sweep = auto, Detector function = peak
2. By using the Max-Hold function record the separation of two adjacent channels.
3. Measure the frequency difference of these two adjacent channels by spectrum analyzer marker function.
4. Repeat above procedures until all frequencies measured were complete.

Limit

Limit kHz
$\geq 25\text{kHz}$ or $2/3$ of the 20 dB bandwidth which is greater

GFSK Modulation Limit


Frequency MHz	2/3 of 20 dB Bandwidth kHz
2402	1775.3
2440	1814.0
2477	1834.0




Carrier Frequency Separation

Test result: The measurement was performed with the typical configuration (normal hopping status), here GFSK modulation mode was used to show compliance.

GFSK Modulation test result



Date: 18.OCT.2016 15:37:37



Date: 18.OCT.2016 15:39:59

9.5 Number of hopping frequencies

Test Method

1. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels, $RBW \geq 1\%$ of the span, $VBW \geq RBW$, Sweep = auto, Detector function = peak
2. Set the spectrum analyzer on Max-Hold Mode, and then keep the EUT in hopping mode.
3. Record all the signals from each channel until each one has been recorded.
4. Repeat above procedures until all frequencies measured were complete.

Limit

Limit
number


 ≥ 15



Number of hopping frequencies

Test result: The measurement was performed with the typical configuration (normal hopping status), Here GFSK modulation mode was used to show compliance.

Number of hopping frequencies	Result
23	Pass



Remark: The product will only use 22 Channels (from Channel 1 to Channel 22) under normal operating condition. The last one Channel (Channel 23) is only used in matching mode.

9.6 Dwell Time

Test Method

1. Connect EUT antenna terminal to the spectrum analyzer with a low loss cable.
Equipment mode: Spectrum analyzer
2. RBW: 1MHz; VBW: 1MHz; SPAN: Zero Span
3. Adjust the center frequency of spectrum analyzer on any frequency be measured.
4. Measure the Dwell Time by spectrum analyzer Marker function.
5. Repeat above procedures until all frequencies measured were complete.

Limit

According to §15.247(a)(1)(iii) & RSS-210 A8.1(c) The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Dwell time

The maximum dwell time shall be 0.4 s.

We test Low frequency, middle frequency and high frequency, only worse case recorded in the report.

The Dwell Time = Burst Width * Total Hops. The detailed calculations are showed as follows:

The duration for dwell time calculation: $0.4 \text{ [s]} * \text{hopping number} = 0.4 \text{ [s]} * 22 \text{ [ch]} = 8.8 \text{ [s*ch]}$;

The burst width, which is directly measured, refers to the duration on one channel hop.

The maximum number of hopping channels in 8.8s $= 30 * (8.8/2) = 132$

Test Result

Modulation	Frequency	Reading (ms)	Total Hops	Test Result (ms)	Limit (ms)	Result
GFSK	2440MHz	0.239	132	31.55	< 400	Pass

Spectrum

Ref Level 21.00 dBm RBW 1 MHz

Att 40 dB SWT 2 s VBW 1 MHz

SGL

1AP Clnw

D1[1]

M1[1]

0.00 dB
239 μs
-33.11 dBm
4.59 ms

CF 2.44 GHz 691 pts 200.0 ms/

Ready 18.18.2016 18:55:25

Spectrum

Ref Level 21.00 dBm RBW 1 MHz

Att 40 dB SWT 5 ms VBW 1 MHz

SGL

1AP Clnw

D1[1] -1.33 dB

M1[1] -42.09 dBm

239.13 μ s

4.58696 ms

CF 2.44 GHz 691 pts 500.0 μ s

Ready 12.18.2016 16:52:27

Page 23 of 36

9.7 Spurious RF conducted emissions

Test Method

1. Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
RBW = 100 kHz, VBW ≥ RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
3. The level displayed must comply with the limit specified in this Section. Submit these plots.
4. Repeat above procedures until all frequencies measured were complete.



Limit

Frequency Range MHz	Limit (dBc)
30-25000	-20



Spurious RF conducted emissions



2402MHz





Spurious RF conducted emissions



2440MHz





Spurious RF conducted emissions

2477MHz



9.8 Band edge testing

Test Method

- 1 Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 kHz, VBW $\geq$ RBW, Sweep = auto, Detector function = peak, Trace = max hold
- 2 Allow the trace to stabilize, use the peak and delta measurement to record the result.
- 3 The level displayed must comply with the limit specified in this Section. .
- 4 Repeat the test at the hopping off and hopping on mode, submit all the plots.

Limit:



According to §15.247(d) & RSS-210 A8.5, in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a) and RSS-Gen7.2.2, must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)) and RSS-Gen.



Band edge testing


GFSK Modulation Test Result:

Hopping On:






Hopping Off:



Date: 18.OCT.2016 15:27:59



Date: 18.OCT.2016 15:22:55

9.9 Spurious radiated emissions for transmitter

Test Method

1. The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned
5. Use the following spectrum analyzer settings According to C63.10:
For Above 1GHz
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 1MHz, VBW $\geq$ RBW for peak measurement and VBW = 10Hz for average measurement, Sweep = auto, Detector function = peak, Trace = max hold.
For Below 1GHz
Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 KHz, VBW $\geq$ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average ((duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($20\log(1/\text{duty cycle})$).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.

Limit

According to part 15.247(d), the radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205, must comply with the radiated emission limits specified in section 15.209.

Frequency MHz	Field Strength uV/m	Field Strength dBµV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK

Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

The only worse case (which is subject to the maximum EIRP, GFSK mode) test result is listed in the report.

Transmitting spurious emission test result as below:

FHSS Mode GFSK Modulation 2402MHz Test Result

Frequency	Emission Level	Polarization	Limit	Detector	Margin	Result
MHz	dBuV/m		dBuV/m		dBuV/m	
87.98	28.87	Horizontal	40.00	QP	11.13	Pass
216.02	37.44	Horizontal	46.00	QP	8.56	Pass
264.04	42.20	Horizontal	46.00	QP	3.80	Pass
344.12	42.61	Horizontal	46.00	QP	3.39	Pass
88.04	31.52	Vertical	43.50	QP	11.98	Pass
208.05	31.66	Vertical	43.50	QP	11.84	Pass
240.06	37.85	Vertical	46.00	QP	8.15	Pass
256.06	40.52	Vertical	46.00	QP	5.48	Pass
360.07	36.48	Vertical	46.00	QP	9.52	Pass
4804.687500	43.40	Horizontal	74.00	PK	30.60	Pass
9609.843750	44.54	Horizontal	74.00	PK	29.46	Pass
14925.937500	47.06	Horizontal	74.00	PK	26.94	Pass
4803.281250	40.88	Vertical	74.00	PK	33.39	Pass
8734.218750	41.60	Vertical	74.00	PK	30.34	Pass
15022.500000	48.14	Vertical	74.00	PK	25.13	Pass

Bluetooth Mode GFSK Modulation 2440MHz Test Result

Frequency	Emission Level	Polarization	Limit	Detector	Margin	Result
MHz	dBuV/m		dBuV/m		dBuV/m	
4879.218750	43.41	Horizontal	74.00	PK	30.59	Pass
8724.843750	39.42	Horizontal	74.00	PK	34.58	Pass
12202.500000	48.76	Horizontal	74.00	PK	25.24	Pass
4879.218750	38.15	Vertical	74.00	PK	35.85	Pass
12202.968750	43.48	Vertical	74.00	PK	30.52	Pass
15441.562500	47.38	Vertical	74.00	PK	26.62	Pass

Bluetooth Mode GFSK Modulation 2477MHz Test Result

Frequency	Emission Level	Polarization	Limit	Detector	Margin	Result
MHz	dBuV/m		dBuV/m		dBuV/m	
4956.562500	43.58	Horizontal	74.00	PK	30.42	Pass
12397.968750	53.24	Horizontal	74.00	PK	20.76	Pass
14870.625000	48.82	Horizontal	74.00	PK	25.18	Pass
4956.562500	40.61	Vertical	74.00	PK	33.39	Pass
9914.062500	43.66	Vertical	74.00	PK	30.34	Pass
12397.968750	48.87	Vertical	74.00	PK	25.13	Pass

Remark: Testing is carried out with frequency rang 30MHz to 18GHz, the detected values which are noise floor or below the limit 30dB will not be recorded.

10 Test Equipment List

List of Test Instruments

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 26	101269	2017-7-15
Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9163	707	2017-8-3
Horn Antenna	Rohde & Schwarz	HF907	102294	2017-7-15
Pre-amplifier	Rohde & Schwarz	SCU 18	102230	2017-7-15
3m Semi-anechoic chamber	TDK	9X6X6	----	2019-5-29
Test software	Rohde & Schwarz	EMC32	Version 9.15.00	N/A

11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Uncertainty for Radiated Emission in 3m chamber 30MHz-1000MHz	Horizontal: 4.99dB; Vertical: 4.97dB;
Uncertainty for Radiated Emission in 3m chamber 1000MHz-18000MHz	Horizontal: 4.96dB; Vertical: 4.95dB;
Uncertainty for Conducted RF test with TS 8997	Power level test involved: 2.04dB Frequency test involved: 1.1×10^{-7}