

TEST REPORT

Application No.: HKEM2107000741AT
Applicant: BINATONE ELECTRONICS INTERNATIONAL LIMITED
Address of Applicant: 25/F, Guangdong Investment Tower, 148 Connaught Road Central, Sheung Wan, Hong Kong
Equipment Under Test (EUT):
EUT Name: Video Baby Monitor
Model No.: Nursery View Deluxe (PU), NV420PU
Additional Model: Please refer to section 2 of this report which indicates which item was actually tested and which were electrically identical.
Trademark: Hubble
FCC ID: VLJ-NV420PU
IC: 4522A-NV420PU
HVIN: NV420PU
Standard(s) : 47 CFR Part 15 Subpart C, 2020
RSS-247 Issue 2, February 2017
RSS-Gen: Issue 5, Amdt 2019
Date of Receipt: 2021-07-16
Date of Test: 2021-07-19 to 2021-07-27
Date of Issue: 2021-07-30

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Law Man Kit
EMC Manager

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request and accessible at <http://www.sgs.com/en/Terms-and-conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-conditions.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. The document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2021-07-30		Original

Authorized for issue by:			
			
		Leo Xu /Project Engineer	Date: 2021-07-30
			
		Law Man Kit /Reviewer	Date: 2021-07-30

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass
Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.247(a)(1),(g),(h)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(1)	Pass
20dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.247(a)(1)	Pass
Carrier Frequencies Separation	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass
Hopping Channel Number	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Dwell Time	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	RSS-247 Issue 2, February 2017	N/A	RSS-Gen Section 6.8	Pass
Pseudorandom Frequency Hopping Sequence	RSS-247 Issue 2, February 2017	N/A	RSS-247 Section 5.1(a)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 6.2	RSS-Gen Section 8.8	Pass
99% Bandwidth	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 6.9.3	RSS-Gen Section 6.7	Pass
Conducted Peak Output Power	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 7.8.5	RSS-247 Section 5.4(b)	Pass
20dB Bandwidth	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 6.9.2	RSS-247 Section 5.1(a)	Pass
Carrier Frequencies Separation	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 7.8.2	RSS-247 Section 5.1(b)	Pass
Hopping Channel Number	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 7.8.3	RSS-247 Section 5.1(d)	Pass
Dwell Time	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 7.8.4	RSS-247 Section 5.1(d)	Pass
Conducted Band Edges Measurement	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 7.8.6	RSS-247 Section 5.5	Pass
Conducted Spurious Emissions	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 7.8.8	RSS-247 Section 5.5	Pass
Radiated Emissions which fall in the restricted bands	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 6.10.5	Section 3.3 & RSS-Gen Section 8.10	Pass
Radiated Spurious Emissions	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 6.4&6.5&6.6	Section 3.3 & RSS-Gen Section 8.9	Pass
Frequency stability	RSS-247 Issue 2, February 2017	RSS-Gen Section 6.11	RSS-Gen Section 8.11	Pass

Note: Frequency stability requested in RSS GEN Section 8.1.1 has been complied since the result of band edge can demonstrate.

Declaration of EUT Family Grouping:

Item no.: Nursery View Deluxe (PU), NV420PU

According to the confirmation from the applicant, the above models are identical in all electrical aspects in relating to the circuit design, PCB layout, electrical components used, internal wiring and functions. The differences are only the model/item No-

Therefore only the model NV420PU was tested in this report.

3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	5
4 GENERAL INFORMATION	7
4.1 DETAILS OF E.U.T.	7
4.2 DESCRIPTION OF SUPPORT UNITS	8
4.3 MEASUREMENT UNCERTAINTY	9
4.4 TEST LOCATION	10
4.5 TEST FACILITY	10
4.6 DEVIATION FROM STANDARDS	10
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	10
5 EQUIPMENT LIST	11
6 RADIO SPECTRUM TECHNICAL REQUIREMENT	14
6.1 ANTENNA REQUIREMENT	14
6.1.1 Test Requirement:	14
6.1.2 Conclusion	14
6.2 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE	15
6.2.1 Test Requirement:	15
6.2.2 Test Setup Diagram	15
6.2.3 Conclusion	15
7 RADIO SPECTRUM MATTER TEST RESULTS	16
7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150KHz-30MHz)	16
7.1.1 E.U.T. Operation	16
7.1.2 Test Setup Diagram	16
7.1.3 Measurement Procedure and Data	17
7.2 99% BANDWIDTH	20
7.2.1 E.U.T. Operation	20
7.2.2 Test Setup Diagram	20
7.2.3 Measurement Procedure and Data	20
7.3 CONDUCTED PEAK OUTPUT POWER	21
7.3.1 E.U.T. Operation	21
7.3.2 Test Setup Diagram	21
7.3.3 Measurement Procedure and Data	21
7.4 20dB BANDWIDTH	22
7.4.1 E.U.T. Operation	22
7.4.2 Test Setup Diagram	22
7.4.3 Measurement Procedure and Data	22
7.5 CARRIER FREQUENCIES SEPARATION	23
7.5.1 E.U.T. Operation	23
7.5.2 Test Setup Diagram	23
7.5.3 Measurement Procedure and Data	23
7.6 HOPPING CHANNEL NUMBER	24
7.6.1 E.U.T. Operation	24
7.6.2 Test Setup Diagram	24
7.6.3 Measurement Procedure and Data	24

7.7	DWELL TIME	25
7.7.1	<i>E.U.T. Operation</i>	25
7.7.2	<i>Test Setup Diagram</i>	25
7.7.3	<i>Measurement Procedure and Data</i>	25
7.8	CONDUCTED BAND EDGES MEASUREMENT	26
7.8.1	<i>E.U.T. Operation</i>	28
7.8.2	<i>Test Setup Diagram</i>	28
7.8.3	<i>Measurement Procedure and Data</i>	28
7.9	CONDUCTED SPURIOUS EMISSIONS.....	29
7.9.1	<i>E.U.T. Operation</i>	29
7.9.2	<i>Test Setup Diagram</i>	29
7.9.3	<i>Measurement Procedure and Data</i>	29
7.10	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	30
7.10.1	<i>E.U.T. Operation</i>	30
7.10.2	<i>Test Setup Diagram</i>	30
7.10.3	<i>Measurement Procedure and Data</i>	31
7.11	RADIATED SPURIOUS EMISSIONS	32
7.11.1	<i>E.U.T. Operation</i>	33
7.11.2	<i>Test Setup Diagram</i>	33
7.11.3	<i>Measurement Procedure and Data</i>	34
8	PHOTOGRAPHS	38
9	APPENDIX.....	39
9.1	PEAK CONDUCTED OUTPUT POWER	39
9.2	EMISSION BANDWIDTH 20 dB	41
9.3	OCCUPIED CHANNEL BANDWIDTH 99%.....	43
9.4	CARRIER FREQUENCY SEPARATION	45
9.5	DWELL TIME	46
9.6	HOPPING FREQUENCIES.....	47
9.7	CONDUCTED BAND EDGE MEASUREMENT	48
9.8	CONDUCTED SPURIOUS EMISSION	52

4 General Information

4.1 Details of E.U.T.

Power supply:	Model: YWK-AD050100-U Input: AC 100-240V, 50/60Hz, Max 0.3A Output: DC 5V, 1000mA or Battery Model: 5C Rated capacity: 1200mAh, 4.44Wh Voltage: 3.7VDC
Test voltage:	AC 120V
Cable:	Power Cable: 185cm unshielded 2 wires DC cable
Antenna Gain:	1 dBi
Antenna Type:	Integral antenna
Modulation Type:	GFSK
Number of Channels:	22
Operation Frequency:	2402MHz to 2477MHz
Spectrum Spread Technology:	Frequency Hopping Spread Spectrum (FHSS)
Series number:	A1
Hardware Version:	V1.0
Software Version:	0.11
	Remark: Power level setting was not adjustable and fixed default through SW Version.

Frequency List

Channel Number	TX Freq (MHz)	Channel Number	TX Freq (MHz)
1	2402	12	2445
2	2404	13	2450
3	2406	14	2455
4	2408	15	2460
5	2410	16	2465
6	2415	17	2467
7	2420	18	2469
8	2425	19	2471
9	2430	20	2473
10	2435	21	2475
11	2440	22	2477

Remark: 1. Operation channel is total 22.
2. Testing Channels are highlighted in **bold**.

4.2 Description of Support Units

The EUT has been tested with corresponding accessories as below:

Supplied by client

Description	Manufacturer	Model No.	SN/Certificate NO
UART Test board	N/A	N/A	N/A

Supplied by SGS:

Description	Manufacturer	Model No.	SN/Certificate NO
NoteBook (EMC4)	Dell	P75F	N/A

4.3 Measurement Uncertainty

RF

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	RF conducted power (30MHz-40GHz)	1.5dB
5	RF power density	1.5dB
6	Conducted Spurious emissions	1.5dB
7	RF Radiated power & Radiated Spurious emission test	4.9dB (30MHz-1GHz)
		4.6dB (1GHz-6GHz)
		4.7dB (6GHz-18GHz)
		5.6dB (18GHz-40GHz)
8	Temperature test	$\pm 1^{\circ}\text{C}$
9	Humidity test	$\pm 3\%$
10	Supply voltages	$\pm 1.5\%$
11	Time	$\pm 3\%$

Remark:

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors in calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the test lab quality system according to ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

4.4 Test Location

All tests were performed at:

SGS Hong Kong Limited
Unit 2 and 3, G/F, Block A, Po Lung Centre,
11 Wang Chiu Road, Kowloon Bay, Kowloon, Hong Kong
Tel: +852 2305 2570 Fax: +852 2756 4480

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **HOKLAS (Lab Code: 009)**

SGS Hong Kong Limited has been accepted by HKAS Executive, on the recommendation of the Accreditation Advisory Board, as a HOKLAS Accredited Laboratory, this laboratory meets the requirements of ISO/IEC 17025:2017 and it has been accredited for performing specific test as listed in the scope of accreditation within the test category of Electrical and Electronic Products.

• **IAS Accreditation (Lab Code: TL-817)**

SGS Hong Kong Limited has met the requirements of AC89, IAS Accreditation Criteria for Testing Laboratories, and has demonstrated compliance with ISO/IEC Standard 17025:2017, General requirements for the competence of testing and calibration laboratories. This organization is accredited to provide the services specified in the scope of accreditation maintained on the IAS website (www.iasonline.org).

The report must not be used by the client to claim product certification, approval, or endorsement by IAS, NIST, or any agency of the Federal Government.

• **FCC Recognized Accredited Test Firm (CAB Registration No.: 514599)**

SGS Hong Kong Limited has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: HK0015, Test Firm Registration Number: 514599.

• **Industry Canada (Site Registration No.: 26103; CAB Identifier No.: HK0015)**

SGS Hong Kong Limited has been recognized by Department of Innovation, Science and Economic Development (ISED) Canada as a wireless testing laboratory. The acceptance letter from the ISED is maintained in our files. CAB Identifier No: HK0015, Site Registration Number: 26103.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None

5 Equipment List

20dB Bandwidth, Conducted Peak Output Power, Hopping Channel Number, Carrier Frequencies Separation, Dwell Time, Conducted Band Edges Measurement, Conducted Spurious Emissions

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
SMBV100A VECTOR SIGNAL GENERATOR	Rohde & Schwarz	SMBV100A	E234	2020/08/31	2021/08/30
FSV40 SIGNAL ANALYZER 40GHz	Rohde & Schwarz	FSV40	E235	2020/08/31	2021/08/30
SMB100A SIGNAL GENERATOR	Rohde & Schwarz	SMB100A	E236	2020/08/31	2021/08/30
Wireless Conn. Tester (CMW)	Rohde & Schwarz	CMW270	E240	CAL IN USE	CAL IN USE
OSP	Rohde & Schwarz	OSP-B157W8	E242	2020/08/31	2021/08/30
Cable	Rohde & Schwarz	J12J103539-00-2	E239	2020/09/21	2021/09/20
WMS32 Test software	Rohde & Schwarz	N/A	Version 11	N/A	N/A

Conducted Emissions at Mains Terminals (150kHz-30MHz)

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test Receiver 9kHz to 3.6GHz	Rohde & Schwarz	ESR3 / 102326	E231	2020/08/31	2021/08/30
Signal Generator	Rohde & Schwarz	SMT03	E177	2021/04/12	2022/04/11
Artificial Mains Network (LISN)	Schwarzbeck	NSLK 8127 / 8127312	E005	2021/04/13	2022/04/12
Impulse Limiter	Rohde & Schwarz	ESH-3-Z2 / 357881052	E028	2020/09/12	2021/09/11
EMC32 Test software	Rohde & Schwarz	Version 10	N/A	N/A	N/A

Radiated Spurious Emissions (30MHz-1GHz)

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	ChamPro	N/A	E229	2020/08/09	2021/08/08
Coaxial Cable	SGS	N/A	E167	2021/07/15	2022/07/14
EMI Test Receiver 9kHz to 7GHz	Rohde & Schwarz	ESR7 / 102298	E314	2021/05/18	2022/05/17
TRILOG Super Broadb. Test Antenna, (25) 30-1000 MHz	Schwarzbeck	9168-1110	E311	2020/02/13	2022/02/12
EMC32 Test software	Rohde & Schwarz	Version 10	N/A	N/A	N/A
Boresight Mast Controller	ChamPro	AM-BS-4500-E	E237	N/A	N/A
Turntable with Controller	ChamPro	EM1000	E238	N/A	N/A

Radiated Spurious Emissions (above 1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	ChamPro	N/A	E229	2020/08/09	2021/08/08
Coaxial Cable	SGS	N/A	E167	2021/07/15	2022/07/14
EMI Test Receiver 9kHz to 7GHz	Rohde & Schwarz	ESR7 / 102298	E314	2021/05/18	2022/05/17
TRILOG Super Broadb. Test Antenna, (25) 30-1000 MHz	Schwarzbeck	9168-1110	E311	2020/02/13	2022/02/12
Signal and Spectrum Analyzer 2Hz - 26.5GHz	Rohde & Schwarz	FSW26	E296	2020/08/31	2021/08/30
Spectrum Analyzer 9kHz - 30GHz	Rohde & Schwarz	FSP30	E204	2020/03/11	2022/03/10
Horn Antenna 1 - 18GHz	Schwarzbeck	BBHA9120D	E211	2020/01/29	2022/01/28
Horn Antenna 15 - 40GHz	Schwarzbeck	BBHA9170	E212	2020/01/29	2022/01/28
Preamplifier 33dB, 1 - 18GHz	Schwarzbeck	BBV9718	E214	2019/04/24	2022/04/23
Preamplifier 33dB, 18 - 26.5GHz	Schwarzbeck	BBV9719	E215	2020/09/21	2022/09/20
Broadband Coaxial Preamplifier typ. 30 dB, 18-40 GHz	Schwarzbeck	BBV 9721	E266	2020/08/31	2021/08/30
Highpass Filter 3.5-26.5GHz	Wainwright	WHNX3.5/26.5 G-6SS	E205	2019/04/24	2022/04/23
Band Reject Filter 2.4-2.5GHz	Wainwright	WRCJV 2400/2500- 2100	E206	2019/04/24	2022/04/23
RF cable SMA to SMA 10000mm	HUBER+SUHNER	SF104- 26.5/2*11SMA 45	E207-1	2020/09/21	2021/09/20
Boresight Mast Controller	ChamPro	AM-BS-4500-E	E237	N/A	N/A
Turntable with Controller	ChamPro	EM1000	E238	N/A	N/A



Report No.: HKEM210700074102
Page: 13 of 53

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Digital temperature & humidity data logger	SATO	SK-L200TH II	E232	2020/09/12	2021/09/11
Electronic Digital Thermometer with Hygrometer	nil	2074/2075	E159	2020/09/12	2021/09/11
Barometer with digital thermometer	SATO	7612-00	E218	2021/03/29	2022/04/29
Conditional Chamber	Zhong Zhi Testing Instruments	CZ-E-608D	E216	2020/08/31	2021/08/30

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

RSS-Gen Section 6.8

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 1dBi.




Photo of antenna refer to Appendix – Internal photo.


6.2 Pseudorandom Frequency Hopping Sequence

6.2.1 Test Requirement:

FCC Part 15 Subpart C Section 15.247(a)(1)


RSS-247 Section 5.1(a)

6.2.2 Test Setup Diagram



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



6.2.3 Conclusion

Standard Requirement:

The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)

Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:

Each frequency used equally on the average by each transmitter.

According to Technical Specification, the receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any transmitters and shift frequencies in synchronization with the transmitted signals.

According to Technical specification, the system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

The system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15 Subpart C 15.207, RSS-Gen Section 8.8
Test Method: ANSI C63.10 (2013) Section 6.2
Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C Humidity: 51.2 % RH :

Test mode c: TX Keep the EUT transmitted the continuous modulation test signal at the specific channel(s).

7.1.2 Test Setup Diagram




7.1.3 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor


Mode: c;
Line: Live Line

Full Spectrum



Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Corr. (dB)	Result
0.354000	---	27.77	48.87	21.10	10.1	Pass
0.358000	42.17	---	58.78	16.61	10.1	Pass
0.394000	---	28.02	47.98	19.96	10.1	Pass
0.402000	36.79	---	57.81	21.02	10.1	Pass
0.434000	---	24.30	47.18	22.88	10.1	Pass
0.434000	38.78	---	57.18	18.39	10.1	Pass
0.470000	34.85	---	56.51	21.66	10.1	Pass
0.794000	34.66	---	56.00	21.34	10.1	Pass
1.074000	---	22.33	46.00	23.67	10.1	Pass
1.262000	---	22.14	46.00	23.86	10.2	Pass
1.474000	---	22.05	46.00	23.95	10.2	Pass
3.422000	33.63	---	56.00	22.37	10.2	Pass

Mode: c;
Line: Neutral Line



Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Corr. (dB)	Result
0.354000	---	33.91	48.87	14.96	10.0	Pass
0.382000	46.27	---	58.24	11.96	10.0	Pass
0.394000	---	33.31	47.98	14.67	10.0	Pass
0.418000	43.30	---	57.49	14.19	10.0	Pass
0.426000	---	31.74	47.33	15.59	10.0	Pass
0.434000	---	29.31	47.18	17.87	10.0	Pass
1.074000	---	26.53	46.00	19.47	10.3	Pass
1.218000	38.61	---	56.00	17.39	10.3	Pass
1.418000	---	26.39	46.00	19.61	10.3	Pass
3.078000	38.68	---	56.00	17.32	10.5	Pass
3.430000	36.86	---	56.00	19.15	10.5	Pass
3.534000	38.07	---	56.00	17.93	10.5	Pass

7.2 99% Bandwidth

Test Requirement RSS-Gen Section 6.7
Test Method: ANSI C63.10 (2013) Section 6.9.3


7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 20.0 °C Humidity: 48.0 % RH :

Test mode b: TX_non-Hop mode_Keep the EUT in continuously transmitting mode with modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.2.2 Test Setup Diagram



7.2.3 Measurement Procedure and Data

The detailed test data see section 9: Appendix

7.3 Conducted Peak Output Power

Test Requirement 47 CFR Part 15 Subpart C 15.247:2019(b)(1) & 15.247(b)(3),
RSS-247 Section 5.4(b)

Test Method: ANSI C63.10 (2013) Section 7.8.5


7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 20.0 °C Humidity: 48.0 % RH :

Test mode a: TX_Hop mode_Keep the EUT in frequency hopping mode with modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.3.2 Test Setup Diagram



7.3.3 Measurement Procedure and Data

The detailed test data see section 9: Appendix

7.4 20dB Bandwidth

Test Requirement 47 CFR Part 15 Subpart C 15.215, RSS-247 Section 5.1(a)
Test Method: ANSI C63.10 (2013) Section 6.9.2


7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 20.0 °C Humidity: 48.0 % RH :

Test mode b: TX_non-Hop mode_Keep the EUT in continuously transmitting mode with modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.4.2 Test Setup Diagram



7.4.3 Measurement Procedure and Data

The detailed test data see section 9: Appendix


7.5 Carrier Frequencies Separation

Test Requirement 47 CFR Part 15 Subpart C 15.247:2019a(1), RSS-247 Section 5.1(b)
Test Method: ANSI C63.10 (2013) Section 7.8.2
Limit: 2/3 of the 20dB bandwidth base on the transmission power is less than 0.125W

7.5.1 E.U.T. Operation

Operating Environment:
Temperature: 20.0 °C Humidity: 48.0 % RH :
Test mode a: TX_Hop mode_Keep the EUT in frequency hopping mode with modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.5.2 Test Setup Diagram



7.5.3 Measurement Procedure and Data

The detailed test data see section 9: Appendix

7.6 Hopping Channel Number

Test Requirement 47 CFR Part 15 Subpart C 15.247:2019a(1)(iii), RSS-247 Section 5.1(d)
Test Method: ANSI C63.10 (2013) Section 7.8.3
Limit:

Frequency range(MHz)	Number of hopping channels (minimum)
902-928	50 for 20dB bandwidth <250kHz
	25 for 20dB bandwidth ≥250kHz
2400-2483.5	15
5725-5850	75


7.6.1 E.U.T. Operation

Operating Environment:

Temperature: °C Humidity: % RH :

Test mode a: TX_Hop mode_Keep the EUT in frequency hopping mode with modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.6.2 Test Setup Diagram



7.6.3 Measurement Procedure and Data

The detailed test data see section 9: Appendix

7.7 Dwell Time

Test Requirement: 47 CFR Part 15 Subpart C 15.247:2019a(1)(iii), RSS-247 Section 5.1(d)
Test Method: ANSI C63.10 (2013) Section 7.8.4
Limit:

Frequency(MHz)	Limit
902-928	0.4S within a 20S period(20dB bandwidth<250kHz)
	0.4S within a 10S period(20dB bandwidth≥250kHz)
2400-2483.5	0.4S within a period of 0.4S multiplied by the number of hopping channels
5725-5850	0.4S within a 30S period


7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 20.0 °C Humidity: 48.0 % RH :

Test mode: a: TX_Hop mode_Keep the EUT in frequency hopping mode with modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.7.2 Test Setup Diagram



7.7.3 Measurement Procedure and Data

The detailed test data see section 9: Appendix

7.8 Conducted Band Edges Measurement

Test Requirement	47 CFR Part 15 Subpart C 15.247:2019(d), RSS-247 Section 5.5
Test Method:	ANSI C63.10 (2013) Section 7.8.6
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))

FCC Part 15 C Section 15.205 Restricted bands of operation.

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	
13.36 - 13.41			

RSS-Gen Section 8.10 Restricted bands of operation.

Restricted frequency bands, identified in table 7, are designated primarily for safety-of-life services (distress calling and certain aeronautical activities), certain satellite downlinks, radio astronomy and some government uses. Except where otherwise indicated, the following conditions related to the restricted frequency bands apply:

(a) The transmit frequency, including fundamental components of modulation, of licence-exempt radio

apparatus shall not fall within the restricted frequency bands listed in table 7 except for apparatus compliant with RSS-287, *Emergency Position Indicating Radio Beacons (EPIRB)*, *Emergency Locator Transmitters (ELT)*, *Personal Locator Beacons (PLB)*, and *Maritime Survivor Locator Devices (MSLD)*.

(b) Unwanted emissions that fall into restricted frequency bands listed in table 7 shall comply with the limits specified in table 5 and table 6.

(c) Unwanted emissions that do not fall within the restricted frequency bands listed in table 7 shall comply either with the limits specified in the applicable RSS or with those specified in table 5 and table 6.

Table 7 – Restricted frequency bands* MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	* Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138	--	


7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 20.0 °C Humidity: 48.0 % RH :

Test mode a: TX_Hop mode_Keep the EUT in frequency hopping mode with modulation. All modes have been tested and only the data of worst case is recorded in the report.
b: TX_non-Hop mode_Keep the EUT in continuously transmitting mode with modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.8.2 Test Setup Diagram



7.8.3 Measurement Procedure and Data

The detailed test data see section 9: Appendix


7.9 Conducted Spurious Emissions

Test Requirement	47 CFR Part 15 Subpart C 15.247:2019(d), RSS-247 Section 5.5
Test Method:	ANSI C63.10 (2013) Section 7.8.8
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

7.9.1 E.U.T. Operation

Operating Environment:				
Temperature:	20.0 °C	Humidity:	48.0 % RH	:
Test mode	a: TX_Hop mode_Keep the EUT in frequency hopping mode with modulation. All modes have been tested and only the data of worst case is recorded in the report. b: TX_non-Hop mode_Keep the EUT in continuously transmitting mode with modulation. All modes have been tested and only the data of worst case is recorded in the report.			

7.9.2 Test Setup Diagram



7.9.3 Measurement Procedure and Data

The detailed test data see section 9: Appendix

7.10 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15 Subpart C 15.209 & 15.247(d), Section 3.3
& RSS-Gen Section 8.10
Test Method: ANSI C63.10 (2013) Section 6.10.5
Limit:

Table 5 – General field strength limits at frequencies above 30 MHz

Frequency (MHz)	Field strength (μ V/m at 3 m)
30 - 88	100
88 - 216	150
216 - 960	200
Above 960	500

Table 6 – General field strength limits at frequencies below 30 MHz

Frequency	Magnetic field strength (H-Field) (μ A/m)	Measurement distance (m)
9 - 490 kHz 1	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.


7.10.1 E.U.T. Operation

Operating Environment:

Temperature: 20.0 °C Humidity: 48.0 % RH :

Test mode b: TX_non-Hop mode. Keep the EUT in continuously transmitting mode with modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.10.2 Test Setup Diagram



7.10.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Frequency (MHz)	Antenna Polarization	Emission Level (dBμV/m)		Limit (dBμV/m)		Remark
		Peak	Average	Peak	Average	
2390.000	H	54.8	42.2	74.0	54.0	Pass
2483.500	H	71.0	52.4	74.0	54.0	Pass
2390.000	V	58.2	42.3	74.0	54.0	Pass
2483.500	V	69.8	51.6	74.0	54.0	Pass

7.11 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15 Subpart C 15.205 & 15.209, Section 3.3
& RSS-Gen Section 8.9
Test Method: ANSI C63.10 (2013) Section 6.4&6.5&6.6
Limit:

Table 5 – General field strength limits at frequencies above 30 MHz

Frequency (MHz)	Field strength (μ V/m at 3 m)
30 - 88	100
88 - 216	150
216 - 960	200
Above 960	500

Table 6 – General field strength limits at frequencies below 30 MHz

Frequency	Magnetic field strength (H-Field) (μ A/m)	Measurement distance (m)
9 - 490 kHz 1	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.


7.11.1 E.U.T. Operation

Operating Environment:

Temperature: 22.2 °C Humidity: 48.6 % RH :

Test mode b: TX_non-Hop mode Keep the EUT in continuously transmitting mode with modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.11.2 Test Setup Diagram



7.11.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark:


- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Radiated emission below 1GHz

Mode: b;


Polarization: Horizontal

Quasi-peak measurement:



Frequency (MHz)	QuasiPeak (dBμV/m)	Pol.	Corr. (dB/m)	Margin (dB)	Limit (dBμV/m)	Result
106.630000	35.7	H	10.3	7.8	43.5	Pass
159.980000	35.0	H	14.4	8.5	43.5	Pass
213.330000	33.1	H	11.1	10.4	43.5	Pass
266.680000	38.0	H	13.6	8.0	46.0	Pass
319.960714	41.0	H	15.5	3.0	46.0	Pass
800.041429	35.9	H	24.9	10.1	46.0	Pass

Mode: b;
Polarization: Vertical
Quasi-peak measurement:



Frequency (MHz)	QuasiPeak (dBμV/m)	Pol.	Corr. (dB/m)	Margin (dB)	Limit (dBμV/m)	Result
53.280124	30.1	V	14.1	10.0	40.0	Pass
106.645301	37.9	V	10.3	5.6	43.5	Pass
133.320643	36.1	V	13.0	7.5	43.5	Pass
213.320062	32.0	V	11.1	11.5	43.5	Pass
319.960540	34.9	V	15.5	11.1	46.0	Pass
506.680012	36.4	V	19.8	9.6	46.0	Pass

Above 1GHz

Channel: Low

Frequency (MHz)	Antenna Polarization	Emission Level (dB μ V/m)		Limit (dB μ V/m)		Remark
		Peak	Average	Peak	Average	
1926.250	V	39.7	/	74	54	Pass
3690.625	H	46.4	/	74	54	Pass
4882.500	H	47.2	/	74	54	Pass
7204.500	H	61.5	50.8	74	54	Pass
8149.500	H	57.3	43.9	74	54	Pass
11455.000	V	60.7	47.7	74	54	Pass

Channel: Middle

Frequency (MHz)	Antenna Polarization	Emission Level (dB μ V/m)		Limit (dB μ V/m)		Remark
		Peak	Average	Peak	Average	
1930.375	H	40.4	/	74.0	54.0	Pass
3681.625	V	45.3	/	74.0	54.0	Pass
4944.500	H	47.8	/	74.0	54.0	Pass
7204.500	V	60.2	49.0	74.0	54.0	Pass
10999.000	V	61.5	47.9	74.0	54.0	Pass
11959.000	V	60.8	47.6	74.0	54.0	Pass

Channel: High

Frequency (MHz)	Antenna Polarization	Emission Level (dB μ V/m)		Limit (dB μ V/m)		Remark
		Peak	Average	Peak	Average	
1930.375	V	37.5	/	74	54	Pass
3671.875	V	46.7	/	74	54	Pass
4801.000	H	47.2	/	74	54	Pass
7432.500	V	61.5	50.2	74	54	Pass
10492.500	H	59.7	46.8	74	54	Pass
12113.000	H	60.8	48.0	74	54	Pass



Report No.: HKEM210700074102
Page: 38 of 53

8 Photographs

Remark: Photos refer to Appendix: External Photo, Internal Photo and setup Photo.


9 Appendix

9.1 Peak conducted output power


DUT Frequency (MHz)	Peak Power (dBm)	Limit Max (dBm)	Result
2402.000000	13.9	21.0	PASS
2440.000000	12.6	21.0	PASS
2477.000000	13.6	21.0	PASS

Remark: Antenna gain: 1dBi


Remark: Cable loss 0.8dB was considered and set in system configuration.



Peak Power




Peak Power




9.2 Emission Bandwidth 20 dB


DUT Frequency (MHz)	Bandwidth (MHz)	Limit (MHz)	Result
2402.000000	2.5	---	PASS
2440.000000	2.6	---	PASS
2477.000000	2.6	---	PASS

20 dB Bandwidth



20 dB Bandwidth





Measurement Setting


Setting	Instrument Value	Target Value
Span	6.000 MHz	6.000 MHz
RBW	30.000 kHz	≥ 30.000 kHz
VBW	100.000 kHz	≥ 90.000 kHz
SweepPoints	400	~ 400
SweepTime	75.781 μ s	AUTO
Reference Level	10.000 dBm	10.000 dBm
Attenuation	30.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	24 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.15 dB	0.50 dB

Remark: Cable loss 0.8dB was considered and set in system configuration.


9.3 Occupied Channel Bandwidth 99%

DUT Frequency (MHz)	Bandwidth (MHz)	Limit (MHz)	Result
2402.000	2.1	---	PASS
2440.000	2.3	---	PASS
2477.000	2.3	---	PASS


99 % Bandwidth



99 % Bandwidth



99 % Bandwidth



Measurement Setting

Setting	Instrument Value	Target Value
Span	10.000 MHz	10.000 MHz
RBW	30.000 kHz	≥ 30.000 kHz
VBW	100.000 kHz	≥ 90.000 kHz
SweepPoints	400	~ 400
Sweptime	75.781 μ s	AUTO
Reference Level	10.000 dBm	10.000 dBm
Attenuation	30.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	36 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.30 dB


Remark: Cable loss 0.8dB was considered and set in system configuration.

9.4 Carrier Frequency Separation

DUT Frequency (MHz)	Frequency Separation (MHz)	Limit (MHz)	Result
2402	1.71	>1.60	PASS

Remark: Limit = $2/3 \times 20\text{dB Bandwidth}$

The channel shown is the worst case:



Remark: Cable loss 0.8dB was considered and set in system configuration.

Measurement Setting


Setting	Instrument Value	Target Value
Span	3.000 MHz	3.000 MHz
RBW	300.000 kHz	≤ 300.000 kHz
VBW	300.000 kHz	≥ 300.000 kHz
SweepPoints	101	~ 10
SweepTime	1.000 ms	AUTO
Reference Level	10.000 dBm	10.000 dBm
Attenuation	30.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	62 / max. 150	max. 150
Stable	10 / 10	10
Max Stable Difference	0.37 dB	0.50 dB

9.5 Dwell Time

Channel (MHz)	Width of Burst (ms)	Number of Burst(s)	Active Channels	Measurement Time (s)	Dwell Time (ms)	Limit (ms)	Result
2402	0.13	117	22	8.8	15.21	≤400	Pass

*Remark: the channel shown is the worst case.

Time of Channel Occupancy



Measurement Setting


Setting	Instrument Value	Target Value
Span	ZeroSpan	ZeroSpan
RBW	2.000 MHz	~ 2.500 MHz
VBW	5.000 MHz	~ 6.000 MHz
SweepPoints	30001	~ 30001
Reference Level	-20.000 dBm	-20.000 dBm
Attenuation	0.000 dB	0.000 dB
Detector	MaxPeak	MaxPeak
SweepCount	1	1
Filter	Channel	Channel
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamp	off	off
Trigger	External	External
Trigger Offset	0.000 s	0.000 s

Remark: Cable loss 0.8dB was considered and set in system configuration.

9.6 Hopping Frequencies

Channels	Limit Min	Result
22	15	PASS

Sequence



Measurement Setting

Setting	Instrument Value	Target Value
Span	83.500 MHz	83.500 MHz
RBW	200.000 kHz	≤ 299.000 kHz
VBW	200.000 kHz	≥ 200.000 kHz
SweepPoints	418	~ 418
SweepTime	1.060 ms	AUTO
Reference Level	10.000 dBm	10.000 dBm
Attenuation	30.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	47 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

9.7 Conducted Band Edge Measurement

Non-hopping mode

Inband Peak


Frequency (MHz)	Level (dBm)
2401.925000	10.8
2476.975000	10.3

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2399.975000	-16.2	7.1	-9.2	PASS
2484.025000	-43.9	34.2	-9.7	PASS


Remark: Limit = Inband peak – 20dB

Band Edge



— Limit — Sum Level × Fail

Band Edge



— Limit — Sum Level × Fail

Measurement Setting

Setting	Instrument Value	Target Value
RBW	100.000 kHz	≤ 100.000 kHz
VBW	300.000 kHz	≥ 300.000 kHz
SweepPoints	1800	~ 1800
SweepTime	1.800 ms	AUTO
Reference Level	10.000 dBm	10.000 dBm
Attenuation	30.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	10 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.29 dB	0.50 dB

Remark: Cable loss 0.8dB was considered and set in system configuration.

Hopping mode

Inband Peak


Frequency (MHz)	Level (dBm)
2476.975000	13.5
2476.975000	13.4

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2399.975000	-16.7	10.2	-6.5	PASS
2483.925000	-44.5	37.9	-6.6	PASS


Remark: Limit = Inband peak – 20dB

Band Edge



— Limit — Sum Level × Fail

Band Edge



— Limit — Sum Level × Fail


Measurement Setting

Setting	Instrument Value	Target Value
RBW	100.000 kHz	≤ 100.000 kHz
VBW	300.000 kHz	≥ 300.000 kHz
SweepPoints	1670	~ 1670
SweepTime	1.670 ms	AUTO
Reference Level	10.000 dBm	10.000 dBm
Attenuation	30.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	85 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.07 dB	0.50 dB


Remark: Cable loss 0.8dB was considered and set in system configuration.

9.8 Conducted spurious emission


Lowest Channel



Middle Channel



Highest Channel



Measurement Setting

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000
VBW	300.000 kHz	>= 300.000
SweepPoints	238	~ 238
SweepTime	23.700 ms	AUTO
Reference Level	-10.000 dBm	-30.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	3	3
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	14 / max. 40	max. 40
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

Remark: Cable loss 0.8dB was considered and set in system configuration.

- End of the Report -