



849 NW State Road 45
Newberry, FL 32669 USA
Ph: 888.472.2424 or 352.472.5500
Fax: 352.472.2030
Email: info@timcoengr.com
Website: www.timcoengr.com

FCC PART 15.249 TEST REPORT

UNLICENSED INTENTIONAL RADIATOR

Applicant	ONE WORLD TECHNOLOGIES, INC
Address	1428 PEARMAN DAIRY ROAD ANDERSON SOUTH CAROLINA 29625 USA
FCC ID	VMZEL2200
Model Number	EL2200
Product Description	AM/FM RADIO WITH BT
FCC Standard Applied	47 CFR §15.249
Date Sample Received	8/14/2014
Date Tested	8/19/2014
Tested By	Sid SANDERS
Approved By	Cory Leverett
Report Number	1439AUT14TestReport.docx
Test Results	☒ PASS ☐ FAIL

THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.
--

TABLE OF CONTENTS

GENERAL REMARKS	2
GENERAL INFORMATION.....	3
TEST RESULTS SUMMARY	3
TEST PROCEDURES	4
RADIATION INTERFERENCE.....	5
POWER LINE CONDUCTED INTERFERENCE	6
POWER LINE CONDUCTED INTERFERENCE	7
POWER LINE CONDUCTED INTERFERENCE	8
RADIATION INTERFERENCE.....	9
EMC EQUIPMENT LIST	10
TEST EQUIPMENT LIST	10

GENERAL REMARKS

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

Summary

The device under test does:

- ☒ fulfill the general approval requirements as identified in this test report
☐ not fulfill the general approval requirements as identified in this test report

Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025: 2005 requirements.

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, FL 32669

Authorized Signatory Name:



Sid Sanders
Project Manager:

Date: 8/20/2014

GENERAL INFORMATION

EUT Specification

The test results relate only to the items tested.			
Applicable Standard	Part 15.249		
EUT Description	AM/FM RADIO WITH BT		
FCC ID	VMZEL2200		
Model Number	EL2200		
Operating Frequency	TX:	RX: Same	
No. of Channels		Modulations	
EUT Power Source	☒ 110–120Vac/50– 60Hz		
	☒ DC Power		
	☐ Battery Operated Exclusively		
Test Item	☐ Prototype	☒ Pre-Production	☐ Production
Type of Equipment	☐ Fixed	☐ Mobile	☒ Portable
Antenna Connector	FCC Rules require that the antenna connector be unique.		
Test Facility	Timco Engineering Inc. located at 849 NW State Road 45 Newberry, FL 32669 USA.		
Conditions in the Test laboratory	Temperature: 27°C Relative humidity: 59%		
Test Exercise	The EUT was placed in continuous transmit mode of operation.		
Revision History of EUT	New		

Test Supporting Equipment

Supporting Device	Manufacturer	Model / FCC ID	Serial Number
N/A			

TEST RESULTS SUMMARY

Specification – Rules Part No.	RESULTS – Pass/Fail/NA
FCC Rule 15.249 Fundamental	Pass
FCC Rule 15.249 Harmonics & Spurious	Pass
Bandedge	Pass
Power Line Emissions 15.207	Pass

[TABLE OF CONTENTS](#)

APPLICANT: ONE WORLD TECHNOLOGIES, INC

FCC ID: VMZEL2200

REPORT: O\ONE WORLD_VMZ\1439AUT14\1439AUT14TestReport.docx

TEST PROCEDURES

Radiation Interference: ANSI C63.4-2003 using a spectrum analyzer, a preselector, a quasi-peak adapter, and an appropriate antenna. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100 kHz with an appropriate sweep speed and the video bandwidth was 300 kHz up to 1 GHz and 1 MHz with a video BW of 3 MHz above 1 GHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worst case emissions were reported. The spectrum was searched to at least the tenth (10) harmonic of the fundamental.

Formula Of Conversion Factors: The field strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the preselector was accounted for in the spectrum analyzer meter reading.

Example:

Freq (MHz)	Meter Reading	+ ACF	+ CL	= FS
33	20 dBuV	+ 10.36 dB	+ 0.5	= 30.86 dBuV/m @ 3m

Power Line Conducted Interference: The procedure used was ANSI C63.4-2003 using a 50uH LISN. Both lines were observed. The bandwidth of the spectrum analyzer was 10kHz with an appropriate sweep speed. The spectrum was scanned from 0.15 to 30 MHz.

Occupied Bandwidth: A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was printed. The vertical scale is set to -10 dBm per division.

ANSI C63.4-2003 10.1 Measurement Procedures: The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The EUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes. Emissions attenuated more than 20 dB below the permissible value are not reported.

[TABLE OF CONTENTS](#)

RADIATION INTERFERENCE

Rules Part No.: 15.249, 15.209

Requirements:

Frequency	Limits
Part 15.209	
9 to 490 kHz	2400/F (kHz) μ V/m @ 300 meters
490 to 1705 kHz	24000/F (kHz) μ V/m @ 30 meters
1705 kHz to 30 MHz	29.54 dB μ V/m @ 30 meters
30 – 88	40.0 dB μ V/m @ 3 meters
80 – 216	43.5 dB μ V/m @ 3 meters
216 – 960	46.0 dB μ V/m @ 3 meters
Above 960	54.0 dB μ V/m @ 3 meters
Part 15.249	
Fundamental 902 – 928 MHz	94.0 dB μ V/m @ 3 meters
Fundamental 2.4 – 2.4835 GHz	94.0 dB μ V/m @ 3 meters
Harmonics	54.0 dB μ V/m @ 3 meters

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBuV	Ant. Polarity	Coax Loss dB	Correction Factor dB / m	Field Strength dBuV / m	Margin dB
2,402.0	2,402.00	41.1	H	3.18	32.48	76.76	17.24
2,402.0	2,402.00	44.3	V	3.18	32.48	79.96	14.04
2402.0	4808.00	2.0	V	4.904	34.1	41.004	12.99
2402.0	7208.00	2.2	H	5.7236	35.82	43.004	10.25
2,443.0	2,443.00	42.2	H	3.21	32.57	77.98	16.02
2,443.0	2,443.00	43.6	V	3.21	32.57	79.38	14.02
2443.0	4886.00	1.8	V	4.943	34.1	40.84	13.15
2443.0	7329.00	1.6	H	5.79	35.77	43.16	10.83
2,480.0	2,480.00	43.0	H	3.24	32.66	78.90	15.10
2,480.0	2,480.00	44.1	V	3.24	32.66	80.00	14.00
2,480.0	2,483.50	-1.5	V	3.24	32.66	34.40	19.60
2480.0	7440	1.6	H	5.86	35.72	43.18	10.81

Results: Meet requirements

APPLICANT: ONE WORLD TECHNOLOGIES, INC

FCC ID: VMZEL2200

REPORT: O\ONE WORLD_VMZ\1439AUT14\1439AUT14TestReport.docx

POWER LINE CONDUCTED INTERFERENCE


Rules Part No.: 15.207

Requirements:

Frequency (MHz)	Quasi Peak Limits (dBuV)	Average Limits (dBuV)
0.15 – 0.5	66 – 56	56 – 46
0.5 – 5.0	56	46
5.0 – 30	60	50

Test Data: The attached graphs represent the emissions read for power line conducted for this device. Both lines were observed.

Rules Part No.: 15.207 Line 1



Date: 18.AUG.2014 17:15:20

Results: Meets Requirements

APPLICANT: ONE WORLD TECHNOLOGIES, INC


FCC ID: VMZEL2200

REPORT: O\ONE WORLD_VMZ\1439AUT14\1439AUT14TestReport.docx

POWER LINE CONDUCTED INTERFERENCE

Rules Part No.: 15.207 Neutral

PwrLineCond2



Date: 18.AUG.2014 17:16:50

Results: Meets Requirements

APPLICANT: ONE WORLD TECHNOLOGIES, INC

FCC ID: VMZEL2200

REPORT: O\ONE WORLD_VMZ\1439AUT14\1439AUT14TestReport.docx

POWER LINE CONDUCTED INTERFERENCE

Test Set Up Photo




APPLICANT: ONE WORLD TECHNOLOGIES, INC

FCC ID: VMZEL2200

REPORT: O\ONE WORLD_VMZ\1439AUT14\1439AUT14TestReport.docx

RADIATION INTERFERENCE

Test Set up Photo



[TABLE OF CONTENTS](#)

APPLICANT: ONE WORLD TECHNOLOGIES, INC

FCC ID: VMZEL2200

REPORT: O\ONE WORLD_VMZ\1439AUT14\1439AUT14TestReport.docx

EMC EQUIPMENT LIST

TEST EQUIPMENT LIST

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
Antenna: Biconnical	Eaton	94455-1	1057	06/14/13	06/14/15
Antenna: Log-Periodic	Eaton	96005	1243	05/31/13	05/31/15
LISN	Electro-Metrics	ANS-25/2	2604	01/07/14	01/07/16
LISN	Electro-Metrics	EM-7820	2682	02/26/13	02/26/15
3-Meter Semi-Anechoic Chamber	Panashield	N/A	N/A	12/31/13	12/31/15
Antenna: Double-Ridged Horn/ETS Horn 2	ETS-Lindgren	3117	00041534	10/05/12	10/05/14
EMI Test Receiver R & S ESIB 40	Rohde & Schwarz	ESIB 40	100274	08/12/14	08/12/16
Software: Field Strength Program	Timco	N/A	Version 4.0	12/12/99	12/12/99
EMI Test Receiver R & S ESU 40	Rohde & Schwarz	ESU 40	100320	03/11/14	03/11/16

*EMI RECEIVER SOFTWARE VERSION

[TABLE OF CONTENTS](#)

APPLICANT: ONE WORLD TECHNOLOGIES, INC

FCC ID: VMZEL2200

REPORT: O\ONE WORLD_VMZ\1439AUT14\1439AUT14TestReport.docx