



LCIE SUD EST
Laboratoire de Moirans
Z.I. Centr'Alp
170, Rue de Chatagnon
38430 MOIRANS – FRANCE

FCCID: VPQ-EZ3NDTNFC

RF Exposure Information KDB 447498

Calculations:

For transmitter:	RFID	
Frequency:	13.56	MHz
Prediction distance:	20.00	cm (Portable:0.5cm / Mobile:20cm)
Output Power:	-31.10	at the antenna terminal (dBm)
Antenna gain(typical):	0.00	(dBi)
MPE limit for uncontrolled exposure at prediction frequency:		1.00

Calculation:

Maximum peak output power at the antenna terminal:	-31.10	(dBm)
Maximum peak output power at the antenna terminal:	0.00	(mW)
Antenna gain(typical):	0.00	(dBi)
Maximum antenna gain:	1.00	(numeric)
Prediction distance:	20.00	(cm)
Prediction frequency:	13.56	(MHz)
MPE limit for uncontrolled exposure at prediction frequency:	1.00	(mW/cm ²)

Power density at prediction frequency: 0.0000002 (mW/cm²)

For transmitter:	WIFI 2.4GHz (worst case)	
Frequency:	2480.00	MHz
Prediction distance:	0.50	cm (Portable:0.5cm / Mobile:20cm)
Output Power:	-3.49	at the antenna terminal (dBm)
Antenna gain(typical):	2.50	(dBi)
MPE limit for uncontrolled exposure at prediction frequency:		1.00

Calculation:

Maximum peak output power at the antenna terminal:	-3.49	(dBm)
Maximum peak output power at the antenna terminal:	0.45	(mW)
Antenna gain(typical):	2.50	(dBi)
Maximum antenna gain:	1.78	(numeric)
Prediction distance:	20.00	(cm)
Prediction frequency:	2480.00	(MHz)
MPE limit for uncontrolled exposure at prediction frequency:	1.00	(mW/cm ²)

Power density at prediction frequency: 0.00016 (mW/cm²)

Calculation : $(P_d(2.4GHz) / L_{Pd}(2.4GHz)) + (P_d(FM) / L_{Pd}(FM)) = 0.0141 \text{ mW/cm}^2 < 1$

Colocation:	0.00	<1
--------------------	-------------	--------------

Conclusion:

The device complies with FCC's RF radiation exposure limit for general population as a **mobile** device (**d>20cm**) under the collocation conditions described above.