

FCC ID: VPYLB1ZM
Report No.: T201215W01-RP3

IC: 772C-LB1ZM
Ref. No.: T200915W04-RP3

Page: 1 / 108
Rev.: 01

RADIO TEST REPORT

FCC 47 CFR PART 15 SUBPART C

INDUSTRY CANADA RSS-247

Test Standard	FCC Part 15.247 IC RSS-247 issue 2 and IC RSS-GEN issue 5
Product name	Communication Module
Brand Name	muRata
Model No.	LBEE5QD1ZM
Test Result	Pass
Statements of Conformity	Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10: 2013 and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report.

The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc. (Wugu Laboratory).

Approved by:



Kevin Tsai
Deputy Manager

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	December 11, 2020	Initial Issue	ALL	Mita Wu
01	January 7, 2021	See the following Note Rev.(01)	ALL	Allison Chen

Note:
Rev.(01)

1. This test report is an addendum to the original test report T200915W04-RP3, the EUTs represent the original and this test report are assessed as identical in hardware and software, measurement results in the original report are fully leveraged in this test report without further verification test.

Table of contents

1.	GENERAL INFORMATION.....	4
1.1	EUT INFORMATION.....	4
1.2	EUT CHANNEL INFORMATION.....	5
1.3	ANTENNA INFORMATION.....	6
1.4	MEASUREMENT UNCERTAINTY	6
1.5	FACILITIES AND TEST LOCATION.....	7
1.6	INSTRUMENT CALIBRATION	7
1.7	SUPPORT AND EUT ACCESSORIES EQUIPMENT	8
1.8	TEST METHODOLOGY AND APPLIED STANDARDS.....	8
2.	TEST SUMMARY.....	9
3.	DESCRIPTION OF TEST MODES.....	10
3.1	THE WORST MODE OF OPERATING CONDITION	10
3.2	THE WORST MODE OF MEASUREMENT.....	11
4.	EUT DUTY CYCLE	12
5.	TEST RESULT	13
5.1	AC POWER LINE CONDUCTED EMISSION.....	13
5.2	6DB BANDWIDTH AND OCCUPIED BANDWIDTH(99%).....	14
5.3	OUTPUT POWER MEASUREMENT	22
5.4	POWER SPECTRAL DENSITY	25
5.5	CONDUCTED BANDEDGE AND SPURIOUS EMISSION.....	30
5.6	RADIATION BANDEDGE AND SPURIOUS EMISSION.....	40
	APPENDIX 1 - PHOTOGRAPHS OF EUT	

1. GENERAL INFORMATION

1.1 EUT INFORMATION

Applicant	Murata Manufacturing Co., Ltd. 1-10-1, Higashikotari, Nagaokakyo-shi, Kyoto 617-8555 Japan
Manufacturer	Murata Manufacturing Co., Ltd. 1-10-1, Higashikotari, Nagaokakyo-shi, Kyoto 617-8555 Japan
Equipment	Communication Module
Model No.	LBEE5QD1ZM
Model Discrepancy	N/A
Trade Name	muRata
Received Date	September 15, 2020
Date of Test	September 23 ~ October 21, 2020
Power Supply	Power from power supply.
HW Version	1.0
SW Version	1.0
EUT Serial #	Conducted : NO.1 Radiated : NO.12

Remark:

1. For more details, refer to the User's manual of the EUT.
2. Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.

1.2 EUT CHANNEL INFORMATION

Frequency Range	802.11b/g/n HT 20/ac VHT 20: 2412MHz ~ 2462MHz
Modulation Type	1. IEEE 802.11b mode: CCK 2. IEEE 802.11g mode: OFDM 3. IEEE 802.11n HT 20 MHz mode : OFDM 4. IEEE 802.11ac VHT 20 MHz mode : OFDM
Number of channel	1. IEEE 802.11b mode: 11 Channels 2. IEEE 802.11g mode: 11 Channels 3. IEEE 802.11n HT 20 MHz mode : 11 Channels 4. IEEE 802.11ac VHT20 MHz mode : 11 Channels

Remark:

Refer as ANSI C63.10: 2013 clause 5.6.1 Table 4 and RSS-GEN Table A1 for test channels

Number of frequencies to be tested		
Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
☐ 1 MHz or less	1	Middle
☐ 1 MHz to 10 MHz	2	1 near top and 1 near bottom
☒ More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

1.3 ANTENNA INFORMATION

Antenna Specification	No	Maker	P/N	Ant. Type	Gain (dBi)
	1	Molex	146153	dipole	3.2
	2	Molex	146187	dipole	3.4
	3	Murata	LBEE5QD1ZM-Antenna	Monopole (PCB)	3.6
Antenna Connector	No	Maker	P/N	Connector	
	1	Molex	146153	u.FL	
	2	Molex	146187	u.FL	
	3	Murata	LBEE5QD1ZM-Antenna	N/A	

1.4 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	+/- 1.2575
Emission bandwidth, 20dB bandwidth	+/- 0.0014
RF output power, conducted	+/- 1.14
Power density, conducted	+/- 1.40
3M Semi Anechoic Chamber / 30M~200M	+/- 4.12
3M Semi Anechoic Chamber / 200M~1000M	+/- 4.68
3M Semi Anechoic Chamber / 1G~8G	+/- 5.18
3M Semi Anechoic Chamber / 8G~18G	+/- 5.47
3M Semi Anechoic Chamber / 18G~26G	+/- 3.81
3M Semi Anechoic Chamber / 26G~40G	+/- 3.87

Remark:

- 1.This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2
2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

1.5 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan. (R.O.C.)

Test site	Test Engineer	Remark
AC Conduction Room	-	Not applicable, because EUT doesn't connect to AC Main Source direct.
Radiation	Jerry Chang	-
RF Conducted	Rick Lee	-

Remark: The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

1.6 INSTRUMENT CALIBRATION

RF Conducted Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Coaxial Cable	Woken	WC12	CC003	06/29/2020	06/28/2021
Signal Analyzer	R&S	FSV 40	101073	09/17/2020	09/16/2021
EXA Signal Analyzer	KEYSIGHT	N9010B	MY55460167	09/07/2020	09/06/2021
Power Meter	Anritsu	ML2487A	6K00003260	05/21/2020	05/20/2021
Power Seneor	Anritsu	MA2490A	032910	05/21/2020	05/20/2021
Software	N/A				

3M 966 Chamber Test Site					
Equipment	Manufacturer	Model	Serial Number	Cal Date	Cal Due
Band Reject Filters	MICRO TRONICS	BRM 50702	120	02/25/2020	02/24/2021
Bilog Antenna	Sunol Sciences	JB3	A030105	07/24/2020	07/23/2021
Coaxial Cable	HUBER SUHNER	SUCOFLEX 104PEA	20995	02/25/2020	02/24/2021
Coaxial Cable	EMCI	EMC105	190914+25111	09/19/2020	09/19/2021
Digital Thermo-Hygro Meter	WISEWIND	1206	D07	01/15/2020	01/14/2021
double Ridged Guide Horn Antenna	ETC	MCTD 1209	DRH13M02003	10/04/2019	10/03/2020
Loop Ant	COM-POWER	AL-130	121051	03/27/2020	03/26/2021
Pre-Amplifier	EMEC	EM330	060609	02/25/2020	02/24/2021
Pre-Amplifier	HP	8449B	3008A00965	02/25/2020	02/24/2021
PSA Series Spectrum Analyzer	Agilent	E4446A	MY46180323	07/24/2020	07/23/2021
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Software	e3 6.11-20180413				

Remark: Each piece of equipment is scheduled for calibration once a year.

1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT

EUT Accessories Equipment					
No.	Equipment	Brand	Model	Series No.	FCC ID
	N/A				

Support Equipment					
No.	Equipment	Brand	Model	Series No.	FCC ID
1	DC Power Source	Agilent	E3640A	N/A	N/A

1.8 TEST METHODOLOGY AND APPLIED STANDARDS

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10:2013, FCC Part 2, FCC Part 15.247, RSS-247 Issue 2 and RSS-GEN Issue 5.

2. TEST SUMMARY

FCC Standard Section	IC Standard Section	Report Section	Test Item	Result
15.203	-	1.3	Antenna Requirement	Pass
15.207(a)	RSS-GEN 8.8	4.1	AC Conducted Emission	N/A
15.247(a)(2)	RSS-247(5.2)(a)	4.2	6 dB Bandwidth	Pass
-	RSS-GEN 6.7	4.2	Occupied Bandwidth (99%)	Pass
15.247(b)(3)	RSS-247(5.4)(d)	4.3	Output Power Measurement	Pass
15.247(e)	RSS-247(5.2)(b)	4.4	Power Spectral Density	Pass
15.247(d)	RSS-247(5.5)	4.5	Conducted Band Edge	Pass
15.247(d)	RSS-247(5.5)	4.5	Conducted Emission	Pass
15.247(d)	RSS-GEN 8.9, 8.10	4.6	Radiation Band Edge	Pass
15.247(d)	RSS-GEN 8.9, 8.10	4.6	Radiation Spurious Emission	Pass

3. DESCRIPTION OF TEST MODES

3.1 THE WORST MODE OF OPERATING CONDITION

Operation mode	IEEE 802.11b mode :1Mbps IEEE 802.11g mode :6Mbps IEEE 802.11n HT20 mode :MCS0
Test Channel Frequencies	IEEE 802.11b mode : 1. Lowest Channel : 2412MHz 2. Middle Channel : 2437MHz 3. Highest Channel : 2462MHz IEEE 802.11g mode : 1. Lowest Channel : 2412MHz 2. Middle Channel : 2437MHz 3. Highest Channel : 2462MHz IEEE 802.11n HT20 mode : 1. Lowest Channel : 2412MHz 2. Middle Channel : 2437MHz 3. Highest Channel : 2462MHz
Operation Transmitter	IEEE 802.11b mode :1T1R IEEE 802.11g mode :1T1R IEEE 802.11n HT20 mode : 1T1R

Remark:

1. EUT pre-scanned data rate of output power for each mode, the worst data rate were recorded in this report.
2. The mode IEEE 802.11ac VHT 20 MHz is only different in control messages with IEEE 802.11n HT 20 MHz, and have same power setting. Therefore, the highest power(IEEE 802.11n HT 20 MHz) was test conducted and radiated measurement and recorded in this report.

3.2 THE WORST MODE OF MEASUREMENT

PCB Test mode

Radiated Emission Measurement Above 1G	
Test Condition	Radiated Emission Above 1G
Power supply Mode	Mode 1: EUT power by Power supply
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4
Worst Position	☐ Placed in fixed position. ☒ Placed in fixed position at X-Plane (E2-Plane) ☐ Placed in fixed position at Y-Plane (E1-Plane) ☐ Placed in fixed position at Z-Plane (H-Plane)

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by Power supply
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Remark:

1. The worst mode was record in this test report.
2. EUT pre-scanned in three axis ,X,Y, Z and two polarity, for radiated measurement. The worst case(X-Plane) were recorded in this report.

Dipole Test mode

Radiated Emission Measurement Above 1G	
Test Condition	Radiated Emission Above 1G
Power supply Mode	Mode 1: EUT power by Power supply
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4
Worst Position	☐ Placed in fixed position. ☐ Placed in fixed position at X-Plane (E2-Plane) ☒ Placed in fixed position at Y-Plane (E1-Plane) ☐ Placed in fixed position at Z-Plane (H-Plane)

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by Power supply
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Remark:

1. The worst mode was record in this test report.
2. EUT pre-scanned in three axis ,X,Y, Z and two polarity, for radiated measurement. The worst case(Y-Plane) were recorded in this report.

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

4. EUT DUTY CYCLE

Temperature: 24.2°C

Humidity: 56.5% RH

Tested by: Rick Lee

Test date: September 23, 2020

Temperature: 23.9°C


Humidity: 55% RH

Tested by: Rick Lee


Test date: September 29, 2020

Duty Cycle				
Configuration	Duty Cycle (%)	Duty Factor (dB) =10*log (1/Duty Cycle)	1/T (kHz)	VBW setting (kHz)
802.11b	98.77%	0.05	0.12	0.01
802.11g	96.85%	0.14	0.32	1.00
802.11n HT20	97.93%	0.09	0.21	1.00
802.11ac VHT20	97.74%	0.10	0.21	1.00


802.11b




802.11g



802.11n HT20



802.11ac VHT20



5. TEST RESULT

5.1 AC POWER LINE CONDUCTED EMISSION

5.1.1 Test Limit

According to §15.207(a)(2) and RSS-GEN section 8.8,

Frequency Range (MHz)	Limits(dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50


* Decreases with the logarithm of the frequency.

5.1.2 Test Procedure

Test method Refer as ANSI C63.10: 2013 clause 6.2,

1. The EUT was placed on a non-conducted table, which is 0.8m above horizontal ground plane and 0.4m above vertical ground plane.
2. EUT connected to the line impedance stabilization network (LISN)
3. Receiver set RBW of 9kHz and Detector Peak, and note as quasi-peak and average.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Recorded Line for Neutral and Line.

5.1.3 Test Setup



5.1.4 Test Result

Not applicable, because EUT doesn't connect to AC Main Source direct.

5.2 6dB BANDWIDTH AND OCCUPIED BANDWIDTH(99%)

5.2.1 Test Limit

According to §15.247(a)(2) and RSS-247 section 5.2(a),

6 dB Bandwidth :

Limit	Shall be at least 500kHz
-------	--------------------------

Occupied Bandwidth(99%) : For reporting purposes only.

5.2.2 Test Procedure

Test method Refer as ANSI C63.10: 2013,

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 100kHz, VBW = 300kHz and Detector = Peak, to measurement 6 dB Bandwidth.
4. SA set RBW = 1% ~ 5% OBW, VBW = three times the RBW and Detector = Peak, to measurement 99% Bandwidth
5. Measure and record the result of 6 dB Bandwidth and 99% Bandwidth. in the test report.

5.2.3 Test Setup



5.2.4 Test Result

Temperature: 24.2°C

Humidity: 56.5% RH

Tested by: Rick Lee

Test date: September 23, 2020

Test mode: IEEE 802.11b mode / 2412-2462 MHz				
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	6dB limit (kHz)
Low	2412	13.488	10.10	≥500
Mid	2437	13.475	10.10	
High	2462	13.452	10.11	

Test mode: IEEE 802.11g mode / 2412-2462 MHz				
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	6dB limit (kHz)
Low	2412	16.817	16.41	≥500
Mid	2437	16.784	16.40	
High	2462	16.829	16.39	

Test mode: IEEE 802.11n HT 20 MHz mode / 2412-2462 MHz				
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	6dB limit (kHz)
Low	2412	17.716	17.60	≥500
Mid	2437	17.746	17.59	
High	2462	17.723	17.60	




Report No.: T201215W01-RP3


Ref. No.: T200915W04-RP3


Rev.: 01

Test Data

6dB BANDWIDTH










Test Data

BANDWIDTH 99%







5.3 OUTPUT POWER MEASUREMENT

5.3.1 Test Limit

According to §15.247(b) and RSS-247 section 5.4(d),

Peak output power :

For systems using digital modulation in the 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt(30 dBm) and the e.i.r.p. shall not exceed 4Watt(36 dBm), base on the use of antennas with directional gain not exceed 6 dBi If transmitting antennas of directional gain greater than 6dBi are used the peak output power the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Limit	☒ Antenna not exceed 6 dBi : 30dBm ☐ Antenna with DG greater than 6 dBi : [Limit = 30 – (DG – 6)] ☐ Point-to-point operation :
-------	---


Average output power : For reporting purposes only.

5.3.2 Test Procedure

Test method Refer as ANSI C63.10:2013.

1. The EUT RF output connected to the power meter by RF cable.
2. Setting maximum power transmit of EUT.
3. The path loss was compensated to the results for each measurement.
4. Measure and record the result of Peak output power and Average output power. in the test report.

5.3.3 Test Setup



Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

5.3.4 Test Result

Temperature: 25°C

Humidity: 50% RH

Tested by: Rick Lee

Test Date: October 21, 2020

Peak output power :

Wifi 2.4G										
Config	CH	Freq. (MHz)	power setting	PK Power (dBm)	PK Total Power (W)	EIRP PK Total Power (dBm)	EIRP PK Total Power (W)	DG (dBi)	Limit (dBm)	EIRP Limit (dBm)
			chain0	chain0						
IEEE 802.11b Data rate: 1Mbps	Low	2412	18	25.41	0.3475	29.01	0.7962	3.6	30	36
	Mid	2437	18	25.36	0.3436	28.96	0.7870			
	High	2462	18	25.39	0.3459	28.99	0.7925			
IEEE 802.11g Data rate: 6Mbps	Low	2412	16	25.22	0.3327	28.82	0.7621			
	Mid	2437	19	25.21	0.3319	28.81	0.7603			
	High	2462	16	25.39	0.3459	28.99	0.7925			
IEEE 802.11n HT20 Data rate: MCS0	Low	2412	14	25.30	0.3388	28.90	0.7762			
	Mid	2437	18	25.31	0.3396	28.91	0.7780			
	High	2462	14	25.26	0.3357	28.86	0.7691			
IEEE 802.11acV HT 20 Data rate: MCS0	Low	2412	15	24.24	0.2655	24.24	0.2655			
	Mid	2437	17	25.58	0.3614	25.58	0.3614			
	High	2462	15	24.19	0.2624	24.19	0.2624			

Average output power :

Wifi 2.4G			
Config	CH	Freq. (MHz)	AV Power(dBm)
			chain0
IEEE 802.11b Data rate: 1Mbps	Low	2412	18.51
	Mid	2437	18.50
	High	2462	18.56
IEEE 802.11g Data rate: 6Mbps	Low	2412	15.83
	Mid	2437	18.76
	High	2462	15.69
IEEE 802.11n HT20 Data rate: MCS0	Low	2412	14.53
	Mid	2437	17.89
	High	2462	14.53
IEEE 802.11ac VHT 20 Data rate: MCS0	Low	2412	14.84
	Mid	2437	17.54
	High	2462	14.89

5.4 POWER SPECTRAL DENSITY

5.4.1 Test Limit

According to §15.247(e) and RSS-247 section 5.2(b),

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


Limit	☒ Antenna not exceed 6 dBi : 8dBm ☐ Antenna with DG greater than 6 dBi : [Limit = 8 – (DG – 6)] ☐ Point-to-point operation :
-------	---

5.4.2 Test Procedure

Test method Refer as ANSI C63.10:2013

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 3kHz, VBW = 30kHz, Span = 1.5 times DTS Bandwidth (6 dB BW), Detector = Peak, Sweep Time = Auto and Trace = Max hold.
4. The path loss and Duty Factor were compensated to the results for each measurement by SA.
5. Mark the maximum level.
6. Measure and record the result of power spectral density. in the test report.

5.4.3 Test Setup



5.4.4 Test Result

Temperature: 24.2°C

Humidity: 56.5% RH

Tested by: Rick Lee

Test date: September 23, 2020

Test mode: IEEE 802.11b mode / 2412-2462 MHz			
Channel	Frequency (MHz)	Chain 0 PPSD (dBm)	Limit (dBm)
Low	2412	-3.99	8
Mid	2437	-2.78	
High	2462	-2.8	

Test mode: IEEE 802.11g mode / 2412-2462 MHz			
Channel	Frequency (MHz)	Chain 0 PPSD (dBm)	Limit (dBm)
Low	2412	-8.98	8
Mid	2437	-9.28	
High	2462	-9.83	


Test mode: IEEE 802.11n HT 20 MHz mode / 2412-2462 MHz			
Channel	Frequency (MHz)	Chain 0 PPSD (dBm)	Limit (dBm)
Low	2412	-8.39	8
Mid	2437	-7.59	
High	2462	-9.13	

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Rev.: 01

Test Data






Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3


Rev.: 01



Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Rev.: 01



5.5 CONDUCTED BANDEDGE AND SPURIOUS EMISSION

5.5.1 Test Limit

According to §15.247(d) and RSS-247 section 5.5,

In any 100 kHz bandwidth outside the authorized frequency band,


Non-restricted bands shall be attenuated at least 20 dB/30 dB relative to the maximum PSD level in 100 kHz by RF conducted or a radiated measurement which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

5.5.2 Test Procedure

Test method Refer as ANSI C63.10:2013.

1. EUT RF output port connected to the SA by RF cable, and the path loss was compensated to result.
2. SA setting, RBW=100kHz, VBW=300kHz, Detector=Peak, Trace mode = max hold, SWT = Auto.
3. In any 100 kHz bandwidth outside the authorized frequency band, shall be attenuated at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when conducted power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

5.5.3 Test Setup



Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

5.5.4 Test Result

Test Data

Temperature: 24.2°C

Humidity: 56.5% RH

Tested by: Rick Lee

Test date: September 23, 2020


Temperature: 24.1°C

Humidity: 56.1% RH

Tested by: Rick Lee

Test date: October 8, 2020

Chain 0:








Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Rev.: 01










Report No.: T201215W01-RP3


Ref. No.: T200915W04-RP3


Rev.: 01











5.6 RADIATION BANDEDGE AND SPURIOUS EMISSION

5.6.1 Test Limit

FCC according to §15.247(d), §15.209 and §15.205,

IC according to RSS-247 section 5.5, RSS-Gen, Section 8.9 and 8.10

In any 100 kHz bandwidth outside the authorized frequency band, all harmonic and spurious must be least 20 dB below the highest emission level with the authorized frequency band. Radiation emission which fall in the restricted bands must also follow the FCC section 15.209 as below limit in table.

Below 30 MHz

Frequency	Field Strength (microvolts/m)	Magnetic H-Field (microamperes/m)	Measurement Distance (metres)
9-490 kHz	2,400/F (F in kHz)	2,400/F (F in kHz)	300
490-1,705 kHz	24,000/F (F in kHz)	24,000/F (F in kHz)	30
1.705-30 MHz	30	N/A	30

Above 30 MHz

Frequency	Field Strength (microvolts/m)	Measurement Distance (metres)
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark:

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

IC according to RSS-247 section 5.5, RSS-Gen, Section 8.9 and 8.10

RSS-Gen Table 3 and Table 5 – General Field Strength Limits for Transmitters and Receivers at Frequencies Above 30 MHz ^(Note)

Frequency (MHz)	Field Strength microvolts/m at 3 metres (watts, e.i.r.p.)	
	Transmitters	Receivers
30-88	100 (3 nW)	100 (3 nW)
88-216	150 (6.8 nW)	150 (6.8 nW)
216-960	200 (12 nW)	200 (12 nW)
Above 960	500 (75 nW)	500 (75 nW)

Note: Measurements for compliance with the limits in table 3 may be performed at distances other than 3 metres, in accordance with Section 6.6.

RSS-Gen Table 6: General Field Strength Limits for Transmitters at Frequencies Below 30 MHz (Transmit)

Frequency	Magnetic field strength (H-Field) ($\mu\text{A/m}$)	Measurement Distance (m)
9-490 kHz ^{Note}	6.37/F (F in kHz)	300
490-1,705 kHz	63.7/F (F in kHz)	30
1.705-30 MHz	0.08	30

Note: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

5.6.2 Test Procedure

Test method Refer as ANSI C63.10:2013.

1. The EUT is placed on a turntable, Above 1 GHz is 1.5m and below 1 GHz is 0.8m above ground plane. The EUT Configured un accordance with ANSI C63.10: 2013, and the EUT set in a continuous mode.

2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. And EUT is set 3m away from the receiving antenna, which is scanned from 1m to 4m above the ground plane to find out the highest emissions. Measurement are made polarized in both the vertical and the horizontal positions with antenna.

3. Span shall wide enough to full capture the emission measured. The SA from 9kHz to 26.5GHz set to the low, Mid and High channels with the EUT transmit.

Note: No emission found between lowest internal used/generated frequency to 30MHz (9KHz~30MHz)

Remark:

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open are test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

4. The SA setting following :

(1) Below 1G : RBW = 100kHz, VBW $\geq$ 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.

(2) Above 1G :

(2.1) For Peak measurement : RBW = 1MHz, VBW $\geq$ 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.


(2.2) For Average measurement : RBW = 1MHz, VBW

'If Duty Cycle $\geq$ 98%, VBW=10Hz.


'If Duty Cycle < 98%, VBW=1/T.

5.6.3 Test Setup


9kHz ~ 30MHz



30MHz ~ 1GHz



Above 1 GHz




5.6.4 Test Result

Type: Dipole Antenna


Band Edge Test Data

Test Mode	IEEE 802.11b Low CH 2412MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 26, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Peak	51.51	1.25	52.76	74.00	-21.24
2390.00	Average	40.56	1.25	41.81	54.00	-12.19

Test Mode	IEEE 802.11b Low CH 2412MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 26, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak / Average		




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Peak	52.87	1.25	54.12	74.00	-19.88
2390.00	Average	41.73	1.25	42.98	54.00	-11.02

Test Mode	IEEE 802.11b High CH 2462MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 26, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Peak	51.57	1.62	53.19	74.00	-20.81
2483.50	Average	41.23	1.62	42.85	54.00	-11.15

Test Mode	IEEE 802.11b High CH 2462MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 26, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak / Average		




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Peak	51.30	1.62	52.92	74.00	-21.08
2483.50	Average	40.15	1.62	41.77	54.00	-12.23

Test Mode	IEEE 802.11g Low CH 2412MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 26, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Peak	61.98	1.25	63.23	74.00	-10.77
2390.00	Average	39.07	1.25	40.32	54.00	-13.68

Test Mode	IEEE 802.11g Low CH 2412MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 26, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak / Average		




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Peak	70.44	1.25	71.69	74.00	-2.31
2390.00	Average	44.84	1.25	46.09	54.00	-7.91

Test Mode	IEEE 802.11g High CH 2462MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 26, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Peak	61.46	1.62	63.08	74.00	-10.92
2483.50	Average	43.52	1.62	45.14	54.00	-8.86

Test Mode	IEEE 802.11g High CH 2462MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 26, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak / Average		




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Peak	69.17	1.62	70.79	74.00	-3.21
2483.50	Average	50.54	1.62	52.16	54.00	-1.84

Test Mode	IEEE 802.11n HT20 Low CH 2412MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 26, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Peak	61.55	1.25	62.80	74.00	-11.20
2390.00	Average	44.40	1.25	45.65	54.00	-8.35

Test Mode	IEEE 802.11 n20 Low CH 2412MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 26, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak / Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Peak	62.55	1.25	63.80	74.00	-10.20
2390.00	Average	45.86	1.25	47.11	54.00	-6.89


Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Page: 55 / 108


Rev.: 01

Test Mode	IEEE 802.11n HT20 High CH 2462MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 26, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Peak	62.63	1.62	64.25	74.00	-9.75
2483.50	Average	49.96	1.62	51.58	54.00	-2.42

Test Mode	IEEE 802.11n20 High CH 2462MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 26, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak / Average		




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Peak	69.17	1.62	70.79	74.00	-3.21
2483.50	Average	50.96	1.62	52.58	54.00	-1.42

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Below 1G Test Data


Test Mode	Mode 1	Temp/Hum	24.5(°C)/ 40%RH
Test Item	30MHz-1GHz	Test Date	September 27, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak	Test Voltage	



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
41.64	Peak	43.87	-10.90	32.97	40.00	-7.03
105.66	Peak	49.33	-11.23	38.10	43.50	-5.40
442.25	Peak	38.16	-4.53	33.63	46.00	-12.37
638.19	Peak	35.96	-0.53	35.43	46.00	-10.57
749.74	Peak	30.75	0.72	31.47	46.00	-14.53
925.31	Peak	26.68	3.38	30.06	46.00	-15.94

Note: No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)

Test Mode	Mode 1	Temp/Hum	24.5(°C)/ 40%RH
Test Item	30MHz-1GHz	Test Date	September 27, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak	Test Voltage	



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
42.61	Peak	38.79	-11.59	27.20	40.00	-12.80
105.66	Peak	47.55	-11.23	36.32	43.50	-7.18
442.25	Peak	37.18	-4.53	32.65	46.00	-13.35
539.25	Peak	42.45	-2.43	40.02	46.00	-5.98
624.61	Peak	43.04	-1.02	42.02	46.00	-3.98
875.84	Peak	34.88	2.70	37.58	46.00	-8.42


Note: No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Above 1G Test Data

Test Mode	IEEE 802.11b Low CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 26, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4824.00	Peak	38.66	6.37	45.03	74.00	-28.97
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11b Low CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 26, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4824.00	Peak	38.50	6.37	44.87	74.00	-29.13
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11b Mid CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 26, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4874.00	Peak	39.03	6.41	45.44	74.00	-28.56
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11b Mid CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 26, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4874.00	Peak	38.85	6.41	45.26	74.00	-28.74
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11b High CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 26, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4924.00	Peak	39.01	6.59	45.60	74.00	-28.40
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11b High CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 26, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4924.00	Peak	38.72	6.59	45.31	74.00	-28.69
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11g Low CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 26, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4824.00	Peak	38.87	6.37	45.24	74.00	-28.76
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11g Low CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 26, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4824.00	Peak	39.60	6.37	45.97	74.00	-28.03
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11g Mid CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 26, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4874.00	Peak	39.28	6.41	45.69	74.00	-28.31
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11g Mid CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 26, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4874.00	Peak	39.34	6.41	45.75	74.00	-28.25
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11g High CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 26, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4924.00	Peak	39.38	6.59	45.97	74.00	-28.03
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11g High CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 26, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4924.00	Peak	38.42	6.59	45.01	74.00	-28.99
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT20 Low CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 26, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4824.00	Peak	36.75	6.37	43.12	74.00	-30.88
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT20 Low CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 26, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4824.00	Peak	36.12	6.37	42.49	74.00	-31.51
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11n HT20 Mid CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 26, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4874.00	Peak	36.48	6.41	42.89	74.00	-31.11
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11n HT20 Mid CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 26, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4874.00	Peak	35.83	6.41	42.24	74.00	-31.76
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT20 High CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 26, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4924.00	Peak	35.22	6.59	41.81	74.00	-32.19
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT20 High CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 26, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4924.00	Peak	36.78	6.59	43.37	74.00	-30.63
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Type: Monopole Antenna (PCB)


Band Edge Test Data

Test Mode	IEEE 802.11b Low CH 2412MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 29, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Peak	51.16	1.25	52.41	74.00	-21.59
2390.00	Average	41.93	1.25	43.18	54.00	-10.82

Test Mode	IEEE 802.11b Low CH 2412MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 29, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak / Average		




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Peak	51.89	1.25	53.14	74.00	-20.86
2390.00	Average	43.59	1.25	44.84	54.00	-9.16

Test Mode	IEEE 802.11b High CH 2462MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 29, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Peak	49.95	1.62	51.57	74.00	-22.43
2483.50	Average	39.80	1.62	41.42	54.00	-12.58

Test Mode	IEEE 802.11b High CH 2462MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 29, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak / Average		




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Peak	51.11	1.62	52.73	74.00	-21.27
2483.50	Average	41.51	1.62	43.13	54.00	-10.87

Test Mode	IEEE 802.11g Low CH 2412MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 29, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2385.00	Peak	60.72	1.24	61.96	74.00	-12.04
2385.00	Average	47.47	1.24	48.71	54.00	-5.29
2388.24	Peak	61.63	1.24	62.87	74.00	-11.13
2388.24	Average	49.90	1.24	51.14	54.00	-2.86
2390.00	Peak	57.65	1.25	58.90	74.00	-15.10
2390.00	Average	46.54	1.25	47.79	54.00	-6.21

Test Mode	IEEE 802.11g Low CH 2412MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 29, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak / Average		




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Peak	68.10	1.25	69.35	74.00	-4.65
2390.00	Average	50.13	1.25	51.38	54.00	-2.62

Test Mode	IEEE 802.11g High CH 2462MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 29, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Peak	60.30	1.62	61.92	74.00	-12.08
2483.50	Average	41.47	1.62	43.09	54.00	-10.91
2486.30	Peak	58.74	1.62	60.36	74.00	-13.64
2486.30	Average	40.42	1.62	42.04	54.00	-11.96

Test Mode	IEEE 802.11g High CH 2462MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 29, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak / Average		




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Peak	64.14	1.62	65.76	74.00	-8.24
2483.50	Average	45.81	1.62	47.43	54.00	-6.57

Test Mode	IEEE 802.11n HT20 Low CH 2412MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 29, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Peak	57.55	1.25	58.80	74.00	-15.20
2390.00	Average	41.40	1.25	42.65	54.00	-11.35

Test Mode	IEEE 802.11 n20 Low CH 2412MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 29, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak / Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Peak	62.34	1.25	63.59	74.00	-10.41
2390.00	Average	47.19	1.25	48.44	54.00	-5.56


Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Page: 87 / 108


Rev.: 01

Test Mode	IEEE 802.11n HT20 High CH 2462MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 29, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Peak	51.12	1.62	52.74	74.00	-21.26
2483.50	Average	40.78	1.62	42.40	54.00	-11.60


Test Mode	IEEE 802.11n20 High CH 2462MHz	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Band Edge	Test Date	September 29, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak / Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Peak	59.39	1.62	61.01	74.00	-12.99
2483.50	Average	44.63	1.62	46.25	54.00	-7.75

Below 1G Test Data


Test Mode	Mode 1	Temp/Hum	24.5(°C)/ 40%RH
Test Item	30MHz-1GHz	Test Date	September 29, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak	Test Voltage	



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
77.53	Peak	42.89	-15.25	27.64	40.00	-12.36
162.89	Peak	38.20	-10.42	27.78	43.50	-15.72
420.91	Peak	35.23	-5.02	30.21	46.00	-15.79
530.52	Peak	30.33	-2.75	27.58	46.00	-18.42
722.58	Peak	27.01	0.42	27.43	46.00	-18.57
905.91	Peak	25.89	3.19	29.08	46.00	-16.92

Note: No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)

Test Mode	Mode 1	Temp/Hum	24.5(°C)/ 40%RH
Test Item	30MHz-1GHz	Test Date	September 29, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak	Test Voltage	



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
98.87	Peak	41.41	-13.36	28.05	43.50	-15.45
228.85	Peak	41.04	-11.29	29.75	46.00	-16.25
372.41	Peak	29.06	-6.60	22.46	46.00	-23.54
557.68	Peak	28.96	-2.42	26.54	46.00	-19.46
638.19	Peak	36.10	-0.53	35.57	46.00	-10.43
928.22	Peak	25.13	3.49	28.62	46.00	-17.38


Note: No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Above 1G Test Data

Test Mode	IEEE 802.11b Low CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 29, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBUV)	Factor (dB)	Actual FS (dBUV/m)	Limit @3m (dBUV/m)	Margin (dB)
4824.00	Peak	38.75	6.37	45.12	74.00	-28.88
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11b Low CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 29, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4824.00	Peak	38.62	6.37	44.99	74.00	-29.01
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11b Mid CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 29, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4874.00	Peak	39.21	6.41	45.62	74.00	-28.38
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11b Mid CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 29, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4874.00	Peak	39.21	6.41	45.62	74.00	-28.38
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11b High CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 29, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4924.00	Peak	39.76	6.59	46.35	74.00	-27.65
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11b High CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 29, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4924.00	Peak	38.97	6.59	45.56	74.00	-28.44
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11g Low CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 29, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4824.00	Peak	39.23	6.37	45.60	74.00	-28.40
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11g Low CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 29, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4824.00	Peak	39.74	6.37	46.11	74.00	-27.89
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11g Mid CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 29, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4874.00	Peak	39.50	6.41	45.91	74.00	-28.09
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11g Mid CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 29, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4874.00	Peak	39.67	6.41	46.08	74.00	-27.92
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11g High CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 29, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4924.00	Peak	39.60	6.59	46.19	74.00	-27.81
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11g High CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 29, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4924.00	Peak	39.30	6.59	45.89	74.00	-28.11
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT20 Low CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 29, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4824.00	Peak	36.93	6.37	43.30	74.00	-30.70
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT20 Low CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 29, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4824.00	Peak	36.37	6.37	42.74	74.00	-31.26
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11n HT20 Mid CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 29, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4874.00	Peak	36.81	6.41	43.22	74.00	-30.78
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11n HT20 Mid CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 29, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4874.00	Peak	36.05	6.41	42.46	74.00	-31.54
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T201215W01-RP3

Ref. No.: T200915W04-RP3

Test Mode	IEEE 802.11n HT20 High CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 29, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4924.00	Peak	35.88	6.59	42.47	74.00	-31.53
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT20 High CH	Temp/Hum	24.5(°C)/ 40%RH
Test Item	Harmonic	Test Date	September 29, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4924.00	Peak	37.11	6.59	43.70	74.00	-30.30
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

- End of Test Report -