

FCC Test Report

FCC ID : VQK-F04G
Equipment : Mobile Phone
Model No. : F-04G
Brand Name : FUJITSU
Applicant : FUJITSU LIMITED
Address : 1-1, Kamikodanaka 4-chome, Nakahara-ku,
Kawasaki 211-8588, Japan
Standard : 47 CFR FCC Part 15.247
Received Date : Dec. 17, 2014
Tested Date : Mar. 06 ~ Mar. 12, 2015

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:


Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	8
1.4	The Equipment List	9
1.5	Test Standards	10
1.6	Measurement Uncertainty	10
2	TEST CONFIGURATION	11
2.1	Testing Condition	11
2.2	The Worst Test Modes and Channel Details	11
3	TRANSMITTER TEST RESULTS.....	12
3.1	Conducted Emissions.....	12
3.2	6dB and Occupied Bandwidth	17
3.3	RF Output Power	20
3.4	Power Spectral Density	22
3.5	Unwanted Emissions into Restricted Frequency Bands	24
3.6	Unwanted Emissions into Non-Restricted Frequency Bands	48
4	TEST LABORATORY INFORMATION	58

Release Record

Report No.	Version	Description	Issued Date
FR4D1701AC	Rev. 01	Initial issue	Apr. 01, 2015

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.575MHz 40.82 (Margin -5.18dB) - AV	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 4924.00MHz 49.78 (Margin -4.22dB) - AV	Pass
15.247(b)(3)	Fundamental Emission Output Power	Power [dBm]: 20.17	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

1 General Description

1.1 Information

1.1.1 Product Details

Product Name	Mobile Phone
Brand Name	FUJITSU
Model Name	F-04G
IMEI Code	357241060024329 / 357241060024287
H/W Version	v2.1.0
S/W Version	R21.5e

1.1.2 Specification of the Equipment under Test (EUT)

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N _{TX})	Data Rate / MCS
2400-2483.5	b	2412-2462	1-11 [11]	1	1-11 Mbps
2400-2483.5	g	2412-2462	1-11 [11]	1	6-54 Mbps
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	2	MCS 0-15

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.
 Note 2: 802.11b uses a combination of DSSS-DBPSK, DQPSK, CCK modulation.
 Note 3: 802.11g/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.

1.1.3 Antenna Details

Ant.	Type	Gain (dBi)	Connector	Remark
0	$\lambda/4$ Monopole	-6.48	---	---
1	$\lambda/4$ Monopole	-7.57	---	---

1.1.4 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	AC adapter: (normal output rating) 5.0Vdc, 1.8A (quick charge output rating) 9.0Vdc, 1.8A Battery: 3.75Vdc
-------------------	---

1.1.5 Accessories

No.	Equipment	Description
1	Cradle	Brand Name: Fujitsu Limited Model Name: F50 Input rating: (quick charge) 9.0Vdc, 1.5A Output rating: (quick charge) 9.0Vdc, 1.5A
2	Battery (Unremovable)	Brand Name: NTT Docomo Model Name: CA54310-0061 Power Rating: 3.75Vdc, 3120mAh, 12Wh

1.1.6 Channel List

Frequency band (MHz)	
802.11 b / g / n HT20	
Channel	Frequency(MHz)
1	2412
2	2417
3	2422
4	2427
5	2432
6	2437
7	2442
8	2447
9	2452
10	2457
11	2462

1.1.7 Test Tool and Duty Cycle

Test Tool	QRCT, version 3.0.54.0		
Duty Cycle and Duty Factor	Mode	Duty cycle (%)	Duty factor (dB)
	11b	100.00%	0.00
	11g	98.58%	0.06
	HT20	96.45%	0.16

1.1.8 Power Setting



Modulation Mode	Test Frequency (MHz)	Power Set
11b	2412	17
11b	2437	17
11b	2462	17
11g	2412	15
11g	2437	15
11g	2462	15
HT20	2412	14
HT20	2437	14
HT20	2462	14

1.2 Local Support Equipment List

Support Equipment List						
No.	Equipment	Brand	Model	S/N	FCC ID	Signal cable / Length (m)
1	Adapter	NTT docomo	AC Adaptor 05	---	---	---
2	Earphone	APPLE	MD827FE/A	6	---	1.2m non-shielded w/o core

Note: Item 1 was provided by client.

1.3 Test Setup Chart



1.4 The Equipment List

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Feb. 03, 2015	Feb. 02, 2016
Power Meter	Anritsu	ML2495A	1241002	Sep. 29, 2014	Sep. 28, 2015
Power Sensor	Anritsu	MA2411B	1207366	Sep. 29, 2014	Sep. 28, 2015
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emission				
Test Site	966 chamber 3 / (03CH03-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	Agilent	N9010A	MY53400091	Sep. 16, 2014	Sep. 15, 2015
Receiver	Agilent	N9038A	MY53290044	Oct. 21, 2014	Oct. 20, 2015
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-562	Jan. 19, 2015	Jan. 18, 2016
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Feb. 03, 2015	Feb. 02, 2016
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 10, 2014	Nov. 09, 2015
Loop Antenna	R&S	HFH2-Z2	11900	Nov. 10, 2014	Nov. 09, 2015
Preamplifier	EMC	EMC02325	980187	Sep. 26, 2014	Sep. 25, 2015
Preamplifier	Agilent	83017A	MY53270014	Sep. 17, 2014	Sep. 16, 2015
Preamplifier	EMC	EMC184045B	980192	Aug. 26, 2014	Aug. 25, 2015
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Feb. 09, 2015	Feb. 08, 2016
RF cable-8M	HUBER+SUHNER	SUCOFLEX104	MY22601/4	Feb. 09, 2015	Feb. 08, 2016
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Feb. 09, 2015	Feb. 08, 2016
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800-001	Feb. 09, 2015	Feb. 08, 2016
LF cable-3M	EMC	EMC8D-NM-NM-3000	131103	Feb. 09, 2015	Feb. 08, 2016
LF cable-13M	EMC	EMC8D-NM-NM-13000	131104	Feb. 09, 2015	Feb. 08, 2016
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
EMC Receiver	R&S	ESCS 30	100169	Oct. 17, 2014	Oct. 16, 2015
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 17, 2014	Nov. 16, 2015
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Dec. 31, 2014	Dec. 30, 2015
Measurement Software	AUDIX	e3	6.120210k	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2013

FCC KDB 558074 D01 DTS Meas Guidance v03r02

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	±34.134 Hz
Conducted power	±0.808 dB
Power density	±0.463 dB
Conducted emission	±2.670 dB
AC conducted emission	±2.92 dB
Radiated emission ≤ 1GHz	±3.99 dB
Radiated emission > 1GHz	±5.52 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	18°C / 76%	Peter Lin
Radiated Emissions	03CH03-WS	20-21°C / 63-64%	Aska Huang
RF Conducted	TH01-WS	22°C / 65%	Brad Wu

➤ FCC site registration No.: 390588

➤ IC site registration No.: 10807C-1

2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data rate (Mbps) / MCS	Test Configuration
Conducted Emissions	HT20	2462	MCS 0	1, 2
Radiated Emissions ≤ 1GHz	HT20	2462	MCS 0	1, 2
Radiated Emissions > 1GHz	11b 11g HT20	2412 / 2437 / 2462 2412 / 2437 / 2462 2412 / 2437 / 2462	1 Mbps 6 Mbps MCS 0	1
Fundamental Emission Output Power	11b 11g HT20	2412 / 2437 / 2462 2412 / 2437 / 2462 2412 / 2437 / 2462	1 Mbps 6 Mbps MCS 0	1
6dB bandwidth				
Power spectral density				

NOTE:

- The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **X-plane** results were found as the worst case and were shown in this report.
- The EUT had been tested by following test configurations for radiated emission below 1GHz.
 - Configuration 1 : Adapter mode
 - Configuration 2 : Cradle mode
- Adapter and cradle mode had been pretested for radiated emission above 1GHz and found that the adapter mode was the worst case and was selected for final test.

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions


Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.

3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V/60Hz


3.1.3 Test Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions


Modulation	HT20	Test Freq. (MHz)	2462
Power Phase	Line	Test Configuration	1



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.159	37.04	55.52	-18.48	36.17	0.79	0.08	Average
2	0.159	44.36	65.52	-21.16	43.49	0.79	0.08	QP
3	0.213	37.94	53.10	-15.16	37.61	0.24	0.09	Average
4	0.213	45.89	63.10	-17.21	45.56	0.24	0.09	QP
5	0.398	33.51	47.90	-14.39	33.22	0.18	0.11	Average
6	0.398	39.77	57.90	-18.13	39.48	0.18	0.11	QP
7*	0.569	39.37	46.00	-6.63	39.09	0.15	0.13	Average
8	0.569	44.59	56.00	-11.41	44.31	0.15	0.13	QP
9	2.581	26.28	46.00	-19.72	25.52	0.49	0.27	Average
10	2.581	35.38	56.00	-20.62	34.62	0.49	0.27	QP
11	3.799	31.56	46.00	-14.44	30.97	0.29	0.30	Average
12	3.799	38.92	56.00	-17.08	38.33	0.29	0.30	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).


Modulation	HT20	Test Freq. (MHz)	2462
Power Phase	Neutral	Test Configuration	1



	Freq	Level	Limit	Over	Read	LISN	cable	
	MHz	dBuV	Line dBuV	Limit dB	Level dBuV	factor dB	loss dB	Remark
1	0.157	36.35	55.61	-19.26	35.52	0.75	0.08	Average
2	0.157	43.71	65.61	-21.90	42.88	0.75	0.08	QP
3*	0.568	40.14	46.00	-5.86	39.83	0.18	0.13	Average
4	0.568	47.84	56.00	-8.16	47.53	0.18	0.13	QP
5	2.460	30.73	46.00	-15.27	30.09	0.38	0.26	Average
6	2.460	36.87	56.00	-19.13	36.23	0.38	0.26	QP
7	2.761	30.99	46.00	-15.01	30.26	0.46	0.27	Average
8	2.761	39.19	56.00	-16.81	38.46	0.46	0.27	QP
9	3.406	34.39	46.00	-11.61	33.48	0.62	0.29	Average
10	3.406	43.14	56.00	-12.86	42.23	0.62	0.29	QP
11	3.881	29.18	46.00	-16.82	28.15	0.72	0.31	Average
12	3.881	36.97	56.00	-19.03	35.94	0.72	0.31	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).


Modulation	HT20	Test Freq. (MHz)	2462
Power Phase	Line	Test Configuration	2



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.169	42.64	55.01	-12.37	41.93	0.63	0.08	Average
2	0.169	51.34	65.01	-13.67	50.63	0.63	0.08	QP
3	0.236	40.31	52.22	-11.91	39.99	0.23	0.09	Average
4	0.236	46.77	62.22	-15.45	46.45	0.23	0.09	QP
5	0.535	39.64	46.00	-6.36	39.36	0.15	0.13	Average
6	0.535	45.05	56.00	-10.95	44.77	0.15	0.13	QP
7*	0.565	40.22	46.00	-5.78	39.94	0.15	0.13	Average
8	0.565	40.28	56.00	-15.72	40.00	0.15	0.13	QP
9	0.633	26.43	46.00	-19.57	26.16	0.14	0.13	Average
10	0.633	36.60	56.00	-19.40	36.33	0.14	0.13	QP
11	2.899	30.04	46.00	-15.96	29.33	0.43	0.28	Average
12	2.899	39.99	56.00	-16.01	39.28	0.43	0.28	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Modulation	HT20	Test Freq. (MHz)	2462
Power Phase	Neutral	Test Configuration	2



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.519	39.41	46.00	-6.59	39.12	0.17	0.12	Average
2	0.519	47.94	56.00	-8.06	47.65	0.17	0.12	QP
3*	0.575	40.82	46.00	-5.18	40.51	0.18	0.13	Average
4	0.575	49.01	56.00	-6.99	48.70	0.18	0.13	QP
5	0.679	33.64	46.00	-12.36	33.29	0.21	0.14	Average
6	0.679	42.42	56.00	-13.58	42.07	0.21	0.14	QP
7	0.981	30.53	46.00	-15.47	30.10	0.27	0.16	Average
8	0.981	40.19	56.00	-15.81	39.76	0.27	0.16	QP
9	1.472	28.41	46.00	-17.59	27.97	0.24	0.20	Average
10	1.472	37.86	56.00	-18.14	37.42	0.24	0.20	QP
11	3.918	36.38	46.00	-9.62	35.35	0.72	0.31	Average
12	3.918	44.69	56.00	-11.31	43.66	0.72	0.31	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

3.2 6dB and Occupied Bandwidth


3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.2.2 Test Procedures

1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.


3.2.3 Test Setup




3.2.4 Test Result of 6dB and Occupied Bandwidth

Modulation Mode	N _{TX}	Freq. (MHz)	6dB Bandwidth (MHz)				Limit (kHz)
			Chain 0	Chain 1	Chain 2	Chain 3	
11b	1	2412	7.59	---	---	---	500
11b	1	2437	7.54	---	---	---	500
11b	1	2462	8.00	---	---	---	500
11g	1	2412	16.35	---	---	---	500
11g	1	2437	16.35	---	---	---	500
11g	1	2462	15.94	---	---	---	500
HT20	2	2412	16.70	16.99	---	---	500
HT20	2	2437	17.22	17.57	---	---	500
HT20	2	2462	16.93	17.57	---	---	500

Worst Plots



Modulation Mode	N _{TX}	Freq. (MHz)	99% Occupied Bandwidth (MHz)			
			Chain 0	Chain 1	Chain 2	Chain 3
11b	1	2412	13.17	---	---	---
11b	1	2437	13.11	---	---	---
11b	1	2462	13.41	---	---	---
11g	1	2412	16.51	---	---	---
11g	1	2437	16.55	---	---	---
11g	1	2462	16.52	---	---	---
HT20	2	2412	17.62	17.61	---	---
HT20	2	2437	17.66	17.60	---	---
HT20	2	2462	17.62	17.62	---	---



3.3 RF Output Power

3.3.1 Limit of RF Output Power

Conducted power shall not exceed 1Watt.


- ☒ Antenna gain $\leq 6\text{dBi}$, no any corresponding reduction is in output power limit.
- ☐ Antenna gain $> 6\text{dBi}$
 - ☐ Non Fixed, point to point operations.
The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB
 - ☐ Fixed, point to point operations
Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations ,no any corresponding reduction is in transmitter peak output power

3.3.2 Test Procedures

- ☒ Maximum Peak Conducted Output Power
 - ☐ **Spectrum analyzer**
 1. Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
 2. Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
 3. Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.
 - ☒ **Power meter**
 1. A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.
- ☒ Maximum Conducted Output Power (For reference only)
 - ☒ **Power meter**
 1. A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

3.3.3 Test Setup



3.3.4 Test Result of Maximum Output Power

Modulation Mode	N _{TX}	Freq. (MHz)	Peak conducted output power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)
			Chain 0	Chain 1	Chain 2	Chain 3			
11b	1	2412	16.57	---	---	---	45.394	16.57	30.00
11b	1	2437	16.85	---	---	---	48.417	16.85	30.00
11b	1	2462	18.22	---	---	---	66.374	18.22	30.00
11g	1	2412	17.19	---	---	---	52.360	17.19	30.00
11g	1	2437	17.22	---	---	---	52.723	17.22	30.00
11g	1	2462	18.40	---	---	---	69.183	18.40	30.00
HT20	2	2412	15.96	15.85	---	---	77.905	18.92	30.00
HT20	2	2437	16.12	16.08	---	---	81.477	19.11	30.00
HT20	2	2462	17.13	17.18	---	---	103.881	20.17	30.00

Modulation Mode	N _{TX}	Freq. (MHz)	Conducted (average) output power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)
			Chain 0	Chain 1	Chain 2	Chain 3			
11b	1	2412	14.11	---	---	---	25.763	14.11	30.00
11b	1	2437	14.42	---	---	---	27.669	14.42	30.00
11b	1	2462	15.96	---	---	---	39.446	15.96	30.00
11g	1	2412	11.38	---	---	---	13.740	11.38	30.00
11g	1	2437	11.48	---	---	---	14.060	11.48	30.00
11g	1	2462	13.03	---	---	---	20.091	13.03	30.00
HT20	2	2412	10.26	10.08	---	---	20.803	13.18	30.00
HT20	2	2437	10.49	10.49	---	---	22.389	13.50	30.00
HT20	2	2462	11.82	11.51	---	---	29.363	14.68	30.00

Note: Conducted average output power is for reference only.

3.4 Power Spectral Density


3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.4.2 Test Procedures

- ☒ Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.
 1. Set the RBW = 3kHz, VBW = 10kHz.
 2. Detector = Peak, Sweep time = auto couple.
 3. Trace mode = max hold, allow trace to fully stabilize.
 4. Use the peak marker function to determine the maximum amplitude level.
- ☐ Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.
 1. Set the RBW = 100kHz, VBW = 300 kHz.
 2. Detector = RMS, Sweep time = auto couple.
 3. Set the sweep time to: $\geq 10 \times (\text{number of measurement points in sweep}) \times (\text{maximum data rate per stream})$.
 4. Perform the measurement over a single sweep.
 5. Use the peak marker function to determine the maximum amplitude level.\


3.4.3 Test Setup



3.4.4 Test Result of Power Spectral Density

Modulation Mode	N _{TX}	Freq. (MHz)	Total Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
11b	1	2412	-8.25	8.00
11b	1	2437	-8.71	8.00
11b	1	2462	-7.76	8.00
11g	1	2412	-14.32	8.00
11g	1	2437	-13.69	8.00
11g	1	2462	-13.10	8.00
HT20	2	2412	-14.03	8.00
HT20	2	2437	-13.48	8.00
HT20	2	2462	-11.88	8.00

Note: Test result for HT20 is bin-by-bin summing measured value of each TX port.



3.5 Unwanted Emissions into Restricted Frequency Bands

3.5.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Quasi-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.5.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.5.3 Test Setup

Radiated Emissions below 1 GHz




Radiated Emissions above 1 GHz



3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	HT20	Test Freq. (MHz)	2462
Polarization	Horizontal	Test Configuration	1




The graph displays the radiated unwanted emissions for a transmitter. The y-axis represents the Level in dBuV/m, ranging from 0 to 90. The x-axis represents the Frequency in MHz, ranging from 30 to 1000. A red line indicates the FCC CLASS-B limit, which is 40 dBuV/m from 30 to 100 MHz, 45 dBuV/m from 100 to 1000 MHz. Six measured peaks are labeled with numbers 2 through 7. The data for these peaks is provided in the table below.

	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	30.00	33.42	40.00	-6.58	46.91	-13.49	Peak	---	---
2	61.04	26.25	40.00	-13.75	40.67	-14.42	Peak	---	---
3	104.69	24.88	43.50	-18.62	42.47	-17.59	Peak	---	---
4	267.65	28.65	46.00	-17.35	42.62	-13.97	Peak	---	---
5	466.50	23.10	46.00	-22.90	31.49	-8.39	Peak	---	---
6	779.81	36.13	46.00	-9.87	38.94	-2.81	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	HT20	Test Freq. (MHz)	2462
Polarization	Vertical	Test Configuration	1



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	45.52	34.31	40.00	-5.69	47.14	-12.83	Peak	---	---
2	103.72	22.23	43.50	-21.27	39.99	-17.76	Peak	---	---
3	142.52	25.60	43.50	-17.90	39.25	-13.65	Peak	---	---
4	266.68	25.49	46.00	-20.51	39.52	-14.03	Peak	---	---
5	281.23	24.79	46.00	-21.21	38.16	-13.37	Peak	---	---
6	782.72	35.38	46.00	-10.62	38.15	-2.77	Peak	---	---


Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	HT20	Test Freq. (MHz)	2462
Polarization	Horizontal	Test Configuration	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	46.49	25.57	40.00	-14.43	38.42	-12.85	Peak	---	---
2	60.07	26.55	40.00	-13.45	40.82	-14.27	Peak	---	---
3	110.51	23.83	43.50	-19.67	40.41	-16.58	Peak	---	---
4	537.31	25.46	46.00	-20.54	32.68	-7.22	Peak	---	---
5	599.39	25.73	46.00	-20.27	31.46	-5.73	Peak	---	---
6	780.78	32.73	46.00	-13.27	35.53	-2.80	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	HT20	Test Freq. (MHz)	2462
Polarization	Vertical	Test Configuration	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	45.52	31.54	40.00	-8.46	44.37	-12.83	Peak	---	---
2	87.23	24.32	40.00	-15.68	43.22	-18.90	Peak	---	---
3	216.24	20.83	46.00	-25.17	36.99	-16.16	Peak	---	---
4	247.28	23.14	46.00	-22.86	37.86	-14.72	Peak	---	---
5	382.11	22.75	46.00	-23.25	33.29	-10.54	Peak	---	---
6	780.78	34.94	46.00	-11.06	37.74	-2.80	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11b


Modulation	11b	Test Freq. (MHz)	2412
Polarization	Horizontal	Test Configuration	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.67	54.00	-18.33	39.50	-3.83	Average	---	---
2	1500.00	48.78	74.00	-25.22	52.61	-3.83	Peak	---	---
3	2390.00	37.78	54.00	-16.22	39.00	-1.22	Average	---	---
4	2390.00	50.49	74.00	-23.51	51.71	-1.22	Peak	---	---
5	4824.00	46.66	54.00	-7.34	39.65	7.01	Average	---	---
6	4824.00	51.04	74.00	-22.96	44.03	7.01	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11b	Test Freq. (MHz)	2412
Polarization	Vertical	Test Configuration	1




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.72	54.00	-18.28	39.55	-3.83	Average	---	---
2	1500.00	48.78	74.00	-25.22	52.61	-3.83	Peak	---	---
3	2390.00	37.43	54.00	-16.57	38.65	-1.22	Average	---	---
4	2390.00	50.36	74.00	-23.64	51.58	-1.22	Peak	---	---
5	4824.00	47.72	54.00	-6.28	40.71	7.01	Average	---	---
6	4824.00	52.00	74.00	-22.00	44.99	7.01	Peak	---	---

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	11b	Test Freq. (MHz)	2437
Polarization	Horizontal	Test Configuration	1




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.72	54.00	-18.28	39.55	-3.83	Average	---	---
2	1500.00	48.33	74.00	-25.67	52.16	-3.83	Peak	---	---
3	4874.00	49.05	54.00	-4.95	42.24	6.81	Average	---	---
4	4874.00	53.56	74.00	-20.44	46.75	6.81	Peak	---	---
5	7311.00	38.52	54.00	-15.48	27.56	10.96	Average	---	---
6	7311.00	49.60	74.00	-24.40	38.64	10.96	Peak	---	---

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	11b	Test Freq. (MHz)	2437
Polarization	Vertical	Test Configuration	1




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.65	54.00	-18.35	39.48	-3.83	Average	---	---
2	1500.00	48.78	74.00	-25.22	52.61	-3.83	Peak	---	---
3	4874.00	49.67	54.00	-4.33	42.86	6.81	Average	---	---
4	4874.00	53.05	74.00	-20.95	46.24	6.81	Peak	---	---
5	7311.00	38.92	54.00	-15.08	27.96	10.96	Average	---	---
6	7311.00	50.71	74.00	-23.29	39.75	10.96	Peak	---	---

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	11b	Test Freq. (MHz)	2462
Polarization	Horizontal	Test Configuration	1




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.49	54.00	-18.51	39.32	-3.83	Average	---	---
2	1500.00	48.72	74.00	-25.28	52.55	-3.83	Peak	---	---
3	2483.50	37.64	54.00	-16.36	38.53	-0.89	Average	---	---
4	2483.50	51.84	74.00	-22.16	52.73	-0.89	Peak	---	---
5	4924.00	48.96	54.00	-5.04	42.36	6.60	Average	---	---
6	4924.00	52.86	74.00	-21.14	46.26	6.60	Peak	---	---
7	7386.00	38.84	54.00	-15.16	27.72	11.12	Average	---	---
8	7386.00	50.20	74.00	-23.80	39.08	11.12	Peak	---	---

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	11b	Test Freq. (MHz)	2462
Polarization	Vertical	Test Configuration	1



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.51	54.00	-18.49	39.34	-3.83	Average	---	---
2	1500.00	48.83	74.00	-25.17	52.66	-3.83	Peak	---	---
3	2483.50	37.76	54.00	-16.24	38.65	-0.89	Average	---	---
4	2483.50	49.43	74.00	-24.57	50.32	-0.89	Peak	---	---
5	4924.00	49.78	54.00	-4.22	43.18	6.60	Average	---	---
6	4924.00	53.13	74.00	-20.87	46.53	6.60	Peak	---	---
7	7386.00	39.00	54.00	-15.00	27.88	11.12	Average	---	---
8	7386.00	50.87	74.00	-23.13	39.75	11.12	Peak	---	---


Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

3.5.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11g


Modulation	11g	Test Freq. (MHz)	2412
Polarization	Horizontal	Test Configuration	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.47	54.00	-18.53	39.30	-3.83	Average	---	---
2	1500.00	48.44	74.00	-25.56	52.27	-3.83	Peak	---	---
3	2390.00	37.54	54.00	-16.46	38.76	-1.22	Average	---	---
4	2390.00	50.08	74.00	-23.92	51.30	-1.22	Peak	---	---
5	4824.00	32.35	54.00	-21.65	25.34	7.01	Average	---	---
6	4824.00	45.47	74.00	-28.53	38.46	7.01	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2412
Polarization	Vertical	Test Configuration	1




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.74	54.00	-18.26	39.57	-3.83	Average	---	---
2	1500.00	48.92	74.00	-25.08	52.75	-3.83	Peak	---	---
3	2390.00	37.19	54.00	-16.81	38.41	-1.22	Average	---	---
4	2390.00	50.59	74.00	-23.41	51.81	-1.22	Peak	---	---
5	4824.00	32.42	54.00	-21.58	25.41	7.01	Average	---	---
6	4824.00	45.77	74.00	-28.23	38.76	7.01	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2437
Polarization	Horizontal	Test Configuration	1




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.60	54.00	-18.40	39.43	-3.83	Average	---	---
2	1500.00	48.69	74.00	-25.31	52.52	-3.83	Peak	---	---
3	4874.00	32.39	54.00	-21.61	25.58	6.81	Average	---	---
4	4874.00	45.08	74.00	-28.92	38.27	6.81	Peak	---	---
5	7311.00	36.57	54.00	-17.43	25.61	10.96	Average	---	---
6	7311.00	49.60	74.00	-24.40	38.64	10.96	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2437
Polarization	Vertical	Test Configuration	1




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.47	54.00	-18.53	39.30	-3.83	Average	---	---
2	1500.00	48.69	74.00	-25.31	52.52	-3.83	Peak	---	---
3	4874.00	32.35	54.00	-21.65	25.54	6.81	Average	---	---
4	4874.00	45.44	74.00	-28.56	38.63	6.81	Peak	---	---
5	7311.00	36.44	54.00	-17.56	25.48	10.96	Average	---	---
6	7311.00	49.68	74.00	-24.32	38.72	10.96	Peak	---	---

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	11g	Test Freq. (MHz)	2462
Polarization	Horizontal	Test Configuration	1




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.69	54.00	-18.31	39.52	-3.83	Average	---	---
2	1500.00	48.53	74.00	-25.47	52.36	-3.83	Peak	---	---
3	2483.50	39.26	54.00	-14.74	40.15	-0.89	Average	---	---
4	2483.50	52.24	74.00	-21.76	53.13	-0.89	Peak	---	---
5	4924.00	32.14	54.00	-21.86	25.54	6.60	Average	---	---
6	4924.00	45.17	74.00	-28.83	38.57	6.60	Peak	---	---
7	7386.00	36.54	54.00	-17.46	25.42	11.12	Average	---	---
8	7386.00	49.73	74.00	-24.27	38.61	11.12	Peak	---	---

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	11g	Test Freq. (MHz)	2462
Polarization	Vertical	Test Configuration	1



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.62	54.00	-18.38	39.45	-3.83	Average	---	---
2	1500.00	48.85	74.00	-25.15	52.68	-3.83	Peak	---	---
3	2483.50	38.23	54.00	-15.77	39.12	-0.89	Average	---	---
4	2483.50	51.00	74.00	-23.00	51.89	-0.89	Peak	---	---
5	4924.00	32.04	54.00	-21.96	25.44	6.60	Average	---	---
6	4924.00	45.22	74.00	-28.78	38.62	6.60	Peak	---	---
7	7386.00	36.73	54.00	-17.27	25.61	11.12	Average	---	---
8	7386.00	49.92	74.00	-24.08	38.80	11.12	Peak	---	---


Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

3.5.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT20


Modulation	HT20	Test Freq. (MHz)	2412
Polarization	Horizontal	Test Configuration	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.62	54.00	-18.38	39.45	-3.83	Average	---	---
2	1500.00	48.31	74.00	-25.69	52.14	-3.83	Peak	---	---
3	2390.00	38.08	54.00	-15.92	39.30	-1.22	Average	---	---
4	2390.00	50.46	74.00	-23.54	51.68	-1.22	Peak	---	---
5	4824.00	33.23	54.00	-20.77	26.22	7.01	Average	---	---
6	4824.00	45.48	74.00	-28.52	38.47	7.01	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2412
Polarization	Vertical	Test Configuration	1




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.78	54.00	-18.22	39.61	-3.83	Average	---	---
2	1500.00	49.03	74.00	-24.97	52.86	-3.83	Peak	---	---
3	2390.00	37.64	54.00	-16.36	38.86	-1.22	Average	---	---
4	2390.00	50.58	74.00	-23.42	51.80	-1.22	Peak	---	---
5	4824.00	33.24	54.00	-20.76	26.23	7.01	Average	---	---
6	4824.00	45.75	74.00	-28.25	38.74	7.01	Peak	---	---

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	HT20	Test Freq. (MHz)	2437
Polarization	Horizontal	Test Configuration	1




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.46	54.00	-18.54	39.29	-3.83	Average	---	---
2	1500.00	48.42	74.00	-25.58	52.25	-3.83	Peak	---	---
3	4874.00	33.32	54.00	-20.68	26.51	6.81	Average	---	---
4	4874.00	45.73	74.00	-28.27	38.92	6.81	Peak	---	---
5	7311.00	36.44	54.00	-17.56	25.48	10.96	Average	---	---
6	7311.00	49.58	74.00	-24.42	38.62	10.96	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2437
Polarization	Vertical	Test Configuration	1




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.51	54.00	-18.49	39.34	-3.83	Average	---	---
2	1500.00	48.88	74.00	-25.12	52.71	-3.83	Peak	---	---
3	4874.00	33.38	54.00	-20.62	26.57	6.81	Average	---	---
4	4874.00	45.23	74.00	-28.77	38.42	6.81	Peak	---	---
5	7311.00	36.45	54.00	-17.55	25.49	10.96	Average	---	---
6	7311.00	49.57	74.00	-24.43	38.61	10.96	Peak	---	---

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	HT20	Test Freq. (MHz)	2462
Polarization	Horizontal	Test Configuration	1




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.60	54.00	-18.40	39.43	-3.83	Average	---	---
2	1500.00	48.49	74.00	-25.51	52.32	-3.83	Peak	---	---
3	2483.50	39.10	54.00	-14.90	39.99	-0.89	Average	---	---
4	2483.50	53.25	74.00	-20.75	54.14	-0.89	Peak	---	---
5	4924.00	33.03	54.00	-20.97	26.43	6.60	Average	---	---
6	4924.00	45.57	74.00	-28.43	38.97	6.60	Peak	---	---
7	7386.00	36.59	54.00	-17.41	25.47	11.12	Average	---	---
8	7386.00	49.50	74.00	-24.50	38.38	11.12	Peak	---	---

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	HT20	Test Freq. (MHz)	2462
Polarization	Vertical	Test Configuration	1



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.78	54.00	-18.22	39.61	-3.83	Average	---	---
2	1500.00	48.76	74.00	-25.24	52.59	-3.83	Peak	---	---
3	2483.50	38.47	54.00	-15.53	39.36	-0.89	Average	---	---
4	2483.50	51.24	74.00	-22.76	52.13	-0.89	Peak	---	---
5	4924.00	33.57	54.00	-20.43	26.97	6.60	Average	---	---
6	4924.00	45.08	74.00	-28.92	38.48	6.60	Peak	---	---
7	7386.00	36.93	54.00	-17.07	25.81	11.12	Average	---	---
8	7386.00	49.17	74.00	-24.83	38.05	11.12	Peak	---	---

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

3.6 Unwanted Emissions into Non-Restricted Frequency Bands

3.6.1 Limit of Unwanted Emissions into Non-Restricted Frequency Bands

The peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.6.2 Test Procedures


Reference Level Measurement

1. Set the RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
2. Set Sweep time = auto couple, Trace mode = max hold.
3. Allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

Unwanted Emissions Level Measurement


1. Set RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
2. Trace Mode = max hold, Sweep = auto couple.
3. Allow the trace to stabilize.
4. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

3.6.3 Test Setup




3.6.4 Unwanted Emissions into Non-Restricted Frequency Bands


802.11b





Reference Level




Tx 2437MHz / 30MHz~25GHz (down 20dBc)










Reference Level




Tx 2462MHz / 30MHz~25GHz (down 20dBc)









802.11g





Reference Level




Tx 2437MHz / 30MHz~25GHz (down 20dBc)












802.11n HT20





Reference Level




Tx 2437MHz / 30MHz~25GHz (down 20dBc)










Reference Level



Tx 2462MHz / 30MHz~25GHz (down 20dBc)







4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou
District, New Taipei City, Taiwan,
R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd
St., Kwei Shan Hsiang, Tao Yuan
Hsien 333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan Hsiang, Tao Yuan
Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==