

FCC PART 15.247

TEST REPORT

For

Group Sense Mobile-Tech Limited

Room 13-24, 2/F, Sino Industrial Plaza, 9 Kai Cheung Road, Kowloon Bay, Kowloon, Hong Kong

FCC ID: VRI-B231

Report Type: Original Report	Product Type: POS Terminal
Report Number: RSZ170418017-00C	
Report Date: 2017-08-30	
Reviewed By: RF Engineer	Rocky Kang <i>Rocky Kang</i>
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government. This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★". This report may contain data were produced under the subcontractor and shall be marked with an asterisk "△".

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	7
EUT EXERCISE SOFTWARE	7
DUTY CYCLE	8
EXTERNAL I/O CABLE.....	10
BLOCK DIAGRAM OF TEST SETUP	11
SUMMARY OF TEST RESULTS.....	12
TEST EQUIPMENT LIST	13
FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE	14
APPLICABLE STANDARD	14
FCC §15.203 - ANTENNA REQUIREMENT.....	15
APPLICABLE STANDARD	15
ANTENNA CONNECTOR CONSTRUCTION	15
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	16
APPLICABLE STANDARD	16
EUT SETUP	16
EMI TEST RECEIVER SETUP.....	16
TEST PROCEDURE	16
CORRECTED FACTOR & MARGIN CALCULATION	17
TEST RESULTS SUMMARY	17
TEST DATA	17
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	22
APPLICABLE STANDARD	22
EUT SETUP	22
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	23
TEST PROCEDURE	23
CORRECTED AMPLITUDE & MARGIN CALCULATION	23
TEST RESULTS SUMMARY	23
TEST DATA	24
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST DATA	34
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	44
APPLICABLE STANDARD	44

TEST PROCEDURE	44
TEST DATA	44
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	46
APPLICABLE STANDARD	46
TEST PROCEDURE	46
TEST DATA	46
FCC §15.247(e) - POWER SPECTRAL DENSITY	52
APPLICABLE STANDARD	52
TEST PROCEDURE	52
TEST DATA	52

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Group Sense Mobile-Tech Limited*'s product, model number: *DT-10 (FCC ID: VRI-B231)* or the "EUT" in this report was a *POS Terminal*, which was measured approximately: 28.4 cm (L) × 19.3 cm (W) × 1.9 cm (H), rated with input voltage: DC 3.8 V battery or DC 5V from adapter.

Adapter Information:

Model: JK050300-S04US

Input: AC 100-240V, 50/60Hz, 0.5A

Output: DC 5V, 3000 mA

**All measurement and test data in this report was gathered from production sample serial number: 1700742 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2017-07-20.*

Objective

This report is prepared on behalf of *Group Sense Mobile-Tech Limited* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 22H & 24E PCB, Part 15.247 DSS, Part 15.407 NII, Part 15.225 DXX and Part 15B JBC submissions with FCC ID: VRI-B231.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter	uncertainty
Occupied Channel Bandwidth	±5%
RF Output Power with Power meter	±0.5dB
RF conducted test with spectrum	±1.5dB
AC Power Lines Conducted Emissions	±1.95dB
All emissions, radiated	±4.95dB
Temperature	±3°C
Humidity	±6%
Supply voltages	±0.4%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

Bay Area Compliance Laboratories Corp. (Shenzhen) has been accredited to ISO/IEC 17025 by CNAS (Lab code: L2408). And accredited to ISO/IEC 17025 by NVLAP (Lab code: 200707-0), the FCC Designation No. CN5001 under the KDB 974614 D01.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Bay Area Compliance Laboratories Corp. (Shenzhen) was registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g and 802.11n-HT20 mode, 13 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	12	2467
6	2437	13	2472
7	2442	/	/

For 802.11b, 802.11g, 802.11n-HT20 mode, EUT was tested with Channel 1, 7 and 13

For 802.11n-HT40 mode, 9 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2422	6	2447
2	2427	7	2452
3	2432	8	2457
4	2437	9	2462
5	2442	/	/

EUT was tested with Channel 1, 5 and 9.

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

BLE & Wi-Fi test in the engineer mode, software “Win8DutApp_x86_1.0.016” was used.


The device was tested with 100% duty cycle and the worst case was performed as below:

Mode	Data rate	Power level		
		Low channel	Middle channel	High channel
802.11b	1 Mbps	10	10	10
802.11g	6 Mbps	8	8	8
802.11n-HT20	MCS0	8	8	8
802.11n-HT40	MCS0	8	8	8
BLE	/	Default	Default	Default


Pre-scan with all the data rates, the above data rate is the worst case for Wi-Fi test.

Duty cycle


802.11b mode




802.11g mode




802.11n-HT20 Mode



802.11n-HT40 Mode



BLE Mode




Band	Duty Cycle (%)	T(us)	1/T(kHz)	VBW Setting	10log(1/ Duty Cycle)
802.11b	99.66	-	-	10Hz	-
802.11g	94.83	1470	0.68	1kHz	0.23
802.11n-HT20	95.14	1370	0.73	1kHz	0.22
802.11n-HT40	89.37	681	1.47	3kHz	0.49
BLE	65.86	409	2.44	3kHz	1.81

External I/O Cable

Cable Description	Length (m)	From Port	To
Un-shielding Detachable USB Cable	1.0	EUT	Adapter

Block Diagram of Test Setup

For conducted emission



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2016-10-19	2017-10-19
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2016-12-07	2017-12-07
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2017-02-14	2017-08-15
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
N/A	Conducted Emission Cable	N/A	UF A210B-1-0720-504504	2017-05-12	2017-11-12
Radiated Emission Test					
Sunol Sciences	Horn Antenna	DRH-118	A052604	2014-12-29	2017-12-28
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2017-04-24	2018-04-24
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2017-05-21	2018-05-21
HP	Amplifier	HP8447E	1937A01046	2017-05-21	2017-11-19
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2014-12-17	2017-12-16
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2016-12-07	2017-12-07
Ducommun technologies	RF Cable	UFA210A-1-4724-30050U	MFR64369223410-001	2017-05-21	2017-11-19
Ducommun technologies	RF Cable	104PEA	218124002	2017-05-21	2017-11-19
Ducommun technologies	RF Cable	RG-214	1	2017-05-21	2017-11-19
Ducommun technologies	RF Cable	RG-214	2	2017-05-22	2017-11-22
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-04	2014-12-29	2017-12-28
Ducommun Technologies	Pre-amplifier	ALN-22093530-01	991373-01	2017-08-03	2018-08-03
RF Conducted Test					
Agilent	P-Series Power Meter	N1912A	MY5000448	2016-12-05	2017-12-05
Agilent	Wideband Power Sensor	N1921A	MY54210016	2016-12-05	2017-12-05
WEINSCHL	10dB Attenuator	5324	AU 3842	2017-05-23	2017-11-22
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2017-04-24	2018-04-24
Ducommun technologies	RF Cable	RG-214	3	2017-05-22	2017-11-22

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Measurement Result

For worst case:

Mode	Frequency (MHz)	Max Tune-up Conducted Power (dBm)	Max Tune-up Conducted Power (mW)	Calculated Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
BLE	2480	9.0	7.94	5	2.5	3.0	Yes
Wi-Fi	2472	9.5	8.91	5	2.8	3.0	Yes

Result: No SAR test is required

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has an internal antenna arrangement, which was permanently attached and the antenna gain is 2 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions


Temperature:	26 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Haiguo Li on 2017-08-11.

EUT operation mode: Transmitting

BLE Mode:**AC 120V/60 Hz, Line**


EMI Auto Test L



Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.399910	46.1	20.2	57.9	11.8	QP
0.525770	44.7	20.2	56.0	11.3	QP
0.529930	44.7	20.2	56.0	11.3	QP
0.589030	43.9	20.1	56.0	12.1	QP
0.782210	42.6	20.0	56.0	13.4	QP
0.955750	41.8	20.1	56.0	14.2	QP
0.399910	31.2	20.2	47.9	16.7	Ave.
0.525770	28.0	20.2	46.0	18.0	Ave.
0.529930	27.9	20.2	46.0	18.1	Ave.
0.589030	25.9	20.1	46.0	20.1	Ave.
0.782210	24.7	20.0	46.0	21.3	Ave.
0.955750	25.8	20.1	46.0	20.2	Ave.

AC 120V/60 Hz, Neutral


EMI Auto Test N



Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.477050	44.7	20.2	56.4	11.7	QP
0.598850	43.2	20.1	56.0	12.8	QP
0.620790	38.7	20.1	56.0	17.3	QP
0.675890	41.6	20.0	56.0	14.4	QP
0.813730	43.0	20.0	56.0	13.0	QP
0.817910	43.2	20.0	56.0	12.8	QP
0.477050	28.4	20.2	46.4	18.0	Ave.
0.598850	25.1	20.1	46.0	20.9	Ave.
0.620790	21.0	20.1	46.0	25.0	Ave.
0.675890	24.7	20.0	46.0	21.3	Ave.
0.813730	27.1	20.0	46.0	18.9	Ave.
0.817910	27.1	20.0	46.0	18.9	Ave.

Wi-Fi Mode:**AC 120 V/60 Hz, Line:**


EMI Auto Test L



Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.399970	46.2	20.2	57.9	11.7	QP
0.502470	44.7	20.2	56.0	11.3	QP
0.565390	43.2	20.1	56.0	12.8	QP
0.592970	44.4	20.1	56.0	11.6	QP
0.703530	41.7	20.0	56.0	14.3	QP
0.813970	43.4	20.0	56.0	12.6	QP
0.399970	31.2	20.2	47.9	16.7	Ave.
0.502470	27.4	20.2	46.0	18.6	Ave.
0.565390	25.0	20.1	46.0	21.0	Ave.
0.592970	26.0	20.1	46.0	20.0	Ave.
0.703530	23.2	20.0	46.0	22.8	Ave.
0.813970	27.8	20.0	46.0	18.2	Ave.

AC 120V/ 60 Hz, Neutral:

EMI Auto Test N





Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.328990	45.0	20.2	59.5	14.5	QP
0.384270	44.6	20.2	58.2	13.6	QP
0.541990	44.5	20.2	56.0	11.5	QP
0.545810	43.7	20.2	56.0	12.3	QP
0.608850	42.7	20.1	56.0	13.3	QP
1.026670	39.2	20.1	56.0	16.8	QP
0.328990	30.8	20.2	49.5	18.7	Ave.
0.384270	31.0	20.2	48.2	17.2	Ave.
0.541990	27.0	20.2	46.0	19.0	Ave.
0.545810	25.3	20.2	46.0	20.7	Ave.
0.608850	26.1	20.1	46.0	19.9	Ave.
1.026670	27.4	20.1	46.0	18.6	Ave.

Note:

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	PK
	1MHz	> 1/T ^{Note 2}	/	PK

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

In BACL, $U_{(L_m)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data**Environmental Conditions**

Temperature:	22 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Haiguo Li on 2017-07-29.

EUT operation mode: Transmitting

30 MHz-25 GHz:**For Wi-Fi:****802.11b Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2412 MHz)									
185.36	47.57	QP	56	1.5	V	-14.9	32.67	43.5	10.83
2412.00	58.13	PK	220	2.0	H	33.92	92.05	/	/
2412.00	52.23	Ave.	220	2.0	H	33.92	86.15	/	/
2412.00	56.2	PK	50	1.0	V	33.92	90.12	/	/
2412.00	50.83	Ave.	50	1.0	V	33.92	84.75	/	/
2370.92	27.34	PK	300	1.8	H	33.92	61.26	74	12.74
2370.92	13.55	Ave.	300	1.8	H	33.92	47.47	54	6.53
2381.87	26.89	PK	30	1.4	H	33.92	60.81	74	13.19
2381.87	13.11	Ave.	30	1.4	H	33.92	47.03	54	6.97
2490.84	27.26	PK	121	1.0	H	34.08	61.34	74	12.66
2490.84	13.38	Ave.	121	1.0	H	34.08	47.46	54	6.54
4824.00	42.97	PK	337	1.9	H	5.84	48.81	74	25.19
4824.00	29.73	Ave.	337	1.9	H	5.84	35.57	54	18.43
7236.00	35.71	PK	300	1.4	H	14.00	49.71	74	24.29
7236.00	24.63	Ave.	300	1.4	H	14.00	38.63	54	15.37

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Middle Channel (2442MHz)									
185.36	47.74	QP	126	1.7	V	-14.9	32.84	43.5	10.66
2442.00	61.03	PK	160	1.1	H	33.92	94.95	/	/
2442.00	55.62	Ave.	160	1.1	H	33.92	89.54	/	/
2442.00	59.44	PK	356	1.7	V	33.92	93.36	/	/
2442.00	53.91	Ave.	356	1.7	V	33.92	87.83	/	/
2352.41	27.26	PK	223	2.3	H	33.92	61.18	74	12.82
2352.41	13.48	Ave.	223	2.3	H	33.92	47.40	54	6.60
2361.94	27.48	PK	146	1.7	H	33.92	61.40	74	12.60
2361.94	13.66	Ave.	146	1.7	H	33.92	47.58	54	6.42
2485.05	26.88	PK	197	1.0	H	34.08	60.96	74	13.04
2485.05	13.24	Ave.	197	1.0	H	34.08	47.32	54	6.68
4884.00	43.68	PK	130	1.8	H	6.21	49.89	74	24.11
4884.00	29.64	Ave.	130	1.8	H	6.21	35.85	54	18.15
7326.00	35.48	PK	216	1.7	H	13.60	49.08	74	24.92
7326.00	24.72	Ave.	216	1.7	H	13.60	38.32	54	15.68
High Channel (2472 MHz)									
185.36	47.81	QP	101	1.7	V	-14.9	32.91	43.5	10.59
2472.00	62.92	PK	126	1.6	H	34.08	97.00	/	/
2472.00	56.56	Ave.	126	1.6	H	34.08	90.64	/	/
2472.00	58.84	PK	336	1.1	V	34.08	92.92	/	/
2472.00	52.11	Ave.	336	1.1	V	34.08	86.19	/	/
2342.7	27.25	PK	314	2.3	H	33.83	61.08	74	12.92
2342.7	13.38	Ave.	314	2.3	H	33.83	47.21	54	6.79
2487.3	26.91	PK	128	2.3	H	34.08	60.99	74	13.01
2487.3	13.26	Ave.	128	2.3	H	34.08	47.34	54	6.66
2489.21	27.54	PK	152	2.5	H	34.08	61.62	74	12.38
2489.21	13.68	Ave.	152	2.5	H	34.08	47.76	54	6.24
4944.00	44.68	PK	342	1.4	H	6.21	50.89	74	23.11
4944.00	30.51	Ave.	342	1.4	H	6.21	36.72	54	17.28
7416.00	33.54	PK	267	1.6	H	13.02	46.56	74	27.44
7416.00	23.45	Ave.	267	1.6	H	13.02	36.47	54	17.53

802.11g Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2412 MHz)									
185.36	46.68	QP	126	1.7	V	-14.9	31.78	43.5	11.72
2412.00	57.56	PK	17	1.2	H	33.92	91.48	/	/
2412.00	51.54	Ave.	17	1.2	H	33.92	85.46	/	/
2412.00	56.4	PK	127	1.5	V	33.92	90.32	/	/
2412.00	50.34	Ave.	127	1.5	V	33.92	84.26	/	/
2358.25	26.78	PK	279	1.0	H	33.92	60.70	74	13.30
2358.25	13.21	Ave.	279	1.0	H	33.92	47.13	54	6.87
2384.69	27.26	PK	148	1.6	H	33.92	61.18	74	12.82
2384.69	13.35	Ave.	148	1.6	H	33.92	47.27	54	6.73
2496.35	27.43	PK	73	1.4	H	34.08	61.51	74	12.49
2496.35	13.56	Ave.	73	1.4	H	34.08	47.64	54	6.36
4824.00	43.68	PK	30	1.7	H	5.84	49.52	74	24.48
4824.00	30.15	Ave.	30	1.7	H	5.84	35.99	54	18.01
7236.00	34.21	PK	110	1.5	H	14.00	48.21	74	25.79
7236.00	24.32	Ave.	110	1.5	H	14.00	38.32	54	15.68
Middle Channel (2442MHz)									
185.36	47.32	QP	136	1.7	V	-14.9	32.42	43.5	11.08
2442.00	60.45	PK	234	2.0	H	33.92	94.37	/	/
2442.00	54.29	Ave.	234	2.0	H	33.92	88.21	/	/
2442.00	58.17	PK	346	1.3	V	33.92	92.09	/	/
2442.00	52.82	Ave.	346	1.3	V	33.92	86.74	/	/
2368.59	26.87	PK	162	1.5	H	33.92	60.79	74	13.21
2368.59	13.23	Ave.	162	1.5	H	33.92	47.15	54	6.85
2382.46	27.43	PK	128	2.5	H	33.92	61.35	74	12.65
2382.46	13.56	Ave.	128	2.5	H	33.92	47.48	54	6.52
2489.74	27.68	PK	247	2.1	H	34.08	61.76	74	12.24
2489.74	13.59	Ave.	247	2.1	H	34.08	47.67	54	6.33
4884.00	45.64	PK	347	1.6	H	6.21	51.85	74	22.15
4884.00	31.34	Ave.	347	1.6	H	6.21	37.55	54	16.45
7326.00	35.42	PK	303	1.7	H	13.60	49.02	74	24.98
7326.00	24.21	Ave.	303	1.7	H	13.60	37.81	54	16.19

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2472 MHz)									
185.36	46.34	QP	125	1.9	V	-14.9	31.44	43.5	12.06
2472.00	62.96	PK	360	1.5	H	34.08	97.04	/	/
2472.00	56.38	Ave.	360	1.5	H	34.08	90.46	/	/
2472.00	62.86	PK	71	2.4	V	34.08	96.94	/	/
2472.00	56.4	Ave.	71	2.4	V	34.08	90.48	/	/
2335.49	27.36	PK	342	1.8	H	33.83	61.19	74	12.81
2335.49	13.52	Ave.	342	1.8	H	33.83	47.35	54	6.65
2483.66	34.29	PK	123	1.1	H	34.08	68.37	74	5.63
2483.66	15.00	Ave.	123	1.1	H	34.08	49.08	54	4.92
2484.39	30.84	PK	80	2.4	H	34.08	64.92	74	9.08
2484.39	13.75	Ave.	80	2.4	H	34.08	47.83	54	6.17
4944.00	45.23	PK	348	1.2	H	6.21	51.44	74	22.56
4944.00	30.84	Ave.	348	1.2	H	6.21	37.05	54	16.95
7416.00	33.79	PK	174	2.5	H	13.02	46.81	74	27.19
7416.00	22.47	Ave.	174	2.5	H	13.02	35.49	54	18.51

802.11n-HT20 Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2412 MHz)									
185.36	47.58	QP	23	1.7	V	-14.9	32.68	43.5	10.82
2412.00	56.2	PK	163	2.5	H	33.92	90.12	/	/
2412.00	50.68	Ave.	163	2.5	H	33.92	84.60	/	/
2412.00	54.49	PK	320	1.9	V	33.92	88.41	/	/
2412.00	48.8	Ave.	320	1.9	V	33.92	82.72	/	/
2352.48	27.7	PK	246	1.5	H	33.92	61.62	74	12.38
2352.48	13.69	Ave.	246	1.5	H	33.92	47.61	54	6.39
2367.87	26.89	PK	315	1.6	H	33.92	60.81	74	13.19
2367.87	13.26	Ave.	315	1.6	H	33.92	47.18	54	6.82
2488.12	27.38	PK	53	2.3	H	34.08	61.46	74	12.54
2488.12	13.27	Ave.	53	2.3	H	34.08	47.35	54	6.65
4824.00	43.57	PK	59	2.4	H	5.84	49.41	74	24.59
4824.00	30.22	Ave.	59	2.4	H	5.84	36.06	54	17.94
7236.00	33.42	PK	57	1.2	H	14.00	47.42	74	26.58
7236.00	24.15	Ave.	57	1.2	H	14.00	38.15	54	15.85
Middle Channel (2442MHz)									
185.36	47.77	QP	223	1.8	V	-14.9	32.87	43.5	10.63
2442.00	58.69	PK	133	1.0	H	33.92	92.61	/	/
2442.00	52.78	Ave.	133	1.0	H	33.92	86.70	/	/
2442.00	57.47	PK	154	2.5	V	33.92	91.39	/	/
2442.00	51.34	Ave.	154	2.5	V	33.92	85.26	/	/
2357.13	26.69	PK	25	1.7	H	33.92	60.61	74	13.39
2357.13	13.22	Ave.	25	1.7	H	33.92	47.14	54	6.86
2375.89	27.35	PK	214	1.9	H	33.92	61.27	74	12.73
2375.89	13.48	Ave.	214	1.9	H	33.92	47.40	54	6.60
2494.17	27.52	PK	3	1.2	H	34.08	61.60	74	12.40
2494.17	13.77	Ave.	3	1.2	H	34.08	47.85	54	6.15
4884.00	45.64	PK	18	2.4	H	6.21	51.85	74	22.15
4884.00	31.41	Ave.	18	2.4	H	6.21	37.62	54	16.38
7326.00	35.14	PK	28	1.4	H	13.60	48.74	74	25.26
7326.00	24.16	Ave.	28	1.4	H	13.60	37.76	54	16.24

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2472 MHz)									
185.36	46.45	QP	136	1.8	V	-14.9	31.55	43.5	11.95
2472.00	62.96	PK	307	2.4	H	34.08	97.04	/	/
2472.00	56.73	Ave.	307	2.4	H	34.08	90.81	/	/
2472.00	60.2	PK	119	1.5	V	34.08	94.28	/	/
2472.00	54.86	Ave.	119	1.5	V	34.08	88.94	/	/
2383.74	27.54	PK	244	1.9	H	33.92	61.46	74	12.54
2383.74	13.67	Ave.	244	1.9	H	33.92	47.59	54	6.41
2483.53	32.73	PK	286	2.3	H	34.08	66.81	74	7.19
2483.53	15	Ave.	286	2.3	H	34.08	49.08	54	4.92
2484.12	30.57	PK	55	2.2	H	34.08	64.65	74	9.35
2484.12	13.8	Ave.	55	2.2	H	34.08	47.88	54	6.12
4944.00	43.61	PK	163	2.4	H	6.21	49.82	74	24.18
4944.00	30.26	Ave.	163	2.4	H	6.21	36.47	54	17.53
7416.00	33.25	PK	276	2.2	H	13.02	46.27	74	27.73
7416.00	22.32	Ave.	276	2.2	H	13.02	35.34	54	18.66

802.11n-HT40 Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2422 MHz)									
185.36	47.52	QP	85	1.7	V	-14.9	32.62	43.5	10.88
2422.00	61.22	PK	59	2.1	H	33.92	95.14	/	/
2422.00	55.39	Ave.	59	2.1	H	33.92	89.31	/	/
2422.00	59.42	PK	328	1.8	V	33.92	93.34	/	/
2422.00	53.36	Ave.	328	1.8	V	33.92	87.28	/	/
2378.61	31.21	PK	16	2.3	H	33.92	65.13	74	8.87
2378.61	15.01	Ave.	16	2.3	H	33.92	48.93	54	5.07
2388.07	33.31	PK	334	2.4	H	33.92	67.23	74	6.77
2388.07	16.6	Ave.	334	2.4	H	33.92	50.52	54	3.48
2491.83	27.8	PK	68	2.3	H	34.08	61.88	74	12.12
2491.83	13.75	Ave.	68	2.3	H	34.08	47.83	54	6.17
4844.00	43.54	PK	199	2.2	H	5.84	49.38	74	24.62
4844.00	29.87	Ave.	199	2.2	H	5.84	35.71	54	18.29
7266.00	33.78	PK	174	2.0	H	13.60	47.38	74	26.62
7266.00	22.54	Ave.	174	2.0	H	13.60	36.14	54	17.86
Middle Channel (2442MHz)									
185.36	47.31	QP	76	1.9	V	-14.9	32.41	43.5	11.09
2442.00	56.17	PK	150	1.6	H	33.92	90.09	/	/
2442.00	50.91	Ave.	150	1.6	H	33.92	84.83	/	/
2442.00	55.12	PK	206	2.2	V	33.92	89.04	/	/
2442.00	49.71	Ave.	206	2.2	V	33.92	83.63	/	/
2345.59	26.75	PK	219	1.7	H	33.83	60.58	74	13.42
2345.59	13.12	Ave.	219	1.7	H	33.83	46.95	54	7.05
2362.26	27.34	PK	125	2.3	H	33.92	61.26	74	12.74
2362.26	13.58	Ave.	125	2.3	H	33.92	47.50	54	6.50
2487.86	27.45	PK	177	1.4	H	34.08	61.53	74	12.47
2487.86	13.36	Ave.	177	1.4	H	34.08	47.44	54	6.56
4884.00	45.36	PK	24	1.1	H	6.21	51.57	74	22.43
4884.00	31.23	Ave.	24	1.1	H	6.21	37.44	54	16.56
7326.00	33.41	PK	305	1.4	H	13.60	47.01	74	26.99
7326.00	22.24	Ave.	305	1.4	H	13.60	35.84	54	18.16

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2462 MHz)									
185.36	46.58	QP	156	1.8	V	-14.9	31.68	43.5	11.82
2462.00	56.01	PK	343	2.4	H	34.08	90.09	/	/
2462.00	50.8	Ave.	343	2.4	H	34.08	84.88	/	/
2462.00	52.87	PK	273	2.5	V	34.08	86.95	/	/
2462.00	46.82	Ave.	273	2.5	V	34.08	80.90	/	/
2357.77	26.71	PK	261	2.2	H	33.92	60.63	74	13.37
2357.77	13.2	Ave.	261	2.2	H	33.92	47.12	54	6.88
2483.66	30.45	PK	159	1.7	H	34.08	64.53	74	9.47
2483.66	13.86	Ave.	159	1.7	H	34.08	47.94	54	6.06
2484.78	29.23	PK	193	1.0	H	34.08	63.31	74	10.69
2484.78	13.67	Ave.	193	1.0	H	34.08	47.75	54	6.25
4924.00	44.88	PK	305	1.7	H	6.21	51.09	74	22.91
4924.00	30.54	Ave.	305	1.7	H	6.21	36.75	54	17.25
7386.00	33.25	PK	41	1.7	H	13.02	46.27	74	27.73
7386.00	22.62	Ave.	41	1.7	H	13.02	35.64	54	18.36

BLE Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2402 MHz)									
143.56	43.66	QP	178	1.7	V	-13.80	29.86	43.50	13.64
2402.00	61.52	PK	111	2.1	H	33.92	95.44	/	/
2402.00	55.47	Ave.	111	2.1	H	33.92	89.39	/	/
2402.00	59.54	PK	317	1.9	V	33.92	93.46	/	/
2402.00	53.52	Ave.	317	1.9	V	33.92	87.44	/	/
2327.57	28.74	PK	157	1.3	H	33.83	62.57	74	11.43
2327.57	13.92	Ave.	157	1.3	H	33.83	47.75	54	6.25
2341.72	28.94	PK	281	1.4	H	33.83	62.77	74	11.23
2341.72	13.94	Ave.	281	1.4	H	33.83	47.77	54	6.23
2496.84	28.84	PK	184	1.6	H	34.08	62.92	74	11.08
2496.84	13.87	Ave.	184	1.6	H	34.08	47.95	54	6.05
4804.00	43.04	PK	3	1.1	H	5.84	48.88	74	25.12
4804.00	32.23	Ave.	3	1.1	H	5.84	38.07	54	15.93
7206.00	34.21	PK	35	1.6	H	14.00	48.21	74	25.79
7206.00	23.24	Ave.	35	1.6	H	14.00	37.24	54	16.76
Middle Channel (2440 MHz)									
143.56	43.27	QP	123	1.8	V	-13.80	29.47	43.50	14.03
2440.00	60.74	PK	280	2.0	H	33.92	94.66	/	/
2440.00	54.58	Ave.	280	2.0	H	33.92	88.50	/	/
2440.00	57.62	PK	272	1.6	V	33.92	91.54	/	/
2440.00	51.47	Ave.	272	1.6	V	33.92	85.39	/	/
2327.57	28.72	PK	296	1.1	H	33.83	62.55	74	11.45
2327.57	13.81	Ave.	296	1.1	H	33.83	47.64	54	6.36
2341.72	28.52	PK	349	1.2	H	33.83	62.35	74	11.65
2341.72	13.94	Ave.	349	1.2	H	33.83	47.77	54	6.23
2496.84	27.53	PK	109	2.0	H	34.08	61.61	74	12.39
2496.84	13.71	Ave.	109	2.0	H	34.08	47.79	54	6.21
4880.00	40.27	PK	269	2.2	H	6.21	46.48	74	27.52
4880.00	28.54	Ave.	269	2.2	H	6.21	34.75	54	19.25
7320.00	33.12	PK	162	2.0	H	13.60	46.72	74	27.28
7320.00	22.52	Ave.	162	2.0	H	13.60	36.12	54	17.88

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2480 MHz)									
143.56	43.52	QP	56	1.5	V	-13.80	29.72	43.50	13.78
2480.00	61.78	PK	274	1.5	H	34.08	95.86	/	/
2480.00	55.87	Ave.	274	1.5	H	34.08	89.95	/	/
2480.00	57.73	PK	44	2.1	V	34.08	91.81	/	/
2480.00	51.72	Ave.	44	2.1	V	34.08	85.80	/	/
2345.83	28.53	PK	196	2.4	H	33.83	62.36	74	11.64
2345.83	13.97	Ave.	196	2.4	H	33.83	47.80	54	6.20
2487.12	27.72	PK	78	1.1	H	34.08	61.80	74	12.20
2487.12	13.82	Ave.	78	1.1	H	34.08	47.90	54	6.10
2495.47	26.94	PK	269	1.8	H	34.08	61.02	74	12.98
2495.47	13.73	Ave.	269	1.8	H	34.08	47.81	54	6.19
4960.00	41.54	PK	342	2.3	H	7.82	49.36	74	24.64
4960.00	26.35	Ave.	342	2.3	H	7.82	34.17	54	19.83
7440.00	33.14	PK	87	1.5	H	13.02	46.16	74	27.84
7440.00	23.02	Ave.	87	1.5	H	13.02	36.04	54	17.96

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading

Margin = Limit - Corrected. Amplitude

The other spurious emission which is 20dB to the limit was not recorded.


FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	22~24 °C
Relative Humidity:	50~53 %
ATM Pressure:	100.2~101.0 kPa

The testing was performed by Haiguo Li on 2017-07-23 and 2017-08-10.

Test Result: Pass.


Please refer to the following table and plots.

EUT operation mode: Transmitting


Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (kHz)
802.11b mode			
Low	2412	8.18	≥ 500
Middle	2442	8.60	≥ 500
High	2472	8.66	≥ 500
802.11g			
Low	2412	16.41	≥ 500
Middle	2442	16.35	≥ 500
High	2472	16.41	≥ 500
802.11n-HT20 mode			
Low	2412	17.31	≥ 500
Middle	2442	17.62	≥ 500
High	2472	17.62	≥ 500
802.11n-HT40 mode			
Low	2422	36.07	≥ 500
Middle	2442	36.07	≥ 500
High	2462	36.07	≥ 500

Channel	Frequency (MHz)	6 dB Emission Bandwidth(MHz)	Limit (kHz)
BLE mode			
Low	2402	0.741	≥ 500
Middle	2440	0.745	≥ 500
High	2480	0.745	≥ 500


802.11b Low Channel




802.11b Middle Channel




802.11b High Channel




802.11g Low Channel




802.11g Middle Channel




802.11g High Channel



802.11n-HT20 Low Channel



802.11n-HT20 Middle Channel



Delta 1 [T1] -1.08 dB
 RBW 100 kHz RF Att 40 dB
 Ref Lvl 20.5 dBm 17.61523046 MHz
 SWT 7.5 ms Unit dBm

10.5 dB Offset
 -1.08 dB
 -10.06 dBm
 -1.08 dB
 17.61523046 MHz
 -1.08 dB
 2.46319238 GHz
 -1.08 dB
 17.61523046 MHz

D1 -4.06 dBm
 D2 -10.06 dBm
 1MAX
 1MAX

Center 2.472 GHz 3 MHz/
 Span 30 MHz

Date: 23.JUL.2017 15:25:42

Ref Lvl 20.5 dBm Delta 1 [T1] -1.73 dB RBW 100 kHz RF Att 40 dB
 VBW 300 kHz SWT 15 ms Unit dBm

10.5 dB Offset


1 [T1] -13.04 dBm
 2.40402405 GHz
 1 [T1] -1.73 dB
 36.07214429 MHz

D1 -7.7 dBm
 MAX D2 -13.7 dBm


Center 2.422 GHz 6 MHz/ Span 60 MHz

Date: 23. JUL. 2017 15:29:34

802.11n-HT40 Middle Channel



802.11n-HT40 High Channel



Delta 1 [T1] -0.75 dB

Ref Lvl 26.5 dBm 741.48296593 KHz

RBW 100 kHz VBW 300 kHz SWT 5 ms RF Att 30 dB Unit dBm

10.5 dB Offset

D1 8.95 dBm D2 2.95 dBm

1MAX

1 [T1] 3.09 dBm 2.40158517 GHz -0.75 dB 741.48296593 KHz

Center 2.402 GHz 200 kHz/ Span 2 MHz

Date: 10.AUG.2017 09:58:22

Delta 1 [T1] -0.70 dB

Ref Lvl 30.5 dBm

745.49098196 kHz

RBW 100 kHz RF Att 30 dB

VBW 300 kHz

SWT 5 ms Unit dBm

10.5 dB Offset

D1 8.23 dBm

D2 2.23 dBm

1MAX

1 [T1] 2.32 dBm

1 [T1] 2.43958918 GHz

1 [T1] -0.70 dB

745.49098196 kHz


Center 2.44 GHz

200 kHz/

Span 2 MHz

Date: 10.AUG.2017 09:39:16

BLE High Channel




FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	22~24 °C
Relative Humidity:	50~53 %
ATM Pressure:	100.2~101.0 kPa

The testing was performed by Haiguo Li on 2017-07-23 and 2017-08-10.

EUT operation mode: Transmitting

Wi-Fi mode

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Max Conducted Average Output Power (dBm)	Limit (dBm)
802.11b				
Low	2412	10.96	8.10	30
Middle	2442	11.53	8.78	30
High	2472	11.92	9.06	30
802.11g				
Low	2412	14.66	7.83	30
Middle	2442	15.06	8.18	30
High	2472	15.35	8.50	30
802.11n HT20				
Low	2412	14.23	7.63	30
Middle	2442	14.49	8.19	30
High	2472	15.00	8.12	30
802.11n HT40				
Low	2422	14.17	7.50	30
Middle	2442	15.48	8.62	30
High	2462	14.67	7.85	30

BLE mode


Channel	Frequency (MHz)	Max Peak Output Power (dBm)	Limit (dBm)	Result
Low	2402	8.74	30	Pass
Middle	2440	8.56	30	Pass
High	2480	7.72	30	Pass

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

**Test Data****Environmental Conditions**

Temperature:	22~24 °C
Relative Humidity:	50~53 %
ATM Pressure:	100.2~101.0 kPa


The testing was performed by Haiguo Li on 2017-07-23 and 2017-08-10.

EUT operation mode: Transmitting


Test Result: Compliance

Please refer to the following plots.


802.11b: Band Edge, Left Side




802.11b: Band Edge, Right Side




802.11g: Band Edge, Left Side




802.11g: Band Edge, Right Side




802.11n-HT20: Band Edge, Left Side




802.11n-HT20: Band Edge, Right Side




802.11n-HT40: Band Edge, Left Side




802.11n-HT40: Band Edge, Right Side



BLE: Band Edge, Left Side



BLE: Band Edge, Right Side




FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	22~24 °C
Relative Humidity:	50~53 %
ATM Pressure:	100.5~101.0 kPa


The testing was performed by Haiguo Li on 2017-07-23 and 2017-08-10.

EUT operation mode: Transmitting


Test Result: Pass

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b mode			
Low	2412	-14.64	≤ 8
Middle	2442	-14.04	≤ 8
High	2472	-14.02	≤ 8
802.11g mode			
Low	2412	-17.54	≤ 8
Middle	2442	-17.31	≤ 8
High	2472	-16.17	≤ 8
802.11n-HT20 mode			
Low	2412	-19.28	≤ 8
Middle	2442	-17.83	≤ 8
High	2472	-17.06	≤ 8
802.11n HT40			
Low	2422	-21.39	≤ 8
Middle	2442	-20.18	≤ 8
High	2462	-21.01	≤ 8
BLE mode			
Low	2402	-5.55	≤ 8
Middle	2440	-5.90	≤ 8
High	2480	-6.84	≤ 8


Power Spectral Density, 802.11b Low Channel




Power Spectral Density, 802.11b Middle Channel




Power Spectral Density, 802.11b High Channel




Power Spectral Density, 802.11g Low Channel




Power Spectral Density, 802.11g Middle Channel




Power Spectral Density, 802.11g High Channel




Power Spectral Density, 802.11n-HT20 Low Channel




Power Spectral Density, 802.11n-HT20 Middle Channel




Power Spectral Density, 802.11n-HT20 High Channel




Power Spectral Density, 802.11n-HT40 Low Channel




Power Spectral Density, 802.11n-HT40 Middle Channel




Power Spectral Density, 802.11n-HT40 High Channel




Power Spectral Density, BLE Low Channel



Power Spectral Density, BLE Middle Channel



Power Spectral Density, BLE High Channel



***** END OF REPORT *****