

FCC TEST REPORT

(Part 15, Subpart C)

Applicant:	Juniper Systems, Inc.
Address:	1132 W 1700 N Logan, UT 84321 USA



Manufacturer or Supplier:	Juniper Systems, Inc.
Address:	1132 W 1700 N Logan, UT 84321 USA
Product:	ALTA
Brand Name:	Juniper Systems
Model Name:	ALT1 / FC-8000 / SHC8000
FCC ID:	VSFALT1
Date of tests:	Dec. 30, 2025 - Jul. 10, 2026

The tests have been carried out according to the requirements of the following standard:

☒ **FCC Part 15, Subpart C, Section 15.247**

☒ **ANSI C63.10-2020**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Carl Xie Engineer / Mobile Department	Approved by Simon Wang Manager / Mobile Department
	
Date: Jul. 10, 2026	Date: Jul. 10, 2026

Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 SUMMARY OF TEST RESULTS.....	5
1.1 MEASUREMENT UNCERTAINTY	6
2 GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT.....	7
2.2 DESCRIPTION OF TEST MODES.....	9
2.2.1 CONFIGURATION OF SYSTEM UNDER TEST	10
2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	10
2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	12
2.4 DESCRIPTION OF SUPPORT UNITS.....	12
3 TEST TYPES AND RESULTS.....	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	13
3.1.2 TEST INSTRUMENTS.....	14
3.1.3 TEST PROCEDURES	15
3.1.4 DEVIATION FROM TEST STANDARD	15
3.1.5 TEST SETUP	16
3.1.6 EUT OPERATING CONDITIONS	16
3.1.7 TEST RESULTS	17
3.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT	19
3.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT	19
3.2.2 TEST INSTRUMENTS.....	20
3.2.3 TEST PROCEDURES	22
3.2.4 DEVIATION FROM TEST STANDARD	22
3.2.5 TEST SETUP.....	23
3.2.6 EUT OPERATING CONDITIONS	24
3.2.7 TEST RESULTS	25
3.3 NUMBER OF HOPPING FREQUENCY USED.....	57
3.3.1 LIMIT OF HOPPING FREQUENCY USED	57
3.3.2 TEST SETUP	57
3.3.3 TEST INSTRUMENTS.....	58
3.3.4 TEST PROCEDURES	59
3.3.5 DEVIATION FROM TEST STANDARD	59
3.3.6 TEST RESULTS	59
3.4 DWELL TIME ON EACH CHANNEL	60
3.4.1 LIMIT OF DWELL TIME USED	60
3.4.2 TEST SETUP	60
3.4.3 TEST INSTRUMENTS.....	60
3.4.4 TEST PROCEDURES	60
3.4.5 DEVIATION FROM TEST STANDARD	61
3.4.6 TEST RESULTS	61
3.5 CHANNEL BANDWIDTH.....	62
3.5.1 LIMITS OF CHANNEL BANDWIDTH	62
3.5.2 TEST SETUP	62
3.5.3 TEST INSTRUMENTS.....	62
3.5.4 TEST PROCEDURE.....	62
3.5.5 DEVIATION FROM TEST STANDARD	62
3.5.6 EUT OPERATING CONDITION	63
3.5.7 TEST RESULTS	63
3.6 HOPPING CHANNEL SEPARATION	64
3.6.1 LIMIT OF HOPPING CHANNEL SEPARATION	64
3.6.2 TEST SETUP	64
3.6.3 TEST INSTRUMENTS.....	64

Test Report No.: RF260714B013

3.6.4	TEST PROCEDURES	64
3.6.1	DEVIATION FROM TEST STANDARD	64
3.6.2	TEST RESULTS	64
3.7	MAXIMUM OUTPUT POWER	65
3.7.1	LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT	65
3.7.2	TEST SETUP	65
3.7.3	TEST INSTRUMENTS	65
3.7.4	TEST PROCEDURES	65
3.7.5	DEVIATION FROM TEST STANDARD	66
3.7.6	EUT OPERATING CONDITION	66
3.7.7	TEST RESULTS	66
3.7.7.1	MAXIMUM PEAK OUTPUT POWER	66
3.7.7.2	AVERAGE OUTPUT POWER (FOR REFERENCE).....	66
3.8	OUT OF BAND MEASUREMENT	67
3.8.1	LIMITS OF OUT OF BAND MEASUREMENT	67
3.8.2	TEST INSTRUMENTS	67
3.8.3	TEST PROCEDURE	67
3.8.4	DEVIATION FROM TEST STANDARD	67
3.8.5	EUT OPERATING CONDITION	67
3.8.6	TEST RESULTS	67
4	PHOTOGRAPHS OF THE TEST CONFIGURATION	68
5	MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	69
6	APPENDIX.....	70



Test Report No.: RF260714B013

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF260714B013	Original release	Jul. 10, 2026

Test Report No.: RF260714B013

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C		
STANDARD	TEST TYPE AND LIMIT	RESULT
15.207	AC Power Conducted Emission	Compliance
15.247(a)(1)(iii)	Number of Hopping Frequency Used	Compliance
15.247(a)(1)(iii)	Dwell Time on Each Channel	Compliance
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	Compliance
15.247(b)	Maximum Peak Output Power	Compliance
15.247(d)&15.209	Transmitter Radiated Emissions	Compliance
15.247(d)	Out of band Measurement	Compliance
15.203	Antenna Requirement	Compliance

NOTE:

1. If the Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.
2. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

*Test Lab Information Reference

Lab A:

BOOMWAVE TEST (SHENZHEN) CO., LTD.

Lab Address:

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th Road, Chiwan Community, Zhaoshang Street, Nanshan District, Shenzhen, Guangdong, P.R. CHINA

Accredited Test Lab Cert 7607.01


The FCC Site Registration No. is 646781; The Designation No. is CN1429.

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	$\pm 2.70\text{dB}$
Radiated emissions (9KHz~30MHz)	$\pm 2.68\text{dB}$
Radiated emissions (30MHz~1GHz)	$\pm 4.98\text{dB}$
Radiated emissions (1GHz ~6GHz)	$\pm 4.70\text{dB}$
Radiated emissions (6GHz ~18GHz)	$\pm 4.60\text{dB}$
Radiated emissions (18GHz ~40GHz)	$\pm 4.12\text{dB}$
Conducted emissions	$\pm 4.01\text{dB}$
Occupied Channel Bandwidth	$\pm 43.58\text{KHz}$
Conducted Output power	$\pm 2.06\text{dB}$
Power Spectral Density	$\pm 0.85\text{ dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



The verdicts in this test report are given according the above diagram:

Case	Measured Value	Uncertainty Range	Verdict
1	below pass mark	below pass mark	Passed
2	below pass mark	within pass mark	Passed
3	above pass mark	within pass mark	Failed
4	above pass mark	above pass mark	Failed

That means, the laboratory applies, as decision rule (see ISO/IEC 17025:2017), the so-called shared risk principle.

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	ALTA
BRAND NAME	Juniper Systems
MODEL NAME	ALT1 / FC-8000 / SHC8000
NOMINAL VOLTAGE	3.7Vdc
MODULATION TECHNOLOGY	FHSS
MODULATION TYPE	GFSK, $\pi/4$ -DQPSK, 8DPSK
OPERATING FREQUENCY	2402MHz~2480MHz
NUMBER OF CHANNEL	79
MAX. OUTPUT POWER	193.20mW (Max. Measured)
ANTENNA GAIN	☒ Provided by client
	-0.24dBi
ANTENNA TYPE	PIFA Antenna
HW VERSION	DVT2
SW VERSION	JP_W.00.00.0128.T1_USERDEBUG
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	NA

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
- Antenna gain and EUT conducted cable loss are provided by the customer, and the laboratory will record the results based on these items that involve these two parameters.

4. List of Accessory:

ACCESSORIES	BRAND	MANUFACTURER	MODEL	SPECIFICATION
Battery 1	NA	Fullymax Battery Co., Ltd.	FBC442760	3.7Vdc, 700mAh
Battery 2	NA	Fullymax Battery Co., Ltd.	FBC6570106	3.8Vdc, 5700mAh
Battery 3	NA	Fullymax Battery Co., Ltd.	FBC8570106	3.7Vdc, 15000mAh
AC Adapter 1	Juniper	SHENZHEN MERRYKING ELECTRONICS	MK-P301EXC	I/P: 100-240Vac, 800mA, O/P: 12Vdc, 2500mA

Test Report No.: RF260714B013

		CO.,LTD.		
USB Cable 1	CONSHARE	CONSHARE	80.10.320002	1.0 meter

2.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 4 photograph of the test configuration for reference.

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on X axis for radiated emission.

Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G**: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission

RE≥1G: Radiated Emission above 1GHz
APCM: Antenna Port Conducted Measurement

RADIATED EMISSION TEST (BELOW 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- ☒ The following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	39	FHSS	$\pi/4$ -DQPSK	2DH5

RADIATED EMISSION TEST (ABOVE 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- ☒ The following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	0, 39, 78	FHSS	GFSK	1DH5
-	0 to 78	0, 39, 78	FHSS	$\pi/4$ DQPSK	2DH5
-	0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

Test Report No.: RF260714B013

POWER LINE CONDUCTED EMISSION TEST:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture) and packet type.
- ☒ The following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	78	FHSS	$\pi/4$ -DQPSK	2DH5

ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- ☒ The following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH1/DH3/DH5
0 to 78	0, 39, 78	FHSS	$\pi/4$ DQPSK	2DH1/2DH3/2DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH1/3DH3/3DH5

<u>TEST CONDITION</u>			
APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	23deg. C, 70%RH	DC 3.7V By Battery	Carl Xie
RE≥1G	23deg. C, 70%RH	DC 3.7V By Battery	Carl Xie
PLC	25deg. C, 52%RH	DC 3.7V By Battery	Carl Xie
APCM	25deg. C, 60%RH	DC 3.7V By Battery	Alan Yu

Test Report No.: RF260714B013

2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. Section 15.247

ANSI C63.10-2020

NOTE:

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Laptop	Lenovo	ThinkPad E14	HRSW00024	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A

3 TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5		
0.5 ~ 5	66 to 56	56 to 46
5 ~ 30	56	46
	60	50

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Pulse limiter	SCHWARZBECK	VTSD 9561F	01579	2025/7/22	2026/7/21
ESR.EMI TEST RECEIVER	Rohde&SCHWARZ	ESR	101405	2025/6/30	2026/6/29
ESR.EMI TEST RECEIVER	Rohde&SCHWARZ	ESR	101405	2026/6/29	2027/6/28
LISN	SCHWARZBECK	NSLK 8127	01216	2025/8/27	2026/8/26
Cable	Tonscend	/	/	2025/7/22	2026/7/21

NOTE:

1. The test was performed in CE shielded room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

3.1.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 DEVIATION FROM TEST STANDARD

No deviation.

3.1.5 TEST SETUP



- Note: 1.Support units were connected to second LISN.**
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT OPERATING CONDITIONS


- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.

3.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA										
FREQUENCY RANGE		150KHz ~ 30MHz			DETECTOR FUNCTION & RESOLUTION BANDWIDTH			Quasi-Peak (QP) / Average (AV), 9 kHz		
INPUT POWER		120Vac, 60Hz			ENVIRONMENTAL CONDITIONS			26deg. C, 51%RH		
TESTED BY		Carl Xie								
Rg	Frequency [MHz]	QPK Level [dBμV]	QPK Limit [dBμV]	QPK Margin [dB]	CAV Level [dBμV]	CAV: AVG Limit [dBμV]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.182	41.57	64.42	22.85	25.63	54.42	28.79	9.78	L1	9.000
1	0.533	32.29	56.00	23.71	8.14	46.00	37.86	9.75	L1	9.000
1	2.144	32.83	56.00	23.17	19.02	46.00	26.98	9.83	L1	9.000
1	4.506	30.90	56.00	25.10	18.02	46.00	27.98	10.09	L1	9.000
1	11.157	31.19	60.00	28.81	20.17	50.00	29.83	11.29	L1	9.000
1	29.499	32.81	60.00	27.19	23.13	50.00	26.87	14.88	L1	9.000

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Limit value - Emission level
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



FREQUENCY RANGE		150KHz ~ 30MHz			DETECTOR FUNCTION & RESOLUTION BANDWIDTH			Quasi-Peak (QP) / Average (AV), 9 kHz		
INPUT POWER		120Vac, 60Hz			ENVIRONMENTAL CONDITIONS			26deg. C, 51%RH		
TESTED BY		Carl Xie								
Rg	Frequency [MHz]	QPK Level [dBμV]	QPK Limit [dBμV]	QPK Margin [dB]	CAV Level [dBμV]	CAV: AVG Limit [dBμV]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.182	41.22	64.42	23.20	21.20	54.42	33.22	9.78	N	9.000
1	0.470	41.44	56.52	15.08	27.67	46.52	18.86	9.75	N	9.000
1	1.410	34.90	56.00	21.10	18.91	46.00	27.09	9.79	N	9.000
1	3.336	31.20	56.00	24.80	17.99	46.00	28.01	9.98	N	9.000
1	8.421	30.40	60.00	29.60	18.94	50.00	31.06	10.70	N	9.000
1	28.010	32.27	60.00	27.73	20.17	50.00	29.83	14.52	N	9.000

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Limit value - Emission level
5. Correction factor = Insertion loss + Cable loss
7. Emission Level = Correction Factor + Reading Value.



3.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldp n- CT0001143 -1216	2025/7/3	2026/7/2
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldp n- CT0001143 -1216	2026/7/2	2027/7/1
BiConiLog Antenna	ETS-LINDGREN	3143B	161965	2025/7/17	2026/7/16
Horn Antenna	SCHWARZBECK	BBHA9120D	3297	2025/9/27	2026/9/26
Horn Antenna	STEATITE	QWH-SL-18-40-K-SG QMS-00361	15433	2025/7/19	2026/7/18
Preamplifier	Tonscend	TPA184045	AP24L8060 388	2025/7/3	2026/7/2
Preamplifier	Tonscend	TPA184045	AP24L8060 388	2026/7/2	2027/7/1
MXE EMI Receiver	keysight	N9038B	MY5001801 7	2025/7/1	2026/6/30
MXE EMI Receiver	keysight	N9038B	MY5001801 7	2026/6/30	2027/6/29
MXG Vector Signal Generator	Keysight	N5183B	MY5910013 7	2025/6/30	2026/6/29
MXG Vector Signal Generator	Keysight	N5183B	MY5910013 7	2026/6/29	2027/6/28
Preamplifier	Tonscend	TPA001330	806JSAPO 408042510 15	2025/6/30	2026/6/29
Preamplifier	Tonscend	TPA001330	806JSAPO 408042510 15	2026/6/29	2027/6/28
Preamplifier	Tonscend	TPA011845	AP24L8060 392	2025/6/30	2026/6/29
Preamplifier	Tonscend	TPA011845	AP24L8060 392	2026/6/29	2027/6/28
Attenuator 6DB	SHX	TS2-6-6-A	230927166	2025/6/30	2026/6/29
Attenuator 6DB	SHX	TS2-6-6-A	230927166	2026/6/29	2027/6/28
Attenuator 6DB	SHX	TS2-6-6-A	230927165	2025/6/30	2026/6/29
Attenuator 6DB	SHX	TS2-6-6-A	230927165	2026/6/29	2027/6/28
Active Receive Loop Antenna	SCHWARZBECK	FMZB 1519 B	00173	2025/6/30	2026/6/29
Active Receive Loop Antenna	SCHWARZBECK	FMZB 1519 B		2026/6/29	2027/6/28
Temp. & Humi. Recorder	Kejian	HTC-01	157246	2025/7/2	2026/7/1

Test Report No.: RF260714B013

Temp. & Humi. Recorder	Kejian	HTC-01	157246	2026/7/1	2027/6/30
HIGH pass FILTER_1-18	EWT	EWT-57-0222	EWT-57-0222	2025/6/30	2026/6/29
HIGH pass FILTER_1-18	EWT	EWT-57-0222	EWT-57-0222	2026/6/29	2027/6/28
HIGH pass FILTER_7-18	EWT	EWT-57-0223	EWT-57-0223	2025/6/30	2026/6/29
HIGH pass FILTER_7-18	EWT	EWT-57-0223	EWT-57-0223	2026/6/29	2027/6/28
HIGH pass FILTER_3-18	EWT	EWT-57-0221	EWT-57-0221	2025/6/30	2026/6/29
HIGH pass FILTER_3-18	EWT	EWT-57-0221	EWT-57-0221	2026/6/29	2027/6/28
DC~1GHz Lowpass Filter	EWT	EWT-56-0649	EWT-56-0649	2025/7/3	2026/7/2
DC~1GHz Lowpass Filter	EWT	EWT-56-0649	EWT-56-0649	2026/7/2	2027/7/1
Cable 1	N/A	N/A	N/A	2025/9/28	2026/9/27
Cable 2	N/A	N/A	N/A	2025/9/28	2026/9/27
Cable 3	N/A	N/A	N/A	2025/9/28	2026/9/27

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Chamber.
3. The FCC Site Registration No. is 646781; The Designation No. is CN1429.

3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit.
5. All modes of operation were investigated and the worst-case emissions are reported.

3.2.4 DEVIATION FROM TEST STANDARD


No deviation.

3.2.5 TEST SETUP


<Frequency Range 9KHz~30MHz >



< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.

Test Report No.: RF260714B013

3.2.7 TEST RESULTS


NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

BELOW 1GHz WORST-CASE DATA

BT_π/4-DQPSK									
CHANNEL		Channel 39		DETECTOR FUNCTION			Quasi-Peak (QP)		
FREQUENCY RANGE		30MHz ~ 1GHz							
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
Rg	Frequency [MHz]	QPK Level [dBμV/m]	QPK Limit [dBμV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	44.696	21.74	40.00	18.26	-10.28	H	1	1.00	120.000
1	75.833	25.77	40.00	14.23	-16.14	H	359.1	1.00	120.000
1	168.516	27.55	43.50	15.95	-14.08	H	5.5	1.00	120.000
1	276.332	15.89	46.00	30.11	-8.26	H	5.5	1.00	120.000
1	459.662	18.59	46.00	27.41	-4.13	H	359.1	1.00	120.000
1	623.301	22.21	46.00	23.79	-2.23	H	5.5	1.00	120.000

REMARKS:

1. Emission Level(dBuV/m) = Read Level(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Limit value – Emission level.



BOOMWAVE TEST (SHENZHEN)
CO., LTD.

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan
4th Road, Chiwan Community, Zhaoshang Street,
Nanshan District, Shenzhen, Guangdong, P.R. CHINA


Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com

Test Report No.: RF260714B013

CHANNEL		Channel 39		DETECTOR FUNCTION		Quasi-Peak (QP)			
FREQUENCY RANGE		30MHz ~ 1GHz							
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M									
Rg	Frequency [MHz]	QPK Level [dBμV/m]	QPK Limit [dBμV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	36.305	26.36	40.00	13.64	-12.26	V	359	1.00	120.000
1	74.814	32.77	40.00	7.23	-15.89	V	146.3	1.00	120.000
1	170.844	23.07	43.50	20.43	-13.91	V	4.9	1.00	120.000
1	276.962	15.49	46.00	30.51	-8.23	V	298.1	1.00	120.000
1	414.945	18.24	46.00	27.76	-3.85	V	359	1.00	120.000
1	593.231	21.73	46.00	24.27	-2.82	V	146.3	1.00	120.000

REMARKS:

1. Emission Level(dBuV/m) = Read Level(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Limit value – Emission level.



ABOVE 1GHz WORST-CASE DATA


Note: All other emissions that greater than 20dB below the limit were not recorded.


BT_GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,369.500	58.34	74.00	15.66	36.74	H	131	1.00
5	2,390.000	56.83	74.00	17.17	37.00	H	0.9	2.00
5	2,402.500	111.02			37.17	H	5	1.00






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,386.000	57.44	74.00	16.56	36.94	V	1	1.00
5	2,390.000	56.32	74.00	17.68	37.00	V	358.6	1.00
5	2,402.500	106.04			37.17	V	5.7	1.00






REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value – Emission level.
3. 2402MHz: Fundamental frequency.


Test Report No.: RF260714B013



BOOMWAVE TEST (SHENZHEN)
CO., LTD.


Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan
4th Road, Chiwan Community, Zhaoshang Street,
Nanshan District, Shenzhen, Guangdong, P.R. CHINA


Mobile: +86 15118052731
Email:shimin.wang@boomwavelab.com





REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value – Emission level.
3. 2402MHz: Fundamental frequency.











REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value – Emission level.
3. 2480MHz: Fundamental frequency.






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,389.000	57.37	74.00	16.63	36.98	V	86.8	1.00
5	2,390.000	56.52	74.00	17.48	37.00	V	5.1	1.00
5	2,402.500	104.34			37.17	V	131	1.00






REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value – Emission level.
3. 2402MHz: Fundamental frequency.








REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value – Emission level.
3. 2441MHz: Fundamental frequency.











REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value – Emission level.
3. 2480MHz: Fundamental frequency.






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,387.000	57.79	74.00	16.21	36.96	V	40.1	1.00
5	2,390.000	56.59	74.00	17.41	37.00	V	319.9	2.00
5	2,402.000	106.50			37.16	V	128.5	1.00






REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value – Emission level.
3. 2402MHz: Fundamental frequency.





REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value – Emission level.
3. 2402MHz: Fundamental frequency.

