



IML Labels & Systems Ltd
441 Brightside Lane
Sheffield
S9 2RS
Tel – 0114 2422111
Fax – 0114 2612231
Email – info@iml-labels.co.uk
www.iml-labels.co.uk

Product Specification

Etrans S/A

Description

Etrans S/A is a 96 micron matt coated biaxially orientated polypropylene, laminated with a high tack BS5609 marine approved adhesive to a glassine liner. The adhesive is a rubber based hot melt designed to give superior initial tack on moist and rough surfaces. The 63gsm honey glassine liner is suitable for use where there is automatic label registration or dispensing if required. The material & adhesive is Isega approved for direct contact with dry and non-fatty foods.

Printability

Variable information printing and barcodes are possible using a combination of thermal transfer printer and suitable ribbons. IML will be pleased to advise on the best printer and ribbon solution for maximum resistance and readability.

Applications

Etrans S/A is ideally suited to applications where label durability is required, surviving long term outdoor exposure and resisting water and various chemicals to ensure product identification is maintained. These properties are particularly relevant to the Chemical, Steel, Building & Construction, Horticultural and Engineering industries.

Thickness	Micron - 96 + / - 8%
Weight	GSM - 72 + / - 8%
Temperature Resistance	-20 °c / +80°c
Adhesive Strength	Marine Approved Perm (BS5609)
Recommended Ribbons	IML Standard

The above values and information are given in good faith but without warranty. IML recommends the testing of samples to ascertain suitability. It is the responsibility of the end user to satisfy the suitability of the product for the application. All goods are supplied in accordance with our standard conditions of sale.



FM 29508

