

RF TEST REPORT



Report No.: 15020390-FCC-R1

Supersede Report No.: N/A

Applicant	Beijing Jia An Electronic Technology Co., Ltd	
Product Name	Wifi Module	
Main Model	TA3200R1D-UFL	
Test Standard	FCC Part 15.247: 2014, ANSI C63.10: 2013	
Test Date	April 27 to April 29, 2015	
Issue Date	April 29, 2015	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification ☒		
Equipment did not comply with the specification ☐		
		
William Long Test Engineer	Herve Idoko Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (Nanjing-China) Laboratories

2-1 Longcang Avenue Yuhua Economic and
Technology Development Park, Nanjing, China

Tel: +86(25)86730128/86730129 Fax: +86(25)86730127 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	15020390-FCC-R1
Page	3 of 41

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY.....	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	7
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	8
6.1 RF EXPOSURE.....	8
6.2 ANTENNA REQUIREMENT	9
6.3 DTS (6 DB&20 DB) CHANNEL BANDWIDTH	10
6.4 MAXIMUM OUTPUT POWER	16
6.5 POWER SPECTRAL DENSITY	20
6.6 BAND-EDGE & UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS.....	24
6.7 AC POWER LINE CONDUCTED EMISSIONS.....	27
6.8 RADIATED SPURIOUS EMISSIONS.....	28
ANNEX A. TEST INSTRUMENT	32
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	33
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	37
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	40
ANNEX E. DECLARATION OF SIMILARITY	41

Test Report No.	15020390-FCC-R1
Page	5 of 41

1. Report Revision History

Report No.	Report Version	Description	Issue Date
15020390-FCC-R1	NONE	Original	April 29, 2015

2. Customer information

Applicant Name	Beijing Jia An Electronic Technology Co., Ltd
Applicant Add	No.19 GuCheng West Street, Shi Jing Shan District, Beijing 100043,CHINA
Manufacturer	Beijing Jia An Electronic Technology Co., Ltd
Manufacturer Add	No.19 GuCheng West Street, Shi Jing Shan District, Beijing 100043,CHINA

3. Test site information

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Address	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	986914
IC Test Site No.	4842B-1
Test Software	Labview of SIEMIC version 1.0

Test Report No.	15020390-FCC-R1
Page	6 of 41

4. Equipment under Test (EUT) Information

Description of EUT:	Wifi Module
Main Model:	TA3200R1D-UFL
Serial Model:	N/A
Date EUT received:	November 10, 2014
Test Date(s):	April 27 to April 29, 2015
Max Conducted AV Power (dBm)	16.19dBm (802.11b)
Antenna Gain:	External Antenna Gain: 7dBi
Type of Modulation:	802.11b/g/n: DSSS/OFDM
RF Operating Frequency (ies):	802.11b/g/n(20M): 2412-2462 MHz(TX/RX)
Number of Channels:	802.11b/g/n(20M): 11CH
Port:	N/A
Input Power:	DC 3.3V
Trade Name :	N/A
FCC ID:	VVJ-TA3200R1D-SA

Note: the difference between the model TA3200R1D-SA and TA3200R1D-UFL is:
TA3200R1D-SA use PCB antenna, TA3200R1D-UFL use External antenna, others are the same.
So we only change the **Band-Edge** and **Radiated Spurious Emissions** in 15020390-FCC-R1, other test result please refer to report: 14021186-FCC-R1. FCC ID: VVJ-TA3200R1D-SA.

Test Report No.	15020390-FCC-R1
Page	7 of 41

5. Test Summary

The product was tested in accordance with the following specifications.
All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§ 15.247 (i), §2.1091	RF Exposure	Compliance
§ 15.203	Antenna Requirement	Compliance
§ 15.247 (a)(2)	DTS (6 dB&20 dB) CHANNEL BANDWIDTH	Compliance
§ 15.247(b)(3)	Conducted Maximum Output Power	Compliance
§ 15.247(e)	Power Spectral Density	Compliance
§ 15.247(d)	Band-Edge & Unwanted Emissions into Non-Restricted Frequency Bands	Compliance
§ 15.207 (a),	AC Power Line Conducted Emissions	N/A
§ 15.205, §15.209, § 15.247(d)	Radiated Spurious Emissions & Unwanted Emissions into Restricted Frequency Bands	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Radiated Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	3.952dB

Test Report No.	15020390-FCC-R1
Page	8 of 41

6. Measurements, Examination And Derived Results

6.1 RF Exposure

The EUT is a mobile device, thus requires please refer to RF EXPOSURE Report: 15020390-FCC-H1.

6.2 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules.

§15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit. And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction


External Antenna Gain: 7dBi.

Result: Compliance.

6.3 DTS (6 dB&20 dB) Channel Bandwidth

Temperature	20°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
Test date :	April 27, 2015
Tested By :	William Long

Spec	Item	Requirement	Applicable
§ 15.247(a)(2) RSSGen (4.6.1)	a)	6dB BW≥500kHz;	☒
	b)	20dB BW: For FCC reference only; required by IC.	☒

Test Setup	 Spectrum Analyzer EUT
------------	--

Test Procedure	558074 D01 DTS Meas Guidance v03r02, 8.1 DTS bandwidth <u>6dB Emission bandwidth measurement procedure</u> - Set RBW = 100 kHz. - Set the video bandwidth (VBW) ≥ 3 x RBW. - Detector = Peak. - Trace mode = max hold. - Sweep = auto couple. - Allow the trace to stabilize. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. - <u>20dB bandwidth</u> C63.10 Occupied Bandwidth (OBW=20dB bandwidth) - Set RBW = 1%-5% OBW. - Set the video bandwidth (VBW) ≥ 3 x RBW. - Set the span range between 2 times and 5 times of the OBW. - Sweep time=Auto, Detector=PK, Trace=Max hold. - Once reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e., the widest) bandwidth. Unless otherwise specified for an unlicensed wireless device, measure the bandwidth at the 20 dB level with respect to the reference level.
----------------	---

Remark	The following test result please refer to report: 14021186-FCC-R1. FCC ID: VVJ-TA3200R1D-SA		
Result	☒ Pass	☐ Fail	
Test Data	☒ Yes	☐ N/A	
Test Plot	☒ Yes (See below)	☐ N/A	

6dB Bandwidth measurement result


Type	Test mode	CH	Freq (MHz)	Result (MHz)	Limit (MHz)	Result
6dB BW	802.11b	Low	2412	9.968	≥ 0.5	Pass
		Mid	2437	9.567	≥ 0.5	Pass
		High	2462	9.117	≥ 0.5	Pass
	802.11g	Low	2412	16.32	≥ 0.5	Pass
		Mid	2437	16.26	≥ 0.5	Pass
		High	2462	16.32	≥ 0.5	Pass
	802.11n(20M)	Low	2412	17.24	≥ 0.5	Pass
		Mid	2437	17.13	≥ 0.5	Pass
		High	2462	16.99	≥ 0.5	Pass


20 dB Bandwidth measurement result

Type	Test mode	CH	Freq (MHz)	Result (MHz)	Limit (MHz)	Result
20dB BW	802.11b	Low	2412	16.45	≥ 0.5	Pass
		Mid	2437	16.25	≥ 0.5	Pass
		High	2462	15.97	≥ 0.5	Pass
	802.11g	Low	2412	17.38	≥ 0.5	Pass
		Mid	2437	17.06	≥ 0.5	Pass
		High	2462	17.09	≥ 0.5	Pass
	802.11n(20M)	Low	2412	18.64	≥ 0.5	Pass
		Mid	2437	18.46	≥ 0.5	Pass
		High	2462	18.04	≥ 0.5	Pass


Test Plots

6dB Bandwidth measurement result






6dB Bandwidth - Low CH 2412 - 802.11n(20M)





6dB Bandwidth - Mid CH 2437- 802.11n(20M)




6dB Bandwidth - High CH 2462 - 802.11 n(20M)

20dB Bandwidth measurement result





20dB Bandwidth - Low CH 2412 - 802.11n(20M)



20dB Bandwidth - Mid CH 2437- 802.11n(20M)




20dB Bandwidth - High CH 2462 - 802.11 n(20M)

6.4 Maximum Output Power

Temperature	20°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
Test date :	April 29, 2015
Tested By :	William Long

Requirement(s):


Spec	Item	Requirement	Applicable
§15.247(b) (2),RSS210 (A8.4)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	☐
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	☐
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	☐
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	☐
	e)	FHSS in 902-928MHz with ≥ 25 & < 50 channels: ≤ 0.25 Watt	☐
	f)	DSSS in 902-928MHz, 2400-2483.5MHz, 5725-5850MHz: ≤ 1 Watt	☒
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	558074 D01 DTS MEAS Guidance v03r02, 9.1.2 Integrated band power method Maximum output power measurement procedure - a) Set span to at least 1.5 times the OBW. - b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz. - c) Set VBW $\geq 3 \times$ RBW. - d) Number of points in sweep $\geq 2 \times$ span / RBW. (This gives bin-to-bin spacing $\leq$ RBW/2, so that narrowband signals are not lost between frequency bins.) - e) Sweep time = auto. - f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode. - g) If transmit duty cycle $< 98\%$, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run". - h) Trace average at least 100 traces in power averaging (i.e., RMS) mode. - i) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.		
Remark	The following test result please refer to report: 14021186-FCC-R1. FCC ID: VVJ-TA3200R1D-SA		
Result	☒ Pass ☐ Fail		
Test Data	☒ Yes ☐ N/A		
Test Plot	☒ Yes (See below) ☐ N/A		


Output Power measurement result

Type	Test mode	CH	Freq (MHz)	Conducted AV Power (dBm)	Limit (dBm)	Result
Output power	802.11b	Low	2412	15.96	29	Pass
		Mid	2437	16.19	29	Pass
		High	2462	15.23	29	Pass
	802.11g	Low	2412	11.34	29	Pass
		Mid	2437	12.17	29	Pass
		High	2462	11.17	29	Pass
	802.11n(20M)	Low	2412	10.16	29	Pass
		Mid	2437	11.22	29	Pass
		High	2462	9.77	29	Pass


Test Plots

Output Power measurement result






Output power - Low CH 2412 - 802.11n(20M)




Output power - Mid CH 2437 - 802.11 n(20M)



Output power - High CH 2462 - 802.11 n(20M)

6.5 Power Spectral Density

Temperature	20°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
Test date :	April 29, 2015
Tested By :	William Long


Spec	Item	Requirement	Applicable
§15.247(e)	a)	The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	☒
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	558074 D01 DTS MEAS Guidance v03r02, 10.2 power spectral density method power spectral density measurement procedure - a) Set analyzer center frequency to DTS channel center frequency. - b) Set the span to 1.5 times the DTS bandwidth. - c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$. - d) Set the VBW $\geq 3 \times \text{RBW}$. - e) Detector = peak. - f) Sweep time = auto couple. - g) Trace mode = max hold. - h) Allow trace to fully stabilize. - i) Use the peak marker function to determine the maximum amplitude level within the RBW. - j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.		
Remark	The following test result please refer to report: 14021186-FCC-R1. FCC ID: VVJ-TA3200R1D-SA		
Result	☒ Pass ☐ Fail		
Test Data	☒ Yes ☐ N/A		
Test Plot	☒ Yes (See below) ☐ N/A		


Power Spectral Density measurement result

Type	Test mode	CH	Freq (MHz)	PSD (dBm)	Limit (dBm)	Result
PSD	802.11b	Low	2412	-1.749	7	Pass
		Mid	2437	-1.446	7	Pass
		High	2462	-2.775	7	Pass
	802.11g	Low	2412	-9.209	7	Pass
		Mid	2437	-8.169	7	Pass
		High	2462	-9.613	7	Pass
	802.11n(20M)	Low	2412	-10.945	7	Pass
		Mid	2437	-9.896	7	Pass
		High	2462	-11.468	7	Pass


Test Plots

Power Spectral Density measurement result






PSD - Low CH 2412 - 802.11n(20M)



PSD - Mid CH 2437 - 802.11n(20M)




PSD - High CH 2462 - 802.11n(20M)

6.6 Band-Edge & Unwanted Emissions into Non-Restricted Frequency Bands

Temperature	20°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
Test date :	April 29, 2015
Tested By :	William Long

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(d)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	☒


Test Setup	
------------	---

Test Procedure	Radiated Method Only 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range. 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth for Average detection (AV) as below at frequency above 1GHz. ■ 1/T kHz (Duty cycle < 98%) □ 10 Hz (Duty cycle > 98%) 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. 5. Repeat above procedures until all measured frequencies were complete.
----------------	---


Remark	
Result	☒ Pass ☐ Fail
Test Data	☒ Yes ☐ N/A
Test Plot	☒ Yes (See below) ☐ N/A

Test Plots

Band Edge measurement result




Date: 29.APR.2015 14:48:03




Date: 29.APR.2015 14:43:06

Band Edge, Left Side (Average) - 802.11b




Date: 29.APR.2015 14:51:23

Band Edge, Left Side (Peak) - 802.11b




Date: 29.APR.2015 14:53:55

Band Edge, Right Side (Average) - 802.11b



Date: 29.APR.2015 14:55:33


Band Edge, Right Side (Peak) - 802.11b




Date: 29.APR.2015 14:54:37

Band Edge, Left Side (Average) - 802.11g

Band Edge, Left Side (Peak) - 802.11g




Date: 29.APR.2015 14:56:35




Date: 29.APR.2015 14:57:18

Band Edge, Right Side (Average) - 802.11g

Band Edge, Right Side (Peak) - 802.11g




Date: 29.APR.2015 14:58:52




Date: 29.APR.2015 14:58:11

Band Edge, Left Side (Average) - 802.11n(20M)

Band Edge, Left Side (Peak) - 802.11n(20M)



Date: 29.APR.2015 14:59:43



Date: 29.APR.2015 15:00:37


Band Edge, Right Side (Average) - 802.11n(20M)

Band Edge, Right Side (Peak) - 802.11n(20M)

6.7 AC Power Line Conducted Emissions

Temperature	---°C
Relative Humidity	---%
Atmospheric Pressure	---mbar
Test date :	---
Tested By :	William Long

Requirement(s):

Spec	Item	Requirement	Applicable														
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	☒														
		<table><tr><th rowspan="2">Frequency ranges (MHz)</th><th colspan="2">Limit (dBµV)</th></tr><tr><th>QP</th><th>Average</th></tr><tr><td>0.15 ~ 0.5</td><td>66 – 56</td><td>56 – 46</td></tr><tr><td>0.5 ~ 5</td><td>56</td><td>46</td></tr><tr><td>5 ~ 30</td><td>60</td><td>50</td></tr></table>		Frequency ranges (MHz)	Limit (dBµV)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50
		Frequency ranges (MHz)			Limit (dBµV)												
				QP	Average												
		0.15 ~ 0.5		66 – 56	56 – 46												
0.5 ~ 5	56	46															
5 ~ 30	60	50															
Test Setup	 Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.																
Procedure	- The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. - The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. - The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable. - All other supporting equipment were powered separately from another main supply. - The EUT was switched on and allowed to warm up to its normal operating condition. - A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. - High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. - Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).																
Remark	Power supply By Battery																
Result	☐ Pass ☐ Fail																
Test Data	☐ Yes ☒ N/A																
Test Plot	☐ Yes (See below) ☒ N/A																

6.8 Radiated Spurious Emissions


Temperature	20°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
Test date :	April 29, 2015
Tested By :	William Long

Requirement(s):


Spec	Item	Requirement	Applicable										
47CFR§15.247(d) , RSS210 (A8.5)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges <table><tr><th>Frequency range (MHz)</th><th>Field Strength (µV/m)</th></tr><tr><td>30 – 88</td><td>100</td></tr><tr><td>88 – 216</td><td>150</td></tr><tr><td>216 960</td><td>200</td></tr><tr><td>Above 960</td><td>500</td></tr></table>	Frequency range (MHz)	Field Strength (µV/m)	30 – 88	100	88 – 216	150	216 960	200	Above 960	500	☒
	Frequency range (MHz)	Field Strength (µV/m)											
	30 – 88	100											
	88 – 216	150											
216 960	200												
Above 960	500												
b)	For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required ☒ 20 dB down ☐ 30 dB down	☒											
c)	or restricted band, emission must also comply with the radiated emission limits specified in 15.209	☒											

Test Setup

A: Frequency Below 1000MHz:



B: Frequency Above 1000MHz:



Procedure

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:
 - a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen.
 - b. The EUT was then rotated to the direction that gave the maximum emission.
 - c. Finally, the antenna height was adjusted to the height that gave the maximum emission.
3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.
The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.
5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.

Remark

Result

☒ Pass ☐ Fail

Test Data

☒ Yes ☐ N/A


Test Plot

☒ Yes (See below) ☐ N/A

Test Mode: Transmitting Mode

(Below 1GHz)

Peak Detector 
Quasi Peak Limit 



Test Data

Horizontal & Vertical Polarity Plot @3m

Frequency (MHz)	Peak (dBμV/m)	Azimuth	Polarity (H/V)	Height (cm)	Factors (dB)	Limit (dBμV/m)	Margin (dB)
735.19	29.75	285.20	V	100.00	-19.29	46.00	-16.25
790.97	29.58	134.70	V	100.00	-17.74	46.00	-16.42
796.30	29.23	129.00	V	100.00	-17.58	46.00	-16.77
909.30	28.95	31.30	H	100.00	-18.61	46.00	-17.05
916.46	28.78	245.60	V	200.00	-18.49	46.00	-17.22
946.29	28.68	334.30	V	100.00	-18.12	46.00	-17.32

Test Mode:	Transmitting Mode
-------------------	--------------------------

Note: Other modes were verified, only the result of worst case basic rate mode was presented.

Mode: 802.11b

Low Channel (2412 MHz)

Frequency (MHz)	Substituted level (dBμV/m)	Detector (PK/AV)	Direction (degree)	Height (cm)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4824.09	64.22	AV	12	201	V	32.2	7	55	48.42	54	-5.58
4824.09	63.43	AV	122	193	H	32.2	7	55	47.63	54	-6.37
4824.09	77.43	PK	14	292	V	32.2	7	55	61.63	74	-12.37
4824.09	75.53	PK	23	130	H	32.2	7	55	59.73	74	-14.27
3023.43	59.32	AV	42	231	V	30.3	5.33	55	39.95	54	-14.05
1923.09	60.34	AV	123	252	H	25.7	4.17	55	35.21	54	-18.79

Middle Channel (2437 MHz)

Frequency (MHz)	Substituted level (dBμV/m)	Detector (PK/AV)	Direction (degree)	Height (cm)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4874.14	66.5	AV	32	142	V	32.2	7	55	50.7	54	-3.3
4874.64	64.32	AV	134	153	H	32.2	7	55	48.52	54	-5.48
4874.14	79.43	PK	142	251	V	32.2	7	55	63.63	74	-10.37
4874.64	77.65	PK	4	125	H	32.2	7	55	61.85	74	-12.15
2322.43	56.45	AV	142	155	V	27.5	4.33	55	33.28	54	-20.72
2322.43	50.27	AV	164	125	H	27.5	4.33	55	27.1	54	-26.9

High Channel (2462 MHz)

Frequency (MHz)	Substituted level (dBμV/m)	Detector (PK/AV)	Direction (degree)	Height (cm)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4923.82	67.43	AV	164	164	V	32.2	7	55	51.63	54	-2.37
4923.82	66.13	AV	232	209	H	32.2	7	55	50.33	54	-3.67
4923.82	78.65	PK	166	209	V	32.2	7	55	62.85	74	-11.15
4923.82	76.34	PK	187	212	H	32.2	7	55	60.54	74	-13.46
2031.59	53.43	AV	43	143	V	27.5	4.33	55	30.26	54	-23.74
3042.32	55.98	AV	242	153	H	30.3	5.33	55	36.61	54	-17.39

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted Emissions					
R&S EMI Test Receiver	ESPI3	101216	11/04/2014	11/03/2015	N/A
V-LISN	ESH3-Z5	838979/005	09/27/2014	09/26/2015	N/A
INFOMW Antenna (1 ~18GHz)	JXTXLB-10180	J2031081120092	10/09/2014	10/08/2015	N/A
SIEMIC Labview Conducted Emissions software	V1.0	N/A	N/A	N/A	N/A
RF conducted test					
R&S EMI Receiver	ESPI3	101216	11/04/2014	11/03/2015	☒
Power Splitter	1#	1#	02/02/2015	02/01/2016	☒
Hp Spectrum Analyzer	8563E	3821A09023	10/09/2014	10/08/2015	☒
Temperature/Humidity Chamber	1007H	N/A	01/07/2015	01/06/2016	☒
Radiated Emissions					
Hp Spectrum Analyzer	8563E	3821A09023	10/09/2014	10/08/2015	☒
R&S EMI Receiver	ESPI3	101216	11/04/2014	11/03/2015	☒
Antenna (30MHz~6GHz)	JB6	A121411	04/14/2015	04/15/2016	☒
EMCO Horn Antenna (1 ~18GHz)	3115	N/A	11/15/2014	11/14/2015	☒
INFOMW Antenna (1 ~18GHz)	JXTXLB-10180	J2031081120092	10/09/2014	10/08/2015	☒
Horn Antenna (18~40GHz)	AH-840	101013	04/22/2015	04/21/2016	☒
Microwave Pre-Amp (18~40GHz)	PA-840	181250	05/29/2014	05/28/2015	☒
Hp Agilent Pre-Amplifier	8447F	1937A01160	10/27/2014	10/26/2015	☒
MITEQ Pre-Amplifier (0.1 ~ 18GHz)	AMF-7D- 00101800-30- 10P	1451709	10/27/2014	10/26/2015	☒
SIEMIC Labview Radiated Emissions software	V1.0	N/A	N/A	N/A	☒


Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph EUT External Photo




External
Antenna

Front View 1 of EUT




Front View 2 of EUT

Test Report No.	15020390-FCC-R1
Page	34 of 41




Rear View of EUT

Annex B.ii. Photograph EUT Internal Photo




Shielding Off Front View of EUT




Shielding Off Rear View of EUT

Annex B.iii. Photograph: Test Setup Photo



Radiated Spurious Emissions Test Setup Below 1GHz



Radiated Spurious Emissions Test Setup Above 1GHz


Test Report No.	15020390-FCC-R1
Page	37 of 41

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.i. TEST SET UP BLOCK

N/A

Block Configuration Diagram for Radiated Emissions



Test Report No.	15020390-FCC-R1
Page	39 of 41

Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Equipment Description	Model	Calibration Date	Calibration Due Date
Battery	N/A	N/A	N/A

Test Report No.	15020390-FCC-R1
Page	40 of 41

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see attachment



Annex E. DECLARATION OF SIMILARITY

Difference of the Models

There are two antenna styles for TA3200R1D module and corresponding to two names: TA3200R1D-SA and TA3200R1D-UFL. Both of the two modules have the same electrical diagram, PCB Layout, also mounted the same components, and using the same material manufacture of PCB.

The only difference between TA3200R1D-SA module and TA3200R1D-UFL is antenna selection. There are two antenna styles for TA3200R1D Module.

TA3200R1D-SA(PCB Strip Antenna) TA3200R1D-UFL(UFL Connector)



Ref	TA3200 R1D-SA	TA3200 R1D-UFL
Ra	0R	DNM
L4	3.6N	3.6N
C6	1P	1P
Ru	DNM	0R
L3	10P	10P
C7	DNM	DNM

Company Name: Beijing Jia An Electronic Technology Co., Ltd
Address: No. 19 GuCheng West Street, Shi Jing Shan District, Beijing 100043, CHINA
Authorized Person -Print Name: Helen Ban

Signature: *Helen Ban*