

FCC Part 15C

Measurement and Test Report

For

LM Technologies Ltd.

Unit 19, Spectrum House, 32-34, Gordon House Road, London, NW5 1LP,
United Kingdom

FCC ID: VVXLM842

FCC Rule(s):	<u>FCC Part 15.247</u>
Product Description:	<u>LM842 WiFi and Bluetooth 5.0 Dual Mode Combination</u> <u>USB Adapter</u>
Tested Model:	<u>LM842</u>
Report No.:	<u>WTX19X12087485W-2</u>
Sample Receipt Date:	<u>Dec.17, 2019</u>
Tested Date:	<u>Dec.18, 2019 to Jan.19, 2020</u>
Issued Date:	<u>Jan.19, 2020</u>
Tested By:	<u>Mike Shi / Engineer</u> <i>Mike Shi</i>
Reviewed By:	<u>Lion Cai / RF Manager</u> <i>Lion Cai</i>
Approved & Authorized By:	<u>Silin Chen / Manager</u> <i>Silin Chen</i>
Prepared By:	Shenzhen SEM Test Technology Co., Ltd. 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101) Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY.....	5
1.4 TEST FACILITY.....	5
1.5 EUT SETUP AND TEST MODE.....	6
1.6 MEASUREMENT UNCERTAINTY.....	7
1.7 TEST EQUIPMENT LIST AND DETAILS.....	8
2. SUMMARY OF TEST RESULTS.....	10
3. RF EXPOSURE.....	11
3.1 STANDARD APPLICABLE.....	11
3.2 TEST RESULT.....	11
4. ANTENNA REQUIREMENT.....	12
4.1 STANDARD APPLICABLE.....	12
4.2 EVALUATION INFORMATION.....	12
5. POWER SPECTRAL DENSITY.....	13
5.1 STANDARD APPLICABLE.....	13
5.2 TEST PROCEDURE.....	13
5.3 SUMMARY OF TEST RESULTS/PLOTS.....	13
6. DTS BANDWIDTH.....	22
6.1 STANDARD APPLICABLE.....	22
6.2 TEST PROCEDURE.....	22
6.3 SUMMARY OF TEST RESULTS/PLOTS.....	22
7. RF OUTPUT POWER.....	31
7.1 STANDARD APPLICABLE.....	31
7.2 TEST PROCEDURE.....	31
7.3 SUMMARY OF TEST RESULTS/PLOTS.....	31
8. FIELD STRENGTH OF SPURIOUS EMISSIONS.....	41
8.1 STANDARD APPLICABLE.....	41
8.2 TEST PROCEDURE.....	41
8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	43
8.4 SUMMARY OF TEST RESULTS/PLOTS.....	43
9. OUT OF BAND EMISSIONS.....	51
9.1 STANDARD APPLICABLE.....	51
9.2 TEST PROCEDURE.....	51
9.3 SUMMARY OF TEST RESULTS/PLOTS.....	52
10. CONDUCTED EMISSIONS.....	85
10.1 TEST PROCEDURE.....	85
10.2 BASIC TEST SETUP BLOCK DIAGRAM.....	85
10.3 TEST RECEIVER SETUP.....	85
10.4 SUMMARY OF TEST RESULTS/PLOTS.....	85

Report version

Version No.	Date of issue	Description
Rev.00	Jan.19, 2020	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: LM Technologies Ltd.
Address of applicant: Unit 19, Spectrum House, 32-34, Gordon House Road,
London, NW5 1LP, United Kingdom

Manufacturer: LM Technologies Ltd.
Address of manufacturer: Unit 19, Spectrum House, 32-34, Gordon House Road,
London, NW5 1LP, United Kingdom

General Description of EUT	
Product Name:	LM842 WiFi and Bluetooth 5.0 Dual Mode Combination USB Adapter
Trade Name:	LM Technologies
Model No.:	LM842
Adding Model(s):	842-8420, 842-8421, 842-8422, 842-8423, 842-8424
Rated Voltage:	DC 5V
Power Adapter Model:	/
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model LM842, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20) 2422-2452MHz for 802.11n(HT40)
RF Output Power:	15.39 dBm (Conducted)
Type of Modulation:	DBPSK,BPSK,DQPSK,QPSK,16QAM,64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 300Mbps
Quantity of Channels:	11 for 802.11b/g/n(HT20); 7 for 802.11n(HT40)
Channel Separation:	5MHz
Type of Antenna:	Integral
Antenna Gain:	Antenna A: -0.08 dBi; Antenna B: -0.46dBi

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

558074 D01 15.247 Meas Guidance v05r02: Guidance For Compliance Measurements On Digital Transmission System, Frequency Hopping Spread Spectrum System, And Hybrid System Devices Operating Under Section 15.247 Of The Fcc Rules

662911 D01 Multiple Transmitter Output v02r01: Emissions Testing of Transmitters with Multiple Outputs in the Same Band

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 662911 D01 Multiple Transmitter Output v02r01

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Shenzhen SEM Test Technology Co., Ltd.

Address: 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

FCC – Registration No.: 125990

Shenzhen SEM Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM2	802.11g	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM3	802.11n-HT20	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM4	802.11n-HT40	Low:2422MHz, Middle:2437MHz,High:2452MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
USB extension cable	1.2	Shielded	With Ferrite

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	E445	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2019-04-30	2020-04-29
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2019-04-30	2020-04-29
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2019-04-30	2020-04-29
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2019-04-30	2020-04-29
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2019-04-30	2020-04-29
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2019-05-05	2021-05-04
SEMT-1042	Horn Antenna	ETS	3117	00086197	2019-05-05	2021-05-04
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2019-05-05	2021-05-04
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2019-05-05	2021-05-04
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2019-04-30	2020-04-29
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2019-04-30	2020-04-29
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2019-04-30	2020-04-29
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2019-04-30	2020-04-29
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2019-04-30	2020-04-29
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2019-04-30	2020-04-29
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2019-05-05	2021-05-04
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2019-04-30	2020-04-29
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2019-04-30	2020-04-29
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2019-04-30	2020-04-29
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2019-03-18	2020-03-17
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2019-03-18	2020-03-17
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2019-03-18	2020-03-17
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2019-03-18	2020-03-17
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2019-03-18	2020-03-17
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2019-03-18	2020-03-17

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

*Remark: indicates software version used in the compliance certification testing

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§2.1093	RF Exposure	Compliant
§15.203; §15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	DTS Bandwidth	Compliant
§15.247(b)(3)	RF Output Power	Compliant
§15.209(a)	Radiated Emission	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable

3. RF Exposure

3.1 Standard Applicable

According to §1.1307 and §2.1091, the mobile transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has two integral antennas, fulfill the requirement of this section.

5. Power Spectral Density

5.1 Standard Applicable

According to 15.247(a)(1)(iii), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.3, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:




- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set VBW $\geq 3 \times \text{RBW}$.
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

5.3 Summary of Test Results/Plots


Test Mode	Test Channel MHz	Test Result(dBm/3kHz)		Total dBm	Limit dBm/3kHz
		Antenna A	Antenna B		
802.11b_11Mbps	2412	-20.36	-22.70	/	8
	2437	-21.18	-23.37	/	8
	2462	-23.27	-25.01	/	8
802.11g_54Mbps	2412	-22.75	-21.64	/	8
	2437	-23.82	-22.55	/	8
	2462	-24.92	-24.16	/	8
802.11n-HT20_MCS7	2412	-22.54	-21.23	-18.83	8
	2437	-23.91	-22.48	-20.13	8
	2462	-24.60	-24.64	-21.61	8
802.11n-HT40_MCS7	2422	-26.00	-24.99	-22.46	8
	2437	-27.09	-25.60	-23.27	8
	2452	-28.02	-26.47	-24.17	8

Please refer to the following test plots:


➤ Antenna A

802.11b-Low	
802.11b-Middle	
802.11b-High	


802.11g-Low




802.11g-Middle




802.11g-High




802.11n-HT20-Low




802.11n-HT20-Middle




802.11n-HT20-High




802.11n-HT40-Low



802.11n-HT40-Middle




802.11n-HT40-High




➤ Antenna B


802.11b-Low




802.11b-Middle




802.11b-High




802.11g-Low




802.11g-Middle




802.11g-High




802.11n-HT20-Low




802.11n-HT20-Middle




802.11n-HT20-High




802.11n-HT40-Low



802.11n-HT40-Middle



802.11n-HT40-High



6. DTS Bandwidth

6.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:




- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3 Summary of Test Results/Plots


Test Mode	Test Channel MHz	Test Result(MHz)		Limit kHz
		Antenna A	Antenna B	
802.11b_11Mbps	2412	10.122	10.123	≥ 500
	2437	10.127	10.129	≥ 500
	2462	10.109	10.125	≥ 500
802.11g_54Mbps	2412	16.410	16.366	≥ 500
	2437	16.388	16.393	≥ 500
	2462	16.382	16.381	≥ 500
802.11n-HT20_MCS7	2412	17.596	17.596	≥ 500
	2437	17.599	17.624	≥ 500
	2462	17.525	17.619	≥ 500
802.11n-HT40_MCS7	2422	36.396	36.351	≥ 500
	2437	36.399	36.389	≥ 500
	2452	36.387	36.385	≥ 500

Please refer to the following test plots:


➤ Antenna A 6 dB Bandwidth (MHz)

802.11b-Low	 Agilent Spectrum Analyzer screenshot for 802.11b-Low. The display shows a signal centered at 2.412 GHz with a 30 MHz span. The occupied bandwidth is measured as 14.4826 MHz. The transmit frequency error is 85.908 kHz. The signal level is approximately -6.00 dB.
802.11b-Middle	 Agilent Spectrum Analyzer screenshot for 802.11b-Middle. The display shows a signal centered at 2.437 GHz with a 30 MHz span. The occupied bandwidth is measured as 14.5055 MHz. The transmit frequency error is 23.818 kHz. The signal level is approximately -6.00 dB.
802.11b-High	 Agilent Spectrum Analyzer screenshot for 802.11b-High. The display shows a signal centered at 2.462 GHz with a 30 MHz span. The occupied bandwidth is measured as 14.5957 MHz. The transmit frequency error is 53.270 kHz. The signal level is approximately -6.00 dB. The right-hand menu shows settings for Freq/Channel, Start Freq, Stop Freq, CF Step, Freq Offset, Signal Track, and Scale Type.


802.11g-Low




802.11g-Middle




802.11g-High




802.11n-HT20-Low




802.11n-HT20-Middle




802.11n-HT20-High




802.11n-HT40-Low






802.11n-HT40-Middle




802.11n-HT40-High




➤ Antenna B 6 dB Bandwidth (MHz)

802.11b-Low	 Agilent Spectrum Analyzer screenshot for 802.11b-Low. The display shows a signal centered at 2.412 GHz with a span of 30 MHz. The occupied bandwidth is measured as 14.5205 MHz. The transmit frequency error is 17.505 kHz. The signal level is approximately -6.00 dB.
802.11b-Middle	 Agilent Spectrum Analyzer screenshot for 802.11b-Middle. The display shows a signal centered at 2.437 GHz with a span of 30 MHz. The occupied bandwidth is measured as 14.5314 MHz. The transmit frequency error is -38.994 kHz. The signal level is approximately -6.00 dB.
802.11b-High	 Agilent Spectrum Analyzer screenshot for 802.11b-High. The display shows a signal centered at 2.462 GHz with a span of 30 MHz. The occupied bandwidth is measured as 14.5571 MHz. The transmit frequency error is -6.161 kHz. The signal level is approximately -6.00 dB.


802.11g-Low




802.11g-Middle




802.11g-High




802.11n-HT20-Low




802.11n-HT20-Middle




802.11n-HT20-High




802.11n-HT40-Low



802.11n-HT40-Middle



802.11n-HT40-High



7. RF Output Power

7.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

7.2 Test Procedure

According to the KDB-558074 D01 v05r02 Subclause 8.3.2.2 and ANSI C63.10-2013 Subclause 11.9.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth




- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW $\geq 3 \times$ RBW.
- d) Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. (This gives bin-to-bin spacing $\leq \text{RBW}/2$, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “ free run ” .
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.




7.3 Summary of Test Results/Plots

Test Mode	Frequency MHz	Power A dBm	Power B dBm	Power A mW	Power B mW	Total Power dBm	Output Power mW	Limit mW
802.11b _11Mbps	2412	14.26	14.32	26.67	27.04	/	/	1000
	2437	14.17	14.17	26.12	26.12	/	/	1000
	2462	14.62	14	28.97	25.12	/	/	1000
802.11g _54Mbps	2412	12.08	12.72	16.14	18.71	/	/	1000
	2437	12.44	12.5	17.54	17.78	/	/	1000
	2462	12.34	12.6	17.14	18.20	/	/	1000
802.11n HT20_MCS7	2412	12.15	12.11	16.41	16.26	15.14	32.66	1000
	2437	12.24	12.43	16.75	17.50	15.35	34.25	1000
	2462	12.33	12.42	17.10	17.46	15.39	34.56	1000
802.11n HT40_MCS7	2422	11.95	12.21	15.67	16.63	15.09	32.30	1000
	2437	12.26	12.30	16.83	16.98	15.29	33.81	1000
	2452	12.45	11.69	17.58	14.76	15.10	32.34	1000


Please refer to the following test plots:

➤ Antenna A


802.11b-Low 11Mbps	
802.11b-Middle 11Mbps	
802.11b-High 11Mbps	

802.11g-Low 54Mbps	
802.11g-Middle 54Mbps	
802.11g-High 54Mbps	


802.11n-HT20-Low
MCS7




802.11n-HT20-Middle
MCS7




802.11n-HT20-High
MCS7




802.11n-HT40-Low
MCS7






802.11n-HT40-Middle
MCS7




802.11n-HT40-High
MCS7




➤ Antenna B

802.11b-Low 11Mbps	
802.11b-Middle 11Mbps	
802.11b-High 11Mbps	


802.11g-Low
54Mbps




802.11g-Middle
54Mbps




802.11g-High
54Mbps




802.11n-HT20-Low
MCS7






802.11n-HT20-Middle
MCS7



802.11n-HT20-High
MCS7



802.11n-HT40-Low MCS7	
802.11n-HT40-Middle MCS7	
802.11n-HT40-High MCS7	

8. Field Strength of Spurious Emissions

8.1 Standard Applicable



According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.



Frequency :9kHz-30MHz
RBW=10KHz,
VBW =30KHz
Sweep time= Auto
Trace = max hold
Detector function = peak

Frequency :30MHz-1GHz
RBW=120KHz,
VBW=300KHz
Sweep time= Auto
Trace = max hold
Detector function = peak, QP

Frequency :Above 1GHz
RBW=1MHz,
VBW=3MHz(Peak), 10Hz(AV)
Sweep time= Auto
Trace = max hold
Detector function = peak, AV

8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$


8.4 Summary of Test Results/Plots

Note: 1. This EUT was tested in 3 orthogonal positions and the worst case position data was reported.

All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in this report.


- Spurious Emissions Below 1GHz
- Worst case Antenna A

802.11b_11Mbps			
Test Channel	Low	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	43.8119	34.15	-13.99	20.16	40.00	-19.84	QP
2	66.2662	36.67	-16.32	20.35	40.00	-19.65	QP
3	143.8295	40.42	-16.94	23.48	43.50	-20.02	QP
4	294.1137	39.96	-8.34	31.62	46.00	-14.38	QP
5	482.2156	43.61	-8.04	35.57	46.00	-10.43	QP
6	972.3374	30.47	-0.96	29.51	54.00	-24.49	QP


802.11b_11Mbps			
Test Channel	Low	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	67.4382	40.09	-16.49	23.60	40.00	-16.40	QP
2	98.1419	39.01	-15.29	23.72	43.50	-19.78	QP
3	143.8295	42.11	-16.94	25.17	43.50	-18.33	QP
4	215.2678	38.67	-12.28	26.39	43.50	-17.11	QP
5	414.7223	38.65	-7.89	30.76	46.00	-15.24	QP
6	480.5276	38.54	-8.05	30.49	46.00	-15.51	QP


➤ Worst case Antenna B

802.11b_11Mbps			
Test Channel	Low	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	38.7518	35.23	-14.64	20.59	40.00	-19.41	QP
2	65.5727	36.53	-16.21	20.32	40.00	-19.68	QP
3	145.3506	40.27	-16.80	23.47	43.50	-20.03	QP
4	295.1469	40.11	-8.24	31.87	46.00	-14.13	QP
5	480.5276	44.09	-8.05	36.04	46.00	-9.96	QP
6	916.0687	30.95	-0.93	30.02	46.00	-15.98	QP

802.11b_11Mbps			
Test Channel	Middle	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	60.0691	16.32	5.36	21.68	40.00	-18.32	256	100	peak
2	303.5437	15.45	12.19	27.64	46.00	-18.36	360	100	peak
3	737.0714	16.47	19.37	35.84	46.00	-10.16	360	100	peak

802.11b_11Mbps			
Test Channel	High	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	43.5057	35.69	-14.00	21.69	40.00	-18.31	QP
2	67.4382	39.59	-16.49	23.10	40.00	-16.90	QP
3	98.1419	40.09	-15.29	24.80	43.50	-18.70	QP
4	145.3506	42.58	-16.80	25.78	43.50	-17.72	QP
5	414.7223	39.16	-7.89	31.27	46.00	-14.73	QP
6	482.2156	38.49	-8.04	30.45	46.00	-15.55	QP

- Spurious Emissions Above 1GHz
- Test Mode: 802.11b_11Mbps Antenna A worst case

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.00	62.78	-3.86	58.92	74	-15.08	H	PK
4824.00	42.67	-3.86	38.81	54	-15.19	H	AV
7236.00	57.34	1.10	58.44	74	-15.56	H	PK
7236.00	39.96	1.10	41.06	54	-12.94	H	AV
4824.00	62.36	-3.86	58.50	74	-15.50	V	PK
4824.00	44.89	-3.86	41.03	54	-12.97	V	AV
7236.00	54.05	1.10	55.15	74	-18.85	V	PK
7236.00	41.46	1.10	42.56	54	-11.44	V	AV
Middle Channel-2437MHz							
4874.00	63.15	-3.74	59.41	74	-14.59	H	PK
4874.00	42.67	-3.74	38.93	54	-15.07	H	AV
7311.00	55.73	1.47	57.20	74	-16.80	H	PK
7311.00	38.88	1.47	40.35	54	-13.65	H	AV
4874.00	63.11	-3.74	59.37	74	-14.63	V	PK
4874.00	41.73	-3.74	37.99	54	-16.01	V	AV
7311.00	58.17	1.47	59.64	74	-14.36	V	PK
7311.00	40.27	1.47	41.74	54	-12.26	V	AV
High Channel-2462MHz							
4924.00	59.95	-3.63	56.32	74	-17.68	H	PK
4924.00	41.61	-3.63	37.98	54	-16.02	H	AV
7386.00	56.05	1.62	57.67	74	-16.33	H	PK
7386.00	42.67	1.62	44.29	54	-9.71	H	AV
4924.00	60.71	-3.63	57.08	74	-16.92	V	PK
4924.00	43.71	-3.63	40.08	54	-13.92	V	AV
7386.00	57.28	1.62	58.90	74	-15.10	V	PK
7386.00	41.48	1.62	43.10	54	-10.90	V	AV

➤ Test Mode: 802.11b_11Mbps Antenna B worst case

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.00	60.98	-3.86	57.12	74	-16.88	H	PK
4824.00	45.41	-3.86	41.55	54	-12.45	H	AV
7236.00	55.01	1.10	56.11	74	-17.89	H	PK
7236.00	38.78	1.10	39.88	54	-14.12	H	AV
4824.00	59.15	-3.86	55.29	74	-18.71	V	PK
4824.00	42.55	-3.86	38.69	54	-15.31	V	AV
7236.00	57.91	1.10	59.01	74	-14.99	V	PK
7236.00	40.98	1.10	42.08	54	-11.92	V	AV
Middle Channel-2437MHz							
4874.00	60.22	-3.74	56.48	74	-17.52	H	PK
4874.00	40.90	-3.74	37.16	54	-16.84	H	AV
7311.00	54.60	1.47	56.07	74	-17.93	H	PK
7311.00	40.74	1.47	42.21	54	-11.79	H	AV
4874.00	63.06	-3.74	59.32	74	-14.68	V	PK
4874.00	41.51	-3.74	37.77	54	-16.23	V	AV
7311.00	56.17	1.47	57.64	74	-16.36	V	PK
7311.00	41.03	1.47	42.50	54	-11.50	V	AV
High Channel-2462MHz							
4924.00	60.54	-3.63	56.91	74	-17.09	H	PK
4924.00	42.89	-3.63	39.26	54	-14.74	H	AV
7386.00	55.22	1.62	56.84	74	-17.16	H	PK
7386.00	39.76	1.62	41.38	54	-12.62	H	AV
4924.00	62.71	-3.63	59.08	74	-14.92	V	PK
4924.00	45.77	-3.63	42.14	54	-11.86	V	AV
7386.00	53.87	1.62	55.49	74	-18.51	V	PK
7386.00	40.71	1.62	42.33	54	-11.67	V	AV

9. Out of Band Emissions

9.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

9.2 Test Procedure

According to the KDB 558074D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9.
- b) $VBW \geq [3 \times RBW]$.
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

Table 9—RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.


9.3 Summary of Test Results/Plots

➤ Radiated test

Worst case


➤ Antenna B

802.11b_11Mbps			
Test Channel	Low	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	45.65	-9.66	35.99	54.00	-18.01	Average Detector
	2310.000	55.03	-9.66	45.37	74.00	-28.63	Peak Detector
2	2390.000	47.12	-9.50	37.62	54.00	-16.38	Average Detector
	2390.000	58.36	-9.50	48.86	74.00	-25.14	Peak Detector
3	2400.000	65.23	-9.48	55.75	Delta=42.44dBc		Average Detector
4	2414.760	107.64	-9.45	98.19			Average Detector

802.11b_11Mbps			
Test Channel	High	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2461.350	109.98	-9.36	100.62	/	/	Average Detector
	2460.600	114.96	-9.36	105.60	/	/	Peak Detector
2	2483.500	51.69	-9.31	42.38	54.00	-19.57	Average Detector
	2483.500	61.65	-9.31	52.34	74.00	-21.66	Peak Detector
3	2500.000	45.76	-9.28	36.48	54.00	-17.52	Average Detector
	2500.000	57.41	-9.28	48.13	74.00	-25.87	Peak Detector

802.11g_54Mbps			
Test Channel	Low	Polarity:	Vertical(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.50	-9.66	33.84	54.00	-20.16	Average Detector
	2310.000	55.11	-9.66	45.45	74.00	-28.55	Peak Detector
2	2390.000	56.45	-9.50	46.95	54.00	-7.05	Average Detector
	2390.000	78.38	-9.50	68.88	74.00	-5.12	Peak Detector
3	2400.000	73.66	-9.48	64.18	Delta=30.56dB		Average Detector
4	2414.880	104.20	-9.46	94.74			Average Detector


802.11g_54Mbps			
Test Channel	High	Polarity:	Vertical(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2	2460.900	103.20	-9.36	93.84	/	/	Average Detector
	2460.550	113.70	-9.36	104.34	/	/	Peak Detector
1	2483.500	58.33	-9.31	49.02	54.00	-4.98	Average Detector
	2483.500	77.33	-9.31	68.02	74.00	-5.98	Peak Detector
3	2500.000	44.40	-9.28	35.12	54.00	-18.88	Average Detector
	2500.000	57.56	-9.28	48.28	74.00	-25.72	Peak Detector

➤ Antenna A+AntennaB


802.11n-HT20_MCS7			
Test Channel	Low	Polarity:	Vertical(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.49	-9.66	33.83	54.00	-20.17	Average Detector
	2310.000	56.21	-9.66	46.55	74.00	-27.45	Peak Detector
2	2390.000	59.19	-9.50	49.69	54.00	-4.31	Average Detector
	2390.000	79.93	-9.50	70.43	74.00	-3.57	Peak Detector
3	2400.000	72.64	-9.48	63.16	Delta=31.24dBc		Average Detector
4	2415.000	103.86	-9.46	94.40			Average Detector


802.11n-HT20_MCS7

Test Channel	High	Polarity:	Vertical(worst case)
--------------	------	-----------	----------------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2463.600	101.11	-9.35	91.76	/	/	Average Detector
	2459.950	111.86	-9.35	102.51	/	/	Peak Detector
2	2483.500	57.09	-9.31	47.78	54.00	-6.22	Average Detector
	2483.500	78.07	-9.31	68.76	74.00	-5.24	Peak Detector
3	2500.000	45.17	-9.28	35.89	54.00	-18.11	Average Detector
	2500.000	57.55	-9.28	48.27	74.00	-25.73	Peak Detector

802.11n-HT40_MCS7			
Test Channel	Low	Polarity:	Vertical(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.85	-9.66	34.19	54.00	-19.81	Average Detector
	2310.000	56.07	-9.66	46.41	74.00	-27.59	Peak Detector
2	2390.000	58.52	-9.50	49.02	54.00	-4.98	Average Detector
	2390.000	80.94	-9.50	71.44	74.00	-2.56	Peak Detector
3	2400.000	62.85	-9.48	53.37	Delta=34.96dBc		Average Detector
4	2427.880	97.76	-9.43	88.33			Average Detector

802.11n-HT40_MCS7			
Test Channel	High	Polarity:	Vertical(worst case)





No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2459.750	97.82	-9.35	88.47	/	/	Average Detector
	2461.080	108.82	-9.36	99.46	/	/	Peak Detector
2	2483.500	62.12	-9.31	52.81	54.00	-1.19	Average Detector
	2483.500	77.71	-9.31	68.40	74.00	-5.60	Peak Detector
3	2500.000	51.39	-9.28	42.11	54.00	-11.89	Average Detector
	2500.000	68.43	-9.28	59.15	74.00	-14.85	Peak Detector

➤ Antenna A



802.11b_11Mbps

Low





802.11b_11Mbps

Middle





802.11b_11Mbps

High





802.11g_54Mbps

Low





802.11g_54Mbps

Middle





802.11g_54Mbps

High





802.11n-HT20_MCS7

Low





802.11n-HT20_MCS7

Middle





802.11n-HT20_MCS7

High





802.11n-HT40_MCS7

Low





802.11n-HT40_MCS7

Middle



802.11n-HT40_MCS7



High



➤ Antenna B



802.11b_11Mbps

Low





802.11b_11Mbps

Middle





802.11b_11Mbps

High





802.11g_54Mbps

Low





802.11g_54Mbps

Middle





802.11g_54Mbps

High





802.11n-HT20_MCS7

Low





802.11n-HT20_MCS7

Middle





802.11n-HT20_MCS7

High





802.11n-HT40_MCS7

Low





802.11n-HT40_MCS7

Middle



802.11n-HT40_MCS7

High




10. Conducted Emissions

10.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

10.2 Basic Test Setup Block Diagram




10.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency 150 kHz
 Stop Frequency 30 MHz
 Sweep Speed Auto
 IF Bandwidth..... 10 kHz
 Quasi-Peak Adapter Bandwidth 9 kHz
 Quasi-Peak Adapter Mode Normal


10.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1500	46.31	9.95	56.26	66.00	-9.74	QP
2	0.1580	26.31	9.95	36.26	55.57	-19.31	AVG
3	0.4940	19.34	10.02	29.36	46.10	-16.74	AVG
4	0.5020	29.38	10.02	39.40	56.00	-16.60	QP
5	4.1900	26.49	10.31	36.80	56.00	-19.20	QP
6	4.9580	12.62	10.38	23.00	46.00	-23.00	AVG

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1540	45.97	9.95	55.92	65.78	-9.86	QP
2	0.1540	28.45	9.95	38.40	55.78	-17.38	AVG
3	0.4940	19.75	10.02	29.77	46.10	-16.33	AVG
4	0.5020	28.63	10.02	38.65	56.00	-17.35	QP
5	5.1780	28.32	10.39	38.71	60.00	-21.29	QP
6	5.1780	19.92	10.39	30.31	50.00	-19.69	AVG

***** END OF REPORT *****