

Theory of Operation/Technical Description – FCC ID: VW4A092201

- RF circuit function:

The IEEE 802.15.4 compliant AT86RF212B transceiver generates a modulated carrier wave at 906- 924MHz with 10 IEEE 802.15.4 channels. This transceiver circuit is used by system applications as a physical layer for ZigBee applications.

- RF signal flow:

The Transceiver IC outputs a differential RF signal- RFP & RFN which is converted to single ended by the balun and then passes through the RF path till the antenna and gets radiated or vice versa during reception

- Description of Antenna system:

RF signal from/to the SoC goes to U.FL-R-SMT-1(10) Antenna connector. Tuning elements are present to ensure compliance.

- Compliance with 15.203 antenna requirements:

FCC 15.203 requirements for this design are tested and verified during FCC compliance testing.

- Description of all modulation schemes used in the product:

Module uses BPSK.



Saravanakumar Marudhachalam

Manager, Tools HW Development

Specifications of EUT

Operating Frequency	902 - 928 MHz
No. of channel	10
Channel Spacing	2 MHz
Modulation	BPSK
Transmitted Power	08.50dBm
Data Rate	40 kbps
Antenna Type	Refer page 6 of 29 (Test Report)
Number of antenna	Refer page 6 of 29 Test Report)
Antenna Gain	Refer page 6 of 29 (Test Report)
Supply Voltage	1.8VDC – 3.6VDC
Dimensions	30mm X 20mm
Environmental	85C to -25C

24-Apr-14

To whomsoever it may concern

Product Application

This document explains the nature of intended application of the product mentioned below.

Product name: ZigBit RF212B

Product Model: ATZB-RF-212B-0-U

FCC ID: VW4A092201

Product Application:

The ZigBit RF212B is a Zigbit module of the Atmel AT86RF212B radio transceiver. The radio transceiver supports the worldwide accessible 900MHz ISM band.

The system is designed standard-based applications such as ZigBee/IEEE 802.15.4, ZigBee RF4CE, and 6LoWPAN, as well as high data rate ISM applications.

Sincerely,



Saravanakumar Marudhachalam

Manager, Tools HW Development,

Atmel Norway AS