

TEST REPORT

Applicant: SPECTRA Technologies Holdings Co. Ltd.

Address: Unit 1301-09, 19-20, Tower II, Grand Century Place, Kowloon,
Hong Kong

Product Name: Android POS


FCC ID: VWZS1

Standard(s): 47 CFR Part 15, Subpart C(15.225)
ANSI C63.10-2013

Report Number: KS1240221-08647E-RF-00G

Report Date: 2024/5/8

The above device has been tested and found compliant with the requirement of the relative standards by Bay Area Compliance Laboratories Corp. (Dongguan).



Reviewed By: Gavin Xu
Title: RF Engineer



Approved By: Ivan Cao
Title: EMC Manager

Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

CONTENTS

DOCUMENT REVISION HISTORY	4
1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF EQUIPMENT UNDER TEST	5
1.2 ACCESSORY INFORMATION	5
1.3 ANTENNA INFORMATION DETAIL▲	5
1.4 EQUIPMENT MODIFICATIONS	5
2. DESCRIPTION OF TEST CONFIGURATION	6
2.1 EUT OPERATION CONDITION	6
2.2 EUT EXERCISE SOFTWARE	6
2.3 SUPPORT EQUIPMENT LIST AND DETAILS	6
2.4 SUPPORT CABLE LIST AND DETAILS	6
2.5 BLOCK DIAGRAM OF TEST SETUP	7
2.6 TEST FACILITY	8
2.7 MEASUREMENT UNCERTAINTY	8
3. SUMMARY OF TEST RESULTS	9
4. REQUIREMENTS AND TEST RESULTS	10
4.1 AC LINE CONDUCTED EMISSIONS	10
4.1.1 Applicable Standard	10
4.1.2 EUT Setup	11
4.1.3 EMI Test Receiver Setup	11
4.1.4 Test Procedure	12
4.1.5 Corrected Amplitude & Margin Calculation	12
4.1.6 Test Data	13
4.2 RADIATED SPURIOUS EMISSIONS	18
4.2.1 Applicable Standard	18
4.2.2 EUT Setup	18
4.2.3 EMI Test Receiver & Spectrum Analyzer Setup	19
4.2.4 Test Procedure	20
4.2.5 Corrected Result & Margin Calculation	20
4.2.6 Test Data	21
4.3 20 DB EMISSION BANDWIDTH	44
4.3.1 Applicable Standard	44
4.3.2 EUT Setup	44
4.3.3 Test Procedure	44
4.3.4 Test Data	46
4.4 FREQUENCY STABILITY	47
4.4.1 Applicable Standard	47
4.4.2 EUT Setup	47
4.4.3 Test Procedure	47
4.4.4 Test Result	49
4.5 ANTENNA REQUIREMENT	50

4.5.1 Applicable Standard	50
4.5.2 Judgment	50
APPENDIX A - EUT PHOTOGRAPHS	51
APPENDIX B - TEST SETUP PHOTOGRAPHS	52
APPENDIX C - RF EXPOSURE EVALUATION	53
APPLICABLE STANDARD	53

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	KS1240221-08647E-RF-00G	Original Report	2024/5/8

1. GENERAL INFORMATION

1.1 General Description of Equipment under Test

EUT Name:	Android POS
EUT Model:	S1
Multiple Models:	S1 PLUS
Operation Frequency:	13.56 MHz
Modulation Type:	ASK
Rated Input Voltage:	3.8Vdc from battery or Powered by USB Port
Serial Number:	RE/CE: 2HV7-5(S1); 2HV7-6(S1 PLUS) RF:2HV7-2
EUT Received Date:	2024/2/26
EUT Received Status:	Good
Note: The multiple models are electrically identical with the test model. Please refer to the declaration letter for more detail, which was provided by manufacturer.	

Configurations:

Model	Configuration Description
S1	Without thermal printer, without S1_Printer_MB PCBA. Wired LTE DIV Antenna ,LTE Main Antenna , Wifi/GPS/BT Antenna, LTE Main antenna is FPC type, Spring connector. Battery Model is SAH-B2-2500.
S1 Plus	With thermal printer, with S1_Printer_MB PCBA. Wired LTE DIV Antenna ,LTE Main Antenna , Wifi/GPS/BT Antenna, LTE Main antenna is FPC type, IPEX connector. Battery Models are SAH-B2-2500 and SAH-B2-5000.

1.2 Accessory Information

Accessory Description	Manufacturer	Model	Parameters
/	/	/	/

1.3 Antenna Information Detail ▲

Antenna Manufacturer	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
Shenzhen cape deep communication technology co., LTD	Loop	50	13.56MHz	Unknown
The design of compliance with §15.203:				
☒ Unit uses a permanently attached antenna.				
☐ Unit uses a unique coupling to the intentional radiator.				
☐ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.				

1.4 Equipment Modifications

No modifications are made to the EUT during all test items.

2. DESCRIPTION OF TEST CONFIGURATION

2.1 EUT Operation Condition

The system was configured for testing in Engineering Mode, which was provided by the manufacturer. The following summary table is showing all test modes to demonstrate in compliance with the standard:

Test Items	Test Modes
RF Test	Mode 1: Transmitting
Radiated Spurious Emission	Mode 1: Transmitting
AC Line Conducted Emission	Mode 1: Transmitting

2.2 EUT Exercise Software

No software was used in test. The EUT transmit when EUT was power up.

2.3 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	NFC Card	/	/
Huntkey	Adapter(USB)	HKA01105021-XE	0D1805002143

2.4 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	no	no	0.8	Adapter	EUT

2.5 Block Diagram of Test Setup

AC Power Lines Conducted Emission:



Radiated Spurious Emissions:



2.6 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 829273, the FCC Designation No. : CN5044.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

2.7 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9kHz~30MHz: 3.3dB, 30MHz~200MHz: 4.55 dB, 200MHz~1GHz: 5.92 dB, 1GHz~6GHz: 4.98 dB, 6GHz~18GHz: 5.89 dB, 18GHz~26.5GHz:5.47 dB, 26.5GHz~40GHz:5.63 dB
Unwanted Emissions, conducted	±2.47 dB
Temperature	±1℃
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.11 dB (150 kHz to 30 MHz)

3. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.225 §15.209 §15.205	Radiated Spurious Emissions	Compliant
§15.225(e)	Frequency Stability	Compliant
§15.215(c)	20 dB Bandwidth	Compliant
FCC§15.203	Antenna Requirement	Compliant

4. REQUIREMENTS AND TEST RESULTS

4.1 AC Line Conducted Emissions

4.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

4.1.4 Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

According FCC publication number 174176, for a device with a permanent antenna operating at or below 30 MHz, the measurements done with a suitable dummy load, in lieu of the permanent antenna under the following conditions: (1) perform the AC line conducted tests with the permanent antenna to determine compliance with the Section 15.207 limits outside the transmitter's fundamental emission band; (2) retest with a dummy load in lieu of the permanent antenna to determine compliance with the Section 15.207 limits within the transmitter's fundamental emission band.

4.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.1.6 Test Data

Serial Number:	2HV7-5, 2HV7-6	Test Date:	2024/3/10
Test Site:	CE	Test Mode:	Transmitting
Tester:	Lane Sun	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	19.1	Relative Humidity: (%)	64	ATM Pressure: (kPa)	101.5
----------------------	------	------------------------------	----	------------------------	-------


Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101614	2023/10/18	2024/10/17
MICRO-COAX	Coaxial Cable	C-NJNJ-50	C-0200-01	2023/9/5	2024/9/4
R&S	EMI Test Receiver	ESCI	100035	2023/8/18	2024/8/17
R&S	Test Software	EMC32	V9.10.00	N/A	N/A

** Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Mode:S1


Project No: KS1240221-08647E-RF
Port: L
Test Engineer: Lane Sun
Test Date: 2024-3-10
Test Mode: Transmitting
Power Source: AC 120V/60Hz
Note: 2HV7-5



Final Result

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.470023	---	24.82	46.51	21.69	9.000	L1	10.8
0.479495	34.19	---	56.35	22.16	9.000	L1	10.8
0.770122	---	25.60	46.00	20.40	9.000	L1	10.9
1.176724	28.44	---	56.00	27.56	9.000	L1	10.8
1.660095	---	23.71	46.00	22.29	9.000	L1	10.8
2.318778	27.85	---	56.00	28.15	9.000	L1	10.8
2.318778	---	24.65	46.00	21.35	9.000	L1	10.8
2.706494	28.98	---	56.00	27.02	9.000	L1	10.8
4.998419	29.82	---	56.00	26.18	9.000	L1	10.8
5.413644	---	29.23	50.00	20.77	9.000	L1	10.8
13.485870	---	39.78	50.00	10.22	9.000	L1	10.8
13.485870	47.36	---	60.00	12.64	9.000	L1	10.8

Project No: KS1240221-08647E-RF
Port: N
Test Engineer: Lane Sun
Test Date: 2024-3-10
Test Mode: Transmitting
Power Source: AC 120V/60Hz
Note: 2HV7-5



Final Result

Frequency (MHz)	QuasiPeak (dB μV)	Average (dB μV)	Limit (dB μV)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.463043	---	23.64	46.64	23.00	9.000	N	10.8
0.479495	32.57	---	56.35	23.78	9.000	N	10.7
0.537778	29.14	---	56.00	26.86	9.000	N	10.7
0.777842	---	22.38	46.00	23.62	9.000	N	10.8
0.781732	29.11	---	56.00	26.89	9.000	N	10.8
0.963901	---	23.03	46.00	22.97	9.000	N	10.8
0.968720	29.87	---	56.00	26.13	9.000	N	10.8
2.342024	---	22.59	46.00	23.41	9.000	N	10.9
3.914674	29.57	---	56.00	26.43	9.000	N	10.9
3.914674	---	23.97	46.00	22.03	9.000	N	10.9
13.553299	---	37.51	50.00	12.49	9.000	N	10.9
13.553299	43.39	---	60.00	16.61	9.000	N	10.9

Mode:S1 Plus

Project No: KS1240221-08647E-RF

Port: L


Test Engineer: Lane Sun

Test Date: 2024-3-10

Test Mode: Transmitting

Power Source: AC 120V/60Hz


Note: 2HV7-6



Final Result

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.421178	---	27.67	47.42	19.75	9.000	L1	10.8
0.484301	---	28.70	46.26	17.56	9.000	L1	10.8
0.484301	36.05	---	56.26	20.21	9.000	L1	10.8
0.777842	---	25.93	46.00	20.07	9.000	L1	10.9
1.401157	30.43	---	56.00	25.57	9.000	L1	10.8
2.330372	28.80	---	56.00	27.20	9.000	L1	10.8
2.330372	---	24.53	46.00	21.47	9.000	L1	10.8
3.895198	---	19.97	46.00	26.03	9.000	L1	10.8
3.934248	32.89	---	56.00	23.11	9.000	L1	10.8
4.303788	31.90	---	56.00	24.10	9.000	L1	10.8
13.553299	---	40.97	50.00	9.03	9.000	L1	10.8
13.553299	47.59	---	60.00	12.41	9.000	L1	10.8

Project No: KS1240221-08647E-RF
Port: N
Test Engineer: Lane Sun
Test Date: 2024-3-10
Test Mode: Transmitting
Power Source: AC 120V/60Hz
Note: 2HV7-6



Final Result

Frequency (MHz)	QuasiPeak (dB μV)	Average (dB μV)	Limit (dB μV)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.489157	---	29.37	46.18	16.81	9.000	N	10.7
0.494060	32.17	---	56.10	23.93	9.000	N	10.7
0.773973	---	25.87	46.00	20.13	9.000	N	10.8
1.206438	32.36	---	56.00	23.64	9.000	N	10.9
1.206438	---	25.11	46.00	20.89	9.000	N	10.9
1.798001	27.16	---	56.00	28.84	9.000	N	10.9
1.798001	---	23.99	46.00	22.01	9.000	N	10.9
2.318778	---	24.34	46.00	21.66	9.000	N	10.9
2.318778	26.68	---	56.00	29.32	9.000	N	10.9
4.998419	27.63	---	56.00	28.37	9.000	N	10.8
13.553299	45.99	---	60.00	14.01	9.000	N	10.9
13.553299	---	35.59	50.00	14.41	9.000	N	10.9

4.2 Radiated Spurious Emissions


4.2.1 Applicable Standard


As per FCC Part 15.225

- (a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
- (b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- (c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

4.2.2 EUT Setup

9kHz~30MHz:



30MHz~1GHz:

The radiated emission tests were performed in the 3-meter chamber test site, using the setup accordance with the ANSI C63.10-2013.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

4.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 1 GHz.

During the radiated emission test, the EMI test Receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	200 Hz	1 kHz	200 Hz	QP/AV
150 kHz – 30 MHz	9 kHz	30 kHz	9 kHz	QP/AV
30 MHz – 1000 MHz	100 kHz	300 kHz	/	PK
	/	/	120 kHz	QP

If the maximized peak measured value complies with the limit, then it is unnecessary to perform an QP measurement

4.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz-1 GHz except 9-90 kHz, 110-490 kHz, employing an average detector.

All emissions under the average limit and under the noise floor have not recorded in the report.

4.2.5 Corrected Result & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss - Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.2.6 Test Data

Serial Number:	2HV7-5, 2HV7-6	Test Date:	2024/3/19~2024/3/20
Test Site:	Chamber 10m	Test Mode:	Transmitting
Tester:	Zoo Zou	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	23.4~23.9	Relative Humidity: (%)	62~63	ATM Pressure: (kPa)	101.4~101.7
----------------------	-----------	---------------------------	-------	---------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
9kHz~1000MHz					
EMCO	Passive Loop Antenna	6512	9706-1206	2023/10/21	2026/10/20
Sunol Sciences	Hybrid Antenna	JB3	A060611-1	2023/9/6	2026/9/5
Narda	Attenuator	779-6dB	04269	2023/9/6	2026/9/5
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2023/8/1	2024/7/31
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-04	2023/8/1	2024/7/31
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2023/8/1	2024/7/31
Sonoma	Amplifier	310N	185914	2023/8/1	2024/7/31
R&S	EMI Test Receiver	ESCI	100224	2023/8/18	2024/8/17
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
EMCO	Adjustable Dipole Antenna	3121C	9109-753	N/A	N/A
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-02	2023/9/4	2024/9/3
Agilent	Signal Generator	E8247C	MY43321350	2023/10/18	2024/10/17
All-sun	Clamp Meter	EM305A	8348897	2023/8/3	2024/8/2
TDK-Lambda	DC Power Supply	Z+60-14	F-08-EM038-1	N/A	N/A
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30173	2023/10/18	2024/10/17

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

Please refer to the below table and plots.

After pre-scan in the X, Y and Z axes of orientation, the worst case is below:


1) 9kHz~30MHz**Mode:S1**

Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-19
Polarization: Parallel
Test Mode: Transmitting




No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	0.0310	21.62	peak	47.37	68.99	117.78	48.79
2	0.0348	20.39	peak	46.69	67.08	116.77	49.69
3	0.0671	17.96	peak	41.10	59.06	111.07	52.01
4	0.1006	15.60	peak	35.37	50.97	107.55	56.58
5	0.1349	9.72	peak	33.47	43.19	105.00	61.81
6	0.1389	8.58	peak	33.25	41.83	104.75	62.92

Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-19
Polarization: Parallel
Test Mode: Transmitting



No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	0.5731	21.51	peak	22.75	44.26	72.43	28.17
2	0.6406	18.33	peak	22.06	40.39	71.46	31.07
3	1.2824	16.95	peak	15.31	32.26	65.41	33.15
4	4.1356	18.15	peak	7.53	25.68	69.54	43.86
5	5.4186	18.77	peak	6.29	25.06	69.54	44.48
6	24.5291	18.05	peak	4.18	22.23	69.54	47.31


Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-19
Polarization: Parallel
Test Mode: Transmitting



No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	13.3458	50.15	peak	4.57	54.72	80.50	25.78
2	13.4556	51.89	peak	4.55	56.44	90.50	34.06
3	13.5610*	68.45	peak	4.53	72.98	124.00	51.02
4	13.6626	52.52	peak	4.51	57.03	90.50	33.47
5	13.7715	50.75	peak	4.51	55.26	80.50	25.24
6	13.8561	41.41	peak	4.49	45.90	80.50	34.60


*: Fundamental.

Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-19
Polarization: Perpendicular
Test Mode: Transmitting




No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	0.0241	6.81	peak	49.02	55.83	119.96	64.13
2	0.0310	22.25	peak	47.37	69.62	117.78	48.16
3	0.0350	20.79	peak	46.66	67.45	116.72	49.27
4	0.0581	11.67	peak	42.66	54.33	112.32	57.99
5	0.0607	10.88	peak	42.22	53.10	111.94	58.84
6	0.0867	10.33	peak	37.73	48.06	108.84	60.78

Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-19
Polarization: Perpendicular
Test Mode: Transmitting



No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	0.6790	18.20	peak	21.68	39.88	70.95	31.07
2	0.8305	16.58	peak	19.95	36.53	69.20	32.67
3	0.9684	17.42	peak	17.19	34.61	67.86	33.25
4	1.1844	15.69	peak	15.74	31.43	66.10	34.67
5	1.5355	16.29	peak	14.18	30.47	63.83	33.36
6	5.1390	18.40	peak	6.49	24.89	69.54	44.65


Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-19
Polarization: Perpendicular
Test Mode: Transmitting



No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	13.3494	28.79	peak	4.57	33.36	80.50	47.14
2	13.4448	29.10	peak	4.55	33.65	90.50	56.85
3	13.4772	29.54	peak	4.55	34.09	90.50	56.41
4	13.5610*	47.69	peak	4.53	52.22	124.00	71.78
5	13.6707	30.60	peak	4.51	35.11	90.50	55.39
6	13.7760	25.69	peak	4.51	30.20	80.50	50.30


*: Fundamental.

Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-19
Polarization: Ground-parallel
Test Mode: Transmitting




No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	0.0240	9.01	peak	49.04	58.05	120.00	61.95
2	0.0310	22.34	peak	47.37	69.71	117.78	48.07
3	0.0350	20.95	peak	46.66	67.61	116.72	49.11
4	0.0454	6.39	peak	44.84	51.23	114.46	63.23
5	0.0684	6.41	peak	40.86	47.27	110.90	63.63
6	0.0908	9.02	peak	37.00	46.02	108.44	62.42

Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-19
Polarization: Ground-parallel
Test Mode: Transmitting



No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	0.5581	17.01	peak	22.91	39.92	72.66	32.74
2	0.6935	16.09	peak	21.53	37.62	70.77	33.15
3	0.7792	16.77	peak	20.75	37.52	69.75	32.23
4	0.8260	15.02	peak	20.04	35.06	69.24	34.18
5	1.3957	16.08	peak	14.80	30.88	64.67	33.79
6	15.2261	19.46	peak	4.45	23.91	69.54	45.63

Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-19
Polarization: Ground-parallel
Test Mode: Transmitting




No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	13.3494	39.94	peak	4.57	44.51	80.50	35.99
2	13.4538	42.31	peak	4.55	46.86	90.50	43.64
3	13.5600*	57.81	peak	4.53	62.34	124.00	61.66
4	13.6671	41.53	peak	4.51	46.04	90.50	44.46
5	13.7724	40.22	peak	4.51	44.73	80.50	35.77
6	13.8498	31.03	peak	4.49	35.52	80.50	44.98

*: Fundamental.


Mode:S1 Plus

Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-20
Polarization: Parallel
Test Mode: Transmitting




No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	0.0310	19.90	peak	47.37	67.27	117.78	50.51
2	0.0350	17.80	peak	46.66	64.46	116.72	52.26
3	0.0468	12.13	peak	44.59	56.72	114.20	57.48
4	0.0505	16.65	peak	43.97	60.62	113.54	52.92
5	0.0996	11.51	peak	35.47	46.98	107.64	60.66
6	0.1023	11.72	peak	35.27	46.99	107.40	60.41

Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-20
Polarization: Parallel
Test Mode: Transmitting



No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	0.5978	18.50	peak	22.48	40.98	72.06	31.08
2	0.6790	18.01	peak	21.68	39.69	70.95	31.26
3	0.7430	16.62	peak	21.08	37.70	70.17	32.47
4	1.2161	17.78	peak	15.60	33.38	65.87	32.49
5	2.2486	19.06	peak	11.55	30.61	69.54	38.93
6	27.1270	36.22	peak	4.16	40.38	69.54	29.16


Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-20
Polarization: Parallel
Test Mode: Transmitting



No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	13.3503	51.01	peak	4.57	55.58	80.50	24.92
2	13.4547	54.26	peak	4.55	58.81	90.50	31.69
3	13.4871	52.48	peak	4.55	57.03	90.50	33.47
4	13.5610*	70.80	peak	4.53	75.33	124.00	48.67
5	13.6690	54.39	peak	4.51	58.90	90.50	31.60
6	13.7751	52.13	peak	4.51	56.64	80.50	23.86

*: Fundamental.

Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-20
Polarization: Perpendicular
Test Mode: Transmitting




No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	0.0310	21.28	peak	47.37	68.65	117.78	49.13
2	0.0350	18.85	peak	46.66	65.51	116.72	51.21
3	0.0483	12.25	peak	44.35	56.60	113.92	57.32
4	0.0507	12.60	peak	43.93	56.53	113.50	56.97
5	0.0966	11.50	peak	35.99	47.49	107.90	60.41
6	0.0981	10.97	peak	35.73	46.70	107.77	61.07

Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-20
Polarization: Perpendicular
Test Mode: Transmitting



No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	0.5581	18.55	peak	22.91	41.46	72.66	31.20
2	0.6338	18.49	peak	22.13	40.62	71.55	30.93
3	0.7010	18.23	peak	21.46	39.69	70.68	30.99
4	0.8350	17.37	peak	19.86	37.23	69.15	31.92
5	1.2098	17.85	peak	15.63	33.48	65.91	32.43
6	27.1270	41.47	peak	4.16	45.63	69.54	23.91


Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-20
Polarization: Perpendicular
Test Mode: Transmitting



No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	13.3467	46.06	peak	4.57	50.63	80.50	29.87
2	13.4618	50.16	peak	4.55	54.71	90.50	35.79
3	13.4898	51.31	peak	4.55	55.86	90.50	34.64
4	13.5610*	69.50	peak	4.53	74.03	124.00	49.97
5	13.6680	49.12	peak	4.51	53.63	90.50	36.87
6	13.7751	46.68	peak	4.51	51.19	80.50	29.31


*: Fundamental.

Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-20
Polarization: Ground-parallel
Test Mode: Transmitting




No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	0.0310	20.30	peak	47.37	67.67	117.78	50.11
2	0.0350	17.74	peak	46.66	64.40	116.72	52.32
3	0.0531	6.17	peak	43.52	49.69	113.10	63.41
4	0.0820	2.96	peak	38.57	41.53	109.33	67.80
5	0.1064	2.17	peak	35.05	37.22	107.06	69.84
6	0.1140	2.87	peak	34.63	37.50	106.46	68.96

Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-20
Polarization: Ground-parallel
Test Mode: Transmitting



No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	0.5463	18.14	peak	23.03	41.17	72.85	31.68
2	0.6863	17.89	peak	21.61	39.50	70.86	31.36
3	0.7160	18.16	peak	21.32	39.48	70.49	31.01
4	0.8044	17.49	peak	20.47	37.96	69.47	31.51
5	3.6417	20.42	peak	8.45	28.87	69.54	40.67
6	27.1270	18.52	peak	4.16	22.68	69.54	46.86

Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-20
Polarization: Ground-parallel
Test Mode: Transmitting




No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	13.3475	38.06	peak	4.57	42.63	80.50	37.87
2	13.4528	41.21	peak	4.55	45.76	90.50	44.74
3	13.5600*	58.88	peak	4.53	63.41	124.00	60.59
4	13.6481	41.18	peak	4.51	45.69	90.50	44.81
5	13.6661	41.63	peak	4.51	46.14	90.50	44.36
6	13.7697	40.82	peak	4.51	45.33	80.50	35.17

*: Fundamental.

2) 30MHz-1GHz**Mode:S1**


Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-19
Polarization: Horizontal
Test Mode: Transmitting

80.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	30.0000	28.25	peak	-3.80	24.45	40.00	15.55
2	90.1400	41.92	peak	-16.54	25.38	43.50	18.12
3	119.2400	30.02	peak	-9.98	20.04	43.50	23.46
4	152.2200	36.20	peak	-11.01	25.19	43.50	18.31
5	176.4700	43.88	peak	-12.02	31.86	43.50	11.64
6	384.0500	34.45	peak	-7.48	26.97	46.00	19.03


Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-19
Polarization: Vertical
Test Mode: Transmitting



No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	35.8200	32.78	peak	-7.51	25.27	40.00	14.73
2	89.1700	36.33	peak	-16.65	19.68	43.50	23.82
3	147.3700	30.88	peak	-10.83	20.05	43.50	23.45
4	173.5600	37.44	peak	-11.77	25.67	43.50	17.83
5	291.9000	32.03	peak	-9.61	22.42	46.00	23.58
6	384.0500	31.19	peak	-7.48	23.71	46.00	22.29


Mode:S1 Plus

Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-20
Polarization: Horizontal
Test Mode: Transmitting



No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	30.9700	28.20	peak	-4.31	23.89	40.00	16.11
2	149.3100	36.99	peak	-10.99	26.00	43.50	17.50
3	180.3500	45.65	peak	-12.33	33.32	43.50	10.18
4	285.1100	40.37	peak	-9.60	30.77	46.00	15.23
5	299.6600	41.50	peak	-9.53	31.97	46.00	14.03
6	384.0500	42.11	peak	-7.48	34.63	46.00	11.37

Project No: KS1240221-08647E-RF
Test Engineer: Zoo Zou
Test Date: 2024-3-20
Polarization: Vertical
Test Mode: Transmitting



No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	30.0000	30.15	peak	-3.80	26.35	40.00	13.65
2	44.5500	37.19	peak	-14.00	23.19	40.00	16.81
3	149.3100	31.92	peak	-10.99	20.93	43.50	22.57
4	180.3500	38.39	peak	-12.33	26.06	43.50	17.44
5	282.2000	37.01	peak	-9.68	27.33	46.00	18.67
6	384.0500	34.40	peak	-7.48	26.92	46.00	19.08


4.3 20 dB Emission Bandwidth

4.3.1 Applicable Standard

FCC §15.215

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §15.217 through § 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of band operation.

4.3.2 EUT Setup



4.3.3 Test Procedure

According to ANSI C63.10-2013 Section 6.9.2

- The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2
- Steps a) through c) might require iteration to adjust within the specified tolerances.
- The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target

“-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.

f) Set detection mode to peak and trace mode to max hold.

g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).

h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - \text{xx}]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.

i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).

j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

4.3.4 Test Data

Serial Number:	2HV7-5	Test Date:	2024/3/19
Test Site:	Chamber 10m	Test Mode:	Transmitting
Tester:	Zoo Zou	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	23.1	Relative Humidity: (%)	50	ATM Pressure: (kPa)	101.4


Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1206	2023/10/21	2026/10/20
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2023/8/1	2024/7/31
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-04	2023/8/1	2024/7/31
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2023/8/1	2024/7/31
Sonoma	Amplifier	310N	185914	2023/8/1	2024/7/31
R&S	EMI Test Receiver	ESCI	100224	2023/8/18	2024/8/17

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Test Frequency (MHz)	20 dB Emission Bandwidth (kHz)
13.56	1.36




4.4 Frequency Stability

4.4.1 Applicable Standard

As per FCC Part 15.225:

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

4.4.2 EUT Setup



4.4.3 Test Procedure

According to ANSI C63.10-2013 Section 6.8

Frequency stability with respect to ambient temperature

- Supply the EUT with a nominal ac voltage or install a new or fully charged battery in the EUT. If possible, a dummy load shall be connected to the EUT because an antenna near the metallic walls of an environmental test chamber could affect the output frequency of the EUT. If the EUT is equipped with a permanently attached, adjustable-length antenna, then the EUT shall be placed in the center of the chamber with the antenna adjusted to the shortest length possible. Turn ON the EUT and tune it to one of the number of frequencies shown in 5.6.
 - Couple the unlicensed wireless device output to the measuring instrument by connecting an antenna to the measuring instrument with a suitable length of coaxial cable and placing the measuring antenna near the EUT (e.g., 15 cm away), or by connecting a dummy load to the measuring instrument, through an attenuator if necessary.
- NOTE—An instrument that has an adequate level of accuracy as specified by the procuring or regulatory agency is the recommended measuring instrument.
- Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument but is strong enough to allow measurement of the operating or fundamental frequency of the EUT).
 - Turn the EUT OFF and place it inside the environmental temperature chamber. For devices that have oscillator heaters, energize only the heater circuit.

- e) Set the temperature control on the chamber to the highest specified in the regulatory requirements for the type of device and allow the oscillator heater and the chamber temperature to stabilize.
- f) While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized. Four measurements in total are made.
- g) Measure the frequency at each of frequencies specified in 5.6.
- h) Switch OFF the EUT but do not switch OFF the oscillator heater.
- i) Lower the chamber temperature by not more than 10 °C, and allow the temperature inside the chamber to stabilize.
- j) Repeat step f) through step i) down to the lowest specified temperature.

Frequency stability when varying supply voltage

Unless otherwise specified, these tests shall be made at ambient room temperature (+15 °C to +25 °C). An antenna shall be connected to the antenna output terminals of the EUT if possible. If the EUT is equipped with or uses an adjustable-length antenna, then it shall be fully extended.

- a) Supply the EUT with nominal voltage or install a new or fully charged battery in the EUT. Turn ON the EUT and couple its output to a frequency counter or other frequency-measuring instrument.

NOTE—An instrument that has an adequate level of accuracy as specified by the procuring or regulatory agency is the recommended measuring instrument.

- b) Tune the EUT to one of the number of frequencies required in 5.6. Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument but is strong enough to allow measurement of the operating or fundamental frequency of the EUT).
- c) Measure the frequency at each of the frequencies specified in 5.6.
- d) Repeat the above procedure at 85% and 115% of the nominal supply voltage as described in 5.13.

4.4.4 Test Result

Serial Number:	2HV7-5	Test Date:	2024/3/19
Test Site:	Chamber 10m	Test Mode:	Transmitting
Tester:	Zoo Zou	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	23.1	Relative Humidity: (%)	50	ATM Pressure: (kPa)	101.4
----------------------	------	---------------------------	----	---------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1206	2023/10/21	2026/10/20
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2023/8/1	2024/7/31
R&S	EMI Test Receiver	ESCI	100224	2023/8/18	2024/8/17
All-sun	Clamp Meter	EM305A	8348897	2023/8/3	2024/8/2
TDK-Lambda	DC Power Supply	Z+60-14	F-08-EM038-1	N/A	N/A
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30173	2023/10/18	2024/10/17

*** Statement of Traceability:** China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

$f_0 = 13.56 \text{ MHz}$				
Temperature	Voltage	Measured frequency	Frequency Error	Limit
°C	V _{DC}	MHz	Hz	Hz
-30	3.8	13.56048	480	±1356
-20		13.56041	410	±1356
-10		13.56035	350	±1356
0		13.56034	340	±1356
10		13.56029	290	±1356
20		13.56026	260	±1356
25		13.56031	310	±1356
30		13.56035	350	±1356
40		13.5604	400	±1356
50		13.56049	490	±1356
25	3.4	13.56033	330	±1356
25	4.35	13.56052	520	±1356

Note: the voltage range was declared by manufacturer.

4.5 Antenna Requirement

4.5.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

4.5.2 Judgment

Please refer to the Antenna Information detail in Section 1.3.

APPENDIX A - EUT PHOTOGRAPHS

Please refer to the attachment KS1240221-08647E-RF-EXP EUT external photographs and KS1240221-08647E-RF-INP EUT internal photographs.

APPENDIX B - TEST SETUP PHOTOGRAPHS

Please refer to the attachment KS1240221-08647E-RF-00G-TSP test setup photographs.

APPENDIX C - RF EXPOSURE EVALUATION

Applicable Standard

According to KDB447498 D01 General RF Exposure Guidance v06: 4.3. General SAR test exclusion guidance

c) For frequencies below 100 MHz, the following may be considered for SAR test exclusion (also illustrated in Appendix C):

- 1) For *test separation distances* > 50 mm and < 200 mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by $[1 + \log(100/f_{\text{(MHz)}})]$
- 2) For *test separation distances* ≤ 50 mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$
- 3) SAR measurement procedures are not established below 100 MHz

Measurement Result:

For NFC, the power of EUT: E Field@3m is 75.33 dBuV/m = -19.87dBm (0.01mW)

Note: $E[\text{dB}\mu\text{V/m}] = \text{EIRP}[\text{dBm}] + 95.2$ for $d = 3$ m.

SAR test exclusion threshold for NFC(13.56MHz) separation distance < 50 mm

$$=[474*(1 + \log(100/f_{\text{(MHz)}}))]/2$$

$$= 443\text{mW}$$

$$> 0.01\text{mW}$$

Result: Compliant.

***** END OF REPORT *****