

4.5 CONDUCTED BANDEDGE AND SPURIOUS EMISSION

4.5.1 Test Limit

According to §15.247(d) and RSS-247 section 5.5,

In any 100 kHz bandwidth outside the authorized frequency band,


Non-restricted bands shall be attenuated at least 20 dB/30 dB relative to the maximum PSD level in 100 kHz by RF conducted or a radiated measurement which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

4.5.2 Test Procedure

Test method Refer as KDB 662911 D01, KDB 558074 D01.

1. EUT RF output port connected to the SA by RF cable, and the path loss was compensated to result.
2. SA setting, RBW=100kHz, VBW=300kHz, Detector=Peak, Trace mode = max hold, SWT = Auto.
3. In any 100 kHz bandwidth outside the authorized frequency band, shall be attenuated at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when conducted power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.


4.5.3 Test Setup



Report No.: T200416C04-RP1

4.5.4 Test Result

Test Data






Report No.: T200416C04-RP1


Page: 47 / 116

Rev.: 01






Report No.: T200416C04-RP1





Report No.: T200416C04-RP1







Report No.: T200416C04-RP1









Report No.: T200416C04-RP1







Report No.: T200416C04-RP1




Report No.: T200416C04-RP1






Report No.: T200416C04-RP1

Test Data







Report No.: T200416C04-RP1



Report No.: T200416C04-RP1










Report No.: T200416C04-RP1


Page: 62 / 116


Rev.: 01














Report No.: T200416C04-RP1



Report No.: T200416C04-RP1



Report No.: T200416C04-RP1



4.6 RADIATION BANDEDGE AND SPURIOUS EMISSION

4.6.1 Test Limit

FCC according to §15.247(d), §15.209 and §15.205,

In any 100 kHz bandwidth outside the authorized frequency band, all harmonic and spurious must be least 20 dB below the highest emission level with the authorized frequency band. Radiation emission which fall in the restricted bands must also follow the FCC section 15.209 as below limit in table.

Below 30 MHz

Frequency	Field Strength (microvolts/m)	Magnetic H-Field (microamperes/m)	Measurement Distance (metres)
9-490 kHz	2,400/F (F in kHz)	2,400/F (F in kHz)	300
490-1,705 kHz	24,000/F (F in kHz)	24,000/F (F in kHz)	30
1.705-30 MHz	30	N/A	30

Above 30 MHz

Frequency (MHz)	Field Strength microvolts/m at 3 metres (watts, e.i.r.p.)	
	Transmitters	Receivers
30-88	100 (3 nW)	100 (3 nW)
88-216	150 (6.8 nW)	150 (6.8 nW)
216-960	200 (12 nW)	200 (12 nW)
Above 960	500 (75 nW)	500 (75 nW)

Remark:

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

IC according to RSS-247 section 5.5, RSS-Gen, Section 8.9 and 8.10

RSS-Gen Table 3 and Table 5 – General Field Strength Limits for Transmitters and Receivers at Frequencies Above 30 MHz ^(Note)

Frequency (MHz)	Field Strength microvolts/m at 3 metres (watts, e.i.r.p.)	
	Transmitters	Receivers
30-88	100 (3 nW)	100 (3 nW)
88-216	150 (6.8 nW)	150 (6.8 nW)
216-960	200 (12 nW)	200 (12 nW)
Above 960	500 (75 nW)	500 (75 nW)

Note: Measurements for compliance with the limits in table 3 may be performed at distances other than 3 metres, in accordance with Section 6.6.

RSS-Gen Table 6: General Field Strength Limits for Transmitters at Frequencies Below 30 MHz (Transmit)

Frequency	Magnetic field strength (H-Field) (μA/m)	Measurement Distance (m)
9-490 kHz ^{Note}	6.37/F (F in kHz)	300
490-1,705 kHz	63.7/F (F in kHz)	30
1.705-30 MHz	0.08	30

Note: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector..

4.6.2 Test Procedure

Test method Refer as KDB 662911 D01, KDB 558074 D01.

1. The EUT is placed on a turntable, Above 1 GHz is 1.5m and below 1 GHz is 0.8m above ground plane. The EUT Configured un accordance with ANSI C63.10: 2013, and the EUT set in a continuous mode.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. And EUT is set 3m away from the receiving antenna, which is scanned from 1m to 4m above the ground plane to find out the highest emissions. Measurement are made polarized in both the vertical and the horizontal positions with antenna.
3. Span shall wide enough to full capture the emission measured. The SA from 9kHz to 26.5GHz set to the low, Mid and High channels with the EUT transmit.

Note: No emission found between lowest internal used/generated frequency to 30MHz (9KHz~30MHz)

Remark:


Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open are test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

4. The SA setting following :


- (1) Below 1G : RBW = 100kHz, VBW $\geq$ 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.
- (2) Above 1G :
 - (2.1) For Peak measurement : RBW = 1MHz, VBW $\geq$ 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.
 - (2.2) For Average measurement : RBW = 1MHz, VBW
 - 'If Duty Cycle $\geq$ 98%, VBW=10Hz.
 - 'If Duty Cycle < 98%, VBW=1/T.

4.6.3 Test Setup


9kHz ~ 30MHz



30MHz ~ 1GHz




Above 1 GHz



4.6.4 Test Result

Band Edge Test Data

Test Mode	IEEE 802.11b Low CH 2412MHz	Temp/Hum	25.3(°C)/ 61%RH			
Test Item	Band Edge	Test Date	May 25, 2020			
Polarize	Vertical	Test Engineer	Jerry Chang			
Detector	Peak & Average					



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Average	50.56	-3.17	47.39	54.00	-6.61
2390.00	Peak	65.05	-3.17	61.88	74.00	-12.12




Report No.: T200416C04-RP1

Page: 76 / 116

Rev.: 01

Test Mode	IEEE 802.11b Low CH 2412MHz	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Band Edge	Test Date	May 25, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak & Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
2390.00	Average	46.66	-3.17	43.49	54.00	-10.51
2390.00	Peak	56.21	-3.17	53.04	74.00	-20.96




Report No.: T200416C04-RP1

Page: 77 / 116


Rev.: 01

Test Mode	IEEE 802.11b High CH 2462MHz	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Band Edge	Test Date	May 25, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak & Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Average	51.67	-2.71	48.96	54.00	-5.04
2483.50	Peak	58.23	-2.71	55.52	74.00	-18.48

Test Mode	IEEE 802.11b High CH 2462MHz	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Band Edge	Test Date	May 25, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak & Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Average	43.41	-2.71	40.70	54.00	-13.30
2483.50	Peak	52.38	-2.71	49.67	74.00	-24.33




Report No.: T200416C04-RP1

Page: 79 / 116


Rev.: 01

Test Mode	IEEE 802.11g Low CH 2412MHz	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Band Edge	Test Date	May 25, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak & Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dB μ V)	Factor (dB)	Actual FS (dB μ V/m)	Limit @3m (dB μ V/m)	Margin (dB)
2390.00	Average	54.84	-3.17	51.67	54.00	-2.33
2390.00	Peak	72.86	-3.17	69.69	74.00	-4.31

Test Mode	IEEE 802.11g Low CH 2412MHz	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Band Edge	Test Date	May 25, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak & Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Average	47.50	-3.17	44.33	54.00	-9.67
2390.00	Peak	65.20	-3.17	62.03	74.00	-11.97




Report No.: T200416C04-RP1

Page: 81 / 116

Rev.: 01

Test Mode	IEEE 802.11g High CH 2462MHz	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Band Edge	Test Date	May 25, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak & Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Average	53.96	-2.71	51.25	54.00	-2.75
2483.50	Peak	72.34	-2.71	69.63	74.00	-4.37




Report No.: T200416C04-RP1

Page: 82 / 116


Rev.: 01

Test Mode	IEEE 802.11g High CH 2462MHz	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Band Edge	Test Date	May 25, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak & Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Average	45.63	-2.71	42.92	54.00	-11.08
2483.50	Peak	61.52	-2.71	58.81	74.00	-15.19

Test Mode	IEEE 802.11n HT20 Low CH 2412MHz	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Band Edge	Test Date	May 25, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak & Average		



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Average	55.01	-3.17	51.84	54.00	-2.16
2390.00	Peak	70.55	-3.17	67.38	74.00	-6.62




Report No.: T200416C04-RP1

Page: 84 / 116


Rev.: 01

Test Mode	IEEE 802.11 n20 Low CH 2412MHz	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Band Edge	Test Date	May 25, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak & Average		




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Average	47.63	-3.17	44.46	54.00	-9.54
2390.00	Peak	62.36	-3.17	59.19	74.00	-14.81

Test Mode	IEEE 802.11n HT20 High CH 2462MHz	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Band Edge	Test Date	May 25, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak & Average		




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Average	53.00	-2.71	50.29	54.00	-3.71
2483.50	Peak	68.63	-2.71	65.92	74.00	-8.08

Test Mode	IEEE 802.11n20 High CH 2462MHz	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Band Edge	Test Date	May 25, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak & Average		




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)
2483.50	Average	44.42	-2.71	41.71	54.00	-12.29
2483.50	Peak	56.47	-2.71	53.76	74.00	-20.24

Test Mode	IEEE 802.11n HT40 Low CH 2422MHz	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Band Edge	Test Date	May 25, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak & Average	Test Voltage	




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Average	54.19	-3.17	51.02	54.00	-2.98
2390.00	Peak	68.96	-3.17	65.79	74.00	-8.21

Test Mode	IEEE 802.11n HT40 Low CH 2422MHz	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Band Edge	Test Date	May 25, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak & Average	Test Voltage	



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2390.00	Average	46.90	-3.17	43.73	54.00	-10.27
2390.00	Peak	61.23	-3.17	58.06	74.00	-15.94

Test Mode	IEEE 802.11n HT40 High CH 2452MHz	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Band Edge	Test Date	May 25, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak & Average	Test Voltage	




Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)
2483.50	Average	54.15	-2.71	51.44	54.00	-2.56
2483.50	Peak	67.67	-2.71	64.96	74.00	-9.04



Report No.: T200416C04-RP1


Test Mode	IEEE 802.11n HT40 High CH 2452MHz	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Band Edge	Test Date	May 25, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak & Average	Test Voltage	



Frequency (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2483.50	Average	44.34	-2.71	41.63	54.00	-12.37
2483.50	Peak	57.53	-2.71	54.82	74.00	-19.18

Below 1G Test Data


Test Mode	Mode 1	Temp/Hum	25.3(°C)/ 61%RH
Test Item	30MHz-1GHz	Test Date	May 25, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak	Test Voltage	



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
59.10	Peak	52.17	-16.05	36.12	40.00	-3.88
101.78	Peak	48.29	-12.28	36.01	43.50	-7.49
233.70	Peak	45.63	-10.94	34.69	46.00	-11.31
482.02	Peak	33.99	-3.27	30.72	46.00	-15.28
769.14	Peak	29.81	1.18	30.99	46.00	-15.01
847.71	Peak	28.30	2.54	30.84	46.00	-15.16

Note: No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)

Test Mode	Mode 1	Temp/Hum	25.3(°C)/ 61%RH
Test Item	30MHz-1GHz	Test Date	May 25, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak	Test Voltage	




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
54.25	Peak	48.03	-16.01	32.02	40.00	-7.98
223.03	Peak	49.69	-11.58	38.11	46.00	-7.89
369.50	Peak	38.36	-6.62	31.74	46.00	-14.26
480.08	Peak	36.92	-3.26	33.66	46.00	-12.34
517.91	Peak	35.24	-3.07	32.17	46.00	-13.83
757.50	Peak	31.79	0.95	32.74	46.00	-13.26

Note: No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)

Report No.: T200416C04-RP1

Above 1G Test Data

Test Mode	IEEE 802.11b Low CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak & Average		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
4824.00	Peak	43.48	3.35	46.83	74.00	-27.17
7236.00	Average	41.03	10.79	51.82	54.00	-2.18
7236.00	Peak	45.19	10.79	55.98	74.00	-18.02
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11b Low CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak & Average		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
4824.00	Peak	38.74	3.35	42.09	74.00	-31.91
7236.00	Average	40.14	10.79	50.93	54.00	-3.07
7236.00	Peak	44.37	10.79	55.16	74.00	-18.84
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11b Mid CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak & Average		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
4874.00	Peak	38.07	3.48	41.55	74.00	-32.45
7311.00	Average	39.66	11.06	50.72	54.00	-3.28
7311.00	Peak	44.00	11.06	55.06	74.00	-18.94
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11b Mid CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBuV	Factor dB	Actual FS dBuV/m	Limit @3m dBuV/m	Margin dB
4874.00	Peak	40.24	3.48	43.72	74.00	-30.28
7311.00	Peak	41.82	11.06	52.88	74.00	-21.12
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11b High CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
4924.00	Peak	41.52	4.01	45.53	74.00	-28.47
7386.00	Peak	42.53	10.80	53.33	74.00	-20.67
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11b High CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
4924.00	Peak	40.46	4.01	44.47	74.00	-29.53
7386.00	Peak	39.85	10.80	50.65	74.00	-23.35
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11g Low CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
4824.00	Peak	37.26	3.35	40.61	74.00	-33.39
7236.00	Peak	38.65	10.79	49.44	74.00	-24.56
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11g Low CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
4824.00	Peak	36.36	3.35	39.71	74.00	-34.29
7236.00	Peak	38.27	10.79	49.06	74.00	-24.94
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11g Mid CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak & Average		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
4874.00	Peak	38.29	3.48	41.77	74.00	-32.23
7311.00	Average	32.70	11.06	43.76	54.00	-10.24
7311.00	Peak	44.16	11.06	55.22	74.00	-18.78
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11g Mid CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBuV	Factor dB	Actual FS dBuV/m	Limit @3m dBuV/m	Margin dB
4874.00	Peak	37.65	3.48	41.13	74.00	-32.87
7311.00	Peak	40.41	11.06	51.47	74.00	-22.53
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11g High CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
4924.00	Peak	36.62	4.01	40.63	74.00	-33.37
7386.00	Peak	38.38	10.80	49.18	74.00	-24.82
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11g High CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
4924.00	Peak	36.89	4.01	40.90	74.00	-33.10
7386.00	Peak	36.79	10.80	47.59	74.00	-26.41
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT20 Low CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
4824.00	Peak	38.87	3.35	42.22	74.00	-31.78
7236.00	Peak	40.66	10.79	51.45	74.00	-22.55
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT20 Low CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
4824.00	Peak	37.07	3.35	40.42	74.00	-33.58
7236.00	Peak	37.40	10.79	48.19	74.00	-25.81
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT20 Mid CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak & Average		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
4874.00	Peak	37.02	3.48	40.50	74.00	-33.50
7311.00	Average	32.63	11.06	43.69	54.00	-10.31
7311.00	Peak	44.77	11.06	55.83	74.00	-18.17
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11n HT20 Mid CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
4874.00	Peak	37.74	3.48	41.22	74.00	-32.78
7311.00	Peak	42.41	11.06	53.47	74.00	-20.53
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT20 High CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
4924.00	Peak	37.41	4.01	41.42	74.00	-32.58
7386.00	Peak	39.59	10.80	50.39	74.00	-23.61
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT20 High CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBuV	Factor dB	Actual FS dBuV/m	Limit @3m dBuV/m	Margin dB
4924.00	Peak	37.21	4.01	41.22	74.00	-32.78
7386.00	Peak	38.23	10.80	49.03	74.00	-24.97
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT40 Low CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
4844.00	Peak	36.42	3.35	39.77	74.00	-34.23
7266.00	Peak	38.69	10.88	49.57	74.00	-24.43
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT40 Low CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
4844.00	Peak	36.92	3.35	40.27	74.00	-33.73
7266.00	Peak	34.93	10.88	45.81	74.00	-28.19
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT40 Mid CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
4844.00	Peak	38.59	3.35	41.94	74.00	-32.06
7266.00	Peak	38.22	10.88	49.10	74.00	-24.90
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT40 Mid CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
4844.00	Peak	36.63	3.35	39.98	74.00	-34.02
7266.00	Peak	34.84	10.88	45.72	74.00	-28.28
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT40 High CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
4904.00	Peak	37.28	3.69	40.97	74.00	-33.03
7356.00	Peak	39.62	10.89	50.51	74.00	-23.49
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Test Mode	IEEE 802.11n HT40 High CH	Temp/Hum	25.3(°C)/ 61%RH
Test Item	Harmonic	Test Date	May 25, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBuV	Factor dB	Actual FS dBuV/m	Limit @3m dBuV/m	Margin dB
4904.00	Peak	36.12	3.69	39.81	74.00	-34.19
7356.00	Peak	35.92	10.89	46.81	74.00	-27.19
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

- End of Test Report -