FCC RF EXPOSURE REPORT

Applicant	:	Sargent and Greenleaf, Inc.
Address of Applicant	:	1 Security Drive, Nicholasville, Ky.40356
Manufacturer	:	JSW Dongguan Ltd
Address of Manufacturer	:	CHINA Building 1, No. 38 Sanjiang Industrial Zone, Hengli Town Dongguan, Guangdong
Equipment under Test	:	Delaney Smart Deadbolt
Model No.	:	W3U-Nexus
FCC ID	:	W3U-NEXUS
Test Standard(s)	:	KDB447498 D01 General RF Exposure Guidance v06
Report No.	:	DDT-RE23121902-2E02
Issue Date	:	2024/01/12
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd.
Address of Laboratory	:	Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

Test report declares....3
1. General Information 5
1.1. Description of equipment 5
1.2. Assess laboratory.... 5
2. RF Exposure Evaluation 6
2.1. Requirement.... 6
2.2. Calculation method 6
2.3. Estimation result.... 7

Test Report Declare

Applicant	:	Sargent and Greenleaf, Inc.
Address of Applicant	:	1 Security Drive, Nicholasville, Ky.40356
Equipment under Test	:	Delaney Smart Deadbolt
Model No.	:	W3U-Nexus
Manufacturer	:	JSW Dongguan Ltd
Address of Manufacturer	:	CHINA Building 1, No. 38 Sanjiang Industrial Zone, Hengli Town Dongguan, Guangdong

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Guangdong Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Guangdong Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No.:	DDT-RE23121902-2E02		
Date of Receipt:	2023/12/21	**Date of Test:**	2023/12/21 ~ 2024/01/12

Prepared By:

Tiger Mo

Tiger Mo/Engineer

Approved By:

GUANGDONG DONGDIAN TESTING SERVICE CO.,LTD. 广东电检测技术有限公司 Certificate and Report Seal 检验检测专用章

Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2024/01/12	

1. General Information

1.1. Description of equipment

EUT Name	:	Delaney Smart Deadbolt
Model Number	:	W3U-Nexus
EUT function description	:	Please reference user manual of this device
Power Supply	:	DC 5V From external adapter or Battery 1.5V*4(Size:AA)
Radio Technology	:	Bluetooth V5.0
Operation frequency	:	Bluetooth LE: 2402 MHz-2480 MHz
Modulation	:	Bluetooth LE: GFSK
Transmitter rate	:	Bluetooth LE: 1Mbps, 2Mbps
Antenna Type	:	PCB antenna, Maximum PK gain: 4.25 dBi

Note: EUT is the abbreviation of equipment under test.

1.2. Assess laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No.17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China 523808

Tel.: +86-0769-38826678, http://www.dgddt.com, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2. RF Exposure Evaluation

2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm^2)	Averaging Time $\|E\|^2$,$\|H\|^2$ or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2. Calculation method

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } S(mW/cm^2) = \frac{E^2}{377}$$

E = Electric field (V/m)
P = Peak RF output power (mW)
G = EUT Antenna numeric gain (numeric)=
d = Separation distance between radiator and human body (m)
The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2 m, as well as the gain of the used antenna, the RF power density can be obtained.

2.3. Estimation result

Mode	Output power (dBm)	Output power (mW)	tune up power (dBm)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm^2)	MPE Limit (mW/cm^2)
BLE	-0.71	0.849	0	4.25	2.66	0.00045	1

Note: The estimation distance is 20 cm

Conclusion: MPE evaluation required since transmitter power is below FCC threshold

END OF REPORT