



RF EXPOSURE EVALUATION

Report No. : AB0046722(0) Date: 31 Aug 2022

Application No. : LB026967(8)

Applicant : Gatekeeper Systems (HK) Ltd.
36/F, Tower 2, Times Square 1 Matheson Street, Causeway Bay,
Hong Kong

Sample Description : One(1) item of submitted sample stated to be

Product Description : Remote Controlled Locking Wheel
Radio Frequency : 2403 – 2478MHz (MSK)
: 2402 – 2452MHz (FSK)
Supply voltage : DC3V battery
No. of submitted sample : 1

FCC ID : W3Z-W9470B

Date Received : 11 Aug 2022

Evaluation Period : 11 Aug 2022 to 19 Aug 2022

Evaluation Method : 447498 D04 Interim General RF Exposure Guidance v01 - RF Exposure Procedure
and Equipment Authorization Policies for Mobile and Portable Devices

Conclusion : The source-based time-averaged maximum power was satisfied RF exposure
requirements.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature : _____

Wong Lap Pong / Andrew
Deputy Technical Manager

Page 1 of 4

Document name: FCC RF exposure - Document Ref No: RT-EL-EMC-008 - Issue Date: 01 Dec 2017 - Edition: 1

The conformity statement stated in Conclusion above is based on the decision rule agreed with applicant and listed in www.cmateesting.org/qac/statement-of-conformity.pdf.
This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmateesting.org.
This document shall not be reproduced except in full without written approval by CMA Testing. The results apply to the sample as received unless otherwise specified. The observations and test results in this report are relevant only to the sample tested.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmateesting.org Web Site: <http://www.cmateesting.org>



RF EXPOSURE EVALUATION

Report No. : AB0046722(0)

Date: 31 Aug 2022

Simultaneous power

No Simultaneous transmission

RF Exposure Evaluation

According to KDB 447498 D04 clause 2.1.2, if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions.

Result

1.
 - Frequency : 2.402 – 2.452GHz (FSK)
 - Max. peak output power, including tune-up tolerance : 0.479mW
 - Minimum test separation distances : <5mm

Under FSK modulation, the maximum peak output power is lower than 1mW. It is meet the blanket exemption under 1.1307(b)(3)(i)(A)

2.
 - Frequency : 2.403 – 2.478GHz (MSK)
 - Max. peak output power, including tune-up tolerance : 1.122mW
 - Minimum test separation distances : <5mm

Under MSK modulation, the maximum peak output power is greater than 1mW and further evaluation is needed.

RF EXPOSURE EVALUATION

Report No. : AB0046722(0)

Date: 31 Aug 2022

Human exposure to RF emissions from portable devices (47 CFR §2.1093), as defined by the FCC, must be evaluated with respect to the FCC-adopted limits for SAR. Evaluation of mobile devices, as defined by the FCC, may also be performed with respect to SAR limits, but in such case, it is usually simpler and more cost-effective to evaluate compliance with respect to field strength or power density limits. For certain devices that are designed to be used in both mobile and portable configurations similar to those described in 47 CFR §2.1091(d)(4), such as certain desktop phones and wireless modem modules, compliance for mobile configurations is also satisfied when the same device is evaluated for SAR compliance in portable configurations.

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 300 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.



RF EXPOSURE EVALUATION

Report No. : AB0046722(0)

Date: 31 Aug 2022

Field strength = 95.7dBuV/m@3m

$P = \{ [10(95.7/20)/10^6 * 3]^2 / 30 \} * 1000 \text{mW} = 1.115 \text{mW} < 2.72 \text{mW}$

Note:

1. Limited = $3060 * (0.5/20)^x$, $x = -\log(60/(3060 * \sqrt{f}))$.
2. Choosing $f = 2.48 \text{GHz}$ (Highest frequency operate) to calculate MPE limit as higher frequency will have lower MPE limits.
3. SAR Test Exclusion Thresholds is 2.72mW for separation distance 5mm. Therefore, SAR test is not required

Conclusion

The corresponding SAR test exclusion threshold was satisfied 2.1.2 requirements for FSK and was satisfied 2.1.3 requirements for MSK. Further measurement is not required.

***** End of Evaluation *****