


## SAR Test exclusion documentation according to FCC KDB 447498, RSS-102 and EN 62479

Report identification number: 1-3446/17-01-05-A

| Product: Leica Rangefinder 5630               |              |
|-----------------------------------------------|--------------|
| FCC ID                                        | W8J-SIR13D   |
| IC number                                     | 8529A-SIR13D |
| HVIN (Hardware Version Identification Number) | SIR13D       |
| PMN (Product Marketing Name)                  | SIR13D       |
| FVIN (Firmware Version Identification Number) | -/-          |
| HMN (Host Marketing Name)                     | -/-          |



This test report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

### Document authorized:



DN: cn=Thomas Vogler, o=CTC advanced GmbH, ou=VOG-161125, email=thomas.vogler@ctcadvanced.com, c=DE  
Datum: 2017.09.18 12:51:36 +02'00'

Thomas Vogler  
Lab Manager  
Radio Communications & EMC



### EUT technologies:

| Technologies: | Max. rated power: (AVG) | Max. gain: | Min. pathloss:       |
|---------------|-------------------------|------------|----------------------|
| 5.8 GHz radar | -3.36 dBm               | n/a        | 0 dB (if applicable) |

Note:

Test results see CTC advanced test report 1-3446/17-01-02 (derived from 92 dBμV/m @ 3 m)

### SAR test exclusion according to KDB447498 (General RF Exposure Guidance v06)

Equation from Chapter 4.3.1: Standalone SAR test exclusion considerations page 11 and ff.

(1) Standalone SAR test exclusion for 100 MHz to 6 GHz at test separation distances  $\leq 50\text{mm}$

$$(\text{Threshold}_{1\text{-g};10\text{-g}}) \times d_{\text{separation}} / f^{0.5}$$

where

Threshold<sub>1-g;10-g</sub> is 3 for 1-g; 7.5 for 10-g

d<sub>separation</sub> is the min. test separation distance; 5mm is used if the distance is less

f is the RF channel transmit frequency

The table below gives the calculated maximal power that could be used for source based time averaged conducted or radiated power, adjusted for tune up tolerance. If this is at or below the calculated value the DUT is exempted from SAR evaluation.

| f in [MHz] | d <sub>separation</sub> [mm] | Threshold <sub>1-g</sub> | Powerlimit [mW] | P <sub>max-declared</sub> [mW] | Exclusion |
|------------|------------------------------|--------------------------|-----------------|--------------------------------|-----------|
| 5800.00    | 5                            | 3                        | 6.23            | 0.46                           | yes       |

### SAR test exclusion according to RSS-102 Issue 5 Section 2.5.1/Table 1

The table below gives the calculated maximal power that could be used for source based time averaged conducted or radiated power, adjusted for tune up tolerance. If this is at or below the calculated value the DUT is exempted from SAR evaluation.

| f in [MHz] | d <sub>separation</sub> [mm] | tissue volume | Powerlimit [mW] | P <sub>max-declared</sub> [mW] | Exclusion |
|------------|------------------------------|---------------|-----------------|--------------------------------|-----------|
| 5800.00    | 5                            | 1 g           | 1.00            | 0.46                           | yes       |

### SAR test exclusion according to EN 62479

Compliance is given according to EN 62479 because the output power of the DUT is smaller than 20 mW.