

A	1	2	3	4	5	6	7	8	更改履		更改版本	更改内容		更改人	更改日期	A						
	B	RSAG8.805.8132												B					B			
														C						C		
														D							D	
														E								E
														F								
C													C					C				
D																	D					
E																			E			
F																				F		
D																						
E					E																	
F						F																
G							G															
H																						
I																	I					
J																		J				
																			J			
																				J		
格式1	1	2	3	4	5	6	7	8	9	10	11	12	幅面: A3									

ERF2A60 (2002)
IC ID : 10680A-V9H8RC8011
FCC ID : V9H8RC8011

10.5±0.4

logo要求左右居中
左右位偏≤0.4

23.3±0.4

Hisense

Base material color

 Silicon Rubber 1795C

 Silicon Rubber White 90007

 Silicon Rubber Pantone 2347C

 Silicon Rubber Pantone Red 032C

 Silicon Rubber H:213 S:81 B:79

Other Silicon Rubber Black 80007

Printing color

   white

 Pantone 1795C

 Pantone 1795C

 Pantone 7738C

 Pantone 1225C

 Pantone 2173C



 Pantone 2173C

 Pantone 179C

 Pantone 1225C

 Pantone 7738C

ERF2A60 (2002)
IC ID : 10680A-V9H8RC8011
FCC ID : V9H8RC8011

Pantone cool gray 6U

Other printing color

White 90007

技术要求

1. 丝印内容严格按照图纸1:1比例制作，要求清晰，无断笔。

2. 按键表面喷手感油。

3. 机壳及按键表面喷涂、印刷质量可靠性需满足海信 Q/RSAG J07.313《遥控发射器技术要求及测试方法》中的相关要求。

镀涂

ERF2A60(2002)
丝印图

RSAG8.805.8132

阶段标记

质量

比例

A

1:1

第 1 页

共 1 页

青岛海信电器股份有限公司

未注公差标准 单位 : m m				设计	吴祥花 20181229
				结构	
				电路	
				审核	
				标准化	
				批准	