RF TEST REPORT

Applicant	Green Packet Berhad, Taiwan
FCC ID	W9V-DH725-GP
Product	DH-725 LTE Cat. 6 Wi-Fi Router
Brand	Greenpacket
Model	DH-725
Report No.	R1805A0242-R3V2
Issue Date	July 25, 2018

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 15C (2017)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Zhengqiang Zhou

Performed by: Zhengqiang Zhou

Kai Xu

Approved by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

TABLE OF CONTENT

1. Test Laboratory 4
1.1. Notes of the test report 4
1.2. Test facility 4
1.3. Testing Location 5
2. General Description of Equipment under Test 6
3. Applied Standards 7
4. Test Configuration 8
5. Test Case Results 9
5.1. Maximum conducted output power 9
5.2. 6dB Bandwidth 12
5.3. Band Edge 16
5.4. Power Spectral Density 18
5.5. Spurious RF Conducted Emissions 24
5.6. Unwanted Emission 28
5.7. Conducted Emission 61
6. Main Test Instruments 63
ANNEX A: EUT Appearance and Test Setup 64
A.1 EUT Appearance 64
A.2 Test Setup 66

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Summary of measurement results

Number	Summary of measurements of results	Clause in FCC rules	Verdict
1	Maximum conducted output power	15.247(b)(3)	PASS
2	6 dB bandwidth	15.247(a)(2)	PASS
3	Power spectral density	15.247(e)	PASS
4	Band Edge	15.247(d)	PASS
5	Spurious RF Conducted Emissions	15.247(d)	PASS
6	Unwanted Emissions	15.247(d),15.205,15.209	PASS
7	Conducted Emissions	15.207	PASS
Date of Testing: June 9, 2018~ June 22, 2018			

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

1. Test Laboratory

1.1. Notes of the test report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2. Test facility

CNAS (accreditation number: L2264)

TA Technology (Shanghai) Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

IC (recognition number is 8510A)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Canada to perform electromagnetic emission measurement.

VCCI (recognition number is C-4595, T-2154, R-4113, G-10766)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Japan to perform electromagnetic emission measurement.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

1.3. Testing Location

Company:	TA Technology (Shanghai) Co., Ltd.
Address:	No.145, Jintang Rd, Tangzhen Industry Park, Pudong
City:	Shanghai
Post code:	201201
Country:	P. R. China
Contact:	Xu Kai
Telephone:	+86-021-50791141/2/3
Fax:	+86-021-50791141/2/3-8000
Website:	http://www.ta-shanghai.com
E-mail:	xukai@ta-shanghai.com

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

2. General Description of Equipment under Test

Client Information

Applicant	Green Packet Berhad, Taiwan
Applicant address	6F, No.21, Lane 583, Rueiguang Rd. Neihu District, Taipei City 11492, Taiwan
Manufacturer	Green Packet Berhad, Taiwan
Manufacturer address	6F, No.21, Lane 583, Rueiguang Rd. Neihu District, Taipei City 11492, Taiwan

General information

EUT Description	
Model	DH-725
IMEI	351918068946035
Hardware Version	V2.1
Software Version	MG6_0.3.2.14_V1.0-IDU-GP
Power Supply	Battery/AC adapter
Antenna Type	Internal Antenna
Antenna Connector	A permanently attached antenna
Antenna Gain	Antenna 1: 2.50 dBi Antenna 2: 2.50 dBi
Test Mode	802.11b 802.11g, 802.11n(HT20/HT40);
Modulation Type	802.11b: DSSS; 802.11g/n(HT20/HT40): OFDM
Max. Conducted Power	Wi-Fi 2.4G :21.22dBm
Operating Frequency Range(s)	802.11b/g/n(HT20): 2412 ~ 2462 MHz 802.11n(HT40): 2422 ~ 2452 MHz
EUT Accessory	
Adapter	Manufacturer: Aquilstar Precision Industry (Shenzhen) Co., Ltd. Model: ASSA65A-120100
Note: The information of the EUT is declared by the manufacturer.	

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards

- **FCC CFR47 Part 15C (2017) Radio Frequency Devices**
- **ANSI C63.10 (2013)**
- **KDB 558074 D01 DTS Meas Guidance v04**
- **KDB 662911 D01 Multiple Transmitter Output v02r01**

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

4. Test Configuration

Test Mode

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in stand-up position (Z axis) and the worst case was recorded.

In order to find the worst case condition, Pre-tests are needed at the presence of different data rate. Preliminary tests have been done on all the configuration for confirming worst case. Data rate below means worst-case rate of each test item.

The test software is used secureCRT

Worst-case data rates are shown as following table.

Band	Data Rate	
	MIMO Antenna 1	MIMO Antenna 2
802.11b	1 Mbps	1 Mbps
802.11g	6 Mbps	6 Mbps
802.11n HT20	MCS0	MCS0
802.11n HT40	MCS0	MCS0

The worst case Antenna mode for each of the following tests for Wi-Fi:

Test Cases	MIMO Antenna 1	MIMO Antenna 2
Maximum conducted output power	O	O
6dB Bandwidth	O	--
Band Edge	O	--
Power Spectral Density	O	O
Spurious RF Conducted Emissions	O	--
Unwanted Emissions	O	--
Conducted Emission	O	--
Note：“O”: test all bands		

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5. Test Case Results

5.1. Maximum conducted output power

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

During the process of the testing, The EUT was connected to Average Power meter with a known loss. The EUT is max power transmission with proper modulation. The signal transmission is continuous.

The conducted Power is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically.

Test Setup



Limits

Rule Part 15.247 (b) (3) specifies that " For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz: 1 Watt."

Average Output Power	≤ 1W (30dBm)

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 2, U= 0.44 dB.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Test Results

Single Antenna Power Index						
Packet Type	Antenna 1			Antenna 2		
	CH1	CH6	CH11	CH1	CH6	CH11
802.11b	45	45	45	46	45	45
802.11g	51	51	52	51	51	52
802.11n HT20	51	51	54	51	51	54
Packet Type	**CH3**	**CH6**	**CH9**	**CH3**	**CH6**	**CH9**
802.11n HT40	48	48	48	51	48	48

Band	T_{on} (ms)	$T_{(on+off)}$ (ms)	Duty cycle	Duty cycle correction Factor(dB)
802.11b	12.44	12.56	0.99	NA
802.11g	0.25	0.38	0.65	1.85
802.11n HT20	0.23	0.40	0.58	2.40
802.11n HT40	0.13	0.26	0.49	3.08
Note: when Duty cycle>0.98, Duty cycle correction Factor not required.				

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Network Standards	Carrier frequency (MHz)	MIMO Antenna 1		MIMO Antenna 2		Total Power (dBm)	Limit (dBm)	Conclusion
		Average Power Measured (dBm)	Average Power with duty factor (dBm)	Average Power Measured (dBm)	Average Power with duty factor (dBm)			
802.11b HT20	2412	17.79	17.79	16.86	16.86	20.36	30	PASS
	2437	17.98	17.98	16.79	16.79	20.44	30	PASS
	2462	17.08	17.08	16.73	16.73	19.92	30	PASS
802.11g HT20	2412	15.69	17.54	14.83	16.68	20.14	30	PASS
	2437	15.86	17.71	14.93	16.78	20.28	30	PASS
	2462	15.11	16.96	14.53	16.38	19.69	30	PASS
802.11n HT20	2412	15.71	18.11	15.28	17.68	20.91	30	PASS
	2437	15.81	18.21	15.82	18.22	21.22	30	PASS
	2462	15.61	18.01	15.44	17.84	20.93	30	PASS
802.11n HT40	2422	12.92	16.00	12.03	15.11	18.59	30	PASS
	2437	13.05	16.13	12.39	15.47	18.82	30	PASS
	2452	13.03	16.11	12.77	15.85	18.99	30	PASS

Note: 1.Average Power with duty factor = Average Power Measured +Duty cycle correction factor

2. For Total Power, according to KDB 662911 D01 Multiple Transmitter Output v02r01 1),

The Total Power $=10\log(10^{(\text{Power antenna1 in dBm/10})}+10^{(\text{Power antenna2 in dBm/10})})$.

3. The manufacturer declared the transmitter output signals is CDD mode. And N_{ss}=1. According to KDB 662911 D01 Multiple Transmitter Output v02r01 2)f)(i): If all antennas have the same gain, Directional gain = G_{ANT} + Array Gain,

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT};

Array Gain = 5 $\log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less, for 20-MHz channel widths with $N_{ANT} \geq 5$.

So directional gain = G_{ANT} + Array Gain =2.5+0=2.5 dBi<6dBi. So the power limt is 30dBm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.2. 6dB Bandwidth

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to the spectrum analyzer through an external attenuator (20dB) and a known loss cable. RBW is set to 100 kHz; VBW is set to 300 kHz on spectrum analyzer. Dector=Peak, Trace mode=max hold.

Test Setup



Limits

Rule Part 15.247 (a) (2) specifies that “Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.”

minimum 6 dB bandwidth	≥ 500 kHz

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor *k* = 2, *U*= 936 Hz.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Test Results:

Network Standards	Carrier frequency (MHz)	99% bandwidth (MHz)	Minimum 6 dB bandwidth (MHz)	Limit (kHz)	Conclusion
802.11b	2412	15.095	9.595	500	PASS
	2437	15.030	9.576	500	PASS
	2462	15.033	10.020	500	PASS
802.11g	2412	16.447	16.420	500	PASS
	2437	16.441	16.480	500	PASS
	2462	16.449	16.470	500	PASS
802.11n HT20	2412	17.687	17.320	500	PASS
	2437	17.682	17.700	500	PASS
	2462	17.700	17.710	500	PASS
802.11n HT40	2422	35.976	35.420	500	PASS
	2437	36.013	35.440	500	PASS
	2452	36.037	36.020	500	PASS

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

802.11b, Carrier frequency (MHz): 2412



802.11g, Carrier frequency (MHz): 2412



802.11b, Carrier frequency (MHz): 2437



802.11g, Carrier frequency (MHz): 2437



802.11b, Carrier frequency (MHz):2462



802.11g, Carrier frequency (MHz):2462



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

802.11n(HT20), Carrier frequency (MHz): 2412



802.11n(HT40), Carrier frequency (MHz): 2422



802.11n(HT20), Carrier frequency (MHz): 2437



802.11n(HT40), Carrier frequency (MHz): 2437



802.11n(HT20), Carrier frequency (MHz):2462



802.11n(HT40), Carrier frequency (MHz):2452



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.3. Band Edge

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to the spectrum analyzer through an external attenuator (20dB) and a known loss cable the band edge of the lowest and highest channels were measured. The peak detector is used and RBW is set to 100 kHz and VBW is set to 300 kHz on spectrum analyzer. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

Rule Part 15.247(d) specifies that “In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.” If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.”

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 1.96.

Frequency	Uncertainty
2GHz-3GHz	1.407 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Test Results: PASS

802.11b, Channel No.: 1



802.11b, Channel No.: 11



802.11g, Channel No.: 1



802.11g, Channel No.: 11

802.11n(HT20), Channel No.: 1



802.11n(HT20), Channel No.: 11

802.11n(HT40), Channel No.: 3

802.11n(HT40), Channel No.: 9

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.4. Power Spectral Density

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

During the process of the testing, The EUT was connected to Spectrum Analyzer with a known loss. The EUT is max power transmission with proper modulation. Method AVGPSD-2 in KDB558074 D01 was used for this test.

The conducted Power is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically.

Test setup



Limits

Rule Part 15.247(e) specifies that" For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. ''

Limits	≤ 8 dBm / 3kHz

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 2, U= 0.75dB.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Test Results:

MIMO

Network Standards	Channel Number	Power Spectral Density				Total PSD	Limit (dBm / 3kHz)	Conclusion
		Antenna 1		Antenna 2				
		Read Value (dBm / 3kHz)	Power Spectral Density (dBm / 3kHz)	Read Value (dBm / 3kHz)	Power Spectral Density (dBm / 3kHz)	(dBm / 3kHz)		
802.11b	1	-15.15	-15.15	-15.48	-15.48	-12.30	8.00	PASS
	6	-14.49	-14.49	-17.05	-17.05	-12.57	8.00	PASS
	11	-15.69	-15.69	-15.84	-15.84	-12.75	8.00	PASS
802.11g	1	-16.68	-14.83	-18.67	-16.82	-12.70	8.00	PASS
	6	-15.90	-14.04	-18.22	-16.37	-12.04	8.00	PASS
	11	-17.15	-15.30	-17.41	-15.55	-12.41	8.00	PASS
802.11n HT20	1	-16.22	-13.82	-17.53	-15.14	-11.42	8.00	PASS
	6	-15.70	-13.31	-17.80	-15.40	-11.22	8.00	PASS
	11	-16.34	-13.94	-16.06	-13.67	-10.79	8.00	PASS
802.11n HT40	3	-21.73	-18.65	-22.20	-19.12	-15.87	8.00	PASS
	6	-21.32	-18.24	-23.61	-20.53	-16.23	8.00	PASS
	9	-22.30	-19.22	-23.84	-20.76	-16.91	8.00	PASS

Note: 1.Power Spectral Density =Read Value+Duty cycle correction factor

2. For Total PSD, according to KDB 662911 D01 Multiple Transmitter Output v02r01 2)a),the power spectral density=$10\log(10^{(\text{PSD antenna1 in dBm/10})}+10^{(\text{PSD antenna2 in dBm/10})})$

2. The manufacturer declared the transmitter output signals is CDD mode. And N_{ss}=1. According to KDB 662911 D01 Multiple Transmitter Output v02r01 2)f)(i): If all antennas have the same gain, Directional gain = G_{ANT} + Array Gain, For PSD measurements on all devices, Array Gain=10log(Nant/Nss)dB,so directional gain=GANT+Array Gain=2.5+10log(2/1)=5.51<6dBi. So the power limt is 8 dBm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

MIMO Antenna 1

802.11b, Channel No.: 1

802.11g, Channel No.: 1



802.11b, Channel No.: 6

802.11g, Channel No.: 6



802.11b, Channel No.: 11

802.11g, Channel No.: 11



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

802.11n(HT20), Channel No. 1



802.11n(HT40), Channel No. 3



802.11n(HT20), Channel No. 6



802.11n(HT40), Channel No. 6



802.11n(HT20), Channel No. 11



802.11n(HT40), Channel No. 9



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

MIMO Antenna 2

802.11b, Channel No.: 1

802.11g, Channel No.: 1



802.11b, Channel No.: 6

802.11g, Channel No.: 6



802.11b, Channel No.: 11

802.11g, Channel No.: 11



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

802.11n(HT20), Channel No. 1



802.11n(HT40), Channel No. 3



802.11n(HT20), Channel No. 6



802.11n(HT40), Channel No. 6



802.11n(HT20), Channel No. 11



802.11n(HT40), Channel No. 9

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.5. Spurious RF Conducted Emissions

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to the spectrum analyzer with a known loss. The spectrum analyzer scans from 30MHz to the 10th harmonic of the carrier. The peak detector is used. Set RBW to100kHz and VBW to 300 kHz, Sweep is set to ATUO.
The test is in transmitting mode.

Test setup

Limits

Rule Part 15.247(d) pacifies that "In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power." If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB."

Network Standards	Carrier frequency (MHz)	Reference value (dBm)	Limit
802.11b	2412	8.73	-21.27
	2437	9.66	-20.34
	2462	8.87	-21.13
802.11g	2412	7.00	-23.01
	2437	7.16	-22.84
	2462	6.45	-23.55
802.11n HT20	2412	7.19	-22.81
	2437	7.44	-22.56
	2462	7.98	-22.02
802.11n HT40	2422	3.50	-26.50
	2437	3.22	-26.78
	2452	2.54	-27.46

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor *k* = 1.96.

Frequency	Uncertainty
100kHz-2GHz	0.684 dB
2GHz-26GHz	1.407 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Test Results:

802.11b, Channel No.: 1



802.11g, Channel No.: 1

802.11b, Channel No.: 6



802.11g, Channel No.: 6

802.11b, Channel No.: 11



802.11g, Channel No.: 11

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

802.11n(HT20), Channel No. 1



802.11n(HT40), Channel No. 3

802.11n(HT20), Channel No. 6



802.11n(HT40), Channel No. 6

802.11n(HT20), Channel No. 11



802.11n(HT40), Channel No. 9

If disturbances were found more than 20dB below limit line, the mark is not required for the EUT.
The signal beyond the limit is carrier.

Test Data File Name	Frequency (MHz)	Peak (dBm)	Limit (dBm)	Margin (dB)
CSE_ WIFI 11b CH01_0.03-26.5GHz	4821.0	-39.39	-21.27	18.13
CSE_ WIFI 11b CH11_0.03-26.5GHz	4927.0	-40.52	-21.13	19.40

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.6. Unwanted Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	102.5kPa

Method of Measurement

The test set-up was made in accordance to the general provisions of ANSI C63.10-2013.
The Equipment Under Test (EUT) was set up on a non-conductive table in the semi-anechoic chamber. The test was performed at the distance of 3 m between the EUT and the receiving antenna.

The turntable shall be rotated from 0 to 360 degrees for detecting the maximum of radiated spurious signal level. The measurements shall be repeated with orthogonal polarization of the test antenna.The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing. Sweep the Restricted Band and the emissions less than 20 dB below the permissible value are reported.
The radiated emissions measurements were made in a typical installation configuration.
Sweep the whole frequency band through the range from 9 kHz to the 10th harmonic of the carrier, and the emissions less than 20 dB below the permissible value are reported.

This method refer to KDB 558074.
The procedure for peak unwanted emissions measurements above 1000 MHz is as follows:
I) Peak emission levels are measured by setting the instrument as follows:
1) RBW = 1 MHz.
2) VBW ≥ [3 × RBW]
3) Detector = peak.
4) Sweep time = auto.
5) Trace mode = max hold.
6) Allow sweeps to continue until the trace stabilizes. Note that if the transmission is not continuous, then the time required for the trace to stabilize will increase by a factor of approximately 1 / D, where D is the duty cycle.

II) Average emission levels are measured by setting the instrument as follows:
a) RBW = 1 MHz.
b) VBW ≥ [3 × RBW].
c) Detector = RMS (power averaging), if [span / (# of points in sweep)] ≤ RBW / 2. Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.
d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

averaging. Log or dB averaging shall not be used.)

e) Sweep time = auto.

f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of 1 / D, where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)

g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:

1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is [10 log (1 / D)], where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.

2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is [20 log (1 / D)], where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.

3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.

The field strength of spurious emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in stand-up position (Z axis) and the antenna is vertical.

The test is in transmitting mode.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Test setup

9KHz ~ 30MHz



30MHz ~ 1GHz



Above 1GHz



Note: Area side:2.4mX3.6m

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Limits

Rule Part 15.247(d) specifies that "In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c))."

Limit in restricted band

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
0.009–0.490	2400/F(kHz)	/
0.490–1.705	24000/F(kHz)	/
1.705–30.0	30	/
30-88	100	40
88-216	150	43.5
216-960	200	46
Above960	500	54

§15.35(b)

There is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.

Peak Limit=74 dBuV/m

Average Limit=54 dBuV/m

Spurious Radiated Emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1]0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	([2])
13.36 - 13.41			

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor *k* = 1.96.

Frequency	Uncertainty
9KHz-30MHz	3.55 dB
30MHz-200MHz	4.19 dB
200MHz-1GHz	3.63 dB
Above 1GHz	3.68 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Test Results:



802.11b-Channel 1 Peak



802.11b-Channel 1 Average



802.11b-Channel 11 Peak



802.11b-Channel 11Average



802.11g-Channel 1 Peak



802.11g-Channel 1 Average

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



802.11g-Channel 11 Peak



802.11g-Channel 11 Average



802.11n HT20 -Channel 1 Peak



802.11n HT20 -Channel 1 Average



802.11n HT20 -Channel 11 Peak



802.11n HT20 -Channel 11 Average

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



802.11n HT40 -Channel 3 Peak



802.11n HT40 –Channel3 Average



802.11n HT40 -Channel 9 Peak



802.11n HT40 -Channel 9 Average

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Result of RE

Test result

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions more than 20 dB below the limit are not reported.

The following graphs display the maximum values of horizontal and vertical by software.
For above 1GHz, Blue trace uses the peak detection, Green trace uses the average detection.
After the pre test, Antenna1 was selected as the worst antenna.

During the test, the Radiates Emission from 30MHz to 1GHz was performed in all modes with all channels, 802.11b, Channel 11 are selected as the worst condition. The test data of the worst-case condition was recorded in this report.

Continuous TX mode:

RE 30M-1GHz QP



Radiates Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dBuV/m)	Reading value (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
42.059688	24.1	42.2	100.0	V	0.0	-18.1	15.9	40.0
58.709410	29.9	51.1	100.0	V	0.0	-21.2	10.1	40.0
124.986403	35.0	62.6	200.0	H	97.0	-27.6	8.5	43.5
175.017462	27.4	55.4	195.0	H	242.0	-28.0	16.1	43.5
319.990000	33.6	56.4	175.0	V	38.0	-22.8	12.4	46.0
875.044500	30.5	44.6	100.0	H	196.0	-14.1	15.5	46.0

Remark: 1. Quasi-Peak = Reading value + Correction factor
2. Correction Factor = Antenna factor+ Insertion loss(cable loss+amplifier gain)
3. Margin = Limit – Quasi-Peak

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

802.11b CH1

RE 1G-3GHz PK+AV



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

RE 3-18GHz AV



Radiates Emission from 3GHz to 18GHz

Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1190.000000	48.0	200.0	V	212.0	46.2	1.8	26.0	74
1429.500000	49.6	200.0	H	0.0	46.5	3.1	24.4	74
1663.750000	51.7	200.0	H	0.0	46.9	4.8	22.3	74
2028.500000	53.1	200.0	H	0.0	46.5	6.6	20.9	74
2513.750000	56.3	200.0	H	0.0	46.5	9.8	17.7	74
2783.000000	58.6	200.0	H	0.0	47.7	10.9	15.4	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1183.750000	37.4	200.0	H	0.0	35.5	1.9	16.6	54
1438.000000	38.9	200.0	H	0.0	35.8	3.1	15.1	54
1730.500000	40.8	200.0	H	0.0	35.7	5.1	13.2	54
2033.750000	42.5	200.0	H	0.0	35.8	6.7	11.5	54
2518.750000	44.9	200.0	H	0.0	35.2	9.7	9.1	54
2828.500000	47.1	200.0	H	0.0	35.5	11.6	6.9	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

802.11b CH6

RE 1G-3GHz PK+AV



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

RE 3-18GHz AV



Radiates Emission from 3GHz to 18GHz

Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1185.750000	49.0	200.0	V	0.0	47.1	1.9	25.0	74
1224.000000	50.1	200.0	H	95.0	47.9	2.2	23.9	74
1558.500000	51.2	200.0	H	244.0	47.8	3.4	22.8	74
1918.500000	53.0	200.0	H	3.0	47.0	6.0	21.0	74
2537.250000	56.0	200.0	V	0.0	46.4	9.6	18.0	74
2989.500000	58.3	200.0	V	89.0	46.1	12.2	15.7	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1175.750000	36.8	200.0	H	3.0	34.8	2.0	17.2	54
1424.500000	37.9	200.0	V	240.0	34.8	3.1	16.1	54
1694.250000	39.7	200.0	V	233.0	34.7	5.0	14.3	54
1930.250000	41.2	200.0	V	233.0	34.9	6.3	12.8	54
2551.000000	44.0	200.0	V	343.0	34.5	9.5	10.0	54
2989.500000	47.0	200.0	V	89.0	34.8	12.2	7.0	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

802.11b CH11

RE 1G-3GHz PK+AV



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

RE 3-18GHz AV



Radiates Emission from 3GHz to 18GHz

Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1186.250000	48.6	200.0	V	216.0	46.7	1.9	25.4	74
1423.500000	49.5	200.0	H	0.0	46.4	3.1	24.5	74
1678.750000	51.8	200.0	H	0.0	46.9	4.9	22.2	74
1941.750000	53.5	200.0	H	0.0	47.0	6.5	20.5	74
2610.250000	56.2	200.0	H	0.0	46.0	10.2	17.8	74
2992.000000	59.1	200.0	H	0.0	46.9	12.2	14.9	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1162.750000	37.5	200.0	H	0.0	35.8	1.7	16.5	54
1425.250000	38.8	200.0	H	0.0	35.7	3.1	15.2	54
1633.500000	40.7	200.0	H	0.0	35.4	5.3	13.3	54
1990.500000	42.3	200.0	H	0.0	35.6	6.7	11.7	54
2609.500000	45.6	200.0	H	0.0	35.4	10.2	8.4	54
2999.000000	48.4	200.0	H	0.0	36.1	12.3	5.6	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

802.11g CH1

RE 1G-3GHz PK+AV



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1115.250000	48.9	200.0	H	0.0	47.5	1.4	25.1	74
1421.500000	50.0	200.0	H	0.0	46.9	3.1	24.0	74
1730.250000	51.9	200.0	H	0.0	46.9	5.0	22.1	74
1954.500000	54.5	200.0	H	0.0	48.1	6.4	19.5	74
2651.000000	57.4	200.0	H	51.0	47.0	10.4	16.6	74
2995.500000	59.7	200.0	H	0.0	47.4	12.3	14.3	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1186.750000	37.8	200.0	H	91.0	35.9	1.9	16.2	54
1419.750000	39.1	200.0	H	190.0	36.0	3.1	14.9	54
1636.750000	40.8	200.0	H	18.0	35.5	5.3	13.2	54
1991.750000	42.6	200.0	H	0.0	35.9	6.7	11.4	54
2658.500000	46.6	200.0	H	0.0	36.2	10.4	7.4	54
2999.750000	48.8	200.0	H	0.0	36.5	12.3	5.2	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

802.11g CH6

RE 1G-3GHz PK+AV



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1133.250000	49.0	200.0	H	25.0	47.4	1.6	25.0	74
1313.000000	50.6	200.0	H	0.0	48.2	2.4	23.4	74
1720.750000	52.0	200.0	H	0.0	46.9	5.1	22.0	74
1968.000000	54.8	200.0	H	2.0	48.3	6.5	19.2	74
2594.750000	57.9	200.0	H	187.0	47.7	10.2	16.1	74
2993.500000	60.3	200.0	H	19.0	48.1	12.2	13.7	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1179.000000	37.9	200.0	H	95.0	35.9	2.0	16.1	54
1426.000000	39.1	200.0	H	60.0	36.0	3.1	14.9	54
1714.750000	41.1	200.0	H	112.0	36.0	5.1	12.9	54
1991.250000	42.7	200.0	H	170.0	36.0	6.7	11.3	54
2604.500000	46.1	200.0	H	95.0	35.8	10.3	7.9	54
2992.000000	48.9	200.0	H	0.0	36.7	12.2	5.1	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

802.11g CH11

RE 1G-3GHz PK+AV



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1098.000000	48.8	200.0	H	0.0	47.7	1.1	25.2	74
1297.000000	50.6	200.0	H	118.0	48.4	2.2	23.4	74
1639.500000	52.9	200.0	H	0.0	47.6	5.3	21.1	74
2038.250000	54.3	200.0	H	151.0	47.6	6.7	19.7	74
2593.000000	57.1	200.0	H	264.0	47.0	10.1	16.9	74
2973.500000	60.3	200.0	H	5.0	48.1	12.2	13.7	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1167.000000	37.9	200.0	H	101.0	36.1	1.8	16.1	54
1439.250000	39.2	200.0	H	25.0	36.1	3.1	14.8	54
1637.250000	40.9	200.0	H	302.0	35.6	5.3	13.1	54
1990.250000	42.6	200.0	H	0.0	35.9	6.7	11.4	54
2596.000000	45.7	200.0	H	31.0	35.5	10.2	8.3	54
2996.500000	49.3	200.0	H	123.0	37.0	12.3	4.7	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

802.11n (HT20) CH1

RE 1G-3GHz PK+AV



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1154.500000	49.6	200.0	H	0.0	48.0	1.6	24.4	74
1415.000000	50.2	200.0	H	21.0	47.2	3.0	23.8	74
1637.000000	52.8	200.0	H	0.0	47.5	5.3	21.2	74
2056.750000	54.2	200.0	H	121.0	47.4	6.8	19.8	74
2574.750000	57.3	200.0	H	0.0	48.0	9.3	16.7	74
2974.250000	60.4	200.0	H	51.0	48.2	12.2	13.6	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1165.000000	37.8	200.0	H	0.0	36.0	1.8	16.2	54
1390.500000	39.0	200.0	H	150.0	36.0	3.0	15.0	54
1670.750000	41.1	200.0	H	51.0	36.2	4.9	12.9	54
2052.250000	42.6	200.0	H	132.0	35.8	6.8	11.4	54
2602.500000	45.9	200.0	H	0.0	35.6	10.3	8.1	54
2987.500000	48.6	200.0	H	68.0	36.4	12.2	5.4	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

802.11n (HT20) CH6

RE 1G-3GHz PK+AV



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1173.750000	49.6	200.0	H	65.0	47.7	1.9	24.4	74
1439.500000	50.2	200.0	H	0.0	47.1	3.1	23.8	74
1647.250000	51.4	200.0	H	19.0	46.4	5.0	22.6	74
2042.000000	53.4	200.0	H	0.0	46.6	6.8	20.6	74
2673.750000	57.6	200.0	H	65.0	47.4	10.2	16.4	74
2998.750000	59.5	200.0	H	43.0	47.2	12.3	14.5	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1180.000000	37.8	200.0	H	1.0	35.8	2.0	16.2	54
1430.000000	39.1	200.0	H	84.0	36.0	3.1	14.9	54
1639.000000	40.9	200.0	H	96.0	35.6	5.3	13.1	54
2059.500000	42.7	200.0	H	7.0	35.8	6.9	11.3	54
2642.000000	46.1	200.0	H	0.0	35.9	10.2	7.9	54
2994.000000	48.9	200.0	H	0.0	36.6	12.3	5.1	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

802.11n (HT20) CH11

RE 1G-3GHz PK+AV



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1177.000000	49.0	200.0	H	0.0	47.0	2.0	25.0	74
1284.750000	50.0	200.0	H	115.0	47.7	2.3	24.0	74
1640.000000	52.3	200.0	H	234.0	47.0	5.3	21.7	74
1957.000000	53.8	200.0	H	53.0	47.2	6.6	20.2	74
2664.500000	57.1	200.0	H	270.0	46.8	10.3	16.9	74
2953.250000	60.0	200.0	H	192.0	47.9	12.1	14.0	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1179.250000	38.0	200.0	H	192.0	36.0	2.0	16.0	54
1418.000000	39.1	200.0	H	0.0	36.0	3.1	14.9	54
1670.500000	40.9	200.0	H	53.0	36.0	4.9	13.1	54
2056.000000	42.6	200.0	H	98.0	35.8	6.8	11.4	54
2646.500000	46.3	200.0	H	0.0	36.0	10.3	7.7	54
2979.250000	48.5	200.0	H	215.0	36.3	12.2	5.5	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

802.11n (HT40) CH3

RE 1G-3GHz PK+AV



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1144.750000	48.4	200.0	V	350.0	46.9	1.5	25.6	74
1396.750000	49.2	200.0	V	0.0	46.3	2.9	24.8	74
1634.750000	51.6	200.0	H	20.0	46.3	5.3	22.4	74
1943.000000	52.8	200.0	V	155.0	46.2	6.6	21.2	74
2608.000000	55.3	200.0	V	222.0	45.1	10.2	18.7	74
2918.250000	58.2	200.0	V	233.0	46.4	11.8	15.8	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1197.250000	36.7	200.0	V	350.0	34.9	1.8	17.3	54
1419.000000	38.0	200.0	V	275.0	34.9	3.1	16.0	54
1731.750000	39.7	200.0	V	297.0	34.5	5.2	14.3	54
2050.750000	41.1	200.0	V	0.0	34.3	6.8	12.9	54
2608.000000	45.1	200.0	V	222.0	34.9	10.2	8.9	54
2987.000000	46.9	200.0	V	0.0	34.7	12.2	7.1	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

802.11n (HT40) CH6

RE 1G-3GHz PK+AV



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1096.750000	47.7	200.0	V	354.0	46.6	1.1	26.3	74
1427.000000	49.1	200.0	H	260.0	46.0	3.1	24.9	74
1649.750000	50.8	200.0	H	132.0	45.9	4.9	23.2	74
1994.500000	52.5	200.0	H	138.0	45.7	6.8	21.5	74
2605.500000	56.0	200.0	H	0.0	45.7	10.3	18.0	74
2878.000000	58.2	200.0	H	109.0	45.9	12.3	15.8	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1194.000000	36.6	200.0	H	0.0	34.8	1.8	17.4	54
1421.250000	38.3	200.0	V	41.0	35.2	3.1	15.7	54
1732.000000	39.6	200.0	V	118.0	34.4	5.2	14.4	54
2049.000000	41.2	200.0	V	148.0	34.4	6.8	12.8	54
2616.500000	44.6	200.0	V	188.0	34.6	10.0	9.4	54
2989.750000	46.7	200.0	H	144.0	34.5	12.2	7.3	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

802.11n (HT40) CH9

RE 1G-3GHz PK+AV



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 3GHz

RE 3-18GHz PK+AV



Radiates Emission from 3GHz to 18GHz

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1113.750000	47.9	200.0	H	200.0	46.5	1.4	26.1	74
1415.250000	49.3	200.0	H	102.0	46.3	3.0	24.7	74
1639.750000	51.1	200.0	H	309.0	45.8	5.3	22.9	74
2049.500000	52.2	200.0	V	233.0	45.4	6.8	21.8	74
2616.500000	56.0	200.0	V	348.0	46.0	10.0	18.0	74
2939.250000	58.2	200.0	V	204.0	46.3	11.9	15.8	74

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Reading value (dBuV/m)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1189.750000	36.7	200.0	H	125.0	34.9	1.8	17.3	54
1419.250000	38.1	200.0	V	109.0	35.0	3.1	15.9	54
1730.750000	39.6	200.0	V	359.0	34.5	5.1	14.4	54
2052.750000	41.2	200.0	V	354.0	34.4	6.8	12.8	54
2653.000000	45.1	200.0	V	178.0	34.7	10.4	8.9	54
2971.000000	46.9	200.0	V	79.0	34.7	12.2	7.1	54

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.7. Conducted Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.10-2013. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz. The measurement result should include both L line and N line.
The test is in transmitting mode.

Test Setup



Note: AC Power source is used to change the voltage 110V/60Hz.

Limits

Frequency (MHz)	Conducted Limits(dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 *	56 to 46*
0.5 - 5	56	46
5 - 30	60	50
*: Decreases with the logarithm of the frequency.		

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 1.96, U= 2.69 dB.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Test Results:

Following plots, Blue trace uses the peak detection and Green trace uses the average detection. During the test, the Conducted Emission was performed in all modes (WIFI 2.4G /BLE) with all channels, 802.11b, Channel 11 are selected as the worst condition. The test data of the worst-case condition was recorded in this report.

L Line



Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.165750	---	32.24	55.17	22.93	1000.0	9.000	L1	ON	19.1
0.170250	45.21	---	64.95	19.74	1000.0	9.000	L1	ON	19.1
0.561750	---	27.12	46.00	18.89	1000.0	9.000	L1	ON	19.3
0.564000	36.29	---	56.00	19.71	1000.0	9.000	L1	ON	19.3
0.865500	---	16.13	46.00	29.87	1000.0	9.000	L1	ON	19.2
0.984750	24.93	---	56.00	31.07	1000.0	9.000	L1	ON	19.2
2.294250	23.35	---	56.00	32.65	1000.0	9.000	L1	ON	19.0
2.312250	---	14.86	46.00	31.14	1000.0	9.000	L1	ON	19.0
10.263750	32.08	---	60.00	27.93	1000.0	9.000	L1	ON	19.4
10.272750	---	25.14	50.00	24.86	1000.0	9.000	L1	ON	19.4
14.588250	33.47	---	60.00	26.53	1000.0	9.000	L1	ON	19.5
15.162000	---	26.32	50.00	23.68	1000.0	9.000	L1	ON	19.5

N Line



Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.186000	---	38.74	54.21	15.47	1000.0	9.000	N	ON	19.2
0.186000	47.26	---	64.21	16.96	1000.0	9.000	N	ON	19.2
0.451500	35.15	---	56.85	21.70	1000.0	9.000	N	ON	19.2
0.559500	---	30.11	46.00	15.89	1000.0	9.000	N	ON	19.3
0.908250	---	19.72	46.00	26.28	1000.0	9.000	N	ON	19.2
0.998250	27.99	---	56.00	28.01	1000.0	9.000	N	ON	19.2
2.143500	---	18.00	46.00	28.00	1000.0	9.000	N	ON	19.1
2.294250	26.08	---	56.00	29.92	1000.0	9.000	N	ON	19.0
10.258250	33.32	---	60.00	26.68	1000.0	9.000	N	ON	19.4
10.277250	---	25.37	50.00	24.63	1000.0	9.000	N	ON	19.4
14.536500	32.91	---	60.00	27.09	1000.0	9.000	N	ON	19.5
14.622000	---	25.97	50.00	24.03	1000.0	9.000	N	ON	19.5

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

6. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Spectrum Analyzer	R&S	FSV30	100815	2017-12-17	2018-12-16
EMI Test Receiver	R&S	ESCI	100948	2018-05-20	2019-05-19
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	9163-201	2017-11-18	2020-11-17
Double Ridged Waveguide Horn Antenna	R&S	HF907	100126	2014-12-06	2019-12-05
Loop Antenna	SCHWARZBECK	FMZB1519	1519-047	2017-11-18	2020-11-17
Standard Gain Horn	ETS-Lindgren	3160-09	00102644	2015-01-30	2020-01-29
EMI Test Receiver	R&S	ESR	101667	2017-09-06	2018-09-05
LISN	R&S	ENV216	101171	2016-12-16	2019-12-15
Spectrum Analyzer	Agilent	N9010A	MY47191109	2018-05-20	2019-05-19
Power Meter	R&S	NRP2	1144.1374K02 -104306-EX	2017-12-21	2018-12-20
Power Sensor	R&S	NRP-Z21	104799	2018-05-20	2019-05-19
RF Cable	Agilent	SMA 15cm	0001	/	/
Software (CE)	ROHDE&SCHWARZ	EMC32	9.26.0	/	/
Software (RE)	ROHDE&SCHWARZ	EMC32	8.52.0	/	/

*******END OF REPORT *******

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

ANNEX A: EUT Appearance and Test Setup

A.1 EUT Appearance

Front Side

Back Side

a: EUT

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

b:Adapter

Picture 1 EUT and Accessory

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

A.2 Test Setup



30MHz-1GHz



Above 1GHz

Picture 2 Radiated Emission Test Setup

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



Picture 3 Conducted Emission Test Setup

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.