



TEST REPORT

Report Reference No..... : TRE1510017503 R/C.....: 95558

FCC ID..... : WA6S3502

Applicant's name..... : Verykool USA Inc

Address..... : 3636 Nobel Drive, Suite 325, San Diego, CA92122 USA

Manufacturer..... : HUIZHOU QIAOXING ELECTRONICS TECHNOLOGY CO.,LTD

Address..... : Room 1906 of VIA Building, No.9966 Shennan Avenue, Yuehai Street in Nanshan District, Shenzhen ,China

Test item description : Mobile Phone

Trade Mark : verykool

Model/Type reference..... : s3502

Listed Model(s) : --

Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of receipt of test sample..... : Oct 28,2015

Date of testing..... : Oct 29,2015- Nov 17,2015

Date of issue..... : Nov 18,2015

Result..... : PASS

Compiled by
(position+printedname+signature)....: File administrators Candy Liu

Candy Liu

Supervised by
(position+printedname+signature)....: Project Engineer Lion Cai

Lion Cai

Approved by
(position+printedname+signature)....: RF Manager Hans Hu

Hans Hu

Testing Laboratory Name : Shenzhen Huatongwei International Inspection Co., Ltd

Address..... : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Contents

<u>1.</u>	<u>TEST STANDARDS AND TEST DESCRIPTION</u>	<u>3</u>
1.1.	Test Standards	3
1.2.	Test Description	3
<u>2.</u>	<u>SUMMARY</u>	<u>4</u>
2.1.	Client Information	4
2.2.	Product Description	4
2.3.	Operation state	4
2.4.	EUT configuration	5
2.5.	Modifications	5
<u>3.</u>	<u>TEST ENVIRONMENT</u>	<u>6</u>
3.1.	Address of the test laboratory	6
3.2.	Test Facility	6
3.3.	Environmental conditions	7
3.4.	Statement of the measurement uncertainty	7
3.5.	Equipments Used during the Test	8
<u>4.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>9</u>
4.1.	Antenna requirement	9
4.2.	Conducted Emission (AC Main)	10
4.3.	Conducted Peak Output Power	15
4.4.	20dB Emission Bandwidth	18
4.5.	Carrier Frequencies Separation	21
4.6.	Hopping Channel Number	23
4.7.	Dwell Time	25
4.8.	Pseudorandom Frequency Hopping Sequence	28
4.9.	Restricted band (radiated)	29
4.10.	Bandedge and Spurious Emission (conducted)	34
4.11.	Spurious Emission (radiated)	44
<u>5.</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>50</u>
<u>6.</u>	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	<u>51</u>

1. TEST STANDARDS AND TEST DESCRIPTION

1.1. Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

1.2. Test Description

ReportSection	Test Item	Section in CFR 47	Result
4.1	Antenna Requirement	15.203/15.247 (c)	Pass
4.2	AC Power Line Conducted Emission	15.207	Pass
4.3	Conducted Peak Output Power	15.247 (b)(1)	Pass
4.4	20dB Occupied Bandwidth	15.247 (a)(1)	Pass
4.5	Carrier Frequencies Separation	15.247 (a)(1)	Pass
4.6	Hopping Channel Number	15.247 (a)(1)	Pass
4.7	Dwell Time	15.247 (a)(1)	Pass
4.8	Pseudorandom Frequency Hopping Sequence	15.247(b)(4)&TCB Exclusion List (7 July 2002)	Pass
4.9	Restricted band	15.247(d)/15.205	Pass
4.10/4.11	Radiated Emission	15.247(d)/15.209	Pass

Remark: The measurement uncertainty is not included in the test result.

2. SUMMARY

2.1. Client Information

Applicant:	Verykool USA Inc
Address:	3636 Nobel Drive, Suite 325, San Diego, CA92122 USA
Manufacturer:	HUIZHOU QIAOXING ELECTRONICS TECHNOLOGY CO.,LTD
Address:	Room 1906 of VIA Building, No.9966 Shennan Avenue, Yuehai Street in Nanshan District, Shenzhen ,China

2.2. Product Description

Name of EUT	Mobile Phone
Trade Mark:	verykool
Model No.:	s3502
Listed Model(s):	--
Power supply:	DC 3.8V From internal battery
Adapter information:	Model:Q350 Input:AC 100-240V 50/60Hz 0.15A Output:5Vd.c., 700mA
Bluetooth	
Version:	Supported BT4.0+EDR
Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	Internal Antenna
Antenna gain:	3dBi

2.3. Operation state

◆ Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channel which were tested. the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

Channel	Frequency (MHz)
0	2402
1	2403
:	:
39	2441
:	:
77	2479
78	2480

◆ Test mode

For RF test items:

the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions:

the EUT was set to connect with the Bluetooth under large package sizes transmission.

2.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

☐	Power Cable	Length (m) :	/
☐		Shield :	/
☐		Detachable :	/
☐	Multimeter	Manufacturer :	/
☐		Model No. :	/

2.5. Modifications

No modifications were implemented to meet testing criteria.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Phone: 86-755-26748019 Fax: 86-755-26748089

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories, Date of Registration: February 28, 2015. Valid time is until February 27, 2018.

A2LA-Lab Cert. No. 3902.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing. Valid time is until December 31, 2016.

FCC-Registration No.: 317478

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 317478, Renewal date Jul. 18, 2014, valid time is until Jul. 18, 2017.

IC-Registration No.: 5377A&5377B

The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377A on Dec. 31, 2013, valid time is until Dec. 31, 2016.

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377B on Dec. 03, 2014, valid time is until Dec. 03, 2017.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

VCCI

The 3m Semi-

anechoic chamber (12.2m×7.95m×6.7m) of Shenzhen Huatongwei International Inspection Co., Ltd.

has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2484. Date of Registration: Dec. 20, 2012. Valid time is until Dec. 29, 2015.

Radiated disturbance above 1GHz measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-292. Date of Registration: Dec. 24, 2013. Valid time is until Dec. 23, 2016.

Main Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: C-2726. Date of Registration: Dec. 20, 2012. Valid time is until Dec. 19, 2015.

Telecommunication Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: T-1837. Date of Registration: May 07, 2013. Valid time is until May 06, 2016.

DNV

Shenzhen Huatongwei International Inspection Co., Ltd. has been found to comply with the requirements of DNV towards subcontractor of EMC and safety testing services in conjunction with the EMC and Low voltage Directives and in the voluntary field. The acceptance is based on a formal quality Audit and follow-ups according to relevant parts of ISO/IEC Guide 17025 (2005), in accordance with the requirements of the DNV Laboratory Quality Manual towards subcontractors. Valid time is until Aug. 24, 2016.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

3.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system according to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)
Transmitter power Radiated	2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	1.60 dB	(1)
Radiated spurious emission 9KHz-40 GHz	2.20 dB	(1)
Conducted Emission 9KHz-30MHz	3.39 dB	(1)
Radiated Emission 30~1000MHz	4.24 dB	(1)
Radiated Emission 1~18GHz	5.16 dB	(1)
Radiated Emission 18-40GHz	5.54 dB	(1)
Occupied Bandwidth	-----	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

3.5. Equipments Used during the Test

Conducted Emission (AC Main)					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal
1	Artificial Mains	Rohde&Schwarz	ESH2-Z5	100028	2015/11/02
2	EMI Test Receiver	Rohde&Schwarz	ESCI3	100038	2015/11/02
3	Pulse Limiter	Rohde&Schwarz	ESHSZ2	100044	2015/11/02
4	EMI Test Software	Rohde&Schwarz	ES-K1 V1.71	N/A	N/A

Radiated Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal
1	Ultra-Broadband Antenna	ShwarzBeck	VULB9163	538	2015/11/02
2	EMI TEST RECEIVER	Rohde&Schwarz	ESI 26	100009	2015/11/02
3	EMI TEST Software	Audix	E3	N/A	N/A
4	TURNTABLE	ETS	2088	2149	N/A
5	ANTENNA MAST	ETS	2075	2346	N/A
6	EMI TEST Software	Rohde&Schwarz	ESK1	N/A	N/A
7	HORNANTENNA	ShwarzBeck	9120D	1011	2015/11/02
8	Amplifer	Sonoma	310N	E009-13	2015/11/02
9	JS amplifer	Rohde&Schwarz	JS4-00101800-28-5A	F201504	2015/11/02
10	High pass filter	Compliance Direction systems	BSU-6	34202	2015/11/02
11	HORNANTENNA	ShwarzBeck	9120D	1012	2015/11/02
12	Amplifer	Compliance Direction systems	PAP1-4060	120	2015/11/02
13	Loop Antenna	Rohde&Schwarz	HFH2-Z2	100020	2015/11/02
14	TURNTABLE	MATURO	TT2.0	----	N/A
15	ANTENNA MAST	MATURO	TAM-4.0-P	----	N/A
16	Horn Antenna	SCHWARZBECK	BBHA9170	25841	2015/11/02
17	ULTRA-BROADBAND ANTENNA	Rohde&Schwarz	HL562	100015	2015/11/02

Maximum Peak Output Power / Power Spectral Density / 6dB Bandwidth / Band Edge Compliance of RF Emission / Spurious RF Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal
1	Spectrum Analyzer	Rohde&Schwarz	FSP	1164.4391.40	2015/11/02

The Cal.Interval was one year

4. TEST CONDITIONS AND RESULTS

4.1. Antenna requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

Test Result:

The antenna is integral antenna, the best case gain of the antenna is 3.0dBi



4.2. Conducted Emission (AC Main)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm / 50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15 MHz to 30 MHz using a receiver bandwidth of 9 kHz.

TEST RESULTS

Test mode: AC 120V


BT

Polarization

L

SCAN TABLE: "Voltage (9K-30M)FIN"

Short Description: 150K-30M Voltage

**MEASUREMENT RESULT: "GM11165086_fin"**

11/17/2015 5:06PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.159000	49.40	10.2	66	16.1	QP	L1	GND
0.163500	50.20	10.2	65	15.1	QP	L1	GND
0.186000	47.80	10.2	64	16.4	QP	L1	GND
0.465000	46.80	10.2	57	9.8	QP	L1	GND
1.005000	36.40	10.2	56	19.6	QP	L1	GND
1.086000	39.00	10.2	56	17.0	QP	L1	GND

MEASUREMENT RESULT: "GM11165086_fin2"

11/17/2015 5:06PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.163500	35.50	10.2	55	19.8	AV	L1	GND
0.168000	34.30	10.2	55	20.8	AV	L1	GND
0.186000	31.70	10.2	54	22.5	AV	L1	GND
0.465000	30.50	10.2	47	16.1	AV	L1	GND
0.469500	30.10	10.2	47	16.4	AV	L1	GND
0.811500	27.30	10.2	46	18.7	AV	L1	GND

Test mode: AC 120V


BT

Polarization

N

SCAN TABLE: "Voltage (9K-30M)FIN"

Short Description: 150K-30M Voltage

**MEASUREMENT RESULT: "GM11165087_fin"**

11/17/2015 5:09PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.163500	47.70	10.2	65	17.6	QP	N	GND
0.217500	44.00	10.2	63	18.9	QP	N	GND
0.235500	40.30	10.2	62	22.0	QP	N	GND
0.433500	41.60	10.2	57	15.6	QP	N	GND
0.438000	42.50	10.2	57	14.6	QP	N	GND
0.541500	38.70	10.2	56	17.3	QP	N	GND

MEASUREMENT RESULT: "GM11165087_fin2"

11/17/2015 5:09PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.163500	32.60	10.2	55	22.7	AV	N	GND
0.240000	25.90	10.2	52	26.2	AV	N	GND
0.379500	23.40	10.2	48	24.9	AV	N	GND
0.429000	26.50	10.2	47	20.8	AV	N	GND
0.541500	25.00	10.2	46	21.0	AV	N	GND
0.933000	24.00	10.2	46	22.0	AV	N	GND

Test mode: AC 240V


BT

Polarization

L

SCAN TABLE: "Voltage (9K-30M) FIN"

Short Description: 150K-30M Voltage

**MEASUREMENT RESULT: "GM11165089_fin"**

11/17/2015 5:15PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.460500	47.50	10.2	57	9.2	QP	L1	GND
0.523500	41.50	10.2	56	14.5	QP	L1	GND
0.667500	37.60	10.2	56	18.4	QP	L1	GND
0.870000	42.10	10.2	56	13.9	QP	L1	GND
0.942000	38.20	10.2	56	17.8	QP	L1	GND
0.982500	42.30	10.2	56	13.7	QP	L1	GND

MEASUREMENT RESULT: "GM11165089_fin2"


11/17/2015 5:15PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.541500	28.60	10.2	46	17.4	AV	L1	GND
0.699000	27.90	10.2	46	18.1	AV	L1	GND
0.856500	27.40	10.2	46	18.6	AV	L1	GND
0.870000	30.20	10.2	46	15.8	AV	L1	GND
0.924000	31.50	10.2	46	14.5	AV	L1	GND
1.090500	27.90	10.2	46	18.1	AV	L1	GND

Test mode: AC 240V	BT	Polarization	N
--------------------	----	--------------	---

SCAN TABLE: "Voltage (9K-30M) FIN"

Short Description: 150K-30M Voltage

**MEASUREMENT RESULT: "GM11165088_fin"**

11/17/2015 5:12PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.163500	45.80	10.2	65	19.5	QP	N	GND
0.438000	42.40	10.2	57	14.7	QP	N	GND
0.537000	38.60	10.2	56	17.4	QP	N	GND
0.870000	37.10	10.2	56	18.9	QP	N	GND
0.978000	36.50	10.2	56	19.5	QP	N	GND

MEASUREMENT RESULT: "GM11165088_fin2"

11/17/2015 5:12PM


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.244500	25.20	10.2	52	26.7	AV	N	GND
0.433500	30.00	10.2	47	17.2	AV	N	GND
0.541500	25.30	10.2	46	20.7	AV	N	GND
0.874500	23.20	10.2	46	22.8	AV	N	GND
0.928500	26.20	10.2	46	19.8	AV	N	GND
0.982500	23.10	10.2	46	22.9	AV	N	GND

4.3. Conducted Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): **30dBm**

TEST CONFIGURATION




TEST PROCEDURE

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum.

TEST RESULTS

Modulation type	Channel	Output power (dBm)	Limit (dBm)	Result
GFSK	00	1.77	30.00	Pass
	39	1.74		
	78	1.16		
$\pi/4$ DQPSK	00	1.32	21.00	Pass
	39	1.17		
	78	0.62		
8DPSK	00	1.29	21.00	Pass
	39	1.26		
	78	0.47		

Test plot as follows:




4.4. 20dB Emission Bandwidth

LIMIT

N/A

TEST CONFIGURATION




TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. The bandwidth of the fundamental frequency was measured by spectrum analyzer with $RBW \geq 1\%$ of the 20 dB bandwidth and $VBW \geq RBW$.
3. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.


TEST RESULTS

Modulation type	Channel	20dB Bandwidth (MHz)	Limit (MHz)	Result
GFSK	00	0.810	/	Pass
	39	0.816		
	78	0.810		
$\pi/4$ DQPSK	00	1.134	/	Pass
	39	1.134		
	78	1.134		
8DPSK	00	1.164	/	Pass
	39	1.164		
	78	1.164		

Test plot as follows:




8DPSK




Date: 2.NOV.2015 18:29:28

CH00



Date: 2.NOV.2015 18:28:39

CH39



Date: 2.NOV.2015 18:27:24


CH78

4.5. Carrier Frequencies Separation

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):
frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the $2/3 \times 20\text{dB}$ bandwidth of the hopping channel, whichever is greater.

TEST CONFIGURATION







TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=30 KHz and VBW=100KHz.

TEST RESULTS

Modulation type	Channel	Carrier Frequencies Separation (MHz)	Limit (MHz)	Result
GFSK	39	1.000	0.816	Pass
$\pi/4$ DQPSK	39	1.000	0.756	Pass
8DPSK	39	1.000	0.776	Pass

Test plot as follows:




4.6. Hopping Channel Number

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least **15** channels.

TEST CONFIGURATION




TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=1MHz and VBW=3MHz.

TEST RESULTS


Modulation type	Channel number	Limit (MHz)	Result
GFSK	79	15	Pass
$\pi/4$ DQPSK	79		
8DPSK	79		

Test plot as follows:




Date: 2.NOV.2015 18:06:41

GFSK



Date: 2.NOV.2015 18:09:10

$\pi/4$ DQPSK



Date: 2.NOV.2015 18:13:54

8DPSK


4.7. Dwell Time

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. Set center frequency of spectrum analyzer=operating frequency with RBW=1MHz and VBW=1MHz, Span=0Hz.


TEST RESULTS

Modulation type	Channel	Dwell time (Second)	Limit (Second)	Result
GFSK	DH1	0.130	0.40	Pass
	DH3	0.264		
	DH5	0.309		
$\pi/4$ DQPSK	2-DH1	0.128	0.40	Pass
	2-DH3	0.264		
	2-DH5	0.309		
8DPSK	3-DH1	0.128	0.40	Pass
	3-DH3	0.264		
	3-DH5	0.287		


Note:

1. We have tested all mode at high,middle and low channel,and recorded worst case at middle channel.
2. Dwell time=Pulse time (ms) $\times$ (1600 $\div$ 2 $\div$ 79) $\times$ 31.6 Second for DH1, 2-DH1, 3-DH1
Dwell time=Pulse time (ms) $\times$ (1600 $\div$ 4 $\div$ 79) $\times$ 31.6 Second for DH3, 2-DH3, 3-DH3
Dwell time=Pulse time (ms) $\times$ (1600 $\div$ 6 $\div$ 79) $\times$ 31.6 Second for DH5, 2-DH5, 3-DH5

Test plot as follows:




8DPSK




Date: 2.NOV.2015 18:43:01

3-DH1



Date: 2.NOV.2015 18:45:55

3-DH3



Date: 2.NOV.2015 18:46:32

3-DH5

4.8. Pseudorandom Frequency Hopping Sequence

LIMIT


FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

TEST RESULTS


The pseudorandom frequency hopping sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally on the average by each transmitter.

The system receiver has input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shifts frequencies in synchronization with the transmitted signals.


4.9. Restricted band (radiated)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209

Frequency	Limit (dBuV/m @3m)	Value
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION




TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. The receiver set as follow:
RBW=1MHz, VBW=3MHz for Peak value
RBW=1MHz, VBW=10Hz for Average value.
6. The frequency range from 2310MHz to 2483.5MHz harmonic is checked.


TEST RESULTS

Worst mode:	GFSK Modulation	Test Channel:	00
Detector:	Peak	Polarization:	Horizontal




Mark	Frequency MHz	Reading dBUV/m	Antenna dB	Cable dB	Preamp dB	Level dBUV/m	Limit dBUV/m	Over limit	Remark
1	2350.00	40.86	27.41	6.74	37.55	37.46	74.00	-36.54	Peak
2	2390.02	63.25	27.53	6.81	37.57	60.02	74.00	-13.98	Peak
3	2402.00	99.03	27.57	6.83	37.58	95.85	74.00	21.85	Peak

Worst mode:	GFSK Modulation	Test Channel:	00
Detector:	Peak	Polarization:	Vertical




Mark	Frequency MHz	Reading dBUV/m	Antenna dB	Cable dB	Preamp dB	Level dBUV/m	Limit dBUV/m	Over limit	Remark
1	2350.00	43.12	27.41	6.74	37.55	39.72	74.00	-34.28	Peak
2	2390.02	61.96	27.53	6.81	37.57	58.73	74.00	-15.27	Peak
3	2402.00	97.20	27.57	6.83	37.58	94.02	74.00	20.02	Peak

Worst mode:	GFSK Modulation	Test Channel:	00
Detector:	AVG	Polarization:	Horizontal




Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamplifier dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2350.00	25.92	27.41	6.74	37.55	22.52	54.00	-31.48	Average
2	2390.02	26.28	27.53	6.81	37.57	23.05	54.00	-30.95	Average
3	2402.00	76.81	27.57	6.83	37.58	73.63	54.00	19.63	Average

Worst mode:	GFSK Modulation	Test Channel:	00
Detector:	AVG	Polarization:	Vertical




Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamplifier dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2350.00	25.79	27.41	6.74	37.55	22.39	54.00	-31.61	Average
2	2390.02	26.21	27.53	6.81	37.57	22.98	54.00	-31.02	Average
3	2402.00	75.03	27.57	6.83	37.58	71.85	54.00	17.85	Average

Worst mode:	GFSK Modulation	Test Channel:	78
Detector:	Peak	Polarization:	Horizontal




Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2480.01	98.64	27.83	6.94	37.64	95.77	74.00	21.77	Peak
2	2483.50	73.32	27.85	6.96	37.65	70.48	74.00	-3.52	Peak
3	2489.70	66.59	27.88	6.96	37.65	63.78	74.00	-10.22	Peak

Worst mode:	GFSK Modulation	Test Channel:	78
Detector:	Peak	Polarization:	Vertical




Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2480.01	102.51	27.83	6.94	37.64	99.64	74.00	25.64	Peak
2	2483.50	71.63	27.85	6.96	37.65	68.79	74.00	-5.21	Peak
3	2489.02	70.44	27.85	6.96	37.65	67.60	74.00	-6.40	Peak

Worst mode:	GFSK Modulation	Test Channel:	78
Detector:	AVG	Polarization:	Horizontal



Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over Limit	Remark
1	2480.01	77.31	27.83	6.94	37.64	74.4454.00	20.44	Average	
2	2483.50	36.54	27.85	6.96	37.65	33.7054.00	-20.30	Average	
3	2500.00	25.92	27.90	6.98	37.66	23.1454.00	-30.86	Average	

Worst mode:	GFSK Modulation	Test Channel:	78
Detector:	AVG	Polarization:	Vertical



Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2480.01	80.27	27.83	6.94	37.64	77.4054.00	23.40	Average	
2	2483.50	40.19	27.85	6.96	37.65	37.3554.00	-16.65	Average	
3	2500.00	25.98	27.90	6.98	37.66	23.2054.00	-30.80	Average	

Note: Have pre-scan all modulation mode, found the GFSK modulation which it was worst case, so only the worst case's data on the test report. and the Peak Level result is lower than the AV limit, so the AV result is not require.


4.10. Bandedge and Spurious Emission (conducted)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION









TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. Conducted spurious emission the bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=100 KHz and VBW=300KHz.
3. Below -20dB of the highest emission level in operating band.


TEST RESULTS

Test plot as follows:


Modulaiton: GFSK		Test channel: 00	
 Ref 20 dBm *Att 30 dB *RBW 100 kHz Marker 3 [T1] *VBW 300 kHz 2.401960000 GHz SWT 10 ms 1.57 dBm Start 2.31 GHz 9.5 MHz/ Stop 2.405 GHz Date: 2.NOV.2015 19:07:05		 Ref 20 dBm *Att 30 dB *RBW 100 kHz Marker 3 [T1] *VBW 300 kHz 2.404050000 GHz SWT 10 ms 1.63 dBm Start 2.31 GHz 9.5 MHz/ Stop 2.405 GHz Date: 2.NOV.2015 19:07:52	
Bandedge- no hopping mode		Bandedge- hopping mode	
 Ref 20 dBm *Att 30 dB *RBW 100 kHz Marker 1 [T1] *VBW 300 kHz 1.954560000 GHz SWT 300 ms 1.95 dBm Start 30 MHz 297 MHz/ Stop 3 GHz Date: 2.NOV.2015 19:04:16		 Ref 20 dBm *Att 30 dB *RBW 100 kHz Marker 1 [T1] *VBW 300 kHz 13.944000000 GHz SWT 1.2 s 1.2 s Start 3 GHz 1.2 GHz/ Stop 15 GHz Date: 2.NOV.2015 19:04:41	
30 MHz~3GHz		3GHz~15GHz	
 Ref 20 dBm *Att 30 dB *RBW 100 kHz Marker 1 [T1] *VBW 300 kHz 26.454000000 GHz SWT 1.15 s 1.15 s Start 15 GHz 1.15 GHz/ Stop 26.5 GHz Date: 2.NOV.2015 19:05:04			
15GHz~26.5GHz			
Modulaiton: GFSK		Test channel: 39	




30MHz~3GHz









3GHz~15GHz





15GHz~26.5GHz







Modulaiton: $\pi/4$ DQPSK		Test channel: 00	
 Date: 2.NOV.2015 19:09:17		 Date: 2.NOV.2015 19:08:51	
Bandedge- no hopping mode		Bandedge- hopping mode	
 Date: 2.NOV.2015 18:54:46		 Date: 2.NOV.2015 18:55:59	
30MHz~3GHz		3GHz~15GHz	
 Date: 2.NOV.2015 18:56:29			
15GHz~26.5GHz			
Modulaiton: $\pi/4$ DQPSK		Test channel: 39	









30MHz~3GHz



3GHz~15GHz



15GHz~26.5GHz





Modulaiton: 8DPSK		Test channel: 00	
 Date: 2.NOV.2015 19:09:46		 Date: 2.NOV.2015 19:10:17	
Bandedge- no hopping mode		Bandedge- hopping mode	
 Date: 2.NOV.2015 18:52:30		 Date: 2.NOV.2015 18:53:05	
30MHz~3GHz		3GHz~15GHz	
 Date: 2.NOV.2015 18:53:32			
15GHz~26.5GHz			
Modulaiton: 8DPSK		Test channel: 39	




30MHz~3GHz

3GHz~15GHz



15GHz~26.5GHz



4.11. Spurious Emission (radiated)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


◆ Below 30MHz



◆ 30MHz~1000MHz



◆ Above 1GHz



TEST PROCEDURE

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotating table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. Use the following spectrum analyzer settings
 - a) Span shall wide enough to fully capture the emission being measured;
 - b) Below 1GHz, RBW=120KHz, VBW=300KHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - c) Above 1GHz, RBW=1MHz, VBW=3MHz for Peak value
RBW=1MHz, VBW=10Hz for Average value.

TEST RESULTS

Noted:

Have pre-scan all modulation mode, found the GFSK modulation which it was worst case, so only the worst case's data on the test report.


Measurement data:**■ 9kHz ~ 30MHz**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

■ 30MHz ~ 1GHz

SWEEP TABLE: "test (30M-1G)"

Short Description:		Field Strength			
Start	Stop	Detector	Meas.	IF	Transducer
Frequency	Frequency		Time	Bandw.	
30.0 MHz	1.2 GHz	MaxPeak	Coupled	100 kHz	VULB9163 2014


***MEASUREMENT RESULT: "GM1106609_red"***

11/6/2015 9:49AM

Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
52.310000	15.40	-14.4	40.0	24.6	QP	100.0	131.00	HORIZONTAL
59.100000	15.90	-14.8	40.0	24.1	QP	100.0	360.00	HORIZONTAL
116.330000	14.80	-15.6	43.5	28.7	QP	100.0	253.00	HORIZONTAL
203.630000	16.20	-13.7	43.5	27.3	QP	100.0	114.00	HORIZONTAL
543.130000	25.10	-5.2	46.0	20.9	QP	300.0	179.00	HORIZONTAL
955.380000	34.50	3.8	46.0	11.5	QP	300.0	144.00	HORIZONTAL

SWEEP TABLE: "test (30M-1G)"

Short Description:		Field Strength			
Start	Stop	Detector	Meas.	IF	Transducer
Frequency	Frequency		Time	Bandw.	
30.0 MHz	1.2 GHz	MaxPeak	Coupled	100 kHz	VULB9163 2014

***MEASUREMENT RESULT: "GM1106610_red"***

11/6/2015 9:53AM

Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
45.520000	14.80	-14.7	40.0	25.2	QP	100.0	165.00	VERTICAL
59.100000	14.60	-14.8	40.0	25.4	QP	100.0	360.00	VERTICAL
99.840000	15.30	-14.3	43.5	28.2	QP	100.0	253.00	VERTICAL
547.980000	24.90	4.9	46.0	21.1	QP	100.0	92.00	VERTICAL
869.050000	33.40	2.0	46.0	12.6	QP	100.0	234.00	VERTICAL
943.740000	34.10	3.6	46.0	11.9	QP	100.0	234.00	VERTICAL

■ Above 1GHz

CH00 for GFSK									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
4804.00	37.87	31.28	5.66	35.29	39.52	74.00	-34.48	Vertical	Peak
7206.00	36.42	36.22	6.87	35.15	44.36	74.00	-29.64	Vertical	
9608.00	36.48	37.85	8.80	35.55	47.58	74.00	-26.42	Vertical	
12010.00	*							Vertical	
4804.00	39.00	31.28	5.66	35.29	40.65	74.00	-33.35	Horizontal	
7206.00	37.14	36.22	6.87	35.15	45.08	74.00	-28.92	Horizontal	
9608.00	37.64	37.85	8.80	35.55	48.74	74.00	-25.26	Horizontal	
12010.00	*							Horizontal	
4804.00	32.71	31.28	5.66	35.29	34.36	54.00	-19.64	Vertical	Average
7206.00	28.91	36.22	6.87	35.15	36.85	54.00	-17.15	Vertical	
9608.00	28.64	37.85	8.80	35.55	39.74	54.00	-14.26	Vertical	
12010.00	*							Vertical	
4804.00	33.21	31.28	5.66	35.29	34.86	54.00	-19.14	Horizontal	
7206.00	29.44	36.22	6.87	35.15	37.38	54.00	-16.62	Horizontal	
9608.00	28.74	37.85	8.80	35.55	39.84	54.00	-14.16	Horizontal	
12010.00	*							Horizontal	

CH39 for GFSK									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
4882.00	38.53	30.88	5.70	35.27	39.84	74.00	-34.16	Vertical	Peak
7323.00	36.92	35.82	6.91	35.13	44.52	74.00	-29.48	Vertical	
9764.00	37.09	37.45	8.84	35.53	47.85	74.00	-26.15	Vertical	
12205.00	*							Vertical	
4882.00	39.55	30.88	5.70	35.27	40.86	74.00	-33.14	Horizontal	
7323.00	37.48	35.82	6.91	35.13	45.08	74.00	-28.92	Horizontal	
9764.00	37.98	37.45	8.84	35.53	48.74	74.00	-25.26	Horizontal	
12205.00	*							Horizontal	
4882.00	33.52	30.88	5.70	35.27	34.83	54.00	-19.17	Vertical	Average
7323.00	29.15	35.82	6.91	35.13	36.75	54.00	-17.25	Vertical	
9764.00	29.08	37.45	8.84	35.53	39.84	54.00	-14.16	Vertical	
12205.00	*							Vertical	
4882.00	33.37	30.88	5.70	35.27	34.68	54.00	-19.32	Horizontal	
7323.00	29.92	35.82	6.91	35.13	37.52	54.00	-16.48	Horizontal	
9764.00	29.07	37.45	8.84	35.53	39.83	54.00	-14.17	Horizontal	
12205.00	*							Horizontal	

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.



CH78 for GFSK									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
4960.00	38.08	30.98	5.73	35.32	39.47	74.00	-34.53	Vertical	Peak
7440.00	35.84	35.92	6.94	35.18	43.52	74.00	-30.48	Vertical	
9920.00	37.02	37.55	8.87	35.58	47.86	74.00	-26.14	Vertical	
12400.00	*							Vertical	
4960.00	39.26	30.98	5.73	35.32	40.65	74.00	-33.35	Horizontal	
7440.00	37.19	35.92	6.94	35.18	44.87	74.00	-29.13	Horizontal	
9920.00	37.81	37.55	8.87	35.58	48.65	74.00	-25.35	Horizontal	
12400.00	*							Horizontal	
4960.00	33.47	30.98	5.73	35.32	34.86	54.00	-19.14	Vertical	Average
7440.00	28.24	35.92	6.94	35.18	35.92	54.00	-18.08	Vertical	
9920.00	27.98	37.55	8.87	35.58	38.82	54.00	-15.18	Vertical	
12400.00	*							Vertical	
4960.00	33.46	30.98	5.73	35.32	34.85	54.00	-19.15	Horizontal	
7440.00	29.29	35.92	6.94	35.18	36.97	54.00	-17.03	Horizontal	
9920.00	28.94	37.55	8.87	35.58	39.78	54.00	-14.22	Horizontal	
12400.00	*							Horizontal	

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

5. Test Setup Photos of the EUT

Radiated Emission



Conducted Emission (AC Mains)



6. External and Internal Photos of the EUT

Reference to Test Report TRE1510017501

.....End of Report.....