RF TEST REPORT

SIEMIC
A Bureau Veritas Group Company

Report No.: 17070248-FCC-R2

Supersede Report No.: N/A

Applicant	Verykool USA Inc
Product Name	Mobile Phone
Model No.	s4009
Serial No.	N/A
Test Standard	FCC Part 15.247: 2016, ANSI C63.10: 2013
Test Date	April 01 to 20, 2017
Issue Date	April 26, 2017
Test Result	☑ Pass ☐ Fail
Equipment complied with the specification	☑
Equipment did not comply with the specification	☐

Leen Yang	David Huang	
Leen Yang Test Engineer	David Huang Checked By	

This test report may be reproduced in full only

Test result presented in this test report is applicable to the tested sample only

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.

In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY 5

2. CUSTOMER INFORMATION 5

3. TEST SITE INFORMATION 5

4. EQUIPMENT UNDER TEST (EUT) INFORMATION 6

5. TEST SUMMARY 9

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS 10

6.1 ANTENNA REQUIREMENT 10

6.2 DTS (6 DB&20 DB) CHANNEL BANDWIDTH 11

6.3 MAXIMUM OUTPUT POWER 17

6.4 POWER SPECTRAL DENSITY 21

6.5 BAND-EDGE & UNWANTED EMISSIONS INTO RESTRICTED FREQUENCY BANDS 25

6.6 AC POWER LINE CONDUCTED EMISSIONS 31

6.7 RADIATED SPURIOUS EMISSIONS & RESTRICTED BAND 37

ANNEX A. TEST INSTRUMENT 43

ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS 44

ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT 55

ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST 59

ANNEX E. DECLARATION OF SIMILARITY 60

1. Report Revision History

Report No.	Report Version	Description	Issue Date
17070248-FCC-R2	NONE	Original	April 26, 2017

2. Customer information

Applicant Name	Verykool USA Inc
Applicant Add	3636 Nobel Drive, Suite 325, San Diego, California 92122 United States
Manufacturer	TEM MOBILE LIMITED
Manufacturer Add	No 1708, Cangsong Building, Tairan 6 Road, Futian ShenZhen, China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT:	Mobile Phone
Main Model:	s4009
Serial Model:	N/A
Date EUT received:	March 31, 2017
Test Date(s):	April 01 to 20, 2017
Equipment Category :	DTS
Antenna Gain:	GSM850:1.5dBi PCS1900:1.55dBi UMTS-FDD Band V: 1.58dBi UMTS-FDD Band II: 1.56dBi WIFI: 1.35dBi Bluetooth/BLE: 1.35dBi GPS: 1.8dBi
Antenna Type:	PIFA antenna
Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK,8PSK UMTS-FDD: QPSK 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, π /4DQPSK, 8DPSK BLE: GFSK GPS:BPSK

RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz; RX: 1932.4 ~ 1987.6 MHz WIFI: 802.11b/g/n(20M): 2412-2462 MHz WIFI: 802.11n(40M): 2422-2452 MHz Bluetooth& BLE: 2402-2480 MHz GPS: 1575.42 MHz
Max. Output Power:	802.11b: 8.69dBm 802.11g: 9.01dBm 802.11n(20M): 9.11dBm 802.11n(40M): 7.79dBm
Number of Channels:	GSM 850: 124CH PCS1900: 299CH UMTS-FDD Band V : 102CH UMTS-FDD Band II : 277CH WIFI :802.11b/g/n(20M): 11CH WIFI :802.11n(40M): 7CH Bluetooth: 79CH BLE: 40CH GPS:1CH
Port:	USB Port, Earphone Port
Input Power:	Adapter: Model: s4009 Input: AC100-240V~50/60Hz,0.2A Output: DC 5.0V,550mA Battery : Model: s4009 Spec: 3.7V,1200mAh(4.44Wh) Limited charger voltage: 4.2V
Trade Name :	Verykool

FCC ID: WA6S4009

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247 (a)(2)	DTS (6 dB&20 dB) CHANNEL BANDWIDTH	Compliance
§15.247(b)(3)	Conducted Maximum Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247(d)	Band-Edge & Unwanted Emissions into Restricted Frequency Bands	Compliance
§15.207 (a),	AC Power Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands	Compliance

Measurement Uncertainty

Emissions		
Test Item	**Description**	**Uncertainty**
Band-Edge & Unwanted Emissions into Restricted Frequency Bands and Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited.
The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

a. Antenna must be permanently attached to the unit.
b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.
And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 2 antennas:
A permanently attached PIFA antenna for Bluetooth/BLE/WIFI/GPS, the gain is 1.35dBi for Bluetooth/BLE/WIFI, the gain is 1.8dBi for GPS.
A permanently attached PIFA antenna for GSM/PCS/UMTS, the gain is 1.5dBi for GSM850, 1.55dBi for PCS1900,1.58dBi for UMTS-FDD Band V, 1.56dBi for UMTS-FDD Band II.

The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 DTS (6 dB&20 dB) Channel Bandwidth

Temperature	24℃
Relative Humidity	55%
Atmospheric Pressure	1010mbar
Test date :	April 17, 2017
Tested By :	Leen Yang

Spec	Item	Requirement	Applicable
§ 15.247(a)(2)	a)	6dB BW≥ 500kHz; 20dB BW≥ 500kHz;	☑
RSS Gen(4.6.1)	b)	99% BW: For FCC reference only; required by IC.	☑
Test Setup			
Test Procedure	558074 D01 DTS MEAS Guidance v03r03, 8.1 DTS bandwidth 6dB bandwidth a) Set RBW = 100 kHz. b) Set the video bandwidth (VBW) ≥ 3 × RBW. c) Detector = Peak. d) Trace mode = max hold. e) Sweep = auto couple. f) Allow the trace to stabilize. g) Measure the maximum width of the emission that is constrained by the freq uencies associated with the two outermost amplitude points (upper and lower fr equencies) that are attenuated by 6 dB relative to the maximum level measure d in the fundamental emission. 20dB bandwidth C63.10 Occupied Bandwidth (OBW=20dB bandwidth) 1. Set RBW = 1%-5% OBW. 2. Set the video bandwidth (VBW) ≥ 3 x RBW. 3. Set the span range between 2 times and 5 times of the OBW. 4. Sweep time=Auto, Detector=PK, Trace=Max hold. 5. Once the reference level is established, the equipment is conditioned with t ypical modulating signals to produce the worst-		

	case (i.e., the widest) bandwidth. Unless otherwise specified for an unlicensed wireless device, measure the bandwidth at the 20 dB levels with respect to the reference level.
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Measurement result

Test mode	CH	Freq (MHz)	6dB Bandwidth (MHz)	20dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	9.673	16.355	≥ 0.5
	Mid	2437	10.143	16.345	≥ 0.5
	High	2462	9.582	16.340	≥ 0.5
802.11g	Low	2412	16.463	19.432	≥ 0.5
	Mid	2437	15.599	19.399	≥ 0.5
	High	2462	15.619	19.098	≥ 0.5
802.11n (20M)	Low	2412	17.714	19.643	≥ 0.5
	Mid	2437	16.215	19.281	≥ 0.5
	High	2462	16.947	19.738	≥ 0.5
802.11n (40M)	Low	2422	36.290	39.782	≥ 0.5
	Mid	2437	36.237	39.971	≥ 0.5
	High	2452	36.184	40.000	≥ 0.5

Test Plots

6dB Bandwidth measurement result



802.11b 6dB Bandwidth - Low CH 2412



802.11b 6dB Bandwidth - Mid CH 2437



802.11b 6dB Bandwidth - High CH 2462



802.11g 6dB Bandwidth - Low CH 2412



802.11g 6dB Bandwidth - Mid CH 2437



802.11g 6dB Bandwidth - High CH 2462



802.11n20 6dB Bandwidth - Low CH 2412



802.11n20 6dB Bandwidth - Mid CH 2437



802.11n20 6dB Bandwidth - High CH 2462



802.11n40 6dB Bandwidth - Low CH 2422



802.11n40 6dB Bandwidth - Mid CH 2437



802.11n40 6dB Bandwidth - High CH 2452

20 dB Bandwidth measurement result



802.11b 20dB Bandwidth - Low CH 2412



802.11b 20dB Bandwidth - Mid CH 2437



802.11b 20dB Bandwidth - High CH 2462



802.11g 20dB Bandwidth - Low CH 2412



802.11g 20dB Bandwidth - Mid CH 2437



802.11g 20dB Bandwidth - High CH 2462



802.11n20 20dB Bandwidth - Low CH 2412



802.11n20 20dB Bandwidth - Mid CH 2437



802.11n20 20dB Bandwidth - High CH 2462



802.11n40 20dB Bandwidth - Low CH 2422



802.11n40 20dB Bandwidth - Mid CH 2437



802.11n40 20dB Bandwidth - High CH 2452

6.3 Maximum Output Power

Temperature	24℃
Relative Humidity	55%
Atmospheric Pressure	1010mbar
Test date :	April 17, 2017
Tested By :	Leen Yang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b)(3),RSS210(A8.4)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	☐
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	☐
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	☐
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	☐
	e)	FHSS in 902-928MHz with ≥ 25 & <50 channels: ≤ 0.25 Watt	☐
	f)	DTS in 902-928MHz, 2400-2483.5MHz: ≤ 1 Watt	☑
Test Setup			
Test Procedure	558074 D01 DTS MEAS Guidance v03r03, 9.1.2 Integrated band power method Maximum output power measurement procedure - a) Set span to at least 1.5 times the OBW. - b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz. - c) Set VBW ≥ 3 x RBW. - d) Number of points in sweep ≥ 2 × span / RBW. (This gives bin-to-bin spacing ≤ RBW/2, so that narrowband signals are not lost between frequency bins.) - e) Sweep time = auto. - f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode. - g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum		

	power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to " free run" . - h) Trace average at least 100 traces in power averaging (i.e., RMS) mode. - i) Compute power by integrating the spectrum across the OBW of the signal using the instrument' s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Output Power measurement result

Type	Test mode	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Result
Output power	802.11b	Low	2412	8.61	30	Pass
		Mid	2437	8.59	30	Pass
		High	2462	**8.69**	30	Pass
	802.11g	Low	2412	8.43	30	Pass
		Mid	2437	8.19	30	Pass
		High	2462	**9.01**	30	Pass
	802.11n (20M)	Low	2412	8.49	30	Pass
		Mid	2437	7.89	30	Pass
		High	2462	**9.11**	30	Pass
	802.11n (40M)	Low	2422	8.72	30	Pass
		Mid	2437	8.38	30	Pass
		High	2452	**7.79**	30	Pass

Test Plots

The Average Power



802.11b - AV Output power - Low CH 2412



802.11b - AV Output power - Mid CH 2437



802.11b - AV Output power - High CH 2462



802.11g - AV Output power - Low CH 2412



802.11g - AV Output power - Mid CH 2437



802.11g - AV Output power - High CH 2462



Channel Power: 8.49 dBm / 19.6430 MHz

Power Spectral Density: -67.84 dBm/Hz

802.11n20 - AV Output power - Low CH 2412



Channel Power: 7.89 dBm / 19.2810 MHz

Power Spectral Density: -64.96 dBm/Hz

802.11n20 - AV Output power - Mid CH 2437



Channel Power: 9.11 dBm / 19.7380 MHz

Power Spectral Density: -63.85 dBm/Hz

802.11n20 - AV Output power - High CH 2462



Channel Power: 8.72 dBm / 39.7820 MHz

Power Spectral Density: -69.28 dBm/Hz

802.11n40 - AV Output power - Low CH 2422



Channel Power: 8.38 dBm / 39.9710 MHz

Power Spectral Density: -68.84 dBm/Hz

802.11n40 - AV Output power - Mid CH 2437



Channel Power: 7.79 dBm / 40.0000 MHz

Power Spectral Density: -68.11 dBm/Hz

802.11n40 - AV Output power - High CH 2452

6.4 Power Spectral Density

Temperature	24℃
Relative Humidity	55%
Atmospheric Pressure	1010mbar
Test date :	April 17, 2017
Tested By :	Leen Yang

Spec	Item	Requirement	Applicable
§15.247(e)	a)	The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	☑
Test Setup			
Test Procedure	558074 D01 DTS MEAS Guidance v03r03, 10.2 power spectral density method power spectral density measurement procedure - a) Set analyzer center frequency to DTS channel center frequency. - b) Set the span to 1.5 times the DTS bandwidth. - c) Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz. - d) Set the VBW ≥ 3 × RBW. - e) Detector = peak. - f) Sweep time = auto couple. - g) Trace mode = max hold. - h) Allow trace to fully stabilize. - i) Use the peak marker function to determine the maximum amplitude level within the RBW. - j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.		
Remark			
Result	☑ Pass ☐ Fail		

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Power Spectral Density measurement result

Type	Test mode	CH	Freq (MHz)	PSD (dBm)	Limit (dBm)	Result
PSD	802.11b	Low	2412	-13.43	8	Pass
		Mid	2437	-13.13	8	Pass
		High	2462	-11.57	8	Pass
	802.11g	Low	2412	-18.85	8	Pass
		Mid	2437	-16.35	8	Pass
		High	2462	-15.50	8	Pass
	802.11n (20M)	Low	2412	-20.22	8	Pass
		Mid	2437	-16.16	8	Pass
		High	2462	-13.50	8	Pass
	802.11n (40M)	Low	2422	-20.07	8	Pass
		Mid	2437	-20.06	8	Pass
		High	2452	-18.69	8	Pass

Test Plots

Power Spectral Density measurement result



PSD - Low CH 2412 - 802.11b



PSD - Mid CH 2437 – 802.11b



PSD - High CH 2462 - 802.11b



PSD - Low CH 2412 -802.11g



PSD - Mid CH 2437 – 802.11g



PSD - High CH 2462 - 802.11g



PSD - Low CH 2412 - 802.11n20



PSD - Mid CH 2437 – 802.11n20



PSD - High CH 2472 - 802.11n20



PSD - Low CH 2422 - 802.11n40



PSD - Mid CH 2437 – 802.11n40



PSD - High CH 2452 - 802.11n40

6.5 Band-Edge & Unwanted Emissions into Restricted Frequency Bands

Temperature	21℃
Relative Humidity	53%
Atmospheric Pressure	1011mbar
Test date :	April 05, 2017
Tested By :	Leen Yang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(d)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	☑
Test Setup			
Test Procedure	Radiated Method Only - 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. - 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.		

	- 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Test Plots

Band Edge measurement result



Band Edge, Left Side (Peak) - 802.11b

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz



Band Edge, Right Side (Peak) - 802.11b

Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)

Note: (no need if PK value less than the AV limit)

Band Edge, Left Side (Average) - 802.11b

Band Edge, Right Side (Average) - 802.11b



Band Edge, Left Side (Peak) - 802.11g

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz



Band Edge, Right Side (Peak) - 802.11g

Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)

Band Edge, Left Side (Average) - 802.11g

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz

Band Edge, Right Side (Average) - 802.11g

Note: F1 is frequency 2483.5MHz



Band Edge, Left Side (Peak) - 802.11n20

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz



Band Edge, Right Side (Peak) - 802.11n20

Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)

Note: (no need if PK value less than the AV limit)

Band Edge, Left Side (Average) - 802.11n20

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz

Band Edge, Right Side (Average) - 802.11n20

Note: F1 is frequency 2483.5MHz



Band Edge, Left Side (Peak) - 802.11n40

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz



Band Edge, Right Side (Peak) - 802.11n40

Note: F1 is frequency 2483.5MHz



Band Edge, Left Side (Average) - 802.11n40

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz



Band Edge, Right Side (Average) - 802.11n40

Note: F1 is frequency 2483.5MHz

6.6 AC Power Line Conducted Emissions

Temperature	21℃
Relative Humidity	53%
Atmospheric Pressure	1011mbar
Test date :	April 05, 2017
Tested By :	Leen Yang

Requirement(s):

<table>
<tr><th>Spec</th><th>Item</th><th>Requirement</th><th>Applicable</th></tr>
<tr><td>47CFR§15.207, RSS210 (A8.1)</td><td>a)</td><td>For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.
<table>
<tr><th rowspan="2">Frequency ranges (MHz)</th><th colspan="2">Limit (dBμV)</th></tr>
<tr><th>QP</th><th>Average</th></tr>
<tr><td>0.15 ~ 0.5</td><td>66 – 56</td><td>56 – 46</td></tr>
<tr><td>0.5 ~ 5</td><td>56</td><td>46</td></tr>
<tr><td>5 ~ 30</td><td>60</td><td>50</td></tr>
</table></td><td>☑</td></tr>
<tr><td>Test Setup</td><td colspan="3"> 

Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</td></tr>
<tr><td>Procedure</td><td colspan="3">1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table.
2. The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains.
3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss</td></tr>
</table>

	coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Test Mode:	Transmitting Mode



Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBµV)	Detector	Corrected (dB)	Result (dBµV)	Limit (dBµV)	Margin (dB)
1	L1	0.1773	33.36	QP	10.03	43.39	64.61	-21.22
2	L1	0.1773	17.42	AVG	10.03	27.45	54.61	-27.16
3	L1	0.2358	28.36	QP	10.03	38.39	62.24	-23.85
4	L1	0.2358	13.61	AVG	10.03	23.64	52.24	-28.60
5	L1	0.2982	24.61	QP	10.03	34.64	60.29	-25.65
6	L1	0.2982	9.99	AVG	10.03	20.02	50.29	-30.27
7	L1	0.5244	20.25	QP	10.03	30.28	56.00	-25.72
8	L1	0.5244	3.51	AVG	10.03	13.54	46.00	-32.46
9	L1	1.0041	15.22	QP	10.03	25.25	56.00	-30.75
10	L1	1.0041	2.55	AVG	10.03	12.58	46.00	-33.42
11	L1	2.8605	20.21	QP	10.05	30.26	56.00	-25.74
12	L1	2.8605	9.01	AVG	10.05	19.06	46.00	-26.94

Test Mode:	Transmitting Mode



Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBµV)	Detector	Corrected (dB)	Result (dBµV)	Limit (dBµV)	Margin (dB)
1	N	0.2366	31.34	QP	10.02	41.36	62.21	-20.85
2	N	0.2366	15.46	AVG	10.02	25.48	52.21	-26.73
3	N	0.2848	31.20	QP	10.02	41.22	60.67	-19.45
4	N	0.2848	10.13	AVG	10.02	20.15	50.67	-30.52
5	N	0.4659	22.14	QP	10.02	32.16	56.59	-24.43
6	N	0.4659	5.87	AVG	10.02	15.89	46.59	-30.70
7	N	0.5244	22.73	QP	10.02	32.75	56.00	-23.25
8	N	0.5244	7.96	AVG	10.02	17.98	46.00	-28.02
9	N	3.1989	15.02	QP	10.05	25.07	56.00	-30.93
10	N	3.1989	2.05	AVG	10.05	12.10	46.00	-33.90
11	N	23.1279	10.83	QP	10.31	21.14	60.00	-38.86
12	N	23.1279	7.55	AVG	10.31	17.86	50.00	-32.14

Test Mode:	Transmitting Mode



Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBµV)	Detector	Corrected (dB)	Result (dBµV)	Limit (dBµV)	Margin (dB)
1	L1	0.2280	41.12	QP	10.03	51.15	62.52	-11.37
2	L1	0.2280	29.55	AVG	10.03	39.58	52.52	-12.94
3	L1	0.2631	34.15	QP	10.03	44.18	61.33	-17.15
4	L1	0.2631	23.10	AVG	10.03	33.13	51.33	-18.20
5	L1	0.3567	33.69	QP	10.03	43.72	58.80	-15.08
6	L1	0.3567	25.98	AVG	10.03	36.01	48.80	-12.79
7	L1	1.2888	26.44	QP	10.03	36.47	56.00	-19.53
8	L1	1.2888	11.35	AVG	10.03	21.38	46.00	-24.62
9	L1	2.9034	18.98	QP	10.05	29.03	56.00	-26.97
10	L1	2.9034	7.26	AVG	10.05	17.31	46.00	-28.69
11	L1	23.1279	13.79	QP	10.36	24.15	60.00	-35.85
12	L1	23.1279	8.12	AVG	10.36	18.48	50.00	-31.52

Test Mode:	Transmitting Mode



Test Data

Phase Neutral Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBµV)	Detector	Corrected (dB)	Result (dBµV)	Limit (dBµV)	Margin (dB)
1	N	0.1734	32.37	QP	10.02	42.39	64.80	-22.41
2	N	0.1734	21.05	AVG	10.02	31.07	54.80	-23.73
3	N	0.2280	40.61	QP	10.02	50.63	62.52	-11.89
4	N	0.2280	27.81	AVG	10.02	37.83	52.52	-14.69
5	N	0.3567	30.45	QP	10.02	40.47	58.80	-18.33
6	N	0.3567	23.28	AVG	10.02	33.30	48.80	-15.50
7	N	0.4035	21.61	QP	10.02	31.63	57.78	-26.15
8	N	0.4035	14.35	AVG	10.02	24.37	47.78	-23.41
9	N	1.3005	20.98	QP	10.03	31.01	56.00	-24.99
10	N	1.3005	8.50	AVG	10.03	18.53	46.00	-27.47
11	N	2.8098	23.90	QP	10.05	33.95	56.00	-22.05
12	N	2.8098	14.60	AVG	10.05	24.65	46.00	-21.35

6.7 Radiated Spurious Emissions & Restricted Band

Temperature	21℃
Relative Humidity	53%
Atmospheric Pressure	1011mbar
Test date :	April 05, 2017
Tested By :	Leen Yang

Requirement(s):

<table>
<tr><th>Spec</th><th>Item</th><th>Requirement</th><th>Applicable</th></tr>
<tr><td rowspan="3">47CFR§15.247(d), RSS210 (A8.5)</td><td>a)</td><td>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges
<table>
<tr><th>Frequency range (MHz)</th><th>Field Strength (μV/m)</th></tr>
<tr><td>30 – 88</td><td>100</td></tr>
<tr><td>88 – 216</td><td>150</td></tr>
<tr><td>216 960</td><td>200</td></tr>
<tr><td>Above 960</td><td>500</td></tr>
</table></td><td>☑</td></tr>
<tr><td>b)</td><td>For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required
☒ 20 dB down ☐ 30 dB down</td><td>☑</td></tr>
<tr><td>c)</td><td>or restricted band, emission must also comply with the radiated emission limits specified in 15.209</td><td>☑</td></tr>
</table>

Test Setup	
Procedure	1. The EUT was switched on and allowed to warm up to its normal operating condition. 2. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen. b. The EUT was then rotated to the direction that gave the maximum emission. c. Finally, the antenna height was adjusted to the height that gave the maximum emission. 3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. 4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. 5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
Remark	Different RF configuration has been evaluated but not much difference was found. The data presented here is the worst case data with EUT under 802.11n – HT20-2437MHz mode.
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Test Mode:	Transmitting Mode

(Below 1GHz)



Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	H	49.0145	37.32	peak	8.83	22.36	0.79	24.58	40.00	-15.42	100	66
2	H	75.1823	32.20	peak	7.70	22.40	0.96	18.46	40.00	-21.54	200	339
3	H	99.8777	29.60	peak	10.37	22.32	1.12	18.77	43.50	-24.73	100	278
4	H	213.0151	29.51	peak	11.92	22.36	1.58	20.65	43.50	-22.85	100	16
5	H	317.7011	37.97	peak	13.97	22.24	1.88	31.58	46.00	-14.42	100	296
6	H	863.0562	28.23	peak	22.09	20.98	2.92	32.26	46.00	-13.74	100	174

(Below 1GHz)



Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	V	49.0145	35.37	peak	8.83	22.36	0.79	22.63	40.00	-17.37	100	0
2	V	74.9191	32.33	peak	7.70	22.40	0.96	18.59	40.00	-21.41	100	357
3	V	81.2117	32.55	peak	7.65	22.41	1.05	18.84	40.00	-21.16	100	45
4	V	121.1231	27.84	peak	13.83	22.36	1.16	20.47	43.50	-23.03	100	182
5	V	305.6800	32.63	peak	13.72	22.27	1.82	25.90	46.00	-20.10	100	349
6	V	790.6188	29.21	peak	21.29	21.17	2.94	32.27	46.00	-13.73	100	202

Above 1GHz

Test Mode:	Transmitting Mode

Low Channel (2412 MHz) (n40 mode worst case)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4824	38.73	AV	V	33.8	6.86	32.69	46.7	54	-7.30
4824	38.25	AV	H	33.8	6.86	32.69	46.22	54	-7.78
4824	47.94	PK	V	33.8	6.86	32.69	55.91	74	-18.09
4824	47.05	PK	H	33.8	6.86	32.69	55.02	74	-18.98
17901	23.82	AV	V	45.12	11.57	32.11	48.4	54	-5.60
17901	22.22	AV	H	45.12	11.57	32.11	46.8	54	-7.20
17901	39.98	PK	V	45.12	11.57	32.11	64.56	74	-9.44
17901	39.18	PK	H	45.12	11.57	32.11	63.76	74	-10.24

Middle Channel (2437 MHz) (b mode worst case)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4874	38.7	AV	V	33.6	6.82	32.71	46.41	54	-7.59
4874	39.52	AV	H	33.6	6.82	32.71	47.23	54	-6.77
4874	48.42	PK	V	33.6	6.82	32.71	56.13	74	-17.87
4874	48.29	PK	H	33.6	6.82	32.71	56	74	-18.00
17928	23.52	AV	V	45.17	11.63	32.18	48.14	54	-5.86
17928	22.52	AV	H	45.17	11.63	32.18	47.14	54	-6.86
17928	39.31	PK	V	45.17	11.63	32.18	63.93	74	-10.07
17928	39.57	PK	H	45.17	11.63	32.18	64.19	74	-9.81

High Channel (2462 MHz) (n20 mode worst case)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4924	40.09	AV	V	33.83	6.95	32.79	48.08	54	-5.92
4924	39.08	AV	H	33.83	6.95	32.79	47.07	54	-6.93
4924	46.53	PK	V	33.83	6.95	32.79	54.52	74	-19.48
4924	48.04	PK	H	33.83	6.95	32.79	56.03	74	-17.97
17924	23.54	AV	V	45.19	11.61	32.24	48.1	54	-5.90
17924	23.27	AV	H	45.19	11.61	32.24	47.83	54	-6.17
17924	40.26	PK	V	45.19	11.61	32.24	64.82	74	-9.18
17924	39.17	PK	H	45.19	11.61	32.24	63.73	74	-10.27

Note:

*1, The testing has been conformed to 10*2462MHz=24,620MHz*

2, All other emissions more than 30 dB below the limit

3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/16/2016	09/15/2017	☑
Line Impedance	LI-125A	191106	09/24/2016	09/23/2017	☑
Line Impedance	LI-125A	191107	09/24/2016	09/23/2017	☑
LISN	ISN T800	34373	09/24/2016	09/23/2017	☑
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	☑
Transient Limiter	LIT-153	531118	08/31/2016	08/30/2017	☑
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/16/2016	09/15/2017	☑
Power Splitter	1#	1#	08/31/2016	08/30/2017	☑
DC Power Supply	E3640A	MY40004013	09/16/2016	09/15/2017	☑
Radiated Emissions					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	☑
Positioning Controller	UC3000	MF780208282	11/18/2016	11/17/2017	☑
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	☑
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/23/2017	03/22/2018	☑
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	☑
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	☑
Universal Radio Communication Tester	CMU200	121393	09/24/2016	09/23/2017	☑

Annex B. EUT and Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Whole Package View

Adapter - Lable View

EUT - Front View

EUT - Rear View

EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View

Annex B.ii. Photograph: EUT Internal Photo

Cover Off - Top View 1

Cover Off - Top View 2



Battery - Front View



Battery - Rear View(Label)

Mainboard with Shielding - Front View



Mainboard without Shielding - Front View



Mainboard with Shielding – Rear View



Mainboard without Shielding – Rear View



LCD – Front View

LCD – Rear View

GSM/PCS/UMTS-FDD Antenna View



WIFI/BT/BLE/GPS - Antenna View



Annex B.iii. Photograph: Test Setup Photo

	
Conducted Emissions Test Setup Front View	Conducted Emissions Test Setup Side View
	
Radiated Spurious Emissions Test Setup Below 1GHz	Radiated Spurious Emissions Test Setup Above 1GHz

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions （Below 1GHz）.



Block Configuration Diagram for Radiated Emissions （Above 1GHz）.



Annex C. il. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Verykool USA Inc	Adapter	s4009	X20170305

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	X20170305

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Annex E. DECLARATION OF SIMILARITY

N/A