

RF TEST REPORT



Report No.: 15070313-FCC-R1

Supersede Report No.: N/A

Applicant	Verykool USA Inc	
Product Name	Mobile Phone	
Model No.	s5518	
Serial No.	N/A	
Test Standard	FCC Part 22(H), FCC Part 24(E), FCC Part 27: 2014; ANSI/TIAC603 D: 2013	
Test Date	April 30to May 19, 2015	
Issue Date	May 20, 2015	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification	☒	
Equipment did not comply with the specification	☐	
<i>Winnie Zhang</i>	<i>Chris You</i>	
Winnie Zhang Test Engineer	Chris You Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	15070313-FCC-R1
Page	3 of 60

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	9
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	10
6.1 RF EXPOSURE (SAR)	10
6.2 RF OUTPUT POWER	11
6.3 PEAK-AVERAGE RATIO	19
6.4 MODULATION CHARACTERISTIC	21
6.5 OCCUPIED BANDWIDTH	22
6.6 SPURIOUS EMISSIONS AT ANTENNA TERMINALS	27
6.7 SPURIOUS RADIATED EMISSIONS	33
6.8 BAND EDGE	39
6.9 FREQUENCY STABILITY	44
ANNEX A. TEST INSTRUMENT.....	49
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	50
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	56
ANNEX C.II. EUT OPERATING CONKITIONS.....	58
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST.....	59
ANNEX E. DECLARATION OF SIMILARITY.....	60

1. Report Revision History

Report No.	Report Version	Description	Issue Date
15070313-FCC-R1	NONE	Original	May 20, 2015

2. Customer information

Applicant Name	Verykool USA Inc
Applicant Add	3636 Nobel Drive, Suite 325, San Diego, CA 92122 USA
Manufacturer	Zechin Communications Co.,Ltd.
Manufacturer Add	Unit804,8th Floor Desay Tech Building Gaoxin, Road South, Nanshan District Shenzhen,China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT: Mobile Phone

Main Model: s5518

Serial Model: N/A

Date EUT received: April 29 2015

Test Date(s): April 30to May 19, 2015

Equipment Category : PCE

Antenna Gain:

GSM850: 1.6dBi
PCS1900: 3.8dBi
UMTS-FDD Band V:1.7 dBi
UMTS-FDD Band IV:3.7 dBi
UMTS-FDD Band II: 1.75 dBi
Bluetooth/BLE: 3 dBi
WIFI: 2.9 dBi
GPS: 1.6 dBi

Type of Modulation:

GSM / GPRS: GMSK
EGPRS: GMSK, 8PSK
UMTS-FDD: QPSK, 16QAM
802.11b/g/n: DSSS, OFDM
Bluetooth: GFSK, π /4DQPSK, 8DPSK
BLE: GFSK

RF Operating Frequency (ies):

PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz
UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz
UMTS-FDD Band IV TX:1712.4 ~ 1752.6 MHz;
RX : 2112.4 ~ 2152.6 MHz
UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz;
RX: 1932.4 ~ 1987.6 MHz
WIFI:802.11b/g/n(20M): 2412-2462 MHz
WIFI:802.11n(40M): 2422-2452 MHz
Bluetooth& BLE: 2402-2480 MHz

Maximum Conducted AV Power to Antenna:	GSM850: 33.8dBm PCS1900: 30.43dBm UMTS-FDD Band V : 23.59 dBm UMTS-FDD Band II : 21.88 dBm UMTS-FDD Band IV : 22.15 dBm
ERP/EIRP:	GSM850: 25.49 dBm / ERP PCS1900: 23.98 dBm / EIRP UMTS-FDD Band V : 19.71 dBm / ERP UMTS-FDD Band II : 19.85 dBm / EIRP UMTS-FDD Band IV: 19.54 dBm / EIRP
Number of Channels:	GSM 850: 124CH PCS1900: 299CH UMTS-FDD Band V : 102CH UMTS-FDD Band IV: 202CH UMTS-FDD Band II : 277CH WIFI :802.11b/g/n(20M): 11CH WIFI :802.11n(40M): 7CH Bluetooth: 79CH BLE: 40CH
Port:	Power Port, Earphone Port, USB Port
Input Power:	Battery: Model: 345197P Spec: 3.8V 2600mAh 9.88Wh Limited charger voltage:4.35V Adapter: Model: S0500100-US Input: AC 100-240V; 50/60Hz 0.4A Max Output: DC 5.0V; 1A
Trade Name :	verykool
GPRS/EGPRS Multi-slot class	8/10/12

Test Report	15070313-FCC-R1
Page	8 of 60

FCC ID:

WA6S5518

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§ 1.1307; § 2.1093	RF Exposure (SAR)	Compliance
§2.1046; § 22.913(a); § 24.232(c); § 27.50(c.10) ; § 27.50(d.4)	RF Output Power	Compliance
§ 24.232 (d) ; § 27.50(d)	Peak-Average Ratio	Compliance
§ 2.1047	Modulation Characteristics	Compliance
§ 2.1049; § 22.905; § 22.917; § 24.238; § 27.53(a.5)	99% & -26 dB Occupied Bandwidth	Compliance
§ 2.1051; § 22.917(a); § 24.238(a); § 27.53(h)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917(a); § 24.238(a); § 27.53(h)	Field Strength of Spurious Radiation	Compliance
§ 22.917(a); § 24.238(a); § 27.53(h)	Out of band emission, Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235; § 27.5(h); § 27.54	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: Testing was performed by configuring EUT to maximum output power status, the declared output power class for different

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

6.1 RF Exposure (SAR)

Test Result: Pass


The EUT is a portable device, thus requires SAR evaluation;
Please refer to RF Exposure Evaluation Report: 15070313-FCC-H.

6.2 RF Output Power

Temperature	24°C
Relative Humidity	54%
Atmospheric Pressure	1005mbar
Test date :	May 05, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§22.913 (a)	a)	ERP:38.45dBm	☒
§24.232 (c)	b)	EIRP:33dBm	☒
§27.50 (c)	c)	EIRP: 30dBm	☒

Test Setup	 Base Station EUT
------------	--

Test Procedure	For Conducted Power: - The transmitter output port was connected to base station. - Set EUT at maximum power through base station. - Select lowest, middle, and highest channels for each band and different test mode. For ERP/EIRP: - The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. - The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. - The frequency range up to tenth harmonic of the fundamental frequency was investigated. - Remove the EUT and replace it with substitution antenna. A signal
----------------	--

Test Report	15070313-FCC-R1
Page	12 of 60

	generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. - Spurious emissions in dB = 10 log (TX power in Watts/0.001) – the absolute level - Spurious attenuation limit in dB = 43 + 10 Log10 (power out in Watts).
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

Conducted Power

GSM Mode:

Burst Average Power (dBm);								
Band	GSM850				PCS1900			
Channel	128	190	251	Tune up Power tolerant	512	661	810	Tune up Power tolerant
Frequency (MHz)	824.2	836.6	848.8	/	1850.2	1880	1909.8	/
GSM Voice (1 uplink),GMSK	33.72	33.75	33.8	33±1	29.87	30.07	30.43	30±1
GPRS Multi-Slot Class 8 (1 uplink),GMSK	33.69	33.74	33.76	33±1	29.81	30.04	30.42	30±1
GPRS Multi-Slot Class 10 (2 uplink) GMSK	33.00	33.17	33.21	30±1	29.47	29.7	29.93	29±1
GPRS Multi-Slot Class 12 (4 uplink) GMSK (4 uplink),GMSK	30.61	30.77	30.85	30±1	26.64	26.51	26.48	26±1
EGPRS Multi-Slot Class 8 (1 uplink) GMSK MCS1	33.68	33.73	33.74	33±1	29.8	30.03	30.41	30±1
EGPRS Multi-Slot Class 10 (2 uplink) GMSK MCS1	33.11	33.16	33.2	33±1	29.46	29.69	29.92	29±1
EGPRS Multi-Slot Class 12 (4 uplink) GMSK MCS1	30.57	30.64	30.73	30±1	26.21	26.32	26.27	26±1

Remark :

GPRS, CS1 coding scheme.

EGPRS, MCS1 coding scheme.

EGPRS, MCS5 coding scheme.

Multi-Slot Class 8 , Support Max 4 downlink, 1 uplink , 5 working link

Multi-Slot Class 10 , Support Max 4 downlink, 2 uplink , 5 working link

Multi-Slot Class 12 , Support Max 4 downlink, 4 uplink , 5 working link

Note: Since GSM mode has higher power, so the test items below were not performed to GPRS and EGPRS mode.

UMTS Mode:

UMTS-FDD Band V

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)
RMC 12.2kbps	4132	826.4	23.36
	4175	835	23.59
	4233	846.6	23.49
HSDPA Subtest1	4132	826.4	23.32
	4175	835	23.56
	4233	846.6	23.47
HSDPA Subtest2	4132	826.4	23.38
	4175	835	23.58
	4233	846.6	23.41
HSDPA Subtest3	4132	826.4	23.37
	4175	835	23.54
	4233	846.6	23.43
HSDPA Subtest4	4132	826.4	23.36
	4175	835	23.52
	4233	846.6	23.43
HSUPA Subtest1	4132	826.4	23.34
	4175	835	23.42
	4233	846.6	23.49
HSUPA Subtest2	4132	826.4	23.31
	4175	835	23.51
	4233	846.6	23.47
HSUPA Subtest3	4132	826.4	23.38
	4175	835	23.51
	4233	846.6	23.46
HSUPA Subtest4	4132	826.4	23.34
	4175	835	23.58
	4233	846.6	23.43
HSUPA Subtest5	4132	826.4	23.34
	4175	835	23.56
	4233	846.6	23.42

UMTS-FDD Band II

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)
RMC 12.2kbps	9262	1852.4	21.5
	9400	1880	21.48
	9538	1907.6	21.88
HSDPA Subtest1	9262	1852.4	21.46
	9400	1880	21.47
	9538	1907.6	21.87
HSDPA Subtest2	9262	1852.4	21.19
	9400	1880	21.44
	9538	1907.6	21.86
HSDPA Subtest3	9262	1852.4	21.44
	9400	1880	21.47
	9538	1907.6	21.82
HSDPA Subtest4	9262	1852.4	21.44
	9400	1880	21.42
	9538	1907.6	21.81
HSUPA Subtest1	9262	1852.4	21.43
	9400	1880	21.41
	9538	1907.6	21.79
HSUPA Subtest2	9262	1852.4	21.46
	9400	1880	21.43
	9538	1907.6	21.87
HSUPA Subtest3	9262	1852.4	21.43
	9400	1880	21.47
	9538	1907.6	21.79
HSUPA Subtest4	9262	1852.4	21.43
	9400	1880	21.46
	9538	1907.6	21.78
HSUPA Subtest5	9262	1852.4	21.43
	9400	1880	21.47
	9538	1907.6	21.77

UMTS-FDD Band IV

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)
RMC 12.2kbps	1313	1712.6	22.14
	1413	1732.6	22.15
	1512	1752.4	22.02
HSDPA Subtest1	1313	1712.6	22.14
	1413	1732.6	22.14
	1512	1752.4	22.03
HSDPA Subtest2	1313	1712.6	22.14
	1413	1732.6	22.15
	1512	1752.4	22.07
HSDPA Subtest3	1313	1712.6	22.14
	1413	1732.6	22.15
	1512	1752.4	22.05
HSDPA Subtest4	1313	1712.6	22.14
	1413	1732.6	22.14
	1512	1752.4	22.04
HSUPA Subtest1	1313	1712.6	22.15
	1413	1732.6	22.13
	1512	1752.4	22.04
HSUPA Subtest2	1313	1712.6	22.09
	1413	1732.6	22.13
	1512	1752.4	22.07
HSUPA Subtest3	1313	1712.6	22.13
	1413	1732.6	22.14
	1512	1752.4	22.05
HSUPA Subtest4	1313	1712.6	22.14
	1413	1732.6	22.16
	1512	1752.4	22.03
HSUPA Subtest5	1313	1712.6	22.13
	1413	1732.6	22.14
	1512	1752.4	22.04

ERP & EIRP

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	19.16	V	6.8	0.53	25.43	38.45
824.2	17.45	H	6.8	0.53	23.72	38.45
836.6	19.22	V	6.8	0.53	25.49	38.45
836.6	17.33	H	6.8	0.53	23.60	38.45
848.8	18.96	V	6.9	0.53	25.33	38.45
848.8	17.42	H	6.9	0.53	23.79	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	16.95	V	7.88	0.85	23.98	33
1850.2	14.82	H	7.88	0.85	21.85	33
1880	16.77	V	7.88	0.85	23.80	33
1880	14.53	H	7.88	0.85	21.56	33
1909.8	16.92	V	7.86	0.85	23.93	33
1909.8	14.39	H	7.86	0.85	21.40	33

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	13.44	V	6.8	0.53	19.71	38.45
826.4	12.26	H	6.8	0.53	18.53	38.45
835	12.97	V	6.8	0.53	19.24	38.45
835	12.55	H	6.8	0.53	18.82	38.45
846.6	13.13	V	6.9	0.53	19.50	38.45
846.6	12.69	H	6.9	0.53	19.06	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	12.82	V	7.88	0.85	19.85	33
1852.4	11.35	H	7.88	0.85	18.38	33
1880	12.59	V	7.88	0.85	19.62	33
1880	11.48	H	7.88	0.85	18.51	33
1907.6	12.67	V	7.86	0.85	19.68	33
1907.6	11.51	H	7.86	0.85	18.52	33


EIRP for UMTS-FDD Band IV (Part 27E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	12.39	V	7.76	0.82	19.33	30
1712.4	11.92	H	7.76	0.82	18.86	30
1740	12.55	V	7.76	0.82	19.49	30
1740	12.02	H	7.76	0.82	18.96	30
1752.6	12.62	V	7.74	0.82	19.54	30
1752.6	11.68	H	7.74	0.82	18.60	30

6.3 Peak-Average Ratio

Temperature	21°C
Relative Humidity	58%
Atmospheric Pressure	1010mbar
Test date :	April 09, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§24.232(d) § 27.50(d)	a)	The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.	☒
Test Setup	 Base Station Spectrum Analyzer EUT		
Test Procedure	According with KDB 971168 1. The signal analyzer' s CCDF measurement profile is enabled 2. Frequency = carrier center frequency 3. Measurement BW > Emission bandwidth of signal 4. The signal analyzer was set to collect one million samples to generate the CCDF curve 5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal “ RF Burst” trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the “ on time” of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

GSM 1900 PK-AV POWER(PART 22H)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	30.42	29.87	0.55
1880	30.29	30.07	0.22
1909.8	30.76	30.43	0.33

UMTS-FDD Band II PK-AV POWER(PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	24.29	21.5	2.79
1880	24.45	21.48	2.97
1907.6	24.78	21.88	2.90

UMTS-FDD Band IV PK-AV POWER (PART 27)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.6	25.41	22.14	3.27
1732.6	25.46	22.15	3.31
1752.4	25.11	22.02	3.09

6.4 Modulation Characteristic

According to FCC § 2.1047(d), Part 22H, 24E& Part 27 there is no specific requirement for digital modulation, therefore modulation characteristic is not presented

6.5 Occupied Bandwidth

Temperature	23°C
Relative Humidity	53%
Atmospheric Pressure	1004mbar
Test date :	May 04, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1049, §22.917, §22.905 §24.238 §27.53(a)	a)	99% Occupied Bandwidth(kHz)	☒
	b)	26 dB Bandwidth(kHz)	☒
Test Setup	Base Station Spectrum Analyzer EUT		
Test Procedure	- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	243.9392	314.431
190	836.6	247.5429	319.263
251	848.8	242.4378	315.110

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	248.4894	316.895
661	1880.0	251.2242	315.034
810	1909.8	245.3272	317.952

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.1373	4.679
4175	835.0	4.1643	4.703
4233	846.6	4.1792	4.685


UMTS-FDD Band IV (Part 27)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1712.6	4.1825	4.713
9400	1733.0	4.1622	4.697
9538	1752.4	4.1664	4.705

UMTS-FDD Band II (Part 24E)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1736	4.702
9400	1880.0	4.1725	4.726
9538	1907.6	4.1419	4.716

Test Plots







Band V BW - Low CH 826.6 MHz




Band V BW - Mid CH 835.0 MHz




Band V BW - High CH 846.4 MHz



Band IV BW - Low CH 1852.4 MHz





Band IV BW - Mid CH 1880 MHz




Band IV BW - High CH 1907.6 MHz

Test Report	15070313-FCC-R1
Page	26 of 60



Band II BW - Low CH 1852.4MHz

Band II BW - Mid CH 1880MHz




Band II BW - High CH 1907.6MHz

6.6 Spurious Emissions at Antenna Terminals

Temperature	23°C
Relative Humidity	53%
Atmospheric Pressure	1004mbar
Test date :	May 04, 2015
Tested By :	Winnie Zhang

Requirement(s):


Spec	Item	Requirement	Applicable
§2.1051, §22.917(a)& §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB	☒
Test Setup	 Base Station Spectrum Analyzer EUT		
Test Procedure	- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. - Setting RBW as roughly BW/100.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Test Plots


Cellular Band (Part 22H) result




PCS Band (Part24E) result




UMTS-FDD Band V (Part 22H)




UMTS-FDD Band IV (Part 27)




Band IV - Low Channel-1




Band IV - Low Channel-2




Band IV - Middle Channel-1



Band IV - Middle Channel-2




Band IV - High Channel-1



Band IV - High Channel-2


UMTS-FDD Band II (Part 24E)



6.7 Spurious Radiated Emissions

Temperature	21°C
Relative Humidity	53%
Atmospheric Pressure	1007mbar
Test date :	May 07, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1053, §22.917 & §24.238 § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.	☒
Test setup			
Test Procedure	- The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. - The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. - Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. Sample Calculation: EUT Field Strength = Raw Amplitude (dBμV/m) – Amplifier Gain (dB) + Antenna Factor (dB) + Cable Loss (dB) + Filter Attenuation (dB, if used)		
Remark			

Result	☒ Pass	☐ Fail
--------	--	-------------------------------

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

Cellular Band (Part 22H) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1648.4	-45.89	V	7.95	0.78	-38.72	-13	-25.72
1648.4	-45.77	H	7.95	0.78	-38.6	-13	-25.6
422.9	-56.84	V	6.5	0.30	-50.64	-13	-37.64
805.2	-51.38	H	6.9	0.44	-44.92	-13	-31.92

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1673.2	-43.68	V	7.95	0.78	-36.51	-13	-23.51
1673.2	-44.82	H	7.95	0.78	-37.65	-13	-24.65
423.1	-57.16	V	6.50	0.30	-50.96	-13	-37.96
804.5	-52.31	H	6.90	0.44	-45.85	-13	-32.85

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1697.6	-44.91	V	7.95	0.78	-37.74	-13	-24.74
1697.6	-45.76	H	7.95	0.78	-38.59	-13	-25.59
421.5	-56.96	V	6.50	0.30	-50.76	-13	-37.76
806.1	-51.75	H	6.90	0.44	-45.29	-13	-32.29

PCS Band (Part24E) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3700.4	-46.87	V	10.25	2.73	-39.35	-13	-26.35
3700.4	-47.82	H	10.25	2.73	-40.30	-13	-27.30
424.3	-56.99	V	6.50	0.30	-50.79	-13	-37.79
806.5	-51.46	H	6.90	0.44	-45.00	-13	-32.00

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-47.13	V	10.25	2.73	-39.61	-13	-26.61
3760	-46.82	H	10.25	2.73	-39.30	-13	-26.3
421.5	-57.05	V	6.50	0.30	-50.85	-13	-37.85
804.7	-50.84	H	6.90	0.44	-44.38	-13	-31.38

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3819.6	-46.93	V	10.36	2.73	-39.30	-13	-26.3
3819.6	-47.24	H	10.36	2.73	-39.61	-13	-26.61
423.6	-56.84	V	6.50	0.30	-50.64	-13	-37.64
804.8	-50.68	H	6.90	0.44	-44.22	-13	-31.22

UMTS-FDD Band V (Part 22H)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1652.8	-48.92	V	7.95	0.78	-41.75	-13	-28.75
1652.8	-47.38	H	7.95	0.78	-40.21	-13	-27.21
423.3	-57.44	V	6.50	0.30	-51.24	-13	-38.24
806.4	-50.62	H	6.90	0.44	-44.16	-13	-31.16

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1670	-49.01	V	7.95	0.78	-41.84	-13	-28.84
1670	-47.44	H	7.95	0.78	-40.27	-13	-27.27
421.7	-56.92	V	6.5	0.30	-50.72	-13	-37.72
804.9	-51.34	H	6.9	0.44	-44.88	-13	-31.88

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1693.2	-48.59	V	7.95	0.78	-41.42	-13	-28.42
1693.2	-47.84	H	7.95	0.78	-40.67	-13	-27.67
423.5	-57.42	V	6.50	0.30	-51.22	-13	-38.22
806.1	-50.66	H	6.90	0.44	-44.2	-13	-31.20

UMTS-FDD Band II (Part 24E)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3704.8	-48.39	V	10.25	2.73	-40.87	-13	-27.87
3704.8	-47.56	H	10.25	2.73	-40.04	-13	-27.04
423.4	-57.61	V	6.50	0.30	-51.41	-13	-38.41
804.4	-51.22	H	6.90	0.44	-44.76	-13	-31.76

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-48.56	V	10.25	2.73	-41.04	-13	-28.04
3760	-46.68	H	10.25	2.73	-39.16	-13	-26.16
425.1	-58.11	V	6.50	0.30	-51.91	-13	-38.91
806.2	-50.57	H	6.90	0.44	-44.11	-13	-31.11

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3815.2	-46.64	V	10.36	2.73	-39.01	-13	-26.01
3815.2	-48.77	H	10.36	2.73	-41.14	-13	-28.14
424.9	-56.84	V	6.50	0.30	-50.64	-13	-37.64
804.6	-51.26	H	6.90	0.44	-44.80	-13	-31.8

UMTS-FDD Band IV (Part 27E)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3424.8	-46.26	V	10.07	2.52	-38.71	-13	-25.71
3424.8	-47.92	H	10.07	2.52	-40.37	-13	-27.37
266.3	-56.82	V	5.5	0.24	-51.56	-13	-38.56
654.2	-51.44	H	6.8	0.39	-45.03	-13	-32.03

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3480	-44.29	V	10.09	2.52	-36.72	-13	-23.72
3480	-48.63	H	10.09	2.52	-41.06	-13	-28.06
267.1	-57.13	V	5.5	0.24	-51.87	-13	-38.87
653.7	-50.49	H	6.8	0.39	-44.08	-13	-31.08


High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3505.2	-45.98	V	10.09	2.52	-38.41	-13	-25.41
3505.2	-47.47	H	10.09	2.52	-39.9	-13	-26.9
266.8	-57.34	V	5.5	0.24	-52.08	-13	-39.08
654.5	-51.66	H	6.8	0.39	-45.25	-13	-32.25

6.8 Band Edge

Temperature	23°C
Relative Humidity	53%
Atmospheric Pressure	1004mbar
Test date :	May 04, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§22.917(a) §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.	☒
Test setup	 Base Station Spectrum Analyzer EUT		
Procedure	- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9650	-13.51	-13
849.0200	-13.20	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9950	-15.61	-13
1910.0175	-14.18	-13

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9000	-22.83	-13
849.0500	-25.07	-13


UMTS-FDD Band IV (Part 27)


Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.9250	-27.21	-13
1755.0500	-28.38	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9000	-27.67	-13
1910.2250	-25.928	-13


Test Plots






UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(46.79/30)=4.0+1.9=5.9 dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(46.85/30)=4.0+1.9=5.9 dB



UMTS-FDD Band IV- Low Channel


Note: Offset=Cable loss (4.5) + 10log
(47.13/30)=4.5+2.0=6.5 dB



UMTS-FDD Band IV-- High Channel

Note: Offset=Cable loss (4.5) + 10log
(47.05/30)=4.5+2.0=6.5 dB


Test Report	15070313-FCC-R1
Page	43 of 60



6.9 Frequency Stability

Temperature	24°C
Relative Humidity	54%
Atmospheric Pressure	1005mbar
Test date :	May 05, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable																																
§2.1055, §22.355 & §24.235 § 27.5(h); § 27.54	a)	According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below: Frequency Tolerance for Transmitters in the Public Mobile Services <table border="1"> <thead> <tr> <th>Frequency Range (MHz)</th><th>Base, fixed (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th></tr> </thead> <tbody> <tr> <td>25 to 50</td><td>20.0</td><td>20.0</td><td>50.0</td></tr> <tr> <td>50 to 450</td><td>5.0</td><td>5.0</td><td>50.0</td></tr> <tr> <td>450 to 512</td><td>2.5</td><td>5.0</td><td>5.0</td></tr> <tr> <td>821 to 896</td><td>1.5</td><td>2.5</td><td>2.5</td></tr> <tr> <td>928 to 29.</td><td>5.0</td><td>N/A</td><td>N/A</td></tr> <tr> <td>929 to 960.</td><td>1.5</td><td>N/A</td><td>N/A</td></tr> <tr> <td>2110 to 2220</td><td>10.0</td><td>N/A</td><td>N/A</td></tr> </tbody> </table> According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized frequency block.	Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)	25 to 50	20.0	20.0	50.0	50 to 450	5.0	5.0	50.0	450 to 512	2.5	5.0	5.0	821 to 896	1.5	2.5	2.5	928 to 29.	5.0	N/A	N/A	929 to 960.	1.5	N/A	N/A	2110 to 2220	10.0	N/A	N/A	☒
Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)																																
25 to 50	20.0	20.0	50.0																																
50 to 450	5.0	5.0	50.0																																
450 to 512	2.5	5.0	5.0																																
821 to 896	1.5	2.5	2.5																																
928 to 29.	5.0	N/A	N/A																																
929 to 960.	1.5	N/A	N/A																																
2110 to 2220	10.0	N/A	N/A																																
Test setup	 The diagram illustrates the test setup. On the left, a green rectangular box represents the 'Base Station'. A horizontal line connects it to a blue rectangular box labeled 'EUT' (Equipment Under Test). The 'EUT' is enclosed within a dashed-line rectangular box labeled 'Thermal Chamber'.																																		

Test Report	15070313-FCC-R1
Page	45 of 60

Procedure	A communication link was established between EUT and base station. The frequency error was monitored and measured by base station under variation of ambient temperature and variation of primary supply voltage. Limit: The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

Cellular Band (Part 22H) result

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	22	0.0263	2.5
0		17	0.0203	2.5
10		15	0.0179	2.5
20		6	0.0072	2.5
30		12	0.0143	2.5
40		19	0.0227	2.5
50		24	0.0287	2.5
55		30	0.0359	2.5
25	4.2	20	0.0239	2.5
	3.5	23	0.0275	2.5

PCS Band (Part 24E) result

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	37	0.0197	2.5
0		36	0.0191	2.5
10		34	0.0181	2.5
20		29	0.0154	2.5
30		31	0.0165	2.5
40		33	0.0176	2.5
50		34	0.0181	2.5
55		36	0.0191	2.5
25	4.2	32	0.0170	2.5
	3.5	37	0.0197	2.5

UMTS-FDD Band V (Part 22H)

Middle Channel, $f_0 = 835$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	18	0.0216	2.5
0		16	0.0192	2.5
10		12	0.0144	2.5
20		9	0.0108	2.5
30		13	0.0156	2.5
40		16	0.0192	2.5
50		20	0.0240	2.5
55		21	0.0251	2.5
25	4.2	19	0.0228	2.5
	3.5	15	0.0180	2.5

UMTS-FDD Band II (Part 24E)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	15	0.0080	2.5
0		13	0.0069	2.5
10		6	0.0032	2.5
20		5	0.0027	2.5
30		8	0.0043	2.5
40		11	0.0059	2.5
50		14	0.0074	2.5
55		19	0.0101	2.5
25	4.2	8	0.0043	2.5
	3.5	11	0.0059	2.5

UMTS-FDD Band IV (Part 27)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	13	0.0069	2.5
0		9	0.0048	2.5
10		5	0.0027	2.5
20		6	0.0032	2.5
30		8	0.0043	2.5
40		11	0.0059	2.5
50		13	0.0069	2.5
55		14	0.0074	2.5
25	4.2	12	0.0064	2.5
	3.5	15	0.0080	2.5

Annex A. TEST INSTRUMENT


Instrument	Model	Serial #	Cal Date	Cal Due	In use
RF Conducted Test					
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	09/17/2014	09/16/2015	☒
Power Splitter	1#	1#	09/02/2014	09/01/2015	☒
Universal Radio Communication Tester	CMU200	121393	09/26/2014	09/25/2015	☒
Temperature/Humidity Chamber	UHL-270	001	10/10/2014	10/09/2015	☒
DC Power Supply	E3640A	MY40004013	09/18/2014	09/17/2015	☒
Radiated Emissions					
EMI test receiver	ESL6	100262	09/18/2014	09/17/2015	☒
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/02/2014	09/01/2015	☒
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	10/04/2015	10/04/2016	☒
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/22/2014	09/21/2015	☒
Bilog Antenna (30MHz~2GHz)	JB1	A112017	09/22/2014	09/21/2015	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71259	09/25/2014	09/24/2015	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/25/2014	09/24/2015	☒
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	09/18/2014	09/17/2015	☒
Tunable Notch Filter	3NF-800/1000-S	AA4	09/02/2014	09/01/2015	☒
Tunable Notch Filter	3NF-1000/2000-S	AM 4	09/02/2014	09/01/2015	☒

Annex B. EUT And Test Setup Photographs


Annex B.i. Photograph: EUT External Photo



Whole Package - Top View



Adapter - Front View



EUT - Front View



EUT - Rear View



EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View


Annex B.ii. Photograph: EUT Internal Photo




Cover Off - Top View 1




Cover Off - Top View 2




Battery - Top View




Battery - Bottom View



Mainboard With Shielding - Front View



Mainboard Without Shielding - Front View




Mainboard - Rear View




LCD - Front View



LCD - Rear View



GSM/PCS/UMTS-FDD Antenna View



WIFI/BT/BLE - Antenna View

Test Report	15070313-FCC-R1
Page	54 of 60



GPS - Antenna View


Annex B.iii. Photograph: Test Setup Photo




Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above
1GHz

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for Radiated Emissions



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Manufacturer	Equipment Description	Model	Calibration Date	Calibration Due Date
N/A	N/A	N/A	N/A	N/A

Annex C.ii. EUT OPERATING CONKITIONS

The following is the description of how the EUT is exercised during testing.

Test	Description Of Operation
Emissions Testing	The EUT was communicating with base station and set to work at maximum output power.
Others Testing	The EUT was communicating with base station and set to work at maximum output power.

Test Report	15070313-FCC-R1
Page	59 of 60

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see attachment

Test Report	15070313-FCC-R1
Page	60 of 60

Annex E. DECLARATION OF SIMILARITY

N/A