

RF TEST REPORT



Report No.: 15070340-FCC-R2

Applicant	Verykool USA INC.	
Product Name	Tablet	
Model No.	T7440	
Serial No.	N/A	
Test Standard	FCC Part 15.247: 2014, ANSI C63.10: 2013	
Test Date	May 13 to May 28, 2015	
Issue Date	May 29, 2015	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification	☒	
Equipment did not comply with the specification	☐	
<i>Winnie Zhang</i>	<i>Chris You</i>	
Winnie Zhang Test Engineer	Chris You Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	15070340-FCC-R2
Page	3 of 58

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
6.1 ANTENNA REQUIREMENT	9
6.2 CHANNEL SEPARATION	10
6.3 20DB BANDWIDTH	14
6.4 PEAK OUTPUT POWER	18
6.5 NUMBER OF HOPPING CHANNEL	22
6.6 TIME OF OCCUPANCY (DWEIL TIME)	24
6.7 BAND EDGE	28
6.8 AC POWER LINE CONDUCTED EMISSIONS	36
6.9 RADIATED SPURIOUS EMISSIONS	42
ANNEX A. TEST INSTRUMENT	47
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	48
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT	53
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	57
ANNEX E. DECLARATION OF SIMILARITY	58

1. Report Revision History

Report No.	Report Version	Description	Issue Date
15070340-FCC-R2	NONE	Original	May 29, 2015

2. Customer information

Applicant Name	Verykool USA INC.
Applicant Add	3636 Nobel Drive, Suite 325, San Diego, CA 92122 USA
Manufacturer	Mikibobile
Manufacturer Add	Block 5,Hongxin industrial Park, Dabuxiang Village, Guanguang Road, Guanlan Town, Bao' an District,Shenzhen

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT: Tablet

Main Model: T7440

Serial Model: N/A

Date EUT received: May 12, 2015

Test Date(s): May 13 to May 28, 2015

Equipment Category : DSS

Antenna Gain:

GSM850: 1.01 dBi
PCS1900: -0.99 dBi
UMTS-FDD Band V: 0.47dBi
UMTS-FDD Band II: -0.99 dBi
Bluetooth/BLE: 3.12 dBi
WIFI: 3.12 dBi

Type of Modulation:

GSM / GPRS: GMSK
EGPRS: GMSK, 8PSK
UMTS-FDD: QPSK, 16QAM
802.11b/g/n: DSSS, OFDM
Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK
BLE: GFSK

RF Operating Frequency (ies):

GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz
PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz
UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz
UMTS-FDD Band II TX: 1852.4 ~ 1907.6 MHz;
RX: 1932.4 ~ 1987.6 MHz
WIFI: 802.11b/g/n(20M): 2412-2462 MHz
WIFI: 802.11n(40M): 2422-2452 MHz
Bluetooth& BLE: 2402-2480 MHz

Max. Output Power: GFSK: 4.875 dBm

Test Report	15070340-FCC-R2
Page	7 of 58

Number of Channels:	GSM 850: 124CH
	PCS1900: 299CH
	UMTS-FDD Band V : 102CH
	UMTS-FDD Band II : 277CH
	WIFI :802.11b/g/n(20M): 11CH
	WIFI :802.11n(40M): 7CH
	Bluetooth: 79CH
	BLE: 40CH
Port:	Power Port, Earphone Port, USB Port
Input Power:	Battery:
	Model: GY-3553125PL
	Spec: 3.7V 2500mAh
	Adapter:
	Model: PS06B-0501000U
	Input: AC 100-240V; 50/60Hz
	Output: DC 5.0V; 1000mA
Trade Name :	verykool
GPRS/EGPRS Multi-slot class	8/10/12
FCC ID:	WA6T7440

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247(a)(1)	Channel Separation	Compliance
§15.247(a)(1)	20 dB Bandwidth	Compliance
§15.247(b)(1)	Peak Output Power	Compliance
§15.247(a)(1)(iii)	Number of Hopping Channel	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(d)	Band Edge	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 2 antennas:

A permanently attached PIFA antenna for Bluetooth/BLE/WIFI, the gain is -0.5dBi for Bluetooth/BLE/WIFI.

A permanently attached PIFA antenna for GSM and UMTS, the gain is 0.8dBi for GSM850, -0.7dBi for UMTS-FDD Band V, -1dBi for PCS1900, the gain is -0.9dBi for UMTS-FDD Band II


The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 Channel Separation

Temperature	22°C
Relative Humidity	54%
Atmospheric Pressure	1010mbar
Test date :	May 26, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(a)(1)	a)	Channel Separation < 20dB BW and 20dB BW < 25KHz ; Channel Separation Limit=25KHz Chanel Separation < 20dB BW and 20dB BW > 25kHz ; Channel Separation Limit=2/3 20dB BW	
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - The EUT must have its hopping function enabled - Span = wide enough to capture the peaks of two adjacent channels - Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span - Video (or Average) Bandwidth (VBW) ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.		

Remark	
Result	☒ Pass ☐ Fail


Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A

Channel Separation measurement result

Type/ Modulation	CH	CH Freq (MHz)	CH Separation (MHz)	Limit (MHz)	Result
CH Separation GFSK	Low Channel	2402	1.005	0.9596	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.005	0.9594	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.005	0.9648	Pass
	Adjacency Channel	2479			
CH Separation $\pi/4$ DQPSK	Low Channel	2402	1.005	0.851	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.005	0.850	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.005	0.854	Pass
	Adjacency Channel	2479			
CH Separation 8DPSK	Low Channel	2402	1.005	0.870	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.005	0.859	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.005	0.851	Pass
	Adjacency Channel	2479			

Test Plots

Channel Separation measurement result





8DPSK - Low Channel



8DPSK - Middle Channel




8DPSK - High Channel

6.3 20dB Bandwidth

Temperature	22°C
Relative Humidity	54%
Atmospheric Pressure	1010mbar
Test date :	May 26, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)	a)	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.	☒
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel - RBW $\geq$ 1% of the 20 dB bandwidth - VBW $\geq$ RBW - Sweep = auto - Detector function = peak - Trace = max hold. - The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference		

Test Report	15070340-FCC-R2
Page	15 of 58

	marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A


Measurement result

Modulation	CH	CH Freq (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
GFSK	Low	2402	0.9596	0.88315
	Mid	2441	0.9594	0.88036
	High	2480	0.9648	0.88169
$\pi/4$ DQPSK	Low	2402	1.277	1.1612
	Mid	2441	1.275	1.1670
	High	2480	1.281	1.1621
8-DPSK	Low	2402	1.305	1.1847
	Mid	2441	1.289	1.1733
	High	2480	1.276	1.1678


Test Plots

20dB Bandwidth measurement result






8DPSK - Low Channel



8DPSK - Middle Channel




8DPSK - High Channel

6.4 Peak Output Power

Temperature	21°C
Relative Humidity	56%
Atmospheric Pressure	1008mbar
Test date :	May 27, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (2)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	☒
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	☐
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	☒
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	☐
	e)	FHSS in 902-928MHz with ≥ 25 & < 50 channels: ≤ 0.25 Watt	☐
	f)	DSSS in 902-928MHz, 2400-2483.5MHz, 5725-5850MHz: ≤ 1 Watt	☐

Test Setup	 Spectrum Analyzer EUT
------------	--

Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel - RBW $>$ the 20 dB bandwidth of the emission being measured - VBW $\geq$ RBW - Sweep = auto - Detector function = peak - Trace = max hold
----------------	--

	- Allow the trace to stabilize. - Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (see the note above regarding external attenuation and cable loss). The limit is specified in one of the subparagraphs of this Section. Submit this plot. A peak responding power meter may be used instead of a spectrum analyzer.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Peak Output Power measurement result


Type	Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Limit (mW)	Result
Output power	GFSK	Low	2402	3.951	125	Pass
		Mid	2441	3.887	125	Pass
		High	2480	4.875	125	Pass
	$\pi/4$ DQPSK	Low	2402	2.537	125	Pass
		Mid	2441	2.783	125	Pass
		High	2480	2.946	125	Pass
	8-DPSK	Low	2402	2.599	125	Pass
		Mid	2441	2.875	125	Pass
		High	2480	3.042	125	Pass

Test Plots


Output Power measurement result




GFSK Output power - Low CH 2402




GFSK Output power - Mid CH 2441




GFSK Output power - High CH 2480




$\pi/4$ DQPSK Output power - Low CH 2402




$\pi/4$ DQPSK Output power - Mid CH 2441




$\pi/4$ DQPSK Output power - High CH 2480



8DPSK Output power - Low CH 2402



8DPSK Output power - Mid CH 2441




8DPSK Output power - High CH 2480

6.5 Number of Hopping Channel

Temperature	21°C
Relative Humidity	56%
Atmospheric Pressure	1008mbar
Test date :	May 27, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	FHSS in 2400-2483.5MHz $\geq$ 15 channels	☒
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer settings:</u> The EUT must have its hopping function enabled. - Span = the frequency band of operation - RBW $\geq$ 1% of the span - VBW $\geq$ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow trace to fully stabilize. - It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Number of Hopping Channel measurement result

Type	Modulation	Frequency Range	Number of Hopping Channel	Limit
Number of Hopping Channel	GFSK	2400-2483.5	79	15
	π /4 DQPSK	2400-2483.5	79	15
	8-DPSK	2400-2483.5	79	15

Test Plots


Number of Hopping Channels measurement result



6.6 Time of Occupancy (Dwell Time)

Temperature	22°C
Relative Humidity	54%
Atmospheric Pressure	1010mbar
Test date :	May 26, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	Dwell Time < 0.4s	☒
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer</u> - Span = zero span, centered on a hopping channel - RBW = 1 MHz - VBW ≥ RBW - Sweep = as necessary to capture the entire dwell time per hopping channel - Detector function = peak - Trace = max hold - use the marker-delta function to determine the dwell time		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Type	Modulation	CH	Pulse Width (ms)	Dwell Time (ms)	Limit (ms)	Result
Dwell Time	GFSK	Low	2.867	305.813	400	Pass
		Mid	2.867	305.813	400	Pass
		High	2.867	305.813	400	Pass
	$\pi/4$ DQPSK	Low	2.875	306.667	400	Pass
		Mid	2.867	305.813	400	Pass
		High	2.875	306.667	400	Pass
	8-DPSK	Low	2.883	307.520	400	Pass
		Mid	2.875	306.667	400	Pass
		High	2.883	307.520	400	Pass
Note: Dwell time=Pulse Time (ms) $\times$ (1600 $\div$ 6 $\div$ 79) $\times$ 31.6						

Test Plots


Dwell Time measurement result



GFSK - Low CH 2402




GFSK - Mid CH 2441




GFSK - High CH 2480




$\pi/4$ DQPSK - Low CH 2402




$\pi/4$ DQPSK - Mid CH 2441




$\pi/4$ DQPSK - High CH 2480



8DPSK - Low CH 2402



8DPSK - Mid CH 2441




8DPSK - High CH 2480

6.7 Band Edge

Temperature	20°C
Relative Humidity	56%
Atmospheric Pressure	1008mbar
Test date :	May 25, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	☒

Test Setup	
------------	--

Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Radiated Method Only 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range,
----------------	--

Test Report	15070340-FCC-R2
Page	29 of 58


	and make sure the instrument is operated in its linear range. - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☐ Yes ☒ N/A

Test Plot ☒ Yes (See below) ☐ N/A


Test Plots

GFSK Mode:




GFSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz




GFSK-Hopping Right Side-PK


Note: F1 is frequency 2483.5MHz




GFSK-Hopping Left Side-AV



GFSK-Hopping Right Side-AV



Date: 25.MAY.2015 14:43:19




Date: 25.MAY.2015 15:29:44

GFSK-Left Side-PK


Note: F1 is frequency 2400MHz

GFSK-Right Side-PK

Note: F1 is frequency 2483.5MHz



Date: 25.MAY.2015 14:48:06




Date: 25.MAY.2015 15:27:38

GFSK-Left Side-AV


GFSK-Right Side-AV

$\pi/4$ DQPSK Mode:




$\pi/4$ DQPSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz




$\pi/4$ DQPSK-Hopping Right Side-PK



Note: F1 is frequency 2483.5MHz



$\pi/4$ DQPSK-Hopping Left-AV



$\pi/4$ DQPSK-Hopping Right-AV




$\pi/4$ DQPSK-Left Side-PK

Note: F1 is frequency 2400MHz

$\pi/4$ DQPSK-Right Side-PK

Note: F1 is frequency 2483.5MHz





Note: (no need if PK value less than the AV limit)

$\pi/4$ DQPSK-Left Side-AV



$\pi/4$ DQPSK-Right Side-AV

8-DPSK Mode:




8DPSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz




8DPSK-Hopping Left-AV

8DPSK-Hopping Right-AV



Date: 25.MAY.2015 15:13:45




Date: 26.MAY.2015 09:29:40

8DPSK-Left Side-PK

Note: F1 is frequency 2400MHz

8DPSK-Right Side-PK

Note: F1 is frequency 2483.5MHz



Date: 25.MAY.2015 15:15:03

Note: (no need if PK value less than the AV limit)


8DPSK-Left Side-AV

8DPSK-Right Side-AV

6.8 AC Power Line Conducted Emissions

Temperature	21°C
Relative Humidity	56%
Atmospheric Pressure	1008mbar
Test date :	May 27, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable														
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	☒														
		<table><tr><th rowspan="2">Frequency ranges (MHz)</th><th colspan="2">Limit (dBµV)</th></tr><tr><th>QP</th><th>Average</th></tr><tr><td>0.15 ~ 0.5</td><td>66 – 56</td><td>56 – 46</td></tr><tr><td>0.5 ~ 5</td><td>56</td><td>46</td></tr><tr><td>5 ~ 30</td><td>60</td><td>50</td></tr></table>		Frequency ranges (MHz)	Limit (dBµV)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50
		Frequency ranges (MHz)			Limit (dBµV)												
				QP	Average												
		0.15 ~ 0.5		66 – 56	56 – 46												
0.5 ~ 5	56	46															
5 ~ 30	60	50															
Test Setup																	
		Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.															
		Procedure	1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table.														
2. The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains.																	
3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.																	
4. All other supporting equipment were powered separately from another main supply.																	

Test Report	15070340-FCC-R2
Page	37 of 58


	5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode: Bluetooth Mode

120V/60HZ




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Comment
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)	
1	L1	0.1749	27.95	QP	13.11	41.06	64.72	-23.66	
2	L1	0.1749	10.99	AVG	13.11	24.10	54.72	-30.62	
3	L1	0.2242	28.45	QP	12.92	41.37	62.66	-21.29	
4	L1	0.2242	13.15	AVG	12.92	26.07	52.66	-26.59	
5	L1	0.3035	32.94	QP	12.63	45.57	60.15	-14.58	
6	L1	0.3035	20.62	AVG	12.63	33.25	50.15	-16.90	
7	L1	0.3852	33.24	QP	12.33	45.57	58.17	-12.60	
8	L1	0.3852	20.86	AVG	12.33	33.19	48.17	-14.98	
9	L1	0.4588	34.23	QP	12.05	46.28	56.71	-10.43	
10	L1	0.4588	18.48	AVG	12.05	30.53	46.71	-16.18	
11	L1	0.7906	35.02	QP	11.61	46.63	56.00	-9.37	
12	L1	0.7906	20.84	AVG	11.61	32.45	46.00	-13.55	

Test Mode: Bluetooth Mode




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Comment
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)	
1	N	0.1787	31.39	QP	13.09	44.48	64.55	-20.07	
2	N	0.1787	21.17	AVG	13.09	34.26	54.55	-20.29	
3	N	0.2987	34.84	QP	12.65	47.49	60.28	-12.79	
4	N	0.2987	22.84	AVG	12.65	35.49	50.28	-14.79	
5	N	0.3883	40.14	QP	12.31	52.45	58.10	-5.65	
6	N	0.3883	27.85	AVG	12.31	40.16	48.10	-7.94	
7	N	0.4083	37.86	QP	12.24	50.10	57.68	-7.58	
8	N	0.4083	24.24	AVG	12.24	36.48	47.68	-11.20	
9	N	0.4742	38.82	QP	12.00	50.82	56.44	-5.62	
10	N	0.4742	27.73	AVG	12.00	39.73	46.44	-6.71	
11	N	0.6109	38.49	QP	11.79	50.28	56.00	-5.72	
12	N	0.6109	27.58	AVG	11.79	39.37	46.00	-6.63	

Test Mode: Bluetooth Mode

240V/60HZ




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Comment
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)	
1	L1	0.2203	39.94	QP	12.94	52.88	62.81	0.2203	
2	L1	0.2203	32.54	AVG	12.94	45.48	52.81	0.2203	
3	L1	0.3852	24.68	QP	12.33	37.01	58.17	0.3852	
4	L1	0.3852	12.88	AVG	12.33	25.21	48.17	0.3852	
5	L1	0.4703	28.61	QP	12.01	40.62	56.51	0.4703	
6	L1	0.4703	10.15	AVG	12.01	22.16	46.51	0.4703	
7	L1	1.0157	29.15	QP	11.40	40.55	56.00	1.0157	
8	L1	1.0157	21.91	AVG	11.40	33.31	46.00	1.0157	
9	L1	1.1305	30.76	QP	11.40	42.16	56.00	1.1305	
10	L1	1.1305	18.88	AVG	11.40	30.28	46.00	1.1305	
11	L1	1.5523	21.96	QP	11.40	33.36	56.00	1.5523	
12	L1	1.5523	13.27	AVG	11.40	24.67	46.00	1.5523	

Test Mode: Bluetooth Mode



Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Comment
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)	
1	N	0.2203	38.64	QP	12.94	51.58	62.81	-11.23	
2	N	0.2203	31.98	AVG	12.94	44.92	52.81	-7.89	
3	N	0.2711	27.58	QP	12.75	40.33	61.08	-20.75	
4	N	0.2711	20.45	AVG	12.75	33.20	51.08	-17.88	
5	N	0.4156	31.96	QP	12.21	44.17	57.54	-13.37	
6	N	0.4156	21.48	AVG	12.21	33.69	47.54	-13.85	
7	N	1.3023	25.95	QP	11.44	37.39	56.00	-18.61	
8	N	1.3023	12.99	AVG	11.44	24.43	46.00	-21.57	
9	N	1.3609	25.00	QP	11.45	36.45	56.00	-19.55	
10	N	1.3609	14.94	AVG	11.45	26.39	46.00	-19.61	
11	N	1.4234	27.56	QP	11.45	39.01	56.00	-16.99	
12	N	1.4234	17.00	AVG	11.45	28.45	46.00	-17.55	

6.9 Radiated Spurious Emissions

Temperature	21°C
Relative Humidity	56%
Atmospheric Pressure	1008mbar
Test date :	May 27, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable											
47CFR§15.205, §15.209, §15.247(d)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges												
		<table><tr><th>Frequency range (MHz)</th><th>Field Strength (µV/m)</th></tr><tr><td>30 – 88</td><td>100</td></tr><tr><td>88 – 216</td><td>150</td></tr><tr><td>216 960</td><td>200</td></tr><tr><td>Above 960</td><td>500</td></tr></table>		Frequency range (MHz)	Field Strength (µV/m)	30 – 88	100	88 – 216	150	216 960	200	Above 960	500	
		Frequency range (MHz)		Field Strength (µV/m)										
		30 – 88		100										
		88 – 216		150										
		216 960		200										
Above 960	500													

Test Setup	
------------	--

Procedure	- The EUT was switched on and allowed to warm up to its normal operating condition. - The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:
-----------	---

Test Report	15070340-FCC-R2
Page	43 of 58

	a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen. b. The EUT was then rotated to the direction that gave the maximum emission. c. Finally, the antenna height was adjusted to the height that gave the maximum emission. 3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. 4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. 5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
Remark	
Result	☒ Pass ☐ Fail


Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode: Bluetooth Mode

Below 1GHz

80.0 dBuV/m




Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree	Comment
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	()	
1	H	31.3992	26.92	peak	-1.29	25.63	40.00	-14.37	200	225	
2	H	45.0583	25.76	peak	-0.49	25.27	40.00	-14.73	200	359	
3	H	97.1148	31.59	peak	-11.57	20.02	43.50	-23.48	200	360	
4	H	163.7550	27.19	peak	-8.59	18.60	43.50	-24.90	200	143	
5	H	227.6906	31.25	peak	-8.99	22.26	46.00	-23.74	100	224	
6	H	636.1340	25.43	peak	0.59	26.02	46.00	-19.98	100	29	

Below 1GHz



Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree	Comment
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	()	
1	V	31.8427	36.16	peak	-2.52	33.64	40.00	-6.36	100	117	
2	V	36.2541	38.39	peak	-4.87	33.52	40.00	-6.48	100	184	
3	V	52.2079	46.02	peak	-14.10	31.92	40.00	-8.08	100	304	
4	V	79.8003	34.05	peak	-13.77	20.28	40.00	-19.72	100	4	
5	V	95.0930	35.74	peak	-12.81	22.93	43.50	-20.57	100	236	
6	V	796.1830	25.93	peak	3.52	29.45	46.00	-16.55	200	261	

Test Mode:	Transmitting Mode
-------------------	--------------------------

Mode: GFSK (Worst Case)

Low Channel (2402 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4804	33.16	AV	V	33.83	6.86	31.72	42.13	54	-11.87
4804	33.47	AV	H	33.83	6.86	31.72	42.44	54	-11.56
4804	47.52	PK	V	33.83	6.86	31.72	56.49	74	-17.51
4804	47.66	PK	H	33.83	6.86	31.72	56.63	74	-17.37

Middle Channel (2441 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4882	34.29	AV	V	33.86	6.82	31.82	43.15	54	-10.85
4882	34.68	AV	H	33.86	6.82	31.82	43.54	54	-10.46
4882	48.53	PK	V	33.86	6.82	31.82	57.39	74	-16.61
4882	47.95	PK	H	33.86	6.82	31.82	56.81	74	-17.19

High Channel (2480 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4960	35.04	AV	V	33.9	6.76	31.92	43.78	54	-10.22
4960	34.74	AV	H	33.9	6.76	31.92	43.48	54	-10.52
4960	47.66	PK	V	33.9	6.76	31.92	56.4	74	-17.6
4960	47.52	PK	H	33.9	6.76	31.92	56.26	74	-17.74

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/18/2014	09/17/2015	☒
Line Impedance	LI-125A	191106	09/26/2014	09/25/2015	☒
Line Impedance	LI-125A	191107	09/26/2014	09/25/2015	☒
LISN	ISN T800	34373	09/26/2014	09/25/2015	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/25/2014	09/24/2015	☒
Transient Limiter	LIT-153	531118	09/02/2014	09/01/2015	☒
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/18/2014	09/17/2015	☒
Power Splitter	1#	1#	09/02/2014	09/01/2015	☒
DC Power Supply	E3640A	MY40004013	09/18/2014	09/17/2015	☒
Radiated Emissions					
EMI test receiver	ESL6	100262	09/18/2014	09/17/2015	☒
Positioning Controller	UC3000	MF780208282	11/20/2014	11/19/2015	☒
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/02/2014	09/01/2015	☒
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/25/2015	03/24/2016	☒
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/22/2014	09/21/2015	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/25/2014	09/24/2015	☒
Universal Radio Communication Tester	CMU200	121393	09/26/2014	09/25/2015	☒

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo



Whole Package - Top View



Adapter - Front View




EUT - Front View



EUT - Rear View



EUT - Top View




EUT - Bottom View


Test Report	15070340-FCC-R2
Page	49 of 58




EUT - Left View



EUT - Right View



Cover-opening View



Cover Rear View




Cover Front View


Annex B.ii. Photograph: EUT Internal Photo




Cover Off - Top View 1




Battery - Top View




Battery - Bottom View



Mainboard With Shielding - Front View



Mainboard Without Shielding - Front View




Mainboard With Shielding - rear View

Test Report	15070340-FCC-R2
Page	51 of 58



LCD – Front View



LCD - Rear View



GSM/WCDMA Antenna View



BT/WIFI/GPS Antenna View


Annex B.iii. Photograph: Test Setup Photo




Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above 1GHz


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions (Below 1GHz) .



Block Configuration Diagram for Radiated Emissions (Above 1GHz) .



Test Report	15070340-FCC-R2
Page	56 of 58

Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Manufacturer	Equipment Description	Model	Calibration Date	Calibration Due Date
N/A	N/A	N/A	N/A	N/A

Test Report	15070340-FCC-R2
Page	57 of 58

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see attachment

Test Report	15070340-FCC-R2
Page	58 of 58

Annex E. DECLARATION OF SIMILARITY

N/A