

Declaration on model difference

Model No.: 0572 1841, 0572 1842, 0572 1843, 0572 1844, 0572 1845, 0572 1846

Only the model 0572 1844 was tested, all the models, their NFC circuit and antenna are exactly the same. Due to the different measurement functions, their names and models are different, and their measurement circuits and casings are different. The specific differences are as follows:

Product name	Model number	Parameters	Appearance
testo 184 T1	0572 1841	Measure the temperature Lithium battery: CR2032 3V (non-replaceable) Operating ambient temperature: -35°C to +70°C	
testo 184 T2	0572 1842	Measure the temperature Lithium battery: CR2450 3V (non-replaceable) Operating ambient temperature: -35°C to +70°C With a display screen	

Testo SE & Co. KGaA

testo 184 T3	0572 1843	Measure the temperature Lithium battery: CR2450 3V (replaceable) Operating ambient temperature: -35°C to +70°C With a display screen	 The image shows the testo 184 T3 digital thermometer. It has a white plastic body with a green LCD screen at the top displaying '-18.0' and 'Alarm °C'. Below the screen are two buttons labeled 'START' and 'STOP'. Further down are three indicator lights: a red one for 'Alarm', a green one for 'Battery', and a green one for 'Mode'. The 'testo' logo is at the bottom.
testo 184 T4	0572 1844	Measure the temperature Lithium battery: TLH-2450 3.6V (replaceable) Operating ambient temperature: -80°C to +70°C	 The image shows the testo 184 T4 digital thermometer. It has a white plastic body with a green LCD screen at the top. Below the screen are two buttons labeled 'START' and 'STOP'. Further down are three indicator lights: a green one for 'Alarm', a green one for 'Battery', and a green one for 'Mode'. The 'testo' logo is at the bottom.
testo 184 H1	0572 1845	Measure the temperature and humidity Lithium battery: CR2450 3V (replaceable) Operating ambient temperature: -20°C to +70°C With a display screen	 The image shows the testo 184 H1 digital thermometer and humidity meter. It has a white plastic body with a green LCD screen at the top displaying '45.3' and a '%' symbol. Below the screen are two buttons labeled 'START' and 'STOP'. Further down are three indicator lights: a green one for 'Alarm', a green one for 'Battery', and a green one for 'Mode'. The 'testo' logo is at the bottom.

Testo SE & Co. KGaA

testo 184 G1	0572 1846	Measure the temperature, humidity and acceleration Lithium battery: CR2450 3V (replaceable) Operating ambient temperature: -20°C to +70°C With a display screen	
-----------------	--------------	--	---

Signature:


Printed name: Christian Schwar

Company : Testo SE & Co. KGaA

Date:2025/12/18

Testo SE & Co. KGaA
Celsiusstraße 2
79822 Titisee-Neustadt