REPORT No. : SZ17030097S02

# RF EXPOSURE EVALUATION REPORT

| | | |
|---|---|---|
| **APPLICANT** | : | Testo SE & Co. KGaA |
| **PRODUCT NAME** | : | WLAN data logger |
| **MODEL NAME** | : | testo 160 IAQ |
| **TRADE NAME** | : | Testo |
| **BRAND NAME** | : | Testo |
| **FCC ID** | : | WAF-05722014 |
| **STANDARD(S)** | : | 47CFR 2.1091<br>KDB 447498 D01 General RF Exposure Guidance v06 |
| **ISSUE DATE** | : | 2017-04-06 |

**SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.**

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB GROUP
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China
Tel: 86-755-36698555 Http://www.morlab.com
Fax: 86-755-36698525 E-mail: service@morlab.cn

# DIRECTORY

**TEST REPORT DECLARATION** ..... 3

**1. TECHNICAL INFORMATION** ..... 4

**1.1. IDENTIFICATION OF APPLICANT** ..... 4
**1.2. IDENTIFICATION OF MANUFACTURER** ..... 4
**1.3. EQUIPMENT UNDER TEST (EUT)** ..... 4
1.3.1. PHOTOGRAPHS OF THE EUT ..... 5
1.3.2. IDENTIFICATION OF ALL USED EUT ..... 6
**1.4. APPLIED REFERENCE DOCUMENTS** ..... 6

**2. DEVICE CATEGORY AND RF EXPOSURE LIMIT** ..... 7

**3. MEASUREMENT OF CONDUCTED PEAK OUTPUT POWER** ..... 8

**4. RF EXPOSURE EVALUATION** ..... 8

**ANNEX C GENERAL INFORMATION** ..... 9

| Change History | | |
|---|---|---|
| Issue | Date | Reason for change |
| 1.0 | 2017-04-06 | First edition |
| | | |

# TEST REPORT DECLARATION

| | |
|---|---|
| Applicant | Testo SE & Co. KGaA |
| Applicant Address | Testo-Str.1, 79853 Lenzkirch, Germany |
| Manufacturer | testo Instruments (Shenzhen) Co., Ltd |
| Manufacturer Address | Block A, B4 Building, China Merchants Guangming Sci&Tech Park, No.3009 Guan Guang Road, Guangming New District, Shenzhen City |
| Product Name | WLAN data logger |
| Model Name | testo 160 IAQ |
| Brand Name | Testo |
| HW Version | 5.0 |
| SW Version | 1.22 |
| Test Standards | 47CFR 2.1091;<br>KDB 447498 D01 General RF Exposure Guidance v06 |
| Issue Date | 2017-04-06 |
| SAR Evaluation | Not Required |

Reviewed by : Liu Jun

Liu Jun

Approved by : Peng Huarui

Peng Huarui

# 1. TECHNICAL INFORMATION

Note: the following data is based on the information by the applicant.

## 1.1. Identification of Applicant

| | |
|---|---|
| Company Name: | Testo SE & Co. KGaA |
| Address: | Testo-Str.1, 79853 Lenzkirch, Germany |

## 1.2. Identification of Manufacturer

| | |
|---|---|
| Company Name: | testo Instruments (Shenzhen) Co., Ltd |
| Address: | Block A, B4 Building, China Merchants Guangming Sci&Tech Park, No.3009 Guan Guang Road, Guangming New District, Shenzhen City |

## 1.3. Equipment Under Test (EUT)

| | |
|---|---|
| Model Name: | testo 160 IAQ |
| Trade Name: | Testo |
| Brand Name: | Testo |
| Hardware Version: | 5.0 |
| Software Version: | 1.22 |
| Frequency Bands: | WIFI 802.11b/g/n20; |
| Modulation Mode: | WIFI802.11b: DSSS;WIFI802.11g: OFDM;<br>WIFI802.11n: OFDM; |
| Antenna Type: | Copper tube antenna |
| Antenna Gain: | 2 dBi |

### 1.3.1. Photographs of the EUT

1. EUT front view

2. EUT rear view

### 1.3.2. Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

| EUT Identity | Hardware Version | Software Version |
|---|---|---|
| 1# | 5.0 | 1.22 |

## 1.4. Applied Reference Documents

Leading reference documents for testing:

| No. | Identity | Document Title |
|---|---|---|
| 1 | **47 CFR§2.1091** | Radiofrequency Radiation Exposure Evaluation: mobile devices |
| 2 | **KDB 447498 D01v06** | General RF Exposure Guidance |

## 2. DEVICE CATEGORY AND RF EXPOSURE LIMIT

Per user manual, Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

**Mobile Devices:**

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term “fixed location” means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

**GENERAL POPULATION / UNCONTROLLED EXPOSURE**

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

**TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm$^2$) | Averaging time (minutes) |
|---|---|---|---|---|
| **(B) Limits for General Population/Uncontrolled Exposure** | | | | |
| 0.3-1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34-30 | 824/f | 2.19/f | *(180/f$^2$) | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | - | - | f/1500 | 30 |
| 1500-100,000 | - | - | 1.0 | 30 |

f = frequency in MHz  * = Plane-wave equivalent power density

## 3. MEASUREMENT OF CONDUCTED PEAK OUTPUT POWER

Wifi average output power

| Band | Channel | Frequency (MHz) | Output Power(dBm) | | |
|---|---|---|---|---|---|
| | | | 802.11b | 802.11g | 802.11n20 |
| Wifi | 1 | 2412 | 9.66 | 6.50 | 4.55 |
| | 6 | 2437 | 11.63 | 8.24 | 6.21 |
| | 11 | 2462 | 11.44 | 7.12 | 5.62 |

Note:

The conducted average output power of this report reference the wifi module's report whic h repoert number is RKS160620001-00C and FCC ID is N8NLSD4WF0459.

## 4 RF EXPOSURE EVALUATION

**Standalone transmission MPE evaluation**

| **Bands** | **Frequency (MHz)** | **Antenna Gain (dBi)** | **Conducted Average Power (dBm)** | **Time-averaging EIRP (mW)** | **Power density (mW/cm²)** | **Limit for MPE (mW/cm²)** |
|---|---|---|---|---|---|---|
| **2.4GHz** | 2437 | 2 | 11.63 | 23.07 | 0.005 | 1.0 |

1. MPE calculation method

$$\text{Power Density} = EIRP/4\pi R^2$$

Where: EIRP = P·G

P = Peak out power

G = Antenna gain

R = Separation distance (20cm)

# ANNEX C GENERAL INFORMATION

## 1. Identification of the Responsible Testing Laboratory

| | |
|---|---|
| Company Name: | Shenzhen Morlab Communications Technology Co., Ltd. |
| Department: | Morlab Laboratory |
| Address: | FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China |
| Responsible Test Lab Manager: | Mr. Su Feng |
| Telephone: | +86 755 36698555 |
| Facsimile: | +86 755 36698525 |

## 2. Identification of the Responsible Testing Location

| | |
|---|---|
| Name: | Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory |
| Address: | FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China |

***** END OF REPORT *****