


TEST REPORT

Applicant: NEW POS Technology Limited
Address: AB Unit, 14th Floor, Block A, Financial Technology Building, No.11 Keyuan Rd, Nanshan District, Shenzhen, China
Equipment Type: Smart POS Terminal
Model Name: NEW9810P
Brand Name: N/A
FCC ID: WAL9810P
Test Standard: FCC 47 CFR Part 2.1093 (refer section 3.1)
Maximum SAR: Body (1 g@10mm): 1.09 W/kg
Limbs (10 g@0mm): 1.19 W/kg
Sample Arrival Date: Mar. 17, 2026
Test Date: Mar. 25, 2026 - Mar. 26, 2026
Date of Issue: May 25, 2026

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** Song Gui**Checked by:** Xu Rui**Approved by:** Liao Jianming
(Technical Director)

Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>May 25, 2026</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	4
1.1	Test Laboratory	4
1.2	Test Location	4
1.3	Test Environment Condition.....	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information.....	5
2.3	General Description for Equipment under Test (EUT).....	5
2.4	Ancillary Equipment.....	5
2.5	Technical Information	6
3	SUMMARY OF TEST RESULT	7
3.1	Test Standards	7
3.2	Device Category and SAR Limit	8
3.3	Test Result Summary	9
3.4	Test Uncertainty	10
4	MEASUREMENT SYSTEM	11
4.1	Specific Absorption Rate (SAR) Definition	11
4.2	DASY SAR System	12
5	SYSTEM VERIFICATION	19
5.1	Purpose of System Check	19
5.2	System Check Setup	19
6	TEST POSITION CONFIGURATIONS	20
6.1	Body-worn Position Conditions	20
7	MEASUREMENT PROCEDURE	21

7.1	Measurement Process Diagram	21
7.2	SAR Scan General Requirement	22
7.3	Measurement Procedure	23
7.4	Area & Zoom Scan Procedure	23
8	CONDUCTED RF OUTPUT POWER	24
9	TEST EXCLUSION CONSIDERATION	25
9.1	Antenna location sketch.....	25
10	NFC SAR.....	26
11	TEST RESULT	27
11.1	Bluetooth	27
11.2	WIFI 2.4GHz.....	28
11.3	WIFI 5GHz.....	29
12	SAR Measurement Variability	31
13	SIMULTANEOUS TRANSMISSION.....	32
13.1	Simultaneous Transmission Mode Considerations	32
13.2	Highest Total Exposure Ratio of Simultaneous Transmission	32
14	TEST EQUIPMENTS LIST	33
ANNEX A	SIMULATING LIQUID VERIFICATION RESULT	34
ANNEX B	SYSTEM CHECK RESULT	35
ANNEX C	TEST DATA.....	36
ANNEX D	EUT EXTERNAL PHOTOS.....	36
ANNEX E	SAR TEST SETUP PHOTOS	36
ANNEX F	CALIBRATION REPORT	36
ANNEX G	TUNE-UP PROCEDURE.....	36

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	601, Building 2, Intelligent Connected Vehicle Industrial Park, No.55, Xiangshan Road, Luotian Community, Yanluo Sub-district, Bao'an District, Shenzhen
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☐ Building 2, Intelligent Connected Vehicle Industrial Park, No.55, Xiangshan Road, Luotian Community, Yanluo Sub-district, Bao'an District, Shenzhen, Guangdong
	☒ 1/F., Building B, Ganghongji High-Tech Intelligent Industrial Park, No.1008, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

1.3 Test Environment Condition

Ambient Temperature	18°C to 25°C
Ambient Relative Humidity	30% to 70%

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	NEW POS Technology Limited
Address	AB Unit, 14th Floor, Block A, Financial Technology Building, No.11 Keyuan Rd, Nanshan District, Shenzhen, China

2.2 Manufacturer Information

Manufacturer	NEW POS Technology Limited
Address	AB Unit, 14th Floor, Block A, Financial Technology Building, No.11 Keyuan Rd, Nanshan District, Shenzhen, China

2.3 General Description for Equipment under Test (EUT)

EUT Name	Smart POS Terminal
Model Name Under Test	NEW9810P
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	V00
Software Version	1.01.00.20260302
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Ancillary Equipment

Note: Not applicable.

2.5 Technical Information

Network and Wireless connectivity	Bluetooth (BR+EDR+BLE) WIFI 802.11a, 802.11b, 802.11g, 802.11n and 802.11ac NFC
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	WIFI, Bluetooth, NFC	
Frequency Range	802.11b/g/n(HT20)	2400 ~ 2483.5 MHz
	802.11a	5150 ~ 5350 MHz
		5470 ~ 5725 MHz
		5725 ~ 5850 MHz
	802.11n(HT20/HT40)	5150 ~ 5350 MHz
		5470 ~ 5725 MHz
		5725 ~ 5850 MHz
	802.11ac(VHT20/VHT40)	5150 ~ 5350 MHz
		5470 ~ 5725 MHz
		5725 ~ 5850 MHz
	Bluetooth	2400 ~ 2483.5 MHz
	NFC	13.56 MHz
Antenna Type	WIFI	PIFA Antenna
	Bluetooth	PIFA Antenna
	NFC	Coil Antenna
Exposure Category	General Population/Uncontrolled exposure	
EUT Type	Portable Device	

3 SUMMARY OF TEST RESULT

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices
2	ANSI/IEEE Std.C95.1-1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
3	KDB 447498 D04 v01	447498 D04 Interim General RF Exposure Guidance v01
4	KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
5	KDB 865664 D02 v01r02	RF Exposure Reporting
6	KDB 248227 D01 v02r02	SAR Guidance for IEEE 802.11 (Wi-Fi) Transmitters

3.2 Device Category and SAR Limit

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user.

Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

Table of Exposure Limits:

Body Position	SAR Value (W/Kg)	
	General Population/ Uncontrolled Exposure	Occupational/ Controlled Exposure
Whole-Body SAR (averaged over the entire body)	0.08	0.4
Partial-Body SAR (averaged over any 1 gram of tissue)	1.60	8.0
SAR for hands, wrists, feet and ankles (averaged over any 10 grams of tissue)	4.0	20.0

NOTE:

General Population/Uncontrolled Exposure: Locations where there is the exposure of individuals who have no knowledge or control of their exposure. General population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Occupational/Controlled Exposure: Locations where there is exposure that may be incurred by persons who are aware of the potential for exposure. In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

3.3 Test Result Summary

3.3.1 Highest SAR

Equipment Class	Band	Maximum Scaled SAR (W/kg)		Maximum Report SAR (W/kg)	
		Body	Limbs	Body	Limbs
		(10mm)	(0mm)	(10mm)	(0mm)
		1g SAR	10g SAR	1g SAR	10g SAR
DTS	2.4G WIFI	0.24	0.64	1.09	1.19
NII	5.3G WIFI	0.87	1.19		
	5.6G WIFI	1.01	1.03		
	5.8G WIFI	1.09	0.96		
DSS	Bluetooth	0.04	0.12		
Limit (W/kg)		1.60	4.00	1.60	4.00
Verdict		Pass			

3.4 Test Uncertainty

According to KDB 865664 D01, when the highest measured 1 g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis is not required in SAR reports submitted for equipment approval.

The maximum 1 g SAR for the EUT in this report is 1.09 W/kg, which is lower than 1.5 W/kg, so the extensive SAR measurement uncertainty analysis is not required in this report.

The maximum 10 g SAR for the EUT in this report is 1.19 W/kg, which is lower than 3.75 W/kg, so the extensive SAR measurement uncertainty analysis is not required in this report.

4 MEASUREMENT SYSTEM

4.1 Specific Absorption Rate (SAR) Definition

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by


$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,

ρ is the mass density of the tissue and E is the RMS electrical field strength.

4.2 DASY SAR System

4.2.1 DASY SAR System Diagram



The DASY5 system for performing compliance tests consists of the following items:

1. A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
2. A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
3. A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
4. A unit to operate the optical surface detector which is connected to the EOC.
5. The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.
6. The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.
7. DASY5 software and SEMCAD data evaluation software.
8. Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
9. The generic twin phantom enabling the testing of left-hand and right-hand usage.
10. The device holder for handheld mobile phones.
11. Tissue simulating liquid mixed according to the given recipes.
12. System validation dipoles allowing to validate the proper functioning of the system.

4.2.2 Robot

The Dasy SAR system uses the high precision robots. Symmetrical design with triangular core Built-in optical fiber for surface detection system For the 6-axis controller system, Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents). The robot series have many features that are important for our application:



- High precision
(repeatability ± 0.02 mm)
- High reliability
(industrial design)
- Low maintenance costs
(virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements
(brush less synchron motors; no stepper motors)
- Low ELF interference
(motor control _elds shielded via the closed metallic construction shields)

4.2.3 E-Field Probe

The probe is specially designed and calibrated for use in liquids with high permittivities for the measurements the Specific Dosimetric E-Field Probe EX3DV4 with following specifications is used.

Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection system Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., glycolether)
Calibration	ISO/IEC 17025 calibration service available
Frequency	10 MHz to 6 GHz; Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.2 dB in HSL (rotation around probe axis) ; ± 0.4 dB in HSL (rotation normal to probe axis)
Dynamic range	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB
Dimensions	Overall length: 337 mm (Tip: 9 mm) Tip diameter: 2.5 mm (Body: 10 mm) Distance from probe tip to dipole centers: 1.0 mm
Application	General dosimetry up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms (EX3DV4)



E-Field Probe Calibration Process

Probe calibration is realized, in compliance with CENELEC EN 62209-1/-2 and IEEE 1528 std, with CALISAR, Antennessa proprietary calibration system. The calibration is performed with the EN 62209-1/2 annexe technique using reference guide at the five frequencies.

4.2.4 Data Acquisition Electronics


The data acquisition electronics (DAE) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converte and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.



- Input Impedance: 200M Ω m
- The Inputs: Symmetrical and Floating
- Commom Mode Rejection: Above 80dB

4.2.5 Phantoms

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.



- Left hand
- Right hand
- Flat phantom



4.2.6 Device Holder

The DASY5 device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65° . The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. This device holder is used for standard mobile phones or PDA's only. If necessary an additional support of polystyrene material is used. Larger DUT's (e.g. notebooks) cannot be tested using this device holder. Instead a support of bigger polystyrene cubes and thin polystyrene plates is used to position the DUT in all relevant positions to find and measure spots with maximum SAR values. Therefore those devices are normally only tested at the flat part of the SAM.



The positioning system allows obtaining cheek and tilting position with a very good accuracy. Incompliance with CENELEC, the tilt angle uncertainty is lower than 1° .


4.2.7 Simulating Liquid

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5%.

Head Liquid Depth



Body Liquid Depth



The following table gives the recipes for tissue simulating liquid.

TSL	Manufacturer / Model	Freq Range (MHz)	Main Ingredients
Head WideBand	SPEAG HBBL600-10000V6	600-10000	Ethenediol, Sodium petroleum sulfonate, Hexylene Glycol / 2-Methyl-pentane-2.4-diol, Alkoxylated alcohol


5 SYSTEM VERIFICATION

5.1 Purpose of System Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

5.2 System Check Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



6 TEST POSITION CONFIGURATIONS


6.1 Body-worn Position Conditions

Devices that support transmission while used with body-worn accessories must be tested for SAR compliance related to each body-worn condition of use. SAR evaluation is required for body-worn accessories supplied with the device they are attached to.

The general informing principle is that the selected test configurations must conservatively capture the various body-worn accessory use conditions expected by users. For instance, devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, must be tested for SAR compliance using a conservative minimum test separation distance not to exceed 5 mm for all use conditions required by the device.

7 MEASUREMENT PROCEDURE

7.1 Measurement Process Diagram



7.2 SAR Scan General Requirement

Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1 g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2013.

			≤3GHz	>3GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5±1 mm	½·δ·ln(2)±0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30°±1°	20°±1°
Maximum area scan spatial resolution: Δx Area , Δy Area			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3–4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx Zoom , Δy Zoom			≤ 2 GHz: ≤ 8 mm 2 –3 GHz: ≤ 5 mm*	3–4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: Δz Zoom (n)		≤ 5 mm	3–4 GHz: ≤ 4 mm
				4–5 GHz: ≤ 3 mm
				5–6 GHz: ≤ 2 mm
	graded grid	Δz Zoom (1): between 1st two points closest to phantom surface	≤ 4 mm	3–4 GHz: ≤ 3 mm
				4–5 GHz: ≤ 2.5 mm
		Δz Zoom (n>1): between subsequent points	≤ 1.5·Δz Zoom (n-1)	
Minimum zoom scan volume	x, y, z		≥30 mm	3–4 GHz: ≥ 28 mm
				4–5 GHz: ≥ 25 mm
				5–6 GHz: ≥ 22 mm

Note:

1. δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.
2. * When zoom scan is required and the reported SAR from the area scan based 1 g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

7.3 Measurement Procedure

The following steps are used for each test position

- a. Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- b. Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- c. Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- d. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

7.4 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01v01r04 quoted below.


When the 1 g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

8 CONDUCTED RF OUTPUT POWER

Please refer the document “Ti-EE26030353-AP.pdf”.

9 TEST EXCLUSION CONSIDERATION

9.1 Antenna location sketch



Antenna	Support Bands
ANT1	2.4G WIFI&5G WIFI&Bluetooth

10 NFC SAR

According to the ANSI C63.10 clause 11.12.2.2:

The value of maximum peak output power is according to the method described in ANSI C63.10 clause 11.12.2.2 General procedure for conducted measurements in restricted bands:

- a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)
- c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies $\leq$ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies $>$ 1000 MHz).
- d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
- e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship: $E = \text{EIRP} - 20\log D + 104.8$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

Mode	f (MHz)	Max. E-Field strength (dB μ V/m)	D (m)	Ground reflection factor (dB)	ERP (dBm)
NFC (13.56MHz)	13.56	82.37	3	6	-6.89

Note:

1. Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies $\leq$ 30 MHz).
2. ERP= 82.37+20*Log(3) - 104.8 + 6 =-6.89 (dBm)

According to the FCC KDB 447498 D04

Estimated SAR: SAR test = $1.6 \cdot \text{Pant} / \text{Pth}$ [W/kg]

Estimated SAR	$1.6 \cdot \text{Pant} / \text{Pth}$ [W/kg]		
Pmeas.(dBm)	-6.89	Pmeas.(mW)	0.204759
Pth.(mW)	443.13		
NFC Estimated 1g SAR [W/kg]	<0.001		

11 TEST RESULT

11.1 Bluetooth

Antenna	Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	1g Scaled SAR (W/kg)	Meas. No.
Body														
ANT1	DH5	Front Side	10	78	2480	-0.18	0.014	11.72	12.00	1.068	76.88	1.301	0.019	/
		Back Side	10	78	2480	0.06	0.025	11.72	12.00	1.068	76.88	1.301	0.035	1#
		Left Edge	10	78	2480	-0.14	0.002	11.72	12.00	1.068	76.88	1.301	0.003	/
		Right Edge	10	78	2480	-0.16	0.005	11.72	12.00	1.068	76.88	1.301	0.007	/
		Top Edge	10	78	2480	0.10	0.003	11.72	12.00	1.068	76.88	1.301	0.004	/
		Bottom Edge	10	78	2480	0.11	0.003	11.72	12.00	1.068	76.88	1.301	0.004	/
		Back Side	10	0	2402	-0.15	0.019	10.64	12.00	1.369	76.88	1.301	0.034	/
		Back Side	10	39	2441	-0.11	0.021	11.66	12.00	1.082	76.88	1.301	0.030	/
Note: Refer to ANNEX C for the detailed test data for each test configuration.														

Antenna	Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	10g Meas. SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	10g Scaled SAR (W/kg)	Meas. No.
Limbs														
ANT1	DH5	Front Side	0	78	2480	0.02	0.008	11.72	12.00	1.068	76.88	1.301	0.011	/
		Back Side	0	78	2480	-0.13	0.051	11.72	12.00	1.068	76.88	1.301	0.071	/
		Left Edge	0	78	2480	0.06	0.003	11.72	12.00	1.068	76.88	1.301	0.004	/
		Right Edge	0	78	2480	-0.18	0.073	11.72	12.00	1.068	76.88	1.301	0.101	/
		Top Edge	0	78	2480	0.09	0.002	11.72	12.00	1.068	76.88	1.301	0.003	/
		Bottom Edge	0	78	2480	0.18	0.035	11.72	12.00	1.068	76.88	1.301	0.049	/
		Right Edge	0	0	2402	-0.16	0.054	10.64	12.00	1.369	76.88	1.301	0.096	/
		Right Edge	0	39	2441	0.06	0.088	11.66	12.00	1.082	76.88	1.301	0.124	6#
Note: Refer to ANNEX C for the detailed test data for each test configuration.														

11.2WIFI 2.4GHz

Antenna	Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	1g Scaled SAR (W/kg)	Meas. No.
Body														
ANT1	802.11b	Front Side	10	6	2437	0.03	0.043	18.31	18.50	1.045	99.50	1.005	0.045	/
		Back Side	10	6	2437	0.16	0.225	18.31	18.50	1.045	99.50	1.005	0.236	2#
		Left Edge	10	6	2437	0.02	0.064	18.31	18.50	1.045	99.50	1.005	0.067	/
		Right Edge	10	6	2437	-0.01	0.161	18.31	18.50	1.045	99.50	1.005	0.169	/
		Top Edge	10	6	2437	-0.18	0.003	18.31	18.50	1.045	99.50	1.005	0.003	/
		Bottom Edge	10	6	2437	-0.05	0.157	18.31	18.50	1.045	99.50	1.005	0.165	/
		Back Side	10	1	2412	0.18	0.209	18.17	18.50	1.079	99.50	1.005	0.227	/
		Back Side	10	11	2462	-0.11	0.204	18.18	18.50	1.076	99.50	1.005	0.221	/
Note: Refer to ANNEX C for the detailed test data for each test configuration.														

Antenna	Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	10g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	10g Scaled SAR (W/kg)	Meas. No.
Limbs														
ANT1	802.11b	Front Side	0	6	2437	-0.07	0.082	18.31	18.50	1.045	99.50	1.005	0.086	/
		Back Side	0	6	2437	0.12	0.406	18.31	18.50	1.045	99.50	1.005	0.426	/
		Left Edge	0	6	2437	-0.09	0.072	18.31	18.50	1.045	99.50	1.005	0.076	/
		Right Edge	0	6	2437	0.17	0.510	18.31	18.50	1.045	99.50	1.005	0.535	/
		Top Edge	0	6	2437	0.08	0.003	18.31	18.50	1.045	99.50	1.005	0.003	/
		Bottom Edge	0	6	2437	-0.15	0.283	18.31	18.50	1.045	99.50	1.005	0.297	/
		Right Edge	0	1	2412	0.08	0.423	18.17	18.50	1.079	99.50	1.005	0.459	/
		Right Edge	0	11	2462	0.03	0.595	18.18	18.50	1.076	99.50	1.005	0.644	7#
Note: Refer to ANNEX C for the detailed test data for each test configuration.														

11.3WIFI 5GHz

Band	Antenna	Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	1g Scaled SAR (W/kg)	Meas. No.
Body															
5.3G	ANT1	802.11n 40	Front Side	10	54	5270	0.01	0.134	19.77	20.00	1.054	93.41	1.071	0.151	/
			Back Side	10	54	5270	0.14	0.732	19.77	20.00	1.054	93.41	1.071	0.826	/
			Left Edge	10	54	5270	0.14	0.112	19.77	20.00	1.054	93.41	1.071	0.126	/
			Right Edge	10	54	5270	-0.16	0.531	19.77	20.00	1.054	93.41	1.071	0.599	/
			Top Edge	10	54	5270	-0.18	0.002	19.77	20.00	1.054	93.41	1.071	0.002	/
			Bottom Edge	10	54	5270	0.13	0.452	19.77	20.00	1.054	93.41	1.071	0.510	/
			Back Side	10	62	5310	-0.02	0.755	19.66	20.00	1.081	93.41	1.071	0.874	3#
5.6G	ANT1	802.11n 40	Front Side	10	118	5590	0.15	0.084	18.86	19.00	1.033	93.41	1.071	0.093	/
			Back Side	10	118	5590	-0.18	0.762	18.86	19.00	1.033	93.41	1.071	0.842	/
			Left Edge	10	118	5590	0.08	0.029	18.86	19.00	1.033	93.41	1.071	0.032	/
			Right Edge	10	118	5590	0.01	0.344	18.86	19.00	1.033	93.41	1.071	0.380	/
			Top Edge	10	118	5590	-0.15	0.002	18.86	19.00	1.033	93.41	1.071	0.002	/
			Bottom Edge	10	118	5590	-0.12	0.249	18.86	19.00	1.033	93.41	1.071	0.275	/
			Back Side	10	102	5510	-0.12	0.822	18.47	19.00	1.130	93.41	1.071	0.994	/
			Back Side	10	134	5670	0.09	0.859	18.58	19.00	1.102	93.41	1.071	1.013	4#
5.8G	ANT1	802.11n 40	Front Side	10	151	5755	0.17	0.071	18.23	19.00	1.194	93.41	1.071	0.091	/
			Back Side	10	151	5755	0.05	0.833	18.23	19.00	1.194	93.41	1.071	1.065	/
			Left Edge	10	151	5755	-0.17	0.049	18.23	19.00	1.194	93.41	1.071	0.063	/
			Right Edge	10	151	5755	0.17	0.354	18.23	19.00	1.194	93.41	1.071	0.452	/
			Top Edge	10	151	5755	0.07	0.002	18.23	19.00	1.194	93.41	1.071	0.003	/
			Bottom Edge	10	151	5755	-0.01	0.214	18.23	19.00	1.194	93.41	1.071	0.274	/
			Back Side	10	159	5795	0.10	0.842	18.19	19.00	1.205	93.41	1.071	1.086	5#
Note: Refer to ANNEX C for the detailed test data for each test configuration.															

Band	Antenna	Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	10g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	10g Scaled SAR (W/kg)	Meas. No.
Limbs															
5.3G	ANT1	802.11n 40	Front Side	0	54	5270	-0.11	0.054	19.77	20.00	1.054	93.41	1.071	0.061	/
			Back Side	0	54	5270	-0.02	0.697	19.77	20.00	1.054	93.41	1.071	0.787	/
			Left Edge	0	54	5270	-0.04	0.051	19.77	20.00	1.054	93.41	1.071	0.058	/
			Right Edge	0	54	5270	0.05	1.050	19.77	20.00	1.054	93.41	1.071	1.185	8#
			Top Edge	0	54	5270	-0.14	0.003	19.77	20.00	1.054	93.41	1.071	0.003	/
			Bottom Edge	0	54	5270	-0.01	0.301	19.77	20.00	1.054	93.41	1.071	0.340	/
			Right Edge	0	62	5310	0.13	0.990	19.66	20.00	1.081	93.41	1.071	1.146	/
5.6G	ANT1	802.11n 40	Front Side	0	118	5590	0.12	0.103	18.86	19.00	1.033	93.41	1.071	0.114	/
			Back Side	0	118	5590	-0.08	0.777	18.86	19.00	1.033	93.41	1.071	0.859	/
			Left Edge	0	118	5590	-0.12	0.068	18.86	19.00	1.033	93.41	1.071	0.075	/
			Right Edge	0	118	5590	-0.08	0.680	18.86	19.00	1.033	93.41	1.071	0.752	/
			Top Edge	0	118	5590	0.16	0.003	18.86	19.00	1.033	93.41	1.071	0.003	/
			Bottom Edge	0	118	5590	0.18	0.335	18.86	19.00	1.033	93.41	1.071	0.370	/
			Back Side	0	102	5510	0.02	0.851	18.47	19.00	1.130	93.41	1.071	1.029	9#
			Back Side	0	134	5670	0.04	0.698	18.58	19.00	1.102	93.41	1.071	0.823	/
5.8G	ANT1	802.11n 40	Front Side	0	151	5755	-0.02	0.058	18.23	19.00	1.194	93.41	1.071	0.074	/
			Back Side	0	151	5755	0.09	0.749	18.23	19.00	1.194	93.41	1.071	0.957	10#
			Left Edge	0	151	5755	-0.01	0.055	18.23	19.00	1.194	93.41	1.071	0.070	/
			Right Edge	0	151	5755	-0.16	0.618	18.23	19.00	1.194	93.41	1.071	0.790	/
			Top Edge	0	151	5755	-0.16	0.003	18.23	19.00	1.194	93.41	1.071	0.004	/
			Bottom Edge	0	151	5755	-0.16	0.228	18.23	19.00	1.194	93.41	1.071	0.291	/
			Back Side	0	159	5795	0.19	0.733	18.19	19.00	1.205	93.41	1.071	0.946	/
Note: Refer to ANNEX C for the detailed test data for each test configuration.															

12 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Frequency Band (MHz)	Wireless Band	Antenna	RF Exposure Conditions	Test Position	Highest Measured SAR (W/kg)	Repeated SAR (Yes/No)	Highest Measured SAR (W/kg)	Largest to Smallest SAR Radio
5510	802.11n40	ANT1	Body	Back Side	0.822	Yes	0.802	1.02
5670	802.11n40	ANT1	Body	Back Side	0.859	Yes	0.827	1.04
5755	802.11n40	ANT1	Body	Back Side	0.833	Yes	0.816	1.02
5795	802.11n40	ANT1	Body	Back Side	0.842	Yes	0.809	1.04

Note: The ratio of largest to smallest SAR for the original and first repeated measurements is < 1.20 , the second repeated measurement is not required.

13 SIMULTANEOUS TRANSMISSION

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR 1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR 1g 1.6 W/kg), SAR test exclusion is determined by the SAR to Peak Location Ratio (SPLSR).

According KDB 447498 D04, simultaneous transmission:

- a) $SPLSR = (SAR1 + SAR2)^{1.5} / R_i$ (min. separation distance, mm), and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
SAR1 is the highest reported or estimated SAR for the first of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition.
SAR2 is the highest reported or estimated SAR for the second of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition as the first.
- b) If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
- c) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.

13.1 Simultaneous Transmission Mode Considerations

No.	Simultaneous Tx Combination	Body	Limbs
1	BT+NFC	Yes	Yes
2	WIFI 2.4G+NFC	Yes	Yes
3	WIFI 5G+NFC	Yes	Yes

Note:

1. The maximum SAR summation is calculated based on the same configuration and test position.

13.2 Highest Total Exposure Ratio of Simultaneous Transmission

NFC multi-transmit requires the use of the TER formula:

$$TER = \sum_{k=1}^{N_s} \left(\frac{SAR_k}{SAR_{lim}} \right) + \sum_{k=1}^{N_f} \left(\frac{MPE_{field, k}}{MPE_{field, lim}} \right)^2 + \sum_{k=1}^{N_{PD}} \left(\frac{MPE_{PD, k}}{MPE_{PD, lim}} \right)$$

The maximum SAR value for Simultaneous Transmission is 0.001 [W/kg], the worst TER
 $= (1.09 + 0.001) / 1.6 = 0.6819 < 1$, the NFC SAR transmit simultaneously Pass.

14 TEST EQUIPMENTS LIST

Description	Manufacturer	Model	Serial No./Version	Cal. Date	Cal. Due
PC	Dell	N/A	N/A	N/A	N/A
Test Software	Speag	DASY5	52.8.8.1222	N/A	N/A
2450MHz Validation Dipole	Speag	D2450V2	SN: 952	2024/05/07	2027/05/06
5GHz Validation Dipole	Speag	D5GHzV2	SN: 1200	2024/05/09	2027/05/08
Data Acquisition Electronics	Speag	DAE4	SN: 1711	2025/11/11	2026/11/10
E-Field Probe	Speag	EX3DV4	SN: 7607	2025/08/06	2026/08/05
Signal Generator	Keysight	N5173B	MY62150163	2025/07/15	2026/07/14
Power Meter	R&S	NRVD-B2	835843/014	2025/07/15	2026/07/14
Power Sensor	R&S	NRV-Z4	100381	2025/07/15	2026/07/14
Power Sensor	R&S	NRV-Z2	100211	2025/07/15	2026/07/14
Network Analyzer	Agilent	E5071C	MY46103472	2025/08/13	2026/08/12
Thermometer	Elitech	RC-4HC	EF7216002985	2025/10/30	2026/10/29
Thermometer	Elitech	RC-4HC	EF720B004811	2025/09/16	2026/09/15
Power Amplifier	Mini-Circuits	ZVA-183W-S+	932502132	N/A	N/A
Dielectric Probe Kit	Speag	DAK3.5	SN: 1312	N/A	N/A
Phantom	Speag	SAM	SN: 1576	N/A	N/A
Attenuator	COM-MW	ZA-S1-31	1305003187	N/A	N/A
Directional coupler	AA-MCS	AAMCS-UDC	000272	N/A	N/A

Note: For dipole antennas, BALUN has adopted 3 years as calibration intervals, and on annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole;
2. System validation with specific dipole is within 10% of calibrated value;
3. Return-loss in within 20% of calibrated measurement.
4. Impedance (real or imaginary parts) in within 5 Ohms of calibrated measurement.

ANNEX A SIMULATING LIQUID VERIFICATION RESULT

The dielectric parameters of the liquids were verified prior to the SAR evaluation using a DAK3.5

Dielectric Probe Kit.

Head Liquid

Date	Liquid Type	Fre. (MHz)	Temp. (°C)	Meas. Conductivity (σ) (S/m)	Meas. Permittivity (ϵ)	Target Conductivity (σ) (S/m)	Target Permittivity (ϵ)	Conductivity Tolerance (%)	Permittivity Tolerance (%)
2026.03.25	Head	2450	21.6	1.84	39.00	1.80	39.20	2.22	-0.51
2026.03.25	Head	5250	21.6	4.67	36.04	4.71	35.93	-0.85	0.31
2026.03.26	Head	5600	21.3	5.08	35.26	5.07	35.53	0.20	-0.76
2026.03.26	Head	5750	21.3	5.17	35.06	5.22	35.36	-0.96	-0.85

Note: The tolerance limit of Conductivity and Permittivity is $\pm 5\%$.

ANNEX B SYSTEM CHECK RESULT

Comparing to the original SAR value provided by SPEAG, the validation data should be within its specification of 10 % (for 1 g).

Head liquid 1g

Date	Liquid Type	Freq. (MHz)	Power (mW)	Measured SAR (W/kg)	Normalized SAR (W/kg)	Dipole SAR (W/kg)	Tolerance (%)
2026.03.25	Head	2450	100	5.130	51.30	52.60	-2.47
2026.03.25	Head	5250	100	7.710	77.10	77.70	-0.77
2026.03.26	Head	5600	100	8.120	81.20	81.30	-0.12
2026.03.26	Head	5750	100	7.730	77.30	77.60	-0.39

Note: The tolerance limit of System validation $\pm 10\%$.

Head liquid 10g

Date	Liquid Type	Freq. (MHz)	Power (mW)	Measured SAR (W/kg)	Normalized SAR (W/kg)	Dipole SAR (W/kg)	Tolerance (%)
2026.03.25	Head	2450	100	2.440	24.40	24.70	-1.21
2026.03.25	Head	5250	100	2.240	22.40	22.00	1.82
2026.03.26	Head	5600	100	2.330	23.30	23.10	0.87
2026.03.26	Head	5750	100	2.180	21.80	21.90	-0.46

Note: The tolerance limit of System validation $\pm 10\%$.

Please refer the document "Ti-EE26030353-ASC.pdf".

ANNEX C TEST DATA

Please refer the document “Ti-EE26030353-ATD.pdf”.

ANNEX D EUT EXTERNAL PHOTOS

Please refer the document “Ti-EE26030353-AW.pdf”.

ANNEX E SAR TEST SETUP PHOTOS

Please refer the document “Ti-EE26030353-AS.pdf”.

ANNEX F CALIBRATION REPORT

Please refer the document “Ti-EE26030353-AC.pdf”.

ANNEX G TUNE-UP PROCEDURE

Please refer the document “Ti-EE26030353-AT.pdf”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--