

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C REQUIREMENT**

OF

WATERPROOF MEDIA PLAYER

**Model No.: AQ-MP-5BT, AQ-MP-5BT-H, AQ-MP-5BTS, AQ-MP-5BT-HS,
SM-78XB, SM-78XB-H, SM-78XBS, SM-78XB-HS**

Trademark: AQUATIC AV

FCC ID: WBQ-SM78

Report No.: KAD141125085E

Issue Date: April 24, 2015

Prepared for

**AQUATIC AV
282 Kinney Drive San Jose, CA 95112. US**

Prepared by

DONGGUAN EMTEK CO., LTD.

**No.281, Guantai Road, Nancheng District,
Dongguan, Guangdong, China
TEL: 86-769-22807078
FAX: 86-769-22807079**

**This report shall not be reproduced, except in full, without the written approval of
DONGGUAN EMTEK CO., LTD.**

VERIFICATION OF COMPLIANCE

Applicant:	AQUATIC AV 282 Kinney Drive San Jose, CA 95112. US
Manufacturer:	AQUATIC AV 282 Kinney Drive San Jose, CA 95112. US
Product Description:	WATERPROOF MEDIA PLAYER
Trademark:	AQUATIC AV
Model Number:	AQ-MP-5BT, AQ-MP-5BT-H, AQ-MP-5BTS, AQ-MP-5BT-HS, SM-78XB, SM-78XB-H, SM-78XBS, SM-78XB-HS (Note: The samples are the same except appearance (for color and silk-screen only) and model number. So we prepared AQ-MP-5BT for full test.)
Kind of Device:	Bluetooth Ver.2.1+EDR
Date of Test:	November 25, 2014 to April 22, 2015

We hereby certify that:

The above equipment was tested by DONGGUAN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4-2014 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247(2014).

Approved By



**Sam Lv / Q.A. Manager
DONGGUAN EMTEK CO., LTD.**

Modified Information

Version	Summary	Revision Date	Report No.
Ver.1.0	Original Report	/	KAD141125085E

Table of Contents

1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION.....	6
1.2 RELATED SUBMITTAL(S) / GRANT (S).....	6
1.3 TEST METHODOLOGY.....	6
1.4 SPECIAL ACCESSORIES.....	6
1.5 EQUIPMENT MODIFICATIONS	6
1.6 TEST FACILITY	7
2. SYSTEM TEST CONFIGURATION.....	8
2.1 EUT CONFIGURATION.....	8
2.2 EUT EXERCISE	8
2.3 TEST PROCEDURE	8
2.4 LIMITATION.....	8
2.5 CONFIGURATION OF TESTED SYSTEM	12
3. SUMMARY OF TEST RESULTS	13
4. DESCRIPTION OF TEST MODES	13
5. RADIATED EMISSION TEST.....	14
5.1 MEASUREMENT PROCEDURE	14
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	15
5.3 MEASUREMENT EQUIPMENT USED:	16
5.4 MEASUREMENT RESULT	16
5.5 RADIATED MEASUREMENT PHOTOS:	28
6. CHANNEL SEPARATION TEST.....	29
6.1 MEASUREMENT PROCEDURE	29
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	29
6.3 MEASUREMENT EQUIPMENT USED:	29
6.4 MEASUREMENT RESULTS:.....	29
7. 20DB BANDWIDTH TEST	36
7.1 MEASUREMENT PROCEDURE	36
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	36
7.3 MEASUREMENT EQUIPMENT USED:	36
7.4 MEASUREMENT RESULTS:.....	36
8. QUANTITY OF HOPPING CHANNEL TEST	43
8.1 MEASUREMENT PROCEDURE	43
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	43
8.3 MEASUREMENT EQUIPMENT USED:	43
8.4 MEASUREMENT RESULTS:.....	43

9. TIME OF OCCUPANCY (DWELL TIME) TEST	44
9.1 TEST DESCRIPTION	44
9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	44
9.3 MEASUREMENT EQUIPMENT USED:	44
9.4 TEST REQUIREMENTS / LIMITS	44
9.3 MEASUREMENT RESULTS:.....	45
10. MAXIMUM PEAK OUTPUT POWER TEST	47
10.1 MEASUREMENT PROCEDURE	47
10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	47
10.3 MEASUREMENT EQUIPMENT USED:	47
10.4 MEASUREMENT RESULTS:.....	48
11. BAND EDGE TEST	54
11.1 MEASUREMENT PROCEDURE	54
11.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	54
11.3 MEASUREMENT EQUIPMENT USED:	55
11.4 MEASUREMENT RESULTS:.....	56
12. ANTENNA APPLICATION	58
12.1 ANTENNA REQUIREMENT	58
12.2 RESULT	58

1. GENERAL INFORMATION

1.1 Product Description

The AQUATIC AV, Model: AQ-MP-5BT (referred to as the EUT in this report) The EUT is an short range, lower power transmitter. It is designed by way of utilizing the following modulation achieves the system operating.

A major technical descriptions of EUT is described as following:

- A). Operation Frequency: 2402-2480MHz
- B). Kind of Device: Bluetooth Ver.2.1+EDR
- C).Modulation: GFSK, $\pi/4$ -DQPSK, 8DPSK
- D).Number of Channel: 79
- E). Channel space: 1MHz
- F). Measured RF Output Power: 0.31dBm(0. 001074W)
- G). Antenna Type: Wire Antenna
- H). Antenna Gain: 4dBi
- I). Power Supply: DC 9.3-14.4V
- J).Software Version: V02
- K).Hardware Version: DC-02A

The basic data rate of 1Mbps uses GFSK modulation and the enhanced data rate uses PSK modulation. For the enhanced data rate of 3Mbps 8DPSK modulation and of 2Mbps $\pi/4$ -DQPSK modulation is used.

1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: WBQ-SM78 filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules and FCC Public Notice DA 00-705.

1.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4-2014. Radiated testing was performed at an antenna to EUT distance 3 meters.

1.4 Special Accessories

Not available for this EUT intended for grant.

1.5 Equipment Modifications

Not available for this EUT intended for grant.

1.6 Test Facility

Site Description

EMC Lab. :
Registered on FCC, June 18, 2014
The Certificate Number is 247565

Registered on Industry Canada, February 19, 2014
The Certificate Number is 9444A.

Name of Firm : DONGGUAN EMTEK CO., LTD.
Site Location : No.281, Guantai Road, Nancheng District,
Dongguan, Guangdong, China

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. the Tx frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4-2014. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission according to the requirements in Section 13.1.4.1 of ANSI C63.4-2014

2.4 Limitation

(1) Channel Separation test

FCC Part 15, Subpart C Section 15.247(a)(1). Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20 Bandwidth of the hopping channel, whichever is greater.

Frequency Range (MHz)	Limit(kHz)
902-928	>25kHz
2400-2483.5	>25kHz
5725-5850	>25kHz

(2) 20dB Bandwidth

Frequency Range(MHz)	Quantity of Hopping Channel	Limit(kHz)			
		50	25	15	75
902-928		<250	>250	NA	NA
2400-2483.5		NA	NA	>1000	<1000

(3) Quantity of Hopping Channel

FCC Part 15, Subpart C Section 15.247

Frequency Range (MHz)	Limit(Quantity of Hopping Channel)			
	20dB bandwidth <250kHz	20dB bandwidth >250kHz	20dB bandwidth <1MHz	20dB bandwidth >1MHz
902-928	50	25	NA	NA
2400-2483.5	NA	NA	15	15
5725-5850	NA	NA	75	NA

(4) Time of Occupancy(Dwell Time)

FCC Part 15, Subpart C Section 15.247

Frequency Range (MHz)	LIMIT(rms)		
	20dB bandwidth <250kHz(50Channel)	20dB bandwidth >250kHz(25Channel)	20dB bandwidth <1MHz(75Channel)
902-928	400(20S)	400(10S)	NA
2400-2483.5	NA	NA	400(30S)
5725-5850	NA	NA	400(30S)

Note: The “()” is all channel’s average time of occupancy.

(5) Maximum Peak Output Power

FCC Part 15, Subpart C Section 15.247

Frequency Range (MHz)	Quantity of Hopping Channel	LIMIT(W)			
		50	25	15	75
902-928		1(30dBm)	0.125(21dBm)	NA	NA
2400-2483.5		NA	NA	0.125(21dBm)	1(30dBm)
5725-5850		NA	NA	NA	1(30dBm)

(6) Band edge

FCC Part15, Subpart C Section 15.247, In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, attenuation below the general limits specified in section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a).

Operating Frequency Range(MHz)	Spurious emission frequency	Limit Peak power ratio to emission(dBc)	Emission level(dBuV/m)
902-928	<902	>20	NA
	>928	>20	NA
	960-1240	NA	54
2400-2483.5	<2400	>20	NA
	>2483.5-2500	NA	54
	<5350-5460	NA	54
5725-5850	<5725	>20	NA
	>5850	>20	NA

(7) Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

(8) Radiated Emission

FCC Part 15, Subpart C Section 15.209 limit of radiated emission for frequency below 1000GHz. The emissions from an intentional radiator shall not exceed the field strength level specified in the following table:

Frequency (MHz)	Field strength $\mu\text{V/m}$	Distance(m)	Field strength at 3m $\text{dB}\mu\text{V/m}$
0.009-0.490	2400/F(kHz)	300	/
0.490-1.705	24000/F(kHz)	30	/
1.705-30.0	30	30	/
30-88	100	3	40
88-216	150	3	43.5
216-960	200	3	46
Above 960	500	3	54

Remark 1. Emission level in $\text{dB}\mu\text{V/m} = 20 \log (\mu\text{V/m})$

: 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

FCC Part 15, Section 15.35(b) limit of radiated emission for frequency above 1000MHz

Frequency(MHz)	Class A($\text{dB}\mu\text{V/m}$)(at 3m)		Class B($\text{dB}\mu\text{V/m}$)(at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80.0	60.0	74.0	54.0

FCC Part 15, Subpart C Section 15.249. The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Frequency(MHz)	Filed Strength of Fundamental(at 3m)		Filed Strength of Harmonics(at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
902-928	114	94	74.0	54.0
2400-2483.5	114	94	74.0	54.0
5725-5875	114	94	74.0	54.0
24000-24250	128	108	88.0	68.0

2.5 Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

Item	Equipment	Trademark	Model No.	FCC ID	Note
1.	WATERPROOF MEDIA PLAYER	AQUATIC AV	AQ-MP-5BT	WBQ-SM78	EUT
2	DC Power	DF	6-QA-120S	N/A	Support Equipment

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column , device(s) used in tested system is a support equipment.

3. Summary of Test Results

FCC Rules	Description Of Test	Result
§15.247(a)(1)	Channel Separation test	Compliant
§15.247(a)(1)	20dB Bandwidth	Compliant
§15.247(a)(1)(iii)	Quantity of Hopping Channel	Compliant
§15.247(a)(1)(iii)	Time of Occupancy(Dwell Time)	Compliant
§15.247(b)	Max Peak output Power test	Compliant
§15.247(d)	Band edge test	Compliant
§15.207	AC Power Conducted Emission	N/A
§15.247(d),§15.209	Radiated Emission	Compliant
§15.203	Antenna Requirement	Compliant
§1.1310	RF Exposure	Compliant

Remark: The EUT is supplied by Battery, there is no need for AC Power Conducted Emission test to be performed on this product.

4. Description of test modes

The EUT has been tested under TX operating condition.

This EUT is a FHSS system, were conducted to determine the final configuration from all possible combinations. We use software control the EUT, Let EUT hopping on and transmit with highest power, All the modes GFSK, $\pi/4$ -DQPSK, 8DPSK have been tested. 79 Channels are provided by EUT. The 3 channels of lower, medium and higher were chosen for test.

Channel	Frequency(MHz)
1	2402
40	2441
79	2480

5. Radiated Emission Test

5.1 Measurement Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured were complete.
5. For range 9KHz~30MHz, The measured value is really too low to be recorded.

When spectrum scanned from 30MHz to 1GHz setting resolution bandwidth 120KHz and video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	120KHz
VB	300KHz
Detector	QP
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	Peak
Trace	Max hold

5.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



5.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	06/15/2013	06/14/2014
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	06/15/2013	06/14/2014
Pre-Amplifier	HP	8447D	2944A07999	06/02/2013	06/01/2014
Bilog Antenna	SCHWARZBECK	VULB9163	142	06/03/2013	06/02/2014
Loop Antenna	ARA	PLA-1030/B	1029	06/03/2013	06/02/2014
Horn Antenna	Schwarzbeck	BBHA9170	BBHA9170399	06/04/2013	06/03/2014
Horn Antenna	Schwarzbeck	BBHA9120D	D143	06/04/2013	06/03/2014
Cable	Schwarzbeck	AK9513	ACRX1	06/15/2013	06/14/2014
Cable	Schwarzbeck	AK9513	FP2RX2	05/15/2013	05/14/2014
Cable	Schwarzbeck	AK9513	CRPX1	05/17/2013	05/16/2014
Cable	Schwarzbeck	AK9513	CRRX2	05/22/2013	05/21/2014

5.4 Measurement Result

Below 30MHz:

All the modulation modes were tested the data of the test mode are recorded in the following pages.

Operation Mode: TX Mode Test Date : November 29, 2014
Frequency Range: 9KHz~30MHz Temperature : 28℃
Test Result: PASS Humidity : 60 %
Measured Distance: 3m Test By: Andy

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.


Distance extrapolation factor = $40\log(\text{Specific distance}/\text{test distance})$ (dB);

Limit line = Specific limits (dBuV) + distance extrapolation factor.

Below 1000MHz:

Pass.

Please refer to the following data.



Site Chamber #1

Polarization: **Horizontal**

Temperature: 26

Limit: (RE)FCC PART 15 class B 3m

Power: DC 14.4V

Humidity: 55 %


Mode: TX2402(GFSK)

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		69.7700	45.43	-22.04	23.39	40.00	-16.61	QP		
2		121.1800	44.07	-16.82	27.25	43.50	-16.25	QP		
3	*	132.8200	50.65	-16.39	34.26	43.50	-9.24	QP		
4		178.4100	52.70	-18.79	33.91	43.50	-9.59	QP		
5		218.1800	49.04	-16.27	32.77	46.00	-13.23	QP		
6		266.6800	47.92	-15.29	32.63	46.00	-13.37	QP		

*:Maximum data x:Over limit !:over margin

Operator: Hugh



Site Chamber #1

Polarization: **Vertical**

Temperature: 26

Limit: (RE)FCC PART 15 class B 3m

Power: DC 14.4V

Humidity: 55 %


Mode: TX2402(GFSK)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		47.4600	39.39	-14.38	25.01	40.00	-14.99	QP		
2	*	133.7900	49.39	-16.45	32.94	43.50	-10.56	QP		
3		156.1000	44.24	-18.25	25.99	43.50	-17.51	QP		
4		201.6900	44.28	-17.60	26.68	43.50	-16.82	QP		
5		224.0000	43.55	-16.18	27.37	46.00	-18.63	QP		
6		331.6700	37.97	-13.22	24.75	46.00	-21.25	QP		

*:Maximum data x:Over limit !:over margin

Operator: Hugh



Site Chamber #1

Polarization: **Horizontal**

Temperature: 26

Limit: (RE)FCC PART 15 class B 3m

Power: DC 14.4V

Humidity: 55 %


Mode: TX2402(Pi-4/DQPSK)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		70.7400	51.03	-22.19	28.84	40.00	-11.16	QP		
2		130.8800	47.86	-16.29	31.57	43.50	-11.93	QP		
3		153.1900	48.61	-18.03	30.58	43.50	-12.92	QP		
4		177.4400	49.39	-18.75	30.64	43.50	-12.86	QP		
5	*	201.6900	51.31	-17.60	33.71	43.50	-9.79	QP		
6		218.1800	50.36	-16.27	34.09	46.00	-11.91	QP		

*:Maximum data x:Over limit !:over margin

Operator: Hugh



Site Chamber #1

Polarization: **Vertical**

Temperature: 26

Limit: (RE)FCC PART 15 class B 3m

Power: DC 14.4V

Humidity: 55 %


Mode: TX2402(Pi/4-DQPSK)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		70.7400	52.57	-22.19	30.38	40.00	-9.62			
2		130.8800	44.37	-16.38	27.99	43.50	-15.51			
3	*	153.1900	52.28	-18.03	34.25	43.50	-9.25			
4		177.4400	47.76	-18.75	29.01	43.50	-14.49			
5		201.6900	44.45	-17.60	26.85	43.50	-16.65			
6		331.6700	40.50	-13.22	27.28	46.00	-18.72			

*:Maximum data x:Over limit !:over margin


Operator: Hugh



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	69.7700	52.90	-22.04	30.86	40.00	-9.14	QP		
2		130.8800	48.06	-16.29	31.77	43.50	-11.73	QP		
3		153.1900	50.15	-18.03	32.12	43.50	-11.38	QP		
4		177.4400	50.06	-18.75	31.31	43.50	-12.19	QP		
5		201.6900	49.89	-17.60	32.29	43.50	-11.21	QP		
6		218.1800	48.47	-16.27	32.20	46.00	-13.80	QP		

*:Maximum data x:Over limit !:over margin

Operator: Hugh



Site: Chamber #1
 Limit: (RE)FCC PART 15 class B 3m
 Mode: TX2402(8DPSK)
 Note:

Polarization: **Vertical**
 Power: DC 14.4V
 Temperature: 26
 Humidity: 55 %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		70.7400	52.11	-22.19	29.92	40.00	-10.08	QP		
2		130.8800	44.04	-16.38	27.66	43.50	-15.84	QP		
3	*	153.1900	53.57	-18.03	35.54	43.50	-7.96	QP		
4		177.4400	46.76	-18.75	28.01	43.50	-15.49	QP		
5		299.6600	42.18	-14.34	27.84	46.00	-18.16	QP		
6		348.1600	43.66	-12.99	30.67	46.00	-15.33	QP		

*:Maximum data x:Over limit !:over margin

Operator: Hugh

Above 1000MHz~10th Harmonics:

Operation Mode: GFSK (CH1: 2402MHz) Test Date : November 29, 2014

Freq.	Ant. Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK	AV	PK	AV	PK	AV
4804	V	65.23	43.28	74	54	-8.77	-10.72
7206	V	64.08	42.19	74	54	-9.92	-11.81
9608	V	63.12	41.07	74	54	-10.88	-12.93
12010	V	62.85	40.22	74	54	-11.15	-13.78
14412	V	61.07	39.54	74	54	-12.93	-14.46
16814	V	60.33	38.72	74	54	-13.67	-15.28
4804	H	66.75	45.19	74	54	-7.25	-8.81
7206	H	65.72	44.07	74	54	-8.28	-9.93
9608	H	64.19	43.95	74	54	-9.81	-10.05
12010	H	63.85	42.13	74	54	-10.15	-11.87
14412	H	62	41.08	74	54	-12	-12.92
16814	H	61.72	40.95	74	54	-12.28	-13.05

Operation Mode: GFSK (CH40: 2441MHz) Test Date : November 29, 2014

Freq.	Ant. Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK	AV	PK	AV	PK	AV
4882	V	65.13	44.33	74	54	-8.87	-9.67
7323	V	64.82	43.65	74	54	-9.18	-10.35
9764	V	63.18	42.85	74	54	-10.82	-11.15
12205	V	62.85	41.75	74	54	-11.15	-12.25
14646	V	61.07	40.69	74	54	-12.93	-13.31
17087	V	60.59	39.85	74	54	-13.41	-14.15
4882	H	64.39	45.32	74	54	-9.61	-8.68
7323	H	63.95	44.76	74	54	-10.05	-9.24
9764	H	62.78	43.51	74	54	-11.22	-10.49
12205	H	61.85	42.68	74	54	-12.15	-11.32
14646	H	60.73	41.05	74	54	-13.27	-12.95
17087	H	59.84	40.85	74	54	-14.16	-13.15

Operation Mode: TX Mode (CH79: 2480MHz) Test Date : November 29, 2014

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4960	V	66.33	45.13	74	54	-7.67	-8.87
7440	V	65.82	44.05	74	54	-8.18	-9.95
9920	V	64.13	43.95	74	54	-9.87	-10.05
12400	V	63.82	42.18	74	54	-10.18	-11.82
14880	V	62.05	41.08	74	54	-11.95	-12.92
17360	V	61.72	40.22	74	54	-12.28	-13.78
4960	H	65.59	44.88	74	54	-8.41	-9.12
7440	H	64.37	43.95	74	54	-9.63	-10.05
9920	H	63.82	42.75	74	54	-10.18	-11.25
12400	H	62.19	41.06	74	54	-11.81	-12.94
14880	H	61.07	40.85	74	54	-12.93	-13.15
17360	H	60.85	39.55	74	54	-13.15	-14.45

Operation Mode: Pi/4-DQPSK (CH1: 2402MHz) Test Date : November 29, 2014

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4804	V	65.12	44.02	74	54	-8.88	-9.98
7206	V	64.05	43.18	74	54	-9.95	-10.82
9608	V	63.82	42.92	74	54	-10.18	-11.08
12010	V	62.11	41.05	74	54	-11.89	-12.95
14412	V	61.05	40.25	74	54	-12.95	-13.75
16814	V	60.72	45.13	74	54	-13.28	-8.87
4804	H	66.13	44.72	74	54	-7.87	-9.28
7206	H	65.05	43.65	74	54	-8.95	-10.35
9608	H	64.72	42.15	74	54	-9.28	-11.85
12010	H	63.18	41.04	74	54	-10.82	-12.96
14412	H	62.05	40.36	74	54	-11.95	-13.64
16814	H	61.79	39.58	74	54	-12.21	-14.42

Operation Mode: Pi/4-DQPSK (CH40: 2441MHz) Test Date : November 29, 2014

Freq.	Ant. Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK	AV	PK	AV	PK	AV
4882	V	65.13	44.15	74	54	-8.87	-9.85
7323	V	64.72	43.05	74	54	-9.28	-10.95
9764	V	63.05	42.62	74	54	-10.95	-11.38
12205	V	62.15	41.82	74	54	-11.85	-12.18
14646	V	61.82	40.36	74	54	-12.18	-13.64
17087	V	60.36	39.78	74	54	-13.64	-14.22
4882	H	66.22	45.05	74	54	-7.78	-8.95
7323	H	65.15	44.36	74	54	-8.85	-9.64
9764	H	64.42	43.15	74	54	-9.58	-10.85
12205	H	63.29	42.08	74	54	-10.71	-11.92
14646	H	62.71	41.92	74	54	-11.29	-12.08
17087	H	60.25	40.65	74	54	-13.75	-13.35

Operation Mode: Pi/4-DQPSK (CH79: 2480MHz) Test Date : November 29, 2014

Freq.	Ant. Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK	AV	PK	AV	PK	AV
4960	V	66.22	45.15	74	54	-7.78	-8.85
7440	V	65.05	44.05	74	54	-8.95	-9.95
9920	V	64.15	43.12	74	54	-9.85	-10.88
12400	V	63.72	42.04	74	54	-10.28	-11.96
14880	V	62.18	41.92	74	54	-11.82	-12.08
17360	V	61.72	40.05	74	54	-12.28	-13.95
4960	H	65.05	45.18	74	54	-8.95	-8.82
7440	H	64.36	44.36	74	54	-9.64	-9.64
9920	H	63.15	43.62	74	54	-10.85	-10.38
12400	H	62.92	42.85	74	54	-11.08	-11.15
14880	H	60.42	41.72	74	54	-13.58	-12.28
17360	H	58.79	40.95	74	54	-15.21	-13.05

Operation Mode: 8DPSK (CH1: 2402MHz) Test Date : November 29, 2014

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4804	V	65.42	44.25	74	54	-8.58	-9.75
7206	V	64.15	43.15	74	54	-9.85	-10.85
9608	V	63.25	42.01	74	54	-10.75	-11.99
12010	V	62.04	41.36	74	54	-11.96	-12.64
14412	V	61.74	40.25	74	54	-12.26	-13.75
16814	V	60.65	38.79	74	54	-13.35	-15.21
4804	H	66.36	45.15	74	54	-7.64	-8.85
7206	H	65.74	44.25	74	54	-8.26	-9.75
9608	H	64.71	43.66	74	54	-9.29	-10.34
12010	H	63.15	42.15	74	54	-10.85	-11.85
14412	H	62.05	40.28	74	54	-11.95	-13.72
16814	H	61.75	38.42	74	54	-12.25	-15.58

Operation Mode: 8DPSK (CH40: 2441MHz) Test Date : November 29, 2014

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4882	V	66.33	45.25	74	54	-7.67	-8.75
7323	V	65.25	44.13	74	54	-8.75	-9.87
9764	V	64.15	43.25	74	54	-9.85	-10.75
12205	V	63.28	42.18	74	54	-10.72	-11.82
14646	V	62.74	41.92	74	54	-11.26	-12.08
17087	V	61.05	40.34	74	54	-12.95	-13.66
4882	H	66.25	46.25	74	54	-7.75	-7.75
7323	H	65.13	45.01	74	54	-8.87	-8.99
9764	H	64.01	44.85	74	54	-9.99	-9.15
12205	H	63.24	43.15	74	54	-10.76	-10.85
14646	H	62.36	42.13	74	54	-11.64	-11.87
17087	H	61.04	40.72	74	54	-12.96	-13.28

Operation Mode: 8DPSK (CH79: 2480MHz) Test Date : November 29, 2014



Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4960	V	65.74	44.01	74	54	-8.26	-9.99
7440	V	64.18	43.25	74	54	-9.82	-10.75
9920	V	63.25	42.62	74	54	-10.75	-11.38
12400	V	62.95	41.36	74	54	-11.05	-12.64
14880	V	61.42	40.25	74	54	-12.58	-13.75
17360	V	60.32	38.79	74	54	-13.68	-15.21
4960	H	66.25	45.15	74	54	-7.75	-8.85
7440	H	65.14	44.05	74	54	-8.86	-9.95
9920	H	64.36	43.36	74	54	-9.64	-10.64
12400	H	62.25	42.18	74	54	-11.75	-11.82
14880	H	60.36	41.72	74	54	-13.64	-12.28
17360	H	59.42	40.53	74	54	-14.58	-13.47

Other harmonics emissions are lower than 20dB below the allowable limit.

Note:

- (1) All Readings are Peak Value and AV.
- (2) Emission Level= Reading Level+ Probe Factor +Cable Loss.
- (3) The average measurement was not performed when the peak measured data under the limit of average detection.

5.5 Radiated Measurement Photos:




6. Channel Separation test

6.1 Measurement Procedure

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

6.2 Test SET-UP (Block Diagram of Configuration)



6.3 Measurement Equipment Used:



EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	05/16/2014	05/15/2015
Coaxial Cable	CDS	79254	46107086	05/16/2014	05/15/2015
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	05/16/2014	05/15/2015


6.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	November 29, 2014
Test By:	Andy	Temperature :	24°C
Test Result:	PASS	Humidity :	53 %
Modulation:	GFSK		



Channel number	Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit 20dB Down BW(kHz)
1	2402	1001	>818
40	2441	1001	>818
79	2480	1001	>815






Spectrum Detector:	PK	Test Date :	November 29, 2014
Test By:	Andy	Temperature :	24°C
Test Result:	PASS	Humidity :	53 %
Modulation:	1/4Π-DQPSK		



Channel number	Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit 2/3 20dB Down BW(kHz)
1	2402	1001	>828
40	2441	1001	>828
79	2480	1001	>828






Spectrum Detector:	PK	Test Date :	November 29, 2014
Test By:	Andy	Temperature :	24°C
Test Result:	PASS	Humidity :	53 %
Modulation:	8DPSK		

Channel number	Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit 2/3 20dB Down BW(kHz)
1	2402	1001	>812
40	2441	1001	>818
79	2480	1001	>810






7. 20dB Bandwidth test

7.1 Measurement Procedure

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

7.2 Test SET-UP (Block Diagram of Configuration)



7.3 Measurement Equipment Used:



EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	05/16/2014	05/15/2015
Coaxial Cable	CDS	79254	46107086	05/16/2014	05/15/2015
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	05/16/2014	05/15/2015


7.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	November 29, 2014
Test By:	Andy	Temperature :	25 °C
Test Result:	PASS	Humidity :	50 %
Modulation:	GFSK		

Channel number	Channel frequency (MHz)	20dB Down BW(KHz)
1	2402	818
40	2441	818
79	2480	815








Spectrum Detector: PK
 Test By: Andy
 Test Result: PASS
 Modulation: $\pi/4$ -DQPSK

Test Date : November 29, 2014
 Temperature : 24°C
 Humidity : 53 %



Channel number	Channel frequency (MHz)	20dB Down BW(kHz)
1	2402	1243
40	2441	1243
79	2480	1243






Spectrum Detector:	PK	Test Date :	November 29, 2014
Test By:	Andy	Temperature :	24°C
Test Result:	PASS	Humidity :	53 %
Modulation:	8DPSK		

Channel number	Channel frequency (MHz)	20dB Down BW(kHz)
1	2402	1219
40	2441	1228
79	2480	1216






8. Quantity of Hopping Channel Test

8.1 Measurement Procedure

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used:


EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	05/16/2014	05/15/2015
Coaxial Cable	CDS	79254	46107086	05/16/2014	05/15/2015
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	05/16/2014	05/15/2015

8.4 Measurement Results:

Worst test modulation GFSK

Spectrum Detector:	PK	Test Date :	November 29, 2014
Test By:	Andy	Temperature :	25 °C
Test Result:	PASS	Humidity :	50 %

Hopping Channel Frequency Range	Quantity of Hopping Channel	Quantity of Hopping Channel
2402-2480	79	> 15



9. Time of Occupancy (Dwell Time) test

9.1 Test Description

The Equipment Under Test (EUT) was set up to perform the dwell time measurements. The EUT was connected to the spectrum analyzer via a short coax cable. The dwell time is calculated by:


Dwell time = time slot length * hop rate / number of hopping channels * 31.6s

with:

- hop rate = $1600/2 * 1/s$ for DH1 packets = 1600 s^{-1}
- hop rate = $1600/4 * 1/s$ for DH3 packets = 533.33 s^{-1}
- hop rate = $1600/6 * 1/s$ for DH5 packets = 320 s^{-1}
- number of hopping channels = 79
- $31.6 \text{ s} = 0.4 \text{ seconds multiplied by the number of hopping channels} = 0.4 \text{ s} * 79$

The highest value of the dwell time is reported.

9.2 Test SET-UP (Block Diagram of Configuration)



9.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	05/16/2014	05/15/2015
Coaxial Cable	CDS	79254	46107086	05/16/2014	05/15/2015
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	05/16/2014	05/15/2015

9.4 Test Requirements / Limits


FCC Part 15, Subpart C, §15.247 (a) (1) (iii)

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Since the Bluetooth technology uses 79 channels this period is calculated to be 31.6seconds. Refer to attached data chart.


9.3 Measurement Results:

Packet type	Time slot length(ms)	Dwell time	Dwell time(ms)
DH1	0.417	time slot length *1600/2 /79 * 31.6	133.44
DH3	1.674	time slot length *1600/4 /79 * 31.6	267.84
DH5	2.920	time slot length *1600/6 /79 * 31.6	311.47


DH1:



DH3:



DH5:




10. MAXIMUM PEAK OUTPUT POWER TEST

10.1 Measurement Procedure

- Check the calibration of the measuring instrument(SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- The center frequency of the spectrum analyzer is set to the fundamental frequency and using proper RBW and VBW setting.
- Measure the captured power within the band and recording the plot.
- Repeat above procedures until all frequencies required were complete.

10.2 Test SET-UP (Block Diagram of Configuration)



10.3 Measurement Equipment Used:


EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	05/16/2014	05/15/2015
Coaxial Cable	CDS	79254	46107086	05/16/2014	05/15/2015
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	05/16/2014	05/15/2015



10.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	November 29, 2014
Test By:	Andy	Temperature :	25 °C
Test Result:	PASS	Humidity :	50 %
Modulation:	GFSK		


Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(mW)	Pass/Fail
01	2402	-0.24	0.946	1000	PASS
40	2441	-0.3	0.933	1000	PASS
79	2480	0.31	1.074	1000	PASS







Spectrum Detector:	PK	Test Date :	November 29, 2014
Test By:	Andy	Temperature :	25 °C
Test Result:	PASS	Humidity :	50 %
Modulation:	Π/4-DQPSK		


Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(mW)	Pass/Fail
01	2402	-1.170	0.764	125	PASS
40	2441	-1.100	0.776	125	PASS
79	2480	-0.610	0.869	125	PASS







Spectrum Detector:	PK	Test Date :	November 29, 2014
Test By:	Andy	Temperature :	25 °C
Test Result:	PASS	Humidity :	50 %
Modulation:	8DPSK		

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(mW)	Pass/Fail
01	2402	-1.030	0.789	125	PASS
40	2441	-1.180	0.762	125	PASS
79	2480	-0.510	0.889	125	PASS





11. Band EDGE test

11.1 Measurement Procedure

1. The EUT was Operating in hopping mode or could be controlled its channel. Printed out test result from the spectrum by hard copy function.
2. The EUT was placed on a turn table which is 0.8m above ground plane.
3. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
4. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
5. Repeat above procedures until all frequency measured were complete.

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	Peak
Trace	Max hold

11.2 Test SET-UP (Block Diagram of Configuration)

For Conducted Test



For Radiated emission Test



11.3 Measurement Equipment Used:

For Conducted Test

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	05/16/2014	05/15/2015
Coaxial Cable	CDS	79254	46107086	05/16/2014	05/15/2015
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	05/16/2014	05/15/2015

For Radiated emission Test

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	05/16/2014	05/15/2015
Pre-Amplifier	HP	8447D	2944A07999	05/16/2014	05/15/2015
Bilog Antenna	SCHWARZBECK	VULB9163	142	05/16/2014	05/15/2015
Loop Antenna	ARA	PLA-1030/B	1029	05/16/2014	05/15/2015
Horn Antenna	Schwarzbeck	BBHA9170	BBHA9170399	05/16/2014	05/15/2015
Horn Antenna	Schwarzbeck	BBHA9120D	D143	05/16/2014	05/15/2015
Cable	Schwarzbeck	AK9513	ACRX1	05/19/2014	05/18/2015
Cable	Schwarzbeck	N/A	FP2RX2	05/19/2014	05/18/2015
Cable	Schwarzbeck	AK9513	CRPX1	05/19/2014	05/18/2015
Cable	Schwarzbeck	AK9513	CRRX2	05/19/2014	05/18/2015

11.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	November 29, 2014
Test By:	Andy	Temperature :	25 °C
Test Result:	PASS	Humidity :	50 %

1. Conducted Test

For Non-Hopping Mode:

Frequency (MHz)	Modulation	Peak Power Output(dBm)	Emission read Value(dBm)	Result of Band edge(dBc)	Band edge Limit(dBc)
2399.99	GFSK	-0.38	-42.86	42.48	>20dBc
2399.98	pi/4-DQPSK	-2.02	-46.66	44.64	>20dBc
2399.98	8DPSK	-1.97	-46.76	44.79	>20dBc
2483.98	GFSK	0.32	-51	51.32	>20dBc
2484.00	pi/4-DQPSK	-1.14	-44.09	42.95	>20dBc
2484.01	8DPSK	-1.32	-45.9	44.58	>20dBc

For Hopping Mode:

Frequency (MHz)	Modulation	Peak Power Output(dBm)	Emission read Value(dBm)	Result of Band edge(dBc)	Band edge Limit(dBc)
2399.98	GFSK	-0.37	-44.46	44.09	>20dBc
2399.98	pi/4-DQPSK	-2.01	-48.69	46.68	>20dBc
2399.99	8DPSK	1.98	-47.88	49.86	>20dBc
2486.96	GFSK	0.31	-52.6	52.91	>20dBc
2483.51	pi/4-DQPSK	-1.23	-45.82	44.59	>20dBc
2484.31	8DPSK	-1.35	-46.35	45	>20dBc

2. Radiated emission Test

Worst test modulation GFSK

For Non-Hopping Mode:

Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)	
		PK	AV	PK	AV	PK	AV
2398.456	H	63.25	45.04	74	54	-10.75	-8.96
2399.157	V	57.15	40.68	74	54	-16.85	-13.32
2484.013	H	65.72	44.13	74	54	-8.28	-9.87
2483.895	V	59.94	38.48	74	54	-14.06	-15.52

Worst test modulation GFSK

For Hopping Mode:

Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)	
		PK	AV	PK	AV	PK	AV
2399.369	H	63.59	44.23	74	54	-10.41	-9.77
2398.954	V	54.18	40.85	74	54	-19.82	-13.15
2484.123	H	65.24	46.31	74	54	-8.76	-7.69
2484.015	V	56.95	39.55	74	54	-17.05	-14.45

12. Antenna Application

12.1 Antenna requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.203 and 15.247.

FCC part 15C section 15.247 requirements:

Systems operating in the 2402-2480MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

12.2 Result

The EUT used Wire Antenna. The antenna's gain is 4dBi and meets the requirement.

General Appearance of the EUT



