

TEST REPORT

FCC MPE Test for Jaguar Dash Cam Rear
Certification

APPLICANT

Mobile Appliance, Inc.

REPORT NO.

HCT-RF-2008-FC039

DATE OF ISSUE

14 August 2020

Tested by
Kwang Il Yoon



Technical Manager
Jong Seok Lee



HCT CO., LTD.

Soo Chan Lee
SooChan Lee / CEO

HCT CO., LTD.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 F ax. +82 31 645 6401



HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 Fax. +82 31 645 6401

고객비밀
CUSTOMER SECRET

TEST REPORT

FCC MPE Test for
Jaguar Dash Cam
Rear

REPORT NO.

HCT-RF-2008-FC039

DATE OF ISSUE

August 14, 2020

Additional Model

Land Rover Dash Cam Rear

Applicant

Mobile Appliance, Inc.

Gwanyang-dong-1701~1706, Daerung Techno #15, 401, Simin-daero, Dongan-gu, Anyang-si, Gyeonggi-do, Korea

Eut Type Model Name

Jaguar Dash Cam Rear
Jaguar Dash Cam Rear

FCC ID

WHBJLRDASHCAMR

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test results were applied only to the test methods required by the standard.

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	August 14, 2020	Initial Release

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

* The report shall not be reproduced except in full(only partly) without approval of the laboratory.

RF Exposure Statement

1. Limit

According to § 1.1310, § 2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 -				
1.34.....	614	1.63	*(100)	30
1.34 - 30.....	824/f	2.19/f	*(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....			f/1500	30
1500 -			1.0	30
100.000.....				

F = frequency in MHz

* = Plane-wave equivalent power density

2. Maximum Permissible Exposure Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = Power input to antenna

G = Power gain to the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

3. RESULTS

3-1. 24 GHz Radar

Max Average EIRP output Power	-4.01	dBm
Max Average EIRP output Power	0.40	mW
Prediction distance	20.00	cm
Prediction frequency	24050 ~ 24250	MHz
Power density at prediction frequency(S)	0.0001	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²

2.1091

EIRP	-4.01 (dBm)
ERP	-6.16 (dBm)
ERP	0.000 (W)
ERP Limit	3.00 (W)
MARGIN	40.93 (dB)