

RF Exposure Report

Report No.: SA190925C38

FCC ID: WIYQSC20A (For module)

WIYSATURN1KU (For Host)

Original FCC ID: XMR201706SC20A

Test Model: SC20-A

Received Date: Sep. 25, 2019

Date of Evaluation: Oct. 30, 2019

Issued Date: Oct. 30, 2019

Applicant: CASTLES TECHNOLOGY CO., LTD.

Address: 6F, NO. 207-5, SEC. 3, BEIXIN RD., XINDIAN DISTRICT, NEW TAIPEI
CITY 23143, TAIWAN (R. O. C.)

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN

FCC Registration / 788550 / TW0003
Designation Number:



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity.....	4
2 RF Exposure.....	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power.....	6

Release Control Record

Issue No.	Description	Date Issued
SA190925C38	Original release.	Oct. 30, 2019

1 Certificate of Conformity

Product: LTE module (for module)
POS Terminal (For Host)

Brand: Quectel (for module)
CASTLES TECHNOLOGY (For Host)

Test Model: SC20-A (for module)
SATURN1000-E UPT (For Host)

Sample Status: Identical Prototype

Applicant: CASTLES TECHNOLOGY CO., LTD.

Date of Evaluation: Oct. 30, 2019

Standards: FCC Part 2 (Section 2.1091)
KDB 447498 D01 General RF Exposure Guidance v06
IEEE C95.3 -2002

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Polly Chen , **Date:** Oct. 30, 2019
Polly Chen / Specialist

Approved by : Bruce Chen , **Date:** Oct. 30, 2019
Bruce Chen / Senior Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

3 Calculation Result of Maximum Conducted Power

For module (Model: SC20-A, FCC ID: XMR201706SC20A)

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2.4G WLAN	21.64	2.6	20	0.053	1
5G WLAN	13.71	4.9	20	0.014	1
2.4G Bluetooth	7.93	2.6	20	0.002	1

Frequency Band (MHz)	Output Power ERP / EIRP (dBm)	Output Power ERP / EIRP (mW)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
GSM850	30.1	1023.293	20	0.204	0.55
GSM1900	31.1	1288.250	20	0.256	1
WCDMA Band 2	24.8	301.995	20	0.060	1
WCDMA Band 4	25.6	363.078	20	0.072	0.55
WCDMA Band 5	20.1	102.329	20	0.020	1
LTE Band 2	23.6	229.087	20	0.046	1
LTE Band 4	22.3	169.824	20	0.034	1
LTE Band 5	21.1	128.825	20	0.026	0.55
LTE Band 7	22.9	194.984	20	0.039	1
LTE Band 12	23.1	204.174	20	0.041	0.47
LTE Band 13	23.2	208.930	20	0.042	0.52
LTE Band 25	24.4	275.423	20	0.055	1
LTE Band 26	22.8	190.546	20	0.038	0.54

For Host:

Mode	Electric field (dBuV/m) @3m	Electric field (dBuV/m) @10m	Electric field (dBuV/m) @0.2m	Max Power (dBm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
NFC	64.4	53.94	121.90	3.15	0.0004	0.978

Note:

1. The WLAN 2.4GHz and WLAN 5GHz cannot transmit simultaneously.
2. The WLAN 2.4GHz and Bluetooth cannot transmit simultaneously.
3. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

For antenna gain:

Frequency Band	Antenna Gain (dBi)
2.4G WLAN	2.6
5G WLAN	4.9
698-791MHz	0.85
824-960MHz	-0.68
1710-2170MHz	-0.08
2500-2700MHz	0.59

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

1. $WLAN + WWAN = 0.053/1 + 0.256/1 = 0.053+0.256=0.309$
2. $WWAN + BT = 0.256/1 + 0.002/1 = 0.256+0.002=0.258$
3. $WLAN + WWAN + NFC = 0.053/1 + 0.256/1 + 0.0004/0.978 = 0.053+0.256+0.0004=0.3094$
4. $WWAN + BT + NFC = 0.053/1 + 0.002/1 + 0.0004/0.978 = 0.053+0.002+0.0004=0.0554$

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---