FCC RF Test Report

APPLICANT	:	CASTLES TECHNOLOGY CO., LTD.
EQUIPMENT	:	POS Terminal
BRAND NAME	:	CASTLES TECHNOLOGY
MODEL NAME	:	S1F3CT
FCC ID	:	WIYS1F3CT001
STANDARD	:	FCC Part 15 Subpart C §15.247
CLASSIFICATION	:	(DTS) Digital Transmission System
TEST DATE(S)	:	Jun. 22, 2025 ~ Jul. 11, 2025

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia

ACCREDITED Cert #5145.02

Sporton International Inc. (Kunshan)
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**
SUMMARY OF TEST RESULT **4**
1 GENERAL DESCRIPTION **5**
1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 5
1.5 Modification of EUT 5
1.6 Testing Location 6
1.7 Test Software 6
1.8 Applicable Standards 6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **7**
2.1 Carrier Frequency and Channel 7
2.2 Test Mode 7
2.3 Connection Diagram of Test System 8
2.4 Support Unit used in test configuration and system 9
2.5 EUT Operation Test Setup 9
2.6 Measurement Results Explanation Example 9
3 TEST RESULT **10**
3.1 6dB and 99% Bandwidth Measurement 10
3.2 Output Power Measurement 11
3.3 Power Spectral Density Measurement 13
3.4 Conducted Band Edges and Spurious Emission Measurement 14
3.5 Radiated Band Edges and Spurious Emission Measurement 15
3.6 AC Conducted Emission Measurement 19
3.7 Antenna Requirements 21
4 LIST OF MEASURING EQUIPMENT **22**
5 MEASUREMENT UNCERTAINTY **23**
APPENDIX A. CONDUCTED TEST RESULTS
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT
APPENDIX C. RADIATED SPURIOUS EMISSION
APPENDIX D. DUTY CYCLE PLOTS
APPENDIX E. SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR552101C	Rev. 01	Initial issue of report	Jul. 28, 2025

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.1	-	99% Bandwidth	-	Report Only	-
3.2	15.247(b)	Power Output Measurement	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	Conducted Band Edges	≤ 20dBc	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.11 dB at 4924.00 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 11.16 dB at 0.481 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Applicant

CASTLES TECHNOLOGY CO., LTD.
6F, NO. 207-5, SEC. 3, BEIXIN RD., XINDIAN DISTRICT, NEW TAIPEI CITY 231030, TAIWAN (R.O.C.)

1.2 Manufacturer

CASTLES TECHNOLOGY CO., LTD.
6F, NO. 207-5, SEC. 3, BEIXIN RD., XINDIAN DISTRICT, NEW TAIPEI CITY 231030, TAIWAN (R.O.C.)

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	POS Terminal
Brand Name	CASTLES TECHNOLOGY
Model Name	S1F3CT
FCC ID	WIYS1F3CT001
SN Code	Conducted: 139245005666 Conduction: 132945005667 Radiation: 132945005677
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to antenna	802.11b : 18.10 dBm (0.0646 W) 802.11g : 23.97 dBm (0.2495 W) 802.11n HT20 : 24.11 dBm (0.2576 W)
99% Occupied Bandwidth	802.11b : 13.018MHz 802.11g : 17.309MHz 802.11n HT20 : 18.182MHz
Antenna Type / Gain	Monopole Antenna type with gain -3.7 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	CO01-KS 03CH03-KS TH01-KS	CN1257	314309

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH03-KS	AUDIX	E3	210616
3.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.

b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	**1 Mbps**
802.11g	**6 Mbps**
802.11n HT20	**MCS0**

Test Cases	
AC Conducted Emission	Mode 1 :WCDMA Band V Idle + Bluetooth Link + WLAN Link (2.4G) + Adapter + Earphone
Remark: For Radiated Test Cases, The tests were performance with Adapter.	

RSE Co-location mode
WLAN 802.11b CH11 Tx + LTE B41 BW 20M Link + NFC Tx

2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Base Station	Anritus	MT8821C	N/A	N/A	Unshielded,1.8m
2.	Bluetooth Earphone	Lenovo	thinkplus-BH3	N/A	N/A	N/A
3.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
4.	Earphone	N/A	N/A	N/A	N/A	N/A
5.	SD Card	Kingston	8GB	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 2.91 dB and 20dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 2.91 + 20 = 22.91 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) ≥ 3*RBW. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1%~5% of OBW and set the Video bandwidth (VBW) approximately three times the RBW.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

TEST RESULTS DATA Peak Output Power												
2.4GHz Band												
Mode						Power Setting	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	Gain(dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass/Fail
Band	SISO	N_{TX}	Channel	Freq (MHz)	Data Rate		Ant 1	Ant 1	Ant 1	Ant 1	Ant 1	
11b	SISO	1	1	2412	1Mbps	17	17.87	30.00	-3.70	14.17	36.00	Pass
11b	SISO	1	6	2437	1Mbps	17	18.10	30.00	-3.70	14.40	36.00	Pass
11b	SISO	1	11	2462	1Mbps	17	17.88	30.00	-3.70	14.18	36.00	Pass
11g	SISO	1	1	2412	6Mbps	15	23.91	30.00	-3.70	20.21	36.00	Pass
11g	SISO	1	6	2437	6Mbps	17	23.97	30.00	-3.70	20.27	36.00	Pass
11g	SISO	1	11	2462	6Mbps	16.5	23.49	30.00	-3.70	19.79	36.00	Pass
HT20	SISO	1	1	2412	MCS0	14	23.98	30.00	-3.70	20.28	36.00	Pass
HT20	SISO	1	6	2437	MCS0	16	24.11	30.00	-3.70	20.41	36.00	Pass
HT20	SISO	1	11	2462	MCS0	16	23.69	30.00	-3.70	19.99	36.00	Pass

3.2.6 Test Result of Average Output Power (Reporting Only)

TEST RESULTS DATA Average Output Power												
2.4GHz Band												
Mode						Power Setting	Average Conducted Power with duty factor(dBm)	Conducted Power Limit (dBm)	Gain(dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass/Fail
Band	SISO	N_{TX}	Channel	Freq (MHz)	Data Rate		Ant 1	Ant 1	Ant 1	Ant 1	Ant 1	
11b	SISO	1	1	2412	1Mbps	17	15.42	30.00	-3.70	11.72	36.00	Pass
11b	SISO	1	6	2437	1Mbps	17	15.58	30.00	-3.70	11.88	36.00	Pass
11b	SISO	1	11	2462	1Mbps	17	15.56	30.00	-3.70	11.86	36.00	Pass
11g	SISO	1	1	2412	6Mbps	15	13.38	30.00	-3.70	9.68	36.00	Pass
11g	SISO	1	6	2437	6Mbps	17	15.51	30.00	-3.70	11.81	36.00	Pass
11g	SISO	1	11	2462	6Mbps	16.5	14.81	30.00	-3.70	11.11	36.00	Pass
HT20	SISO	1	1	2412	MCS0	14	12.29	30.00	-3.70	8.59	36.00	Pass
HT20	SISO	1	6	2437	MCS0	16	14.58	30.00	-3.70	10.88	36.00	Pass
HT20	SISO	1	11	2462	MCS0	16	14.34	30.00	-3.70	10.64	36.00	Pass

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.11
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
   (3) Set RBW = 1 MHz, VBW= 3MHz for f ≥ 1 GHz for peak measurement.
   For average measurement:
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBµV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 16, 2025	Jun. 22, 2025	Apr. 15, 2026	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Aug. 20, 2024	Jun. 22, 2025	Aug. 19, 2025	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Dec. 24, 2024	Jun. 22, 2025	Dec. 23, 2025	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Oct. 09, 2024	Jun. 22, 2025	Oct. 08, 2025	Conduction (CO01-KS)
EMI Test Receiver	Keysight	N9038A	MY564000 04	3Hz~8.5GHz;Max 30dBm	Oct. 11, 2024	Jul. 11, 2025	Oct. 10, 2025	Radiation (03CH03-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY551502 44	10Hz-44GHz	Apr. 18, 2025	Jul. 11, 2025	Apr. 17, 2026	Radiation (03CH03-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Sep. 08, 2024	Jul. 11, 2025	Sep. 07, 2025	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Nov. 23, 2024	Jul. 11, 2025	Nov. 22, 2025	Radiation (03CH03-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00251982	1GHz~18GHz	Aug. 16, 2024	Jul. 11, 2025	Aug. 15, 2025	Radiation (03CH03-KS)
SHF-EHF Horn	com-power	AH-840	101116	18GHz~40GHz	Oct. 22, 2024	Jul. 11, 2025	Oct. 21, 2025	Radiation (03CH03-KS)
Amplifier	SONOMA	310N	380826	9KHz-1GHz	Jul. 02, 2025	Jul. 11, 2025	Jul. 01, 2026	Radiation (03CH03-KS)
Amplifier	EM	EM18G40GA	060851	18~40GHz	Jan. 02, 2025	Jul. 11, 2025	Jan. 01, 2026	Radiation (03CH03-KS)
high gain Amplifier	EM	EM01G18GA	060834	1Ghz-18Ghz	Dec. 02, 2024	Jul. 11, 2025	Dec. 01, 2025	Radiation (03CH03-KS)
Amplifier	EM	EM01G18GA	EM	1GHz~26.5GHz	Oct. 09, 2024	Jul. 11, 2025	Oct. 08, 2025	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F1040900 04	N/A	NCR	Jul. 11, 2025	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jul. 11, 2025	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jul. 11, 2025	NCR	Radiation (03CH03-KS)
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 10, 2024	Jun. 24, 2025	Oct. 09, 2025	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 02, 2025	Jun. 24, 2025	Jan. 01, 2026	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 02, 2025	Jun. 24, 2025	Jan. 01, 2026	Conducted (TH01-KS)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	**±2.00 dB**
Occupied Channel Bandwidth	**±0.384%**
Conducted Power	**±0.90 dB**
Conducted Power Spectral Density	**±0.90 dB**
Frequency	**±0.04 Hz**

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.84 dB**

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**3.3 dB**

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**6.2 dB**

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**4.88 dB**

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**5.32 dB**

---------- THE END ----------

Appendix A. Conducted Test Results

Ambient Condition: 25 ℃, 45 %RH	
Test Date: 2025.6.24	**Test Engineer:** Zhu Chong

DTS Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	7.06	2408.49	2415.55	0.5	PASS
		2437	8.04	2432.98	2441.02	0.5	PASS
		2462	8.55	2457.51	2466.06	0.5	PASS
11G	Ant1	2412	15.47	2404.45	2419.92	0.5	PASS
		2437	15.65	2429.12	2444.77	0.5	PASS
		2462	15.14	2454.45	2469.59	0.5	PASS
11N20SISO	Ant1	2412	14.67	2405.76	2420.43	0.5	PASS
		2437	15.10	2429.48	2444.59	0.5	PASS
		2462	15.10	2454.48	2469.59	0.5	PASS

Test Graphs

11B_Ant1_2412



Date: 24.JUN.2025 10:33:19

11B_Ant1_2437



Date: 24.JUN.2025 10:35:23

11B_Ant1_2462



Date: 24.JUN.2025 10:36:33

11G_Ant1_2412



Date: 24.JUN.2025 10:38:05

11G_Ant1_2437



Date: 24.JUN.2025 10:39:27

11G_Ant1_2462



Date: 24.JUN.2025 10:40:35

11N20SISO_Ant1_2412



Date: 24.JUN.2025 10:42:14

11N20SISO_Ant1_2437



Date: 24.JUN.2025 10:43:38

11N20SISO_Ant1_2462



Occupied Channel Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	12.909	2405.6182	2418.5273	---	---
		2437	12.873	2430.5818	2443.4545	---	---
		2462	13.018	2455.4364	2468.4545	---	---
11G	Ant1	2412	17.309	2403.4364	2420.7455	---	---
		2437	17.164	2428.4364	2445.6000	---	---
		2462	17.273	2453.2909	2470.5636	---	---
11N20SISO	Ant1	2412	18.182	2402.9636	2421.1455	---	---
		2437	18.036	2428.0000	2446.0364	---	---
		2462	18.182	2452.8182	2471.0000	---	---

Test Graphs

11B_Ant1_2412



Date: 24.JUN.2025 10:33:25

11B_Ant1_2437



Date: 24.JUN.2025 10:35:30

11B_Ant1_2462



Date: 24.JUN.2025 10:36:39

11G_Ant1_2412



Date: 24.JUN.2025 10:38:11

11G_Ant1_2437



Date: 24.JUN.2025 10:39:33

11G_Ant1_2462



Date: 24.JUN.2025 10:40:41

11N20SISO_Ant1_2412



Date: 24.JUN.2025 10:42:20

11N20SISO_Ant1_2437



Date: 24.JUN.2025 10:43:44

11N20SISO_Ant1_2462



Maximum power spectral density

Test Result

TestMode	Antenna	Freq(MHz)	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
11B	Ant1	2412	-6.75	≤8.00	PASS
		2437	-6.1	≤8.00	PASS
		2462	-6.36	≤8.00	PASS
11G	Ant1	2412	-9.45	≤8.00	PASS
		2437	-8.18	≤8.00	PASS
		2462	-9.01	≤8.00	PASS
11N20SISO	Ant1	2412	-10.69	≤8.00	PASS
		2437	-9.6	≤8.00	PASS
		2462	-10.58	≤8.00	PASS

Test Graphs

11B_Ant1_2412



Date: 24.JUN.2025 10:33:36

11B_Ant1_2437



Date: 24.JUN.2025 10:35:41

11B_Ant1_2462



Date: 24.JUN.2025 10:36:50

11G_Ant1_2412



Date: 24.JUN.2025 10:38:23

11G_Ant1_2437



Date: 24.JUN.2025 10:39:44

11G_Ant1_2462



Date: 24.JUN.2025 10:40:52

11N20SISO_Ant1_2412



11N20SISO_Ant1_2437



11N20SISO_Ant1_2462


Reference level measurement

Test Result

TestMode	Antenna	Freq(MHz)	Max.Point[MHz]	Result[dBm/100KHz]
11B	Ant1	2412	2411.00	7.05
		2437	2436.51	7.26
		2462	2461.50	7.23
11G	Ant1	2412	2414.52	4.40
		2437	2435.74	4.69
		2462	2463.25	4.49
11N20SISO	Ant1	2412	2413.27	3.39
		2437	2435.75	3.94
		2462	2460.72	3.68

Test Graphs

11B_Ant1_2412



Date: 24.JUN.2025 10:33:43

11B_Ant1_2437



Date: 24.JUN.2025 10:35:48

11B_Ant1_2462



Date: 24.JUN.2025 10:36:57

11G_Ant1_2412



Date: 24.JUN.2025 10:38:31

11G_Ant1_2437



Date: 24.JUN.2025 10:39:52

11G_Ant1_2462



Date: 24.JUN.2025 10:40:59

11N20SISO_Ant1_2412



Date: 24.JUN.2025 10:42:38

11N20SISO_Ant1_2437



Date: 24.JUN.2025 10:44:02

11N20SISO_Ant1_2462



Band edge measurements

Test Result

TestMode	Antenna	ChName	Freq(MHz)	RefLevel[dBm /100KHz]	Result[dBm /100KHz]	Limit[dBm /100KHz]	Verdict
11B	Ant1	Low	2412	7.05	-42.73	≤-12.95	PASS
		High	2462	7.23	-45.65	≤-12.77	PASS
11G	Ant1	Low	2412	4.40	-27.52	≤-15.6	PASS
		High	2462	4.49	-44.33	≤-15.51	PASS
11N20SISO	Ant1	Low	2412	3.39	-29.75	≤-16.61	PASS
		High	2462	3.68	-43.71	≤-16.32	PASS

Test Graphs

11B_Ant1_Low_2412



Date: 24.JUN.2025 10:33:56

11B_Ant1_High_2462



Date: 24.JUN.2025 10:37:10

11G_Ant1_Low_2412



11G_Ant1_High_2462



11N20SISO_Ant1_Low_2412



11N20SISO_Ant1_High_2462



Conducted Spurious Emission

Test Result

TestMode	Antenna	Freq(MHz)	FreqRange [Mhz]	RefLevel [dBm/100KHz]	Result [dBm/100KHz]	Limit [dBm/100KHz]	Verdict
11B	Ant1	2412	30~1000	7.05	-54.64	≤-12.95	PASS
			1000~26500	7.05	-46.47	≤-12.95	PASS
		2437	30~1000	7.26	-55.51	≤-12.74	PASS
			1000~26500	7.26	-47.57	≤-12.74	PASS
		2462	30~1000	7.23	-55.81	≤-12.77	PASS
			1000~26500	7.23	-46.18	≤-12.77	PASS
11G	Ant1	2412	30~1000	4.40	-55.58	≤-15.6	PASS
			1000~26500	4.40	-50.87	≤-15.6	PASS
		2437	30~1000	4.69	-56.26	≤-15.31	PASS
			1000~26500	4.69	-50.67	≤-15.31	PASS
		2462	30~1000	4.49	-55.59	≤-15.51	PASS
			1000~26500	4.49	-50.7	≤-15.51	PASS
11N20SISO	Ant1	2412	30~1000	3.39	-55.9	≤-16.61	PASS
			1000~26500	3.39	-51.4	≤-16.61	PASS
		2437	30~1000	3.94	-51.22	≤-16.06	PASS
			1000~26500	3.94	-51.02	≤-16.06	PASS
		2462	30~1000	3.68	-55.48	≤-16.32	PASS
			1000~26500	3.68	-50.94	≤-16.32	PASS

Test Graphs

11B_Ant1_2412_30~1000



Date: 24.JUN.2025 10:34:03

11B_Ant1_2412_1000~26500



Date: 24.JUN.2025 10:34:20

11B_Ant1_2437_30~1000



Date: 24.JUN.2025 10:35:54

11B_Ant1_2437_1000~26500



Date: 24.JUN.2025 10:36:11

11B_Ant1_2462_30~1000



Date: 24.JUN.2025 10:37:17

11B_Ant1_2462_1000~26500



Date: 24.JUN.2025 10:37:34

11G_Ant1_2412_30~1000



Date: 24.JUN.2025 10:38:51

11G_Ant1_2412_1000~26500



Date: 24.JUN.2025 10:39:08

11G_Ant1_2437_30~1000



Date: 24.JUN.2025 10:39:58

11G_Ant1_2437_1000~26500



Date: 24.JUN.2025 10:40:15

11G_Ant1_2462_30~1000



Date: 24.JUN.2025 10:41:20

11G_Ant1_2462_1000~26500



Date: 24.JUN.2025 10:41:37

11N20SISO_Ant1_2412_30~1000



Date: 24.JUN.2025 10:42:58

11N20SISO_Ant1_2412_1000~26500



Date: 24.JUN.2025 10:43:15

11N20SISO_Ant1_2437_30~1000



Date: 24.JUN.2025 10:44:08

11N20SISO_Ant1_2437_1000~26500



Date: 24.JUN.2025 10:44:25

11N20SISO_Ant1_2462_30~1000



Date: 24.JUN.2025 10:45:34

11N20SISO_Ant1_2462_1000~26500



Date: 24.JUN.2025 10:45:51

Appendix B. AC Conducted Emission Test Results

Test Engineer :	Amos	**Temperature :**	25.3~26.2℃
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	**Phase :**	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : 15C RSS247-QP LISN-060105-L 24+80 LINE

	Freq MHz	Level dBuV	Over Limit dB	Limit Line dBuV	Read Level dBuV	LISN Factor dB	Cable Loss dB	Remark
1	0.154	46.88	-18.90	65.78	36.20	0.23	10.45	QP
2	0.154	28.58	-27.20	55.78	17.90	0.23	10.45	Average
3	0.165	43.90	-21.31	65.21	33.20	0.25	10.45	QP
4	0.165	26.90	-28.31	55.21	16.20	0.25	10.45	Average
5	0.172	42.80	-22.06	64.86	32.10	0.25	10.45	QP
6	0.172	26.00	-28.86	54.86	15.30	0.25	10.45	Average
7	0.190	42.31	-21.71	64.02	31.60	0.25	10.46	QP
8	0.190	26.91	-27.11	54.02	16.20	0.25	10.46	Average
9	0.242	38.04	-24.00	62.04	27.29	0.28	10.47	QP
10	0.242	25.34	-26.70	52.04	14.59	0.28	10.47	Average
11	0.476	41.78	-14.63	56.41	30.99	0.36	10.43	QP
12 *	0.476	33.48	-12.93	46.41	22.69	0.36	10.43	Average

Test Engineer :	Amos	**Temperature :**	25.3~26.2℃
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	**Phase :**	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : 15C RSS247-QP LISN-060105-N 24+80 NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.154	45.98	-19.80	65.78	35.30	0.23	10.45	QP
2	0.154	28.28	-27.50	55.78	17.60	0.23	10.45	Average
3	0.158	44.09	-21.47	65.56	33.40	0.24	10.45	QP
4	0.158	26.89	-28.67	55.56	16.20	0.24	10.45	Average
5	0.168	43.50	-21.58	65.08	32.80	0.25	10.45	QP
6	0.168	26.30	-28.78	55.08	15.60	0.25	10.45	Average
7	0.181	42.90	-21.56	64.46	32.19	0.25	10.46	QP
8	0.181	26.00	-28.46	54.46	15.29	0.25	10.46	Average
9	0.464	39.38	-17.25	56.63	28.60	0.34	10.44	QP
10	0.464	30.88	-15.75	46.63	20.10	0.34	10.44	Average
11	0.481	41.86	-14.46	56.32	31.10	0.34	10.42	QP
12 *	0.481	35.16	-11.16	46.32	24.40	0.34	10.42	Average

Note:

1. Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)

Appendix C. Radiated Spurious Emission

Test Engineer :	Jake zhou	Relative Humidity :	52 ~56%
		Temperature :	22~25℃

Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 10	2400-2483.5	SISO	802.11b	01	2412	1Mbps	-	-
Mode 11	2400-2483.5	SISO	802.11b	06	2437	1Mbps	-	-
Mode 12	2400-2483.5	SISO	802.11b	11	2462	1Mbps	-	-
Mode 13	2400-2483.5	SISO	802.11g	01	2412	6Mbps	-	-
Mode 14	2400-2483.5	SISO	802.11g	06	2437	6Mbps	-	-
Mode 15	2400-2483.5	SISO	802.11g	11	2462	6Mbps	-	-
Mode 16	2400-2483.5	SISO	802.11n HT20	01	2412	MCS0	Full RU	-
Mode 17	2400-2483.5	SISO	802.11n HT20	06	2437	MCS0	Full RU	-
Mode 18	2400-2483.5	SISO	802.11n HT20	11	2462	MCS0	Full RU	-
Mode 19	2400-2483.5	SISO	802.11b	11	2462	1Mbps	-	-
	Part 27M B41 BW=20M							
	NFC TX							

Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
10	802.11b	01	2388.91	37.59	54.00	-16.41	H	AVERAGE	Pass	Band Edge
10	802.11b	01	4824.00	42.77	74.00	-31.23	V	Peak	Pass	Harmonic
11	802.11b	06	-	-	-	-	-	-	-	Band Edge
11	802.11b	06	4874.00	49.69	54.00	-4.31	H	AVERAGE	Pass	Harmonic
12	802.11b	11	2483.50	41.44	54.00	-12.56	H	AVERAGE	Pass	Band Edge
12	802.11b	11	4924.00	50.89	54.00	-3.11	V	AVERAGE	Pass	Harmonic
13	802.11g	01	2389.82	50.83	54.00	-3.17	H	AVERAGE	Pass	Band Edge
13	802.11g	01	4824.00	39.32	74.00	-34.68	V	PEAK	Pass	Harmonic
14	802.11g	06	-	-	-	-	-	-	-	Band Edge
14	802.11g	06	4874.00	44.81	74.00	-29.19	V	PEAK	Pass	Harmonic
15	802.11g	11	2483.80	49.66	54.00	-4.34	H	AVERAGE	Pass	Band Edge
15	802.11g	11	4924.00	45.17	74.00	-28.83	V	PEAK	Pass	Harmonic
16	802.11n HT20	01	2389.43	70.00	74.00	-4.00	H	PEAK	Pass	Band Edge
16	802.11n HT20	01	4824.00	39.26	74.00	-34.74	V	PEAK	Pass	Harmonic
17	802.11n HT20	06	-	-	-	-	-	-	-	Band Edge
17	802.11n HT20	06	4874.00	45.61	74.00	-28.39	V	PEAK	Pass	Harmonic
18	802.11n HT20	11	2483.50	49.56	54.00	-4.44	H	AVERAGE	Pass	Band Edge
18	802.11n HT20	11	4924.00	43.18	74.00	-30.82	V	PEAK	Pass	Harmonic
19	802.11b	11	2483.50	40.85	54.00	-13.15	H	Average	Pass	Band Edge
	802.11b	11	4924.00	48.75	54.00	-5.25	H	AVERAGE	Pass	Harmonic

Mode	10	
	Band Edge	
	2400-2483.5_802.11b_CH01_2412MHz	
ANT	SISO	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2332.23 49.33 74.00 -24.67 41.82 31.70 7.07 37.26 6.00 262 360 PEAK	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2412.00 106.86 ------ ------ 98.94 31.94 7.20 37.22 6.00 262 360 PEAK
Avg	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2388.91 37.59 54.00 -16.41 29.79 31.87 7.16 37.23 6.00 262 360 AVERAGE	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2412.00 102.45 ------ ------ 94.53 31.94 7.20 37.22 6.00 262 360 AVERAGE

Mode	10	
	Band Edge	
	2400-2483.5_802.11b_CH01_2412MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2327.03 49.42 74.00 -24.58 41.94 31.68 7.06 37.26 6.00 100 127 PEAK	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2412.00 103.63 ------ ------ 95.71 31.94 7.20 37.22 6.00 100 127 PEAK
Avg	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2387.09 37.49 54.00 -16.51 29.70 31.86 7.16 37.23 6.00 100 127 AVERAGE	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2412.00 99.20 ------ ------ 91.28 31.94 7.20 37.22 6.00 100 127 AVERAGE

Mode	10	
	Harmonic	
	2400-2483.5_802.11b_CH01_2412MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4824.00 41.44 74.00 -32.56 63.20 33.90 10.29 65.95 0.00 --- --- Peak	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4824.00 42.77 74.00 -31.23 64.53 33.90 10.29 65.95 0.00 --- --- Peak

Mode	11	
	Harmonic	
	2400-2483.5_802.11b_CH06_2437MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4874.00 51.14 74.00 -22.86 72.90 33.90 10.34 66.00 0.00 297 127 PEAK 2 4874.00 49.69 54.00 -4.31 71.45 33.90 10.34 66.00 0.00 297 127 AVERAGE 3 7311.00 40.84 74.00 -33.16 60.02 35.59 12.78 67.55 0.00 --- --- PEAK	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4874.00 50.42 74.00 -23.58 72.18 33.90 10.34 66.00 0.00 187 345 PEAK 2 4874.00 48.30 54.00 -5.70 70.06 33.90 10.34 66.00 0.00 187 345 AVERAGE 3 7311.00 41.65 74.00 -32.35 60.83 35.59 12.78 67.55 0.00 --- --- PEAK

Mode	12	
	Band Edge	
	2400-2483.5_802.11b_CH11_2462MHz	
ANT	SISO	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2486.68 52.94 74.00 -21.06 44.64 32.16 7.34 37.20 6.00 250 360 PEAK	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2462.00 107.41 ------ ------ 99.24 32.09 7.29 37.21 6.00 250 360 PEAK
Avg	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.50 41.44 54.00 -12.56 33.16 32.15 7.33 37.20 6.00 250 360 AVERAGE	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2462.00 102.95 ------ ------ 94.78 32.09 7.29 37.21 6.00 250 360 AVERAGE

Mode	12	
	Band Edge	
	2400-2483.5_802.11b_CH11_2462MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2485.72 50.68 74.00 -23.32 42.39 32.16 7.33 37.20 6.00 310 114 PEAK	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2462.00 104.40 ------ ------ 96.23 32.09 7.29 37.21 6.00 310 114 PEAK
Avg	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.50 39.04 54.00 -14.96 30.76 32.15 7.33 37.20 6.00 310 114 AVERAGE	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2462.00 99.92 ------ ------ 91.75 32.09 7.29 37.21 6.00 310 114 AVERAGE

Mode	12	
	Harmonic	
	2400-2483.5_802.11b_CH11_2462MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4924.00 50.32 74.00 -23.68 71.62 33.90 10.35 65.55 0.00 286 83 PEAK 2 4924.00 47.85 54.00 -6.15 69.15 33.90 10.35 65.55 0.00 286 83 AVERAGE 3 7386.00 41.86 74.00 -32.14 59.48 35.80 12.73 66.15 0.00 --- --- PEAK	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4924.00 52.74 74.00 -21.26 74.04 33.90 10.35 65.55 0.00 237 353 PEAK 2 4924.00 50.89 54.00 -3.11 72.19 33.90 10.35 65.55 0.00 237 353 AVERAGE 3 7386.00 42.39 74.00 -31.61 60.01 35.80 12.73 66.15 0.00 --- --- PEAK

Mode	13	
	Band Edge	
	2400-2483.5_802.11g_CH01_2412MHz	
ANT	SISO	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2388.65 69.51 74.00 -4.49 61.17 32.23 7.10 36.99 6.00 100 53 PEAK	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2412.00 108.57 ------ ------ 100.01 32.42 7.14 37.00 6.00 100 53 PEAK
Avg	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2389.82 50.83 54.00 -3.17 42.47 32.24 7.11 36.99 6.00 100 53 AVERAGE	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2412.00 99.34 ------ ------ 90.78 32.42 7.14 37.00 6.00 100 53 AVERAGE

Mode	13	
	Band Edge	
	2400-2483.5_802.11g_CH01_2412MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2389.17 67.22 74.00 -6.78 58.87 32.24 7.10 36.99 6.00 343 66 PEAK	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2412.00 105.03 ------ ------ 96.47 32.42 7.14 37.00 6.00 343 66 PEAK
Avg	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2389.56 47.01 54.00 -6.99 38.66 32.24 7.10 36.99 6.00 343 66 AVERAGE	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2412.00 95.96 ------ ------ 87.40 32.42 7.14 37.00 6.00 343 66 AVERAGE

Mode	13	
	Harmonic	
	2400-2483.5_802.11g_CH01_2412MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4824.00 38.66 74.00 -35.34 60.42 33.90 10.29 65.95 0.00 --- --- PEAK	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4824.00 39.32 74.00 -34.68 61.08 33.90 10.29 65.95 0.00 --- --- PEAK

Mode	14	
	Harmonic	
	2400-2483.5_802.11g_CH06_2437MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4874.00 43.73 74.00 -30.27 65.49 33.90 10.34 66.00 0.00 --- --- PEAK 2 7311.00 40.35 74.00 -33.65 59.53 35.59 12.78 67.55 0.00 --- --- PEAK	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4874.00 44.81 74.00 -29.19 66.57 33.90 10.34 66.00 0.00 --- --- PEAK 2 7311.00 41.26 74.00 -32.74 60.44 35.59 12.78 67.55 0.00 --- --- PEAK

Mode	15	
	Band Edge	
	2400-2483.5_802.11g_CH11_2462MHz	
ANT	SISO	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2484.70 66.66 74.00 -7.34 58.38 32.15 7.33 37.20 6.00 281 0 PEAK	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2462.00 109.24 ------ ------ 101.10 32.07 7.28 37.21 6.00 281 0 PEAK
Avg	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.80 49.66 54.00 -4.34 41.38 32.15 7.33 37.20 6.00 281 0 AVERAGE	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2462.00 99.90 ------ ------ 91.76 32.07 7.28 37.21 6.00 281 0 AVERAGE

Mode	15	
	Band Edge	
	2400-2483.5_802.11g_CH11_2462MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2484.22 60.93 74.00 -13.07 52.65 32.15 7.33 37.20 6.00 376 114 PEAK	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2462.00 106.40 ------ ------ 98.26 32.07 7.28 37.21 6.00 376 114 PEAK
Avg	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.56 44.49 54.00 -9.51 36.21 32.15 7.33 37.20 6.00 376 114 AVERAGE	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2462.00 96.86 ------ ------ 88.72 32.07 7.28 37.21 6.00 376 114 AVERAGE

Mode	15	
	Harmonic	
	2400-2483.5_802.11g_CH11_2462MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4924.00 39.72 74.00 -34.28 61.50 33.90 10.40 66.08 0.00 --- --- PEAK 2 7386.00 40.51 74.00 -33.49 59.73 35.51 12.88 67.61 0.00 --- --- PEAK	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4924.00 45.17 74.00 -28.83 66.95 33.90 10.40 66.08 0.00 --- --- PEAK 2 7386.00 41.11 74.00 -32.89 60.33 35.51 12.88 67.61 0.00 --- --- PEAK

Mode	16	
	Band Edge	
	2400-2483.5_802.11n HT20_CH01_Full RU _2412MHz	
ANT	SISO	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2389.43 70.00 74.00 -4.00 62.20 31.87 7.16 37.23 6.00 262 360 PEAK	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2412.00 106.59 ------ ------ 98.68 31.93 7.20 37.22 6.00 262 360 PEAK
Avg	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2389.95 46.69 54.00 -7.31 38.89 31.87 7.16 37.23 6.00 262 360 AVERAGE	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2412.00 97.30 ------ ------ 89.38 31.94 7.20 37.22 6.00 262 360 AVERAGE

Mode	16	
	Band Edge	
	2400-2483.5_802.11n HT20_CH01_Full RU _2412MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2388.78 69.21 74.00 -4.79 61.41 31.87 7.16 37.23 6.00 100 127 PEAK	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2412.00 103.05 ------ ------ 95.14 31.93 7.20 37.22 6.00 100 127 PEAK
Avg	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2389.95 45.54 54.00 -8.46 37.74 31.87 7.16 37.23 6.00 100 127 AVERAGE	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2412.00 94.10 ------ ------ 86.18 31.94 7.20 37.22 6.00 100 127 AVERAGE

Mode	16	
	Harmonic	
	2400-2483.5_802.11n HT20_CH01_Full RU _2412MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4824.00 39.19 74.00 -34.81 60.95 33.90 10.29 65.95 0.00 --- --- PEAK	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4824.00 39.26 74.00 -34.74 61.02 33.90 10.29 65.95 0.00 --- --- PEAK

Mode	17	
	Harmonic	
	2400-2483.5_802.11n HT20_CH06_Full RU _2437MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4874.00 39.21 74.00 -34.79 60.97 33.90 10.34 66.00 0.00 --- --- PEAK 2 7311.00 40.78 74.00 -33.22 59.96 35.59 12.78 67.55 0.00 --- --- PEAK	 Freq Level Limit Line Over Limit Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4874.00 45.61 74.00 -28.39 67.37 33.90 10.34 66.00 0.00 --- --- PEAK 2 7311.00 41.20 74.00 -32.80 60.38 35.59 12.78 67.55 0.00 --- --- PEAK