



RF MEASUREMENT REPORT

FCC ID: WIYS1U2M2B001
Applicant: CASTLES TECHNOLOGY CO., LTD.
Product: POS Terminal
Model No.: S1U2-M2B
Trademark: 
FCC Classification: Part 15 Low Power Communication Device Transmitter (DXX)
FCC Rule Part(s): Part 15 Subpart C (Section 15.225)
Result: Complies
Received Date: 2026-05-06
Test Date: 2026-05-19~2026-06-02

Reviewed By:

Paddy Chen

Paddy Chen

Approved By:

Chenz Ker

Chenz Ker



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report. Testing was performed in accordance with the applicable measurement procedures. The test results reported herein apply only to the specific item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2605TW8704-U7	V1.0	Original Report	2026-07-16	Valid

CONTENTS

Description	Page
1. General Information	5
1.1. Applicant.....	5
1.2. Manufacturer	5
1.3. Testing Facility	5
1.4. Product Information	6
1.5. Radio Specification.....	7
2. Test Configuration.....	8
2.1. Test Mode	8
2.2. Test Configuration and Software.....	9
2.3. Applied Standards	9
2.4. Test Environment Condition	10
3. Antenna Requirements	11
4. Measuring Instrument.....	12
5. Decision Rules and Measurement Uncertainty	13
5.1. Decision Rules	13
5.2. Measurement Uncertainty	13
6. Test Result	14
6.1. Summary	14
6.2. In-band Emission Measurement	15
6.2.1. Test Limit	15
6.2.2. Test Procedure	15
6.2.3. Test Setting.....	15
6.2.4. Test Setup	16
6.2.5. Test Result.....	16
6.3. Out-band Emission Measurement.....	17
6.3.1. Test Limit	17
6.3.2. Test Procedure	17
6.3.3. Test Setting.....	18
6.3.4. Test Setup	19
6.3.5. Test Result.....	19
6.4. 20 dB Bandwidth Measurement	20
6.4.1. Test Limit	20
6.4.2. Test Procedure	20
6.4.3. Test Setting.....	20

6.4.4.	Test Setup	21
6.4.5.	Test Result.....	21
6.5.	Frequency Tolerance Measurement	22
6.5.1.	Test Limit	22
6.5.2.	Test Procedure	22
6.5.3.	Test Setting.....	22
6.5.4.	Test Setup	23
6.5.5.	Test Result.....	23
6.6.	AC Conducted Emissions Measurement	24
6.6.1.	Test Limit	24
6.6.2.	Test Setup	24
6.6.3.	Test Result.....	24
Appendix A - Test Result		25
A.1	In-band Emission Test Result	25
A.2	Out-Band Emission Test Result.....	27
A.3	20 dB Bandwidth Test Result.....	33
A.4	Frequency Tolerance Test Result	34
A.5	AC Conducted Emissions Test Result	35
Appendix B - Test Setup Photograph.....		37
Appendix C - External Photograph.....		37
Appendix D - Internal Photograph		37

1. General Information

1.1. Applicant

CASTLES TECHNOLOGY CO., LTD.

6F, NO. 207-5, SEC. 3, BEIXIN RD., XINDIAN DISTRICT, NEW TAIPEI CITY 231030, TAIWAN (R. O. C.)

1.2. Manufacturer

CASTLES TECHNOLOGY CO., LTD.

6F, NO. 207-5, SEC. 3, BEIXIN RD., XINDIAN DISTRICT, NEW TAIPEI CITY 231030, TAIWAN (R. O. C.)

1.3. Testing Facility

☒	Test Site 1 - MRT Taiwan Laboratory
	Laboratory Location No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
	Laboratory Accreditations
	TAF: 3261 FCC: 291082, TW3261 ISED: TW3261
☐	Test Site 2 - MRT Taiwan Laboratory
	Laboratory Location No. 64, Wenming Rd., Guishan Dist , Taoyuan City 333, Taiwan (R.O.C.)
	Laboratory Accreditations
	TAF: 3261 FCC: 291082, TW3261 ISED: TW3261

1.4. Product Information

Product Name	POS Terminal
Model No.	S1U2-M2B
Specification	WLAN: 802.11a/b/g/n/ac WPAN: Bluetooth dual mode GPS, GLONASS, GALILEO, BEIDOU NFC:13.56MHz WWAN: 3G: band 2, 4, 5 4G: band 2, 4, 5, 7, 12, 13, 14, 17, 25, 26, 38, 41, 66
Operating Temperature	-20 ~ 65 °C
Power Type	AC/DC Adapter
Note: The information of the EUT (Equipment Under Test) was provided by the manufacturer. The accuracy, completeness, and validity of the information are solely the responsibility of the manufacturer.	

1.5. Radio Specification

Frequency Range	13.56 MHz
Channel Number	1
Type of modulation	ASK


2. Test Configuration

2.1. Test Mode

Mode 1: Transmitter at 13.56 MHz

2.2. Test Configuration and Software

The device was tested per the guidance ANSI C63.10-2020 that was used to reference the appropriate EUT setup for radiated spurious emissions and AC line conducted emission testing.



2.3. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.225
- ANSI C63.10-2020
- ANSI C63.10-2020/Cor1-2023
- ANSI C63.10a-2024

2.4. Test Environment Condition

Ambient Temperature	15 ~ 35 °C
Relative Humidity	20 ~ 75 %RH

3. Antenna Requirements

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of this device is permanently attached.
- There are no provisions for connection to an external antenna.

Conclusion:

The unit complies with the requirement of §15.203.

4. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	MRTTWA00002	1 year	2027/4/15	TW-AC1
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00086	1 year	2026/11/13	TW-AC1
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2027/3/4	TW-AC1
Two-Line V-Network	R&S	ENV216	MRTTWA00019	1 year	2027/3/3	TW-SR2
Two-Line V-Network	R&S	ENV216	MRTTWA00020	1 year	2027/4/14	TW-SR2
EMI Test Receiver	R&S	ESR3	MRTTWA00045	1 year	2027/5/13	TW-SR2

Software	Version	Function
e3	9.160520a	EMI Test Software

5. Decision Rules and Measurement Uncertainty

5.1. Decision Rules

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4:2012 Clause 8.2.

(Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.2. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 150kHz~30MHz: $\pm 2.53\text{dB}$
Radiated Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 9kHz ~ 1GHz: $\pm 4.25\text{dB}$ 1GHz ~ 40GHz: $\pm 4.45\text{dB}$
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 3.3\%$

6. Test Result

6.1. Summary

FCC Part Section(s)	Test Description	Test Condition	Verdict
15.225 (a), (b), (c)	In-Band Emission	Radiated	Pass
15.225 (d)	Out-Band Emission		Pass
15.215 (c)	20 dB Bandwidth		Pass
15.225 (e)	Frequency Tolerance		Pass
15.207	AC Conducted Emissions 150 kHz-30 MHz	Line Conducted	Pass

6.2. In-band Emission Measurement

6.2.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.225		
Frequency (MHz)	Distance (m)	Level (μV/m)
13.553 ~ 13.567	30	15848
13.410 ~ 13.553, 13.567 ~ 13.710	30	334
13.110 ~ 13.410, 13.710 ~ 14.010	30	106
Note 1: The lower limit shall apply at the transition frequency. Note 2: Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system. Note 3: E field strength (dBμV/m) = 20log E field strength (μV/m)		

6.2.2. Test Procedure


ANSI C63.10 - 2020 - Section 6.4

6.2.3. Test Setting

1. RBW = 9 kHz or 10 kHz
2. VBW = 3 × RBW
3. Detector = Peak
4. Trace mode = Max hold
5. Sweep = Auto couple
6. Allow the trace to stabilize

6.2.4. Test Setup

9 kHz ~ 30 MHz Test Setup:



6.2.5. Test Result

Refer to Appendix A.1.

6.3. Out-band Emission Measurement

6.3.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.209		
Frequency (MHz)	Distance (m)	Level ($\mu\text{V}/\text{m}$)
0.009 ~ 0.490	300	2400/F (kHz)
0.490 ~ 1.705	30	24000/F (kHz)
1.705 ~ 30	30	30
30 ~ 88	3	100
88 ~ 216	3	150

Note 1: The lower limit shall apply at the transition frequency.

Note 2: Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

Note 3: E field strength (dB $\mu\text{V}/\text{m}$) = 20log E field strength ($\mu\text{V}/\text{m}$)

6.3.2. Test Procedure

ANSI C63.10 - 2020 - Section 6.3 (General Requirements)

ANSI C63.10 - 2020 - Section 6.4 (Standard test method below 30 MHz)

ANSI C63.10 - 2020 - Section 6.5 (Standard test method above 30 MHz to 1 GHz)

6.3.3. Test Setting

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz

Peak Measurement


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = as specified in Table 1
3. VBW = $3 \times \text{RBW}$
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep = Auto couple
7. Allow the trace to stabilize

Quasi-Peak Measurement


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1 MHz
3. RBW = as specified in Table 1
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

6.3.4. Test Setup

9 kHz ~ 30 MHz Test Setup:



Above 30 MHz Test Setup:



6.3.5. Test Result

Refer to Appendix A.2.

6.4. 20 dB Bandwidth Measurement

6.4.1. Test Limit

The occupied bandwidth is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequency.


6.4.2. Test Procedure

ANSI C63.10-2020 - Section 6.9.2

6.4.3. Test Setting

1. Set RBW $\geq$ 1% to 5% of the 20 dB bandwidth
2. VBW = approximately three times RBW
3. Span = approximately 2 to 5 times the 20 dB bandwidth
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. Allow the trace to stabilize
8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

6.4.4. Test Setup



6.4.5. Test Result

Refer to Appendix A.3.

6.5. Frequency Tolerance Measurement

6.5.1. Test Limit

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ ($\pm 100\text{ppm}$) of the operating frequency.

6.5.2. Test Procedure

ANSI C63.10-2020 - Section 6.8

6.5.3. Test Setting

Frequency Stability Under Temperature Variations:


The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20 °C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to highest. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10 °C decreased per stage until the lowest temperature reached.

Frequency Stability Under Voltage Variations:

Set chamber temperature to 20 °C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change. For hand-carried battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

6.5.4. Test Setup



6.5.5. Test Result

Refer to Appendix A.4.

6.6. AC Conducted Emissions Measurement


6.6.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207		
Frequency (MHz)	QP (dB μ V)	AV (dB μ V)
0.15 ~ 0.50	66 ~ 56	56 ~ 46
0.50 ~ 5.0	56	46
5.0 ~ 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

6.6.2. Test Setup




6.6.3. Test Result

Refer to Appendix A.5.

Appendix A - Test Result

A.1 In-band Emission Test Result

EUT	POS Terminal	Date of Test	2026-05-28
Factor	FMZB 1519B	Temp. / Humidity	25°C /47%
Polarity	Face On	Site / Test Engineer	AC1 / James
Test Mode	TX-NFC 13.56MHz	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	13.560	53.87	20.75	74.62	-49.48	124.00	100	246	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	POS Terminal	Date of Test	2026-05-28
Factor	FMZB 1519B	Temp. / Humidity	25°C /47%
Polarity	Face Off	Site / Test Engineer	AC1 / James
Test Mode	TX-NFC 13.56MHz	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	13.560	41.41	20.75	62.16	-61.97	124.00	100	157	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

A.2 Out-Band Emission Test Result

EUT	POS Terminal	Date of Test	2026-05-28
Factor	FMZB 1519B	Temp. / Humidity	25°C /47%
Polarity	Face On	Site / Test Engineer	AC1 / James
Test Mode	TX-NFC 13.56MHz	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	0.022	30.67	18.04	48.71	-72.04	120.75	100	154	Peak
2	0.044	28.42	19.04	47.46	-67.24	114.70	100	154	Peak
3	0.066	25.87	18.70	44.57	-66.60	111.17	100	288	Peak
4	0.088	23.49	18.00	41.49	-67.20	108.69	100	288	Peak
5	* 0.108	23.52	17.64	41.16	-65.74	106.90	100	311	Peak
6	0.135	20.67	17.68	38.35	-66.63	104.98	100	292	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	POS Terminal	Date of Test	2026-05-28
Factor	FMZB 1519B	Temp. / Humidity	25°C /47%
Polarity	Face On	Site / Test Engineer	AC1 / James
Test Mode	TX-NFC 13.56MHz	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	0.240	24.07	17.86	41.93	-58.09	100.01	100	284	Peak
2	0.538	16.81	17.97	34.78	-38.21	72.99	100	298	Peak
3	0.956	13.45	17.98	31.43	-36.59	68.01	100	305	Peak
4	1.434	11.19	17.99	29.19	-35.32	64.50	100	302	Peak
5	2.329	10.56	18.02	28.58	-40.92	69.50	100	338	Peak
6	* 13.553	53.86	20.75	74.60	N/A	N/A	100	180	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. This frequency is 13.553MHz RFID operating frequency.

EUT	POS Terminal	Date of Test	2026-05-28
Factor	FMZB 1519B	Temp. / Humidity	25°C /47%
Polarity	Face Off	Site / Test Engineer	AC1 / James
Test Mode	TX-NFC 13.56MHz	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	0.023	32.48	18.13	50.61	-69.65	120.27	100	218	Peak
2		0.044	24.41	19.02	43.43	-71.35	114.79	100	214	Peak
3		0.066	20.59	18.71	39.30	-71.91	111.21	100	285	Peak
4		0.088	18.10	18.01	36.11	-72.60	108.71	100	285	Peak
5		0.110	16.90	17.64	34.55	-72.23	106.78	100	285	Peak
6		0.132	15.42	17.68	33.10	-72.08	105.18	100	285	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	POS Terminal	Date of Test	2026-05-28
Factor	FMZB 1519B	Temp. / Humidity	25°C /47%
Polarity	Face Off	Site / Test Engineer	AC1 / James
Test Mode	TX-NFC 13.56MHz	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	0.240	21.12	17.86	38.98	-61.03	100.01	100	317	Peak
2	0.419	16.45	17.96	34.41	-60.76	95.17	100	293	Peak
3	0.628	13.57	17.97	31.54	-40.11	71.66	100	344	Peak
4	1.016	11.16	17.98	29.14	-38.35	67.49	100	262	Peak
5	1.672	10.06	18.00	28.06	-35.11	63.17	100	281	Peak
6	* 13.553	41.39	20.75	62.13	N/A	N/A	100	170	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. This frequency is 13.553MHz RFID operating frequency.

EUT	POS Terminal	Date of Test	2026-05-28
Factor	VULB 9162	Temp. / Humidity	25°C /47%
Polarity	Horizontal	Site / Test Engineer	AC1 / James
Test Mode	TX-NFC 13.56MHz	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	101.780	9.25	18.42	27.67	-15.83	43.50	150	50	QP
2	205.570	16.97	17.82	34.79	-8.71	43.50	150	250	QP
3	* 244.370	20.99	19.58	40.56	-5.44	46.00	100	260	QP
4	261.830	16.40	19.83	36.23	-9.77	46.00	100	55	QP
5	324.880	12.70	21.43	34.13	-11.87	46.00	100	55	QP
6	595.510	5.66	26.78	32.44	-13.56	46.00	150	340	QP

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	POS Terminal	Date of Test	2026-05-28
Factor	VULB 9162	Temp. / Humidity	25°C /47%
Polarity	Vertical	Site / Test Engineer	AC1 / James
Test Mode	TX-NFC 13.56MHz	Test Voltage	AC 120V/60Hz



No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	40.670	5.29	19.42	24.71	-15.29	40.00	100	270	QP
2	143.490	11.15	14.80	25.95	-17.55	43.50	100	195	QP
3	243.400	8.93	19.56	28.49	-17.51	46.00	100	180	QP
4	262.800	8.98	19.84	28.81	-17.19	46.00	150	35	QP
5	324.880	6.36	21.43	27.78	-18.22	46.00	150	30	QP
6	* 595.510	4.20	26.78	30.99	-15.01	46.00	100	360	QP


Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

A.3 20 dB Bandwidth Test Result

Test Site	AC1	Test Date	2026-5-28
Test Engineer	James	Test Mode	Mode 1

Frequency (MHz)	20 dB Occupied Bandwidth (kHz)
13.56	0.2458



A.4 Frequency Tolerance Test Result

Test Site	SR3	Test Date	2026-5-19
Test Engineer	James	Test Mode	Mode 1


Temperature vs. Frequency Stability					
Voltage (%)	Power (VDC)	Temp (°C)	Frequency (MHz)	Frequency Tolerance (ppm)	Limit (ppm)
100%	DC 9V	- 20	13.56	0.00	±100
		- 10	13.56	0.00	±100
		0	13.56	0.00	±100
		+ 10	13.56	0.00	±100
		+ 20 (Ref)	13.56	0.00	±100
		+ 30	13.56	0.00	±100
		+ 40	13.5599	-7.37	±100
		+ 50	13.5599	-7.37	±100
Test Result		PASS			
Voltage vs. Frequency Stability					
Voltage (%)	Power (VDC)	Temp (°C)	Frequency (MHz)	Frequency Tolerance (ppm)	Limit (ppm)
100%	DC 9V	+ 20	13.56	0.00	±100
115%	DC 10.35V	+ 20	13.5599	-7.37	±100
85%	DC 9V	+ 20	13.5599	-7.37	±100
Test Result		PASS			

Note:

Frequency Tolerance (ppm) = {[Measured Frequency (Hz) – Declared Frequency (Hz)] / Declared Frequency (Hz)} *10⁶.

A.5 AC Conducted Emissions Test Result

EUT	POS Terminal	Date of Test	2026-06-02
Factor	CE_ENV216-L1 (Filter ON)	Temp. / Humidity	24°C /49%
Polarity	Line1	Site / Test Engineer	SR2 / Todd
Test Mode	TX-NFC 13.56MHz	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV)	Margin (dB)	Limit (dBuV)	Remark (QP/PK/AV)
1	0.235	34.13	9.63	43.76	-18.49	62.25	QP
2	0.235	25.90	9.63	35.53	-16.72	52.25	Average
3	* 0.447	40.24	9.64	49.89	-7.05	56.93	QP
4	* 0.447	30.90	9.64	40.55	-6.39	46.93	Average
5	1.072	31.53	9.67	41.20	-14.80	56.00	QP
6	1.072	22.49	9.67	32.16	-13.84	46.00	Average
7	2.184	30.35	9.70	40.05	-15.95	56.00	QP
8	2.184	20.14	9.70	29.85	-16.15	46.00	Average
9	4.078	32.23	9.75	41.98	-14.02	56.00	QP
10	4.078	22.19	9.75	31.94	-14.06	46.00	Average
11	10.508	29.40	9.86	39.26	-20.74	60.00	QP
12	10.508	22.80	9.86	32.67	-17.33	50.00	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = LISN Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV) = Reading(dBuV) + C.F (Correction Factor).

EUT	POS Terminal	Date of Test	2026-06-02
Factor	CE_ENV216-N (Filter ON)	Temp. / Humidity	24°C /49%
Polarity	Neutral	Site / Test Engineer	SR2 / Todd
Test Mode	TX-NFC 13.56MHz	Test Voltage	AC 120V/60Hz



No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV)	Margin (dB)	Limit (dBuV)	Remark (QP/PK/AV)
1		0.150	36.30	9.62	45.92	-20.08	66.00	QP
2		0.150	22.80	9.62	32.42	-23.58	56.00	Average
3	*	0.460	42.41	9.64	52.06	-4.63	56.68	QP
4	*	0.460	33.85	9.64	43.49	-3.20	46.68	Average
5		1.086	32.13	9.67	41.80	-14.20	56.00	QP
6		1.086	24.53	9.67	34.21	-11.79	46.00	Average
7		1.671	31.23	9.68	40.92	-15.08	56.00	QP
8		1.671	19.23	9.68	28.92	-17.08	46.00	Average
9		4.029	33.54	9.75	43.29	-12.71	56.00	QP
10		4.029	22.55	9.75	32.30	-13.70	46.00	Average
11		10.553	28.25	9.88	38.13	-21.87	60.00	QP
12		10.553	20.81	9.88	30.68	-19.32	50.00	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = LISN Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV) = Reading(dBuV) + C.F (Correction Factor).

Appendix B - Test Setup Photograph

Refer to “ 2605TW8704-UT” file.

Appendix C - External Photograph

Refer to “2605TW8704-UE” file.

Appendix D - Internal Photograph

Refer to “2605TW8704-UI” file.

_____ The End _____