



RF MEASUREMENT REPORT

FCC ID: WIYS1U2M4001
Applicant: CASTLES TECHNOLOGY CO., LTD.
Product: POS Terminal
Model No.: S1U2-M4
Trademark: 
FCC Rule(s): Part 2, 24 (E), 27
Result: Complies
Received Date: 2025-02-12
Test Date: 2025-02-13 ~ 2025-03-04

Reviewed By:

Yuri Li

Yuri Li

Approved By:

Robin Wu

Robin Wu



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.26-2015. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
R25S1016023-U302	V01	Initial Report	2025-03-07	Valid

CONTENTS

Description	Page
1. General Information	5
1.1. Applicant	5
1.2. Manufacturer.....	5
1.3. Testing Facility	5
1.4. Product Information	6
1.5. Radio Specification under Testing	6
1.6. Description of Available Antennas	7
1.7. Test Methodology	7
2. Test Configuration	8
2.1. Test System Connection Diagram	8
2.2. Test Environment Condition.....	8
3. Measuring Instrument	9
4. Decision Rules and Measurement Uncertainty	10
4.1. Decision Rules.....	10
4.2. Measurement Uncertainty	10
5. Test Result.....	11
5.1. Summary	11
5.2. Occupied Bandwidth Measurement	12
5.2.1. Test Limit.....	12
5.2.2. Test Procedure	12
5.2.3. Test Setting	12
5.2.4. Test Setup.....	12
5.2.5. Test Result	12
5.3. Frequency Stability Measurement	13
5.3.1. Test Limit.....	13
5.3.2. Test Procedure	13
5.3.3. Test Setting	13
5.3.4. Test Setup.....	14
5.3.5. Test Result	14
5.4. Equivalent Isotropically Radiated Power Measurement	15
5.4.1. Test Limit.....	15
5.4.2. Test Procedure	15
5.4.3. Test Setting	16
5.4.4. Test Setup.....	16

5.4.5.	Test Result	16
5.5.	Peak-to-Average Power Ratio Measurement	17
5.5.1.	Test Limit.....	17
5.5.2.	Test Procedure	17
5.5.3.	Test Setting	17
5.5.4.	Test Setup.....	17
5.5.5.	Test Result	17
5.6.	Conducted Band-Edge Measurement	18
5.6.1.	Test Limit.....	18
5.6.2.	Test Procedure	18
5.6.3.	Test Setting	18
5.6.4.	Test Setup.....	19
5.6.5.	Test Result	19
5.7.	Conducted Spurious Emissions Measurement	20
5.7.1.	Test Limit.....	20
5.7.2.	Test Procedure	20
5.7.3.	Test Setting	20
5.7.4.	Test Setup.....	21
5.7.5.	Test Result	21
5.8.	Radiated Spurious Emissions Measurement	22
5.8.1.	Test Limit.....	22
5.8.2.	Test Procedure	22
5.8.3.	Test Setting	22
5.8.4.	Test Setup.....	23
5.8.5.	Test Result	23
Appendix A - Test Result.....		24
A.1	Occupied Bandwidth Test Result.....	24
A.2	Frequency Stability Test Result	54
A.3	Equivalent Isotropically Radited Power Test Result	57
A.4	Peak-to-Average Power Radio Test Result	81
A.5	Conducted Band-Edge Test Result	111
A.6	Conducted Spurious Emissions Test Result.....	135
A.7	Radiated Spurious Emissions Test Result.....	146
Appendix B - Test Setup Photograph		152
Appendix C - EUT Photograph		153

1. General Information

1.1. Applicant

CASTLES TECHNOLOGY CO., LTD.

6F, NO. 207-5, SEC. 3, BEIXIN RD., XINDIAN DISTRICT, NEW TAIPEI CITY 231030, TAIWAN (R.O.C.)

1.2. Manufacturer

CASTLES TECHNOLOGY CO., LTD.

6F, NO. 207-5, SEC. 3, BEIXIN RD., XINDIAN DISTRICT, NEW TAIPEI CITY 231030, TAIWAN (R.O.C.)

1.3. Testing Facility

☒	Test Site – MRT Suzhou Laboratory
	Laboratory Location (Suzhou - Wuzhong) D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China
	Laboratory Location (Suzhou - SIP) 4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China
	Laboratory Location (Suzhou - Wujiang) Building 1, No.1 Xingdong Road, Wujiang, Suzhou, Jiangsu, People's Republic of China
	Laboratory Accreditations
	A2LA: 3628.01 FCC: CN1166 VCCI: ☐ R-20025 ☐ G-20034 ☐ C-20020 ☐ T-20020 ☐ R-20141 ☐ G-20134 ☐ C-20103 ☐ T-20104
	CNAS: L10551 ISED: CN0001
☐	Test Site – MRT Shenzhen Laboratory
	Laboratory Location (Shenzhen) 1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China
	Laboratory Accreditations
	A2LA: 3628.02 FCC: CN1284
	CNAS: L10551 ISED: CN0105
☐	Test Site – MRT Taiwan Laboratory
	Laboratory Location (Taiwan) No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
	Laboratory Accreditations
	TAF: 3261 FCC: 291082, TW3261
	ISED: TW3261

1.4. Product Information

Product Name	POS Terminal
Model No.	S1U2-M4
Trademark	
Serial Number	115244802968 (Radiated) 115244802974 (Conducted)
NFC Specification	13.56MHz
Wi-Fi Specification	802.11a/b/g/n/ac
Bluetooth Specification	BT5.0
GNSS Specification	GPS, GLONASS, GALILEO, BEIDOU
3GPP Specification	WCDMA Band II/IV/V LTE Band 2/4/12/17/25/66
Operating Temperature Range	-20 ~ 70 °C
Supply Voltage Rating	9 ~ 48Vdc, Normal 9Vdc
Antenna Specification	Refer to Section 1.6
Remark: The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.	

1.5. Radio Specification under Testing

E-UTRA Specification	
FDD TX Frequency Range	LTE Band 2: 1850 ~ 1910MHz; LTE Band 4: 1710 ~ 1755MHz; LTE Band 12: 699 ~ 716MHz; LTE Band 17: 704 ~ 716MHz; LTE Band 25: 1850 ~ 1915MHz; LTE Band 66: 1710 ~ 1780MHz;
FDD RX Frequency Range	LTE Band 2: 1930 ~ 1990MHz; LTE Band 4: 2110 ~ 2155MHz; LTE Band 12: 729 ~ 746MHz; LTE Band 17: 734 ~ 746MHz; LTE Band 25: 1930 ~ 1995MHz; LTE Band 66: 2110 ~ 2200MHz;
Support Bandwidth	Band 2, 4, 25, 66: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz Band 12, 17: 1.4MHz, 3MHz, 5MHz, 10MHz
Support Power Class	PC3
Modulation	UL up to 64QAM

1.6. Description of Available Antennas

Technology	Frequency Range (MHz)	Antenna Type	Max Peak Gain (dBi)
LTE Band 2	1850 ~ 1910	Monopole Antenna	2.53
LTE Band 4	1710 ~ 1755		2.53
LTE Band 12	699 ~ 716		3.89
LTE Band 17	704 ~ 716		3.89
LTE Band 25	1850 ~ 1915		2.53
LTE Band 66	1710 ~ 1780		2.53
Note: All antenna information (Antenna type and Peak Gain) is provided by the manufacturer.			


1.7. Test Methodology

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ANSI C63.26:2015
- FCC CFR 47 Part 2, Part 24, Part 27
- FCC KDB 971168 D01 v03r01: Power Meas License Digital Systems
- FCC KDB 971168 D02 v02r02: Misc Rev Approv License Devices
- FCC KDB 412172 D01 v01r01: Determining ERP and EIRP

2. Test Configuration

2.1. Test System Connection Diagram



2.2. Test Environment Condition

Ambient Temperature	15 ~ 35°C
Relative Humidity	20% ~ 75%RH

3. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
Temperature Chamber	BAOYT	BYH-150CL	MRTSUE06051	1 year	2025-09-02	WZ-TR3
Thermohygrometer	testo	608-H1	MRTSUE11268	1 year	2025-12-10	WZ-TR3
Thermohygrometer	testo	608-H1	MRTSUE06362	1 year	2026-01-23	WZ-SR6
Shielding Room	HUAMING	WZ-SR6	MRTSUE06443	N/A	N/A	WZ-SR6
Signal Analyzer	Keysight	N9020B	MRTSUE06583	1 year	2025-12-23	WZ-SR6
Radio Communication Analyzer	Anritsu	MT8821C	MRTSUE06960	1 year	2025-06-18	WZ-SR6
Communication Tester	R&S	CMW500	MRTSUE06108	1 year	2025-10-13	WZ-SR6
USB Power Sensor	Keysight	U2021XA	MRTSUE06446	1 year	2025-05-08	WZ-SR6
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2025-12-05	WZ-AC1
Horn Antenna	Schwarzbeck	BBHA 9120D	MRTSUE06023	1 year	2025-07-26	WZ-AC1
Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06024	1 year	2025-09-23	WZ-AC1
Preamplifier	Agilent	83017A	MRTSUE06076	1 year	2025-11-08	WZ-AC1
TRILOG Antenna	Schwarzbeck	VULB 9168	MRTSUE06172	1 year	2025-05-15	WZ-AC1
Anechoic Chamber	TDK	WZ-AC1	MRTSUE06212	1 year	2025-04-19	WZ-AC1
Signal Analyzer	Keysight	N9010B	MRTSUE06607	1 year	2025-10-13	WZ-AC1
Loop Antenna	Schwarzbeck	FMZB 1519 B	MRTSUE06937	1 year	2026-01-04	WZ-AC1
Thermohygrometer	testo	608-H1	MRTSUE11039	1 year	2025-10-16	WZ-AC1

Software	Version	Function
e3	230711	EMI Test Software
Controller_MF 7802	2.03C	RE Antenna & Turntable
UCTS	V 6.23.217.99	license 3G & 4G & 5G
Agilent Power Analyzer/Agilent Power Panel	V R03.09.00	Power

4. Decision Rules and Measurement Uncertainty

4.1. Decision Rules

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2.
(Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

4.2. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

Radiated Spurious Emissions	
Measurement Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$):	
Coaxial:	9kHz~30MHz: 2.35dB
Coplanar:	9kHz~30MHz: 2.37dB
Horizontal:	30MHz~200MHz: 3.46dB
	200MHz~1GHz: 3.78dB
	1GHz~40GHz: 4.97dB
Vertical:	30MHz~200MHz: 4.07dB
	200MHz~1GHz: 5.28dB
	1GHz~40GHz: 4.78dB
Conducted Spurious Emissions	
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$):	
1.47dB	
Output Power	
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$):	
0.66dB	
Occupied Bandwidth	
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$):	
69.28kHz	
Frequency Stability	
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$):	
8.04Hz	

5. Test Result

5.1. Summary

FCC Part Section(s)	Test Description	Test Condition	Test Result
2.1049	Occupied Bandwidth	Conducted	Pass
2.1055, 24.235, 27.54	Frequency Stability		Pass
24.232(c) 27.50 (c)(9) (d)(4)	Equivalent Radiated Power		Pass
24.232 (d), 27.50(d)(5)	Peak-to-Average Power Ratio		Pass
2.1051, 24.238(a) 27.53 (g) (h)	Transmitter unwanted emissions (band-edge)		Pass
2.1051, 24.238(a) 27.53 (g) (h)	Transmitter unwanted emissions (spurious)		
2.1051, 24.238(a) 27.53 (g) (h)	Transmitter Spurious Emissions	Radiated	Pass

Notes:

- 1) The analyzer plots shown in this section were captured using a correction table to account for cable and attenuator losses in the system connecting the EUT to the analyzer across relevant frequencies.
- 2) All supported modulation types were evaluated, and the worst-case emission from modulation types was selected. Therefore, the worst-case results for Frequency Stability, Peak-to-Average Power Ratio, Channel Band Edge, Conducted Spurious Emission, Radiated Spurious Emission were presented in the test report.
- 3) For the radiated emission tests, each axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst-case emissions.
- 4) LTE Band 66 (1710 ~ 1780 MHz) overlaps the entire frequency range of LTE Band 4 (1710 ~ 1755 MHz). Therefore, the test data provided in this report covers Band 4 as well as Band 66.
- 5) LTE Band 12 (699 ~ 716 MHz) overlaps the entire frequency range of LTE Band 17 (704 ~ 716 MHz). Therefore, the test data provided in this report covers Band 17 as well as Band 12.
- 6) LTE Band 25 (1850 ~ 1915 MHz) overlaps the entire frequency range of LTE Band 2 (1850 ~ 1910 MHz). Therefore, the test data provided in this report covers Band 2 as well as Band 25.

5.2. Occupied Bandwidth Measurement

5.2.1. Test Limit

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured.


5.2.2. Test Procedure

ANSI C63.26-2015 - Section 5.4.4

5.2.3. Test Setting

1. Set center frequency to the nominal EUT channel center frequency
2. RBW = The nominal RBW shall be in the range of 1% to 5% of the anticipated OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. Allow the trace to stabilize
8. Use the 99% power bandwidth function of the instrument and report the measured bandwidth.

5.2.4. Test Setup



5.2.5. Test Result

Refer to Appendix A.1.

5.3. Frequency Stability Measurement

5.3.1. Test Limit

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block.

5.3.2. Test Procedure

ANSI C63.26-2015 - Section 5.6

5.3.3. Test Setting

1. A reference point shall be established at the applicable unwanted emissions limit using a RBW equal to the RBW required by the unwanted emissions specification of the applicable regulatory standard. These reference points measured using the lowest and highest channel of operation shall be identified as f_L and f_H respectively.
2. Use the frequency error function of the instrument and record the frequency error.
3. Change the temperature of equipment and repeat Steps 2.
4. Change the Voltage of equipment and repeat Steps 2.
5. The frequency error offset determined in the above methods shall be added or subtracted from the values of f_L and f_H and the resulting frequencies must remain within the band

Frequency Stability Under Temperature Variations:


The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to highest. After the temperature stabilized recorded the frequency. Repeat step measure with 10°C decreased per stage until the lowest temperature reached.

Frequency Stability Under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply/DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change.

5.3.4. Test Setup



5.3.5. Test Result

Refer to Appendix A.2.

5.4. Equivalent Isotropically Radiated Power Measurement

5.4.1. Test Limit

Band 2/25:

Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

Band 4/66:

Fixed, mobile stations operating in the 1710-1755 MHz band and mobile in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP.

Band 12/17:

Control and mobile stations in the 698-746 MHz band are limited to 30 watts ERP.

5.4.2. Test Procedure

ANSI C63.26-2015 - Section 5.2.4.2

5.4.3. Test Setting

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

The relevant equation for determining the maximum ERP or EIRP from the measured RF output power is given in Equation (1) as follows:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_T$$

where


ERP or EIRP effective radiated power or equivalent isotropically radiated power, respectively (expressed in the same units as P_{Meas} , e.g., dBm or dBW)

P_{Meas} measured transmitter output power or PSD, in dBm or dBW

G_T gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP)

$$\text{ERP} = \text{EIRP} - 2.15$$

5.4.4. Test Setup



5.4.5. Test Result

Refer to Appendix A.3.

5.5. Peak-to-Average Power Ratio Measurement

5.5.1. Test Limit

The peak-to-average power ratio (PAPR) of the transmission must not exceed 13 dB.


5.5.2. Test Procedure

ANSI C63.26-2015 - Section 5.2.3.4 (CCDF).

5.5.3. Test Setting

1. Set the resolution/measurement bandwidth $\geq$ signal's occupied bandwidth
2. Set the number of counts to a value that stabilizes the measured CCDF curve
3. Record the maximum PAPR level associated with a probability of 0.1%

5.5.4. Test Setup



5.5.5. Test Result

Refer to Appendix A.4

5.6. Conducted Band-Edge Measurement

5.6.1. Test Limit

24.238 (a), 27.53 (g) (h)

For operations in the 1850 ~ 1915 MHz, 1930 ~ 1995 MHz, 698 ~ 746 MHz and 1710 ~ 1780 MHz, The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


5.6.2. Test Procedure

ANSI C63.26-2015 - Section 5.7

5.6.3. Test Setting

1. Set the analyzer frequency to Low or High channel
2. RBW = specified resolution bandwidth, for improvement of the accuracy in the measurement of the average power of a noise-like emission, a RBW narrower than the specified reference bandwidth can be used (generally limited to no less than 1% of the frequency block group, provided that a subsequent integration is performed over the full required measurement bandwidth. This integration should be performed using the spectrum analyzer's band power functions.
3. VBW $\geq 3 \times$ RBW
4. Sweep time = auto
5. Detector = power averaging (rms)
6. If the EUT can be configured to transmit continuously, then set the trigger to free run
7. If the EUT cannot be configured to transmit continuously, then use a sweep trigger with the level set to enable triggering only on full power bursts and configure the EUT to transmit at full power for the entire duration of each sweep. Verify that the sweep time is less than or equal to the transmission burst duration. Time gating can also be used under similar constraints
8. Compute the power by integrating the spectrum across the specified resolution bandwidth using the instrument's band or channel power measurement function, with the band/channel limits set equal to the specified resolution bandwidth, when using a measurement bandwidth smaller than the specified bandwidth. Otherwise, Use the peak marker function to determine the maximum amplitude level.

5.6.4. Test Setup



5.6.5. Test Result

Refer to Appendix A.5.

5.7. Conducted Spurious Emissions Measurement

5.7.1. Test Limit

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst-case configuration. All modes of operation were investigated and the worst-case configuration results are reported in this section.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


5.7.2. Test Procedure

ANSI C63.26-2015 - Section 5.7

5.7.3. Test Setting

1. Set the analyzer frequency to low, Mid or high channel.
2. RBW = specified resolution bandwidth
3. VBW $\geq 3 \times$ RBW
4. Sweep time = auto
5. Detector = power averaging (rms)
6. If the EUT can be configured to transmit continuously, then set the trigger to free run
7. If the EUT cannot be configured to transmit continuously, then use a sweep trigger with the level set to enable triggering only on full power bursts and configure the EUT to transmit at full power for the entire duration of each sweep. Verify that the sweep time is less than or equal to the transmission burst duration.
Time gating can also be used under similar constraints
8. Use the peak marker function to determine the maximum amplitude level.

5.7.4. Test Setup



5.7.5. Test Result

Refer to Appendix A.6

5.8. Radiated Spurious Emissions Measurement

5.8.1. Test Limit

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm.

$E \text{ (dB}\mu\text{V/m)} = \text{EIRP (dBm)} - 20 \log D + 104.8$; where D is the measurement distance in meters. The emission limit equal to 82.3dB μ V/m.

5.8.2. Test Procedure


ANSI C63.26-2015 - Section 5.2.7 & 5.5

5.8.3. Test Setting


1. RBW = 120kHz or 1MHz
2. VBW $\geq 3 \times$ RBW
3. Sweep time $\geq 10 \times$ (number of points in sweep) $\times$ (transmission symbol period)
4. Detector = CISPR quasi-peak / average detector (Below 1 GHz, compliance with the limits shall be demonstrated using a CISPR quasi-peak detector and the related measurement bandwidth. Above 1 GHz, compliance with the limits shall be demonstrated using a linear average detector with a minimum resolution bandwidth of 1 MHz.)
5. The trace was allowed to stabilize

5.8.4. Test Setup

Below 1GHz Test Setup:



Above 1GHz Test Setup:



5.8.5. Test Result

Refer to Appendix A.7.

Appendix A - Test Result

A.1 Occupied Bandwidth Test Result


Test Site	WZ-SR6	Test Engineer	Edith Yu
Test Date	2025-02-27 ~ 2025-02-28	Test Band	Band 2/25

Modulation	Bandwidth (MHz)	Frequency (MHz)	99% Bandwidth (MHz)
QPSK	1.4	1850.7	1.0766
		1882.5	1.0825
		1914.3	1.0831
	3	1851.5	2.6792
		1882.5	2.6782
		1913.5	2.6808
	5	1852.5	4.4702
		1882.5	4.4695
		1912.5	4.4715
	10	1855.0	8.9370
		1882.5	8.9421
		1910.0	8.9327
	15	1857.5	13.390
		1882.5	13.389
		1907.5	13.353
	20	1860.0	17.795
		1882.5	17.809
		1905.0	17.819
16QAM	1.4	1850.7	1.0809
		1882.5	1.0806
		1914.3	1.0812
	3	1851.5	2.6810
		1882.5	2.6806
		1913.5	2.6793
	5	1852.5	4.4669
		1882.5	4.4642
		1912.5	4.4634
	10	1855.0	8.9136
		1882.5	8.9069
		1910.0	8.9145


Modulation	Bandwidth (MHz)	Frequency (MHz)	99% Bandwidth (MHz)
	15	1857.5	13.362
		1882.5	13.370
		1907.5	13.372
	20	1860.0	17.814
		1882.5	17.822
		1905.0	17.811
64QAM	1.4	1850.7	1.0798
		1882.5	1.0792
		1914.3	1.0795
	3	1851.5	2.6823
		1882.5	2.6794
		1913.5	2.6839
	5	1852.5	4.4791
		1882.5	4.4796
		1912.5	4.4784
	10	1855.0	8.9197
		1882.5	8.9254
		1910.0	8.9234
	15	1857.5	13.352
		1882.5	13.362
		1907.5	13.363
	20	1860.0	17.791
		1882.5	17.845
		1905.0	17.833

99% Bandwidth – 1.4MHz – QPSK


Low Channel



Middle Channel




High Channel




99% Bandwidth – 3MHz – QPSK


Low Channel



Middle Channel




High Channel




99% Bandwidth – 5MHz – QPSK


Low Channel



Middle Channel




High Channel




99% Bandwidth – 10MHz – QPSK


Low Channel



Middle Channel




High Channel




99% Bandwidth – 15MHz – QPSK

Low Channel



Middle Channel




High Channel




99% Bandwidth – 20MHz – QPSK


Low Channel



Middle Channel




High Channel




99% Bandwidth – 1.4MHz –16QAM


Low Channel



Middle Channel




High Channel




99% Bandwidth – 3MHz –16QAM


Low Channel



Middle Channel




High Channel




99% Bandwidth – 5MHz –16QAM


Low Channel



Middle Channel




High Channel




99% Bandwidth – 10MHz –16QAM


Low Channel



Middle Channel




High Channel




99% Bandwidth – 15MHz –16QAM


Low Channel



Middle Channel




High Channel




99% Bandwidth – 20MHz – 16QAM


Low Channel



Middle Channel




High Channel




99% Bandwidth – 1.4MHz –64QAM


Low Channel



Middle Channel




High Channel




99% Bandwidth – 3MHz –64QAM


Low Channel



Middle Channel




High Channel




99% Bandwidth – 5MHz –64QAM


Low Channel



Middle Channel




High Channel




99% Bandwidth – 10MHz –64QAM


Low Channel



Middle Channel




High Channel




99% Bandwidth – 15MHz – 64QAM


Low Channel



Middle Channel




High Channel




99% Bandwidth – 20MHz – 64QAM


Low Channel



Middle Channel



High Channel




Test Site	WZ-SR6	Test Engineer	Edith Yu
Test Date	2025-02-17 ~ 2025-02-21	Test Band	Band 4/66

Modulation	Bandwidth (MHz)	Frequency (MHz)	99% Bandwidth (MHz)
QPSK	1.4	1710.7	1.0812
		1745.0	1.0859
		1779.3	1.0792
	3	1711.5	2.6878
		1745.0	2.6908
		1778.5	2.6845
	5	1712.5	4.4845
		1745.0	4.4667
		1777.5	4.4833
	10	1715.0	8.9384
		1745.0	8.9291
		1775.0	8.1952
	15	1717.5	13.375
		1745.0	13.388
		1772.5	13.372
	20	1720.0	17.841
		1745.0	17.809
		1770.0	17.851
16QAM	1.4	1710.7	1.0798
		1745.0	1.0824
		1779.3	1.0824
	3	1711.5	2.6844
		1745.0	2.6830
		1778.5	2.6803
	5	1712.5	4.4670
		1745.0	4.4721
		1777.5	4.4681
	10	1715.0	8.9159
		1745.0	8.9252
		1775.0	8.9274


Modulation	Bandwidth (MHz)	Frequency (MHz)	99% Bandwidth (MHz)
	15	1717.5	13.375
		1745.0	13.385
		1772.5	13.358
	20	1720.0	17.858
		1745.0	17.849
		1770.0	17.841
64QAM	1.4	1710.7	1.0804
		1745.0	1.0804
		1779.3	1.0795
	3	1711.5	2.6796
		1745.0	2.6810
		1778.5	2.6805
	5	1712.5	4.4718
		1745.0	4.4859
		1777.5	4.4714
	10	1715.0	8.9330
		1745.0	8.9126
		1775.0	8.9276
	15	1717.5	13.363
		1745.0	13.369
		1772.5	13.342
	20	1720.0	17.830
		1745.0	17.853
		1770.0	17.840

99% Bandwidth – 1.4MHz – QPSK


Low Channel



Middle Channel




High Channel




99% Bandwidth – 3MHz – QPSK


Low Channel



Middle Channel




High Channel




99% Bandwidth – 5MHz – QPSK


Low Channel



Middle Channel




High Channel




99% Bandwidth – 10MHz – QPSK


Low Channel



Middle Channel




High Channel




99% Bandwidth – 15MHz – QPSK


Low Channel



Middle Channel




High Channel




99% Bandwidth – 20MHz – QPSK


Low Channel



Middle Channel




High Channel




99% Bandwidth – 1.4MHz –16QAM


Low Channel



Middle Channel




High Channel




99% Bandwidth – 3MHz –16QAM

Low Channel



Middle Channel



High Channel

