

RF Exposure Report

Report No.: SA191209C13

FCC ID: WIYT910 (For module)

WIYUPT1000-BV (For Host)

Test Model: LE910-NA1 (For module)

UPT1000B (For Host)

Received Date: Dec. 09, 2019

Date of Evaluation: Feb. 17 ~ Feb. 21, 2020

Issued Date: Feb. 26, 2020

Applicant: CASTLES TECHNOLOGY CO., LTD.

Address: 6F, NO. 207-5, SEC. 3, BEIXIN RD., XINDIAN DISTRICT, NEW TAIPEI CITY 23143, TAIWAN (R. O. C.)

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specifically mentioned, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SA191209C13	Original release.	Feb. 26, 2020

1 Certificate of Conformity

Product: LTE module (for module)

POS Terminal (For Host)

Brand: Telit (for module)

CASTLES TECHNOLOGY (For Host)

Test Model: LE910-NA1 (For module)

UPT1000B (For Host)

Sample Status: Identical Prototype

Applicant: CASTLES TECHNOLOGY CO., LTD.

Date of Evaluation: Feb. 17 ~ Feb. 21, 2020


Standards: FCC Part 2 (Section 2.1091)

References Test KDB 447498 D01 General RF Exposure Guidance v06

Guidance: IEEE C95.3 -2002

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :



Polly Chien / Specialist

Date:

Feb. 26, 2020

Approved by :



Bruce Chen / Senior Project Engineer

Date:

Feb. 26, 2020

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

3 Calculation Result of Maximum Conducted Power

For module (Model: LE910-NA1, FCC ID: WIYT910)

Frequency Band (MHz)	Output Power ERP / EIRP (dBm)	Output Power ERP / EIRP (mW)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA Band 2	23.5	223.872	20	0.045	1
WCDMA Band 5	23.3	213.796	20	0.043	0.55
LTE Band 2	24.1	257.040	20	0.051	1
LTE Band 4	23.6	229.087	20	0.046	1
LTE Band 5	22.7	186.209	20	0.037	0.55
LTE Band 12	21.7	147.911	20	0.029	0.47
LTE Band 13	21.3	134.896	20	0.027	0.52

For Host:

Frequency Band (MHz)	Max. AV Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2.4G Bluetooth	9.63	-0.1	20	0.002	1

Mode	Electric field (dBuV/m) @3m	Max. Power EIRP (dBm)	Max. Power EIRP (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)
NFC	66.8	-28.43	0.001435	0.0000003	0.978

Note:

- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
- Max. power EIRP (dBm) = Field Strength (dBuV/m)@3m - 95.23, Output power (mW) = $10^{(\text{Max power(dBm)} / 10)}$

For antenna gain:

Frequency Band	Antenna Gain (dBi)
2.4G Bluetooth	-0.1
698-791MHz	0
824-960MHz	1.61
1710-2170MHz	1.95

Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

- WWAN + BT = $0.043/0.55 + 0.002/1 = 0.078+0.002=0.080$
- WWAN + NFC = $0.043/0.55 + 0.0000003/0.978 = 0.078+0.00000031=0.078$
- WWAN + BT + NFC = $0.043/0.55 + 0.002/1 + 0.0000003/0.978 = 0.078+0.002+0.0007=0.080$

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---